

SPEC #105
PRODUCT INFORMATION

valspar

1191 Wheeling Road, Wheeling, IL 60090
Phone: 847-541-9000 Fax: 847-541-7549



73194 Series Valspar Ultra Premium Exterior Flat Latex

PRODUCT: 73194 Series

DESCRIPTION:

Valspar Ultra Premium Exterior Latex Flat

FEATURES:

Valspar Ultra Premium Exterior Paint for the exterior protection and preservation of historic residences and newer homes too. Climate formulated for exceptional mildew resistant performance in hot, humid conditions. The durable flat sheen latex formula goes on easily, dries quickly, and cleans up with soap and water. Valspar Ultra Premium Paints not only cover in one coat, but are also fade, chalk and stain resistant, washable, non-yellowing and durable. Gives mildew resistant coating.

WHERE TO USE:

Properly prepared exterior siding and trim surfaces including hardboard siding, primed metal, shakes, shingles, brick, cement, cinder block, stucco, concrete, stone, asbestos, galvanized steel and aluminum siding. Do not use on glazed surfaces such as brick, tile and masonry or on walking surfaces such as floors and steps.

SURFACE PREPARATION:

Paint must be applied to clean, sound surfaces. Clean and dry surface thoroughly, removing all dirt, dust, chalk, rust, grease, wax and mildew. **Bare Wood:** Coat knots and sappy areas with Valspar Interior Oil Multi-Purpose Primer, after removing sap by scraping and scrubbing with mineral spirits. Prime entire area with Valspar Exterior Latex House & Trim or Valspar Exterior Oil House & Trim Primer. **Previously Painted Surfaces:** Scrape off loose and peeling paint, sand, then prime. Surfaces with many layers of old, brittle paint may require complete removal of all the previous coats prior to repainting. Thoroughly remove chalk by vigorous washing, with a non-residue (TSP) cleanser, then rinse surface well. Wire brush under eaves and porch ceilings to remove invisible residues and increase adhesion in these areas. Dull glossy surfaces with gloss remover or sandpaper. Countersink nails and spot prime nailheads with a rust inhibitive metal primer. When dry, fill with putty. Caulk cracks and open joints, then prime. **Hardboard Siding (unprimed, primed or previously painted):** Remove any wax from bleed through areas by wiping with mineral spirits soaked rags, turning often to avoid merely spreading wax around. Prime all hardboard with Valspar Exterior Oil House & Trim Primer. **Masonry:** Wire brush loose material from chalking areas on concrete, brick and concrete blocks. **Metal:** Remove rust on galvanized gutters and spot prime with a rust inhibitive metal primer. On new galvanized surfaces, allow to age six months before painting, or clean with mild muriatic acid solution. On other unpainted ferrous metal surfaces, remove rust, wipe clean with mineral spirits and prime with a rust inhibitive metal primer. **Important Facts About Mildew.** This paint contains ingredients that help resist mildew growth on dry paint film. Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting or it will grow through any new coat of paint. To remove mildew, scrub house before painting with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts of water. Rinse thoroughly. Protect eyes and skin by wearing rubber gloves and eye goggles when working with bleach solution.

TYPICAL PRODUCT PROPERTIES: 73194

VEHICLE TYPE: 100% Acrylic Resin
SOLIDS: 54% WT. 36% VOL.
VOC: 100 g/l max
WT/GAL: 11.7 lbs.
VISCOSITY: 95-100 KU
FLASHPOINT: N/A
60° GLOSS: 0-4 Units

COVERAGE: 400 Sq. Ft. Gallon, depending on porosity and texture.

FILM THICKNESS: 4.0 mil Wet
1.4 mil Dry

DRY TIMES: Dries to the touch in 30-60 minutes. Paint only when surface or temperatures are above 50°F and below 90°F during application.

APPLICATION:

1. Make sure surface is clean, dry and sound. Prepare surface according to instructions in "Surface Preparation". 2. Use a paint paddle to stir paint up from the bottom of the can. To ensure uniform color, intermix all containers of the same color. Cover grass and shrubbery with plastic or cloth. 3. Use a top quality nylon or polyester brush, top quality roller (1/2" nap to 3/4" nap), or airless sprayer (.017 - .021 tip) to apply paint. Start at the highest point of the house and work from left to right. Paint gutters inside and out while you are at the top. 4. To avoid leaning ladder against fresh paint, apply paint to window sash and frames next. After one hour, move windows up and down to avoid sticking. 5. Move ladder and finish painting the siding. Paint back into freshly painted areas. Always end up at a door, window or outer edge. Never stop in an open space. 6. Clean up is easy with warm, soapy water. Keep a damp cloth handy to wipe up spills as they occur.

STORAGE AND DISPOSAL:

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

THINNING/CLEAN UP:

Thin only for spray application with up to 8oz of water per gallon of paint. Clean up with warm soapy water.

PACKAGING:

4 pk Quart	White, Base 1, 2 & 4
4 pk Gallon	White, Base 1, 2 & 4
5 Gallon Each	White

**Product Information Hotline:
1-888-313-5569**

TYPICAL ANALYSIS 73194

C.A.S. NO.	INGREDIENTS
7732-18-5	Water
13463-67-7	Titanium Dioxide
14808-60-7	Crystalline Silica
25035-69-2	Acrylic Resin
107-21-1	Ethylene Glycol
68855-54-9	Sodium Aluminosilicate
112926-00-8	Silica

CAUTIONS:

CONTAINS CRYSTALLINE SILICA

May cause eye and skin irritation. Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave the area. When sanding wear a dust mask. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use. **WARNING:** This product contains a chemical known to the State of California to cause cancer.

FIRST AID:

EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues **get medical attention.** **IF SWALLOWED:** Drink 2 glasses of water. **Get medical attention immediately. Delayed effect from long-term exposure:** Crystalline silica may cause lung damage and cancer. Risk depends upon duration and level of exposure to sanding dust.

**DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.
EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

**This product contains less than
100 g/L VOC (0.8 lb./Gal VOS)**

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.