

MATERIAL SAFETY DATA SHEET

66-105  
02 00

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

| PRODUCT NUMBER | DATE OF PREPARATION | HMIS CODES   |    |
|----------------|---------------------|--------------|----|
| 66-105         | 29-SEP-07           | Health       | 2* |
|                |                     | Flammability | 0  |
|                |                     | Reactivity   | 0  |

PRODUCT NAME  
ULTRA DELUXE® Exterior 100% Acrylic Latex Flat Finish, Deep Base

MANUFACTURER'S NAME  
DURON  
10406 Tucker St.  
Beltsville, MD 20705-2297

TELEPHONE NUMBERS and WEBSITES  
Product Information  
(800) 723-8766                      www.duron.com  
Regulatory Information  
(800) 306-8961                      www.paintdocs.com  
Medical Emergency  
(216) 566-2917  
Transportation Emergency              for Chemical Emergency ONLY (spill, leak,  
(800) 424-9300                      fire, exposure, or accident)

Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

| % by WT | CAS No.    | INGREDIENT       | UNITS      | VAPOR PRESSURE          |
|---------|------------|------------------|------------|-------------------------|
| 2       | 107-21-1   | Ethylene Glycol  |            |                         |
|         |            | ACGIH TLV        | 100 mg/m3  | CEILI (aerosol) 0.12 mm |
|         |            | OSHA PEL         | 50 ppm     | CEILING                 |
| 5       | 14808-60-7 | Quartz           |            |                         |
|         |            | ACGIH TLV        | 0.05 mg/m3 | as Resp. Dust           |
|         |            | OSHA PEL         | 0.1 mg/m3  | as Resp. Dust           |
| 3       | 14464-46-1 | Cristobalite     |            |                         |
|         |            | ACGIH TLV        | 0.05 mg/m3 | as Resp. Dust           |
|         |            | OSHA PEL         | 0.05 mg/m3 | as Resp. Dust           |
| 4       | 13463-67-7 | Titanium Dioxide |            |                         |
|         |            | ACGIH TLV        | 10 mg/m3   | as Dust                 |
|         |            | OSHA PEL         | 10 mg/m3   | Total Dust              |
|         |            | OSHA PEL         | 5 mg/m3    | Respirable Fraction     |

Section 3 -- HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE  
INHALATION of vapor or spray mist.  
EYE or SKIN contact with the product, vapor or spray mist.

---

EFFECTS OF OVEREXPOSURE

EYES: Irritation.

SKIN: Prolonged or repeated exposure may cause irritation.

INHALATION: Irritation of the upper respiratory system.

In a confined area vapors in high concentration may cause headache, nausea or dizziness.

Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver and urinary systems.

## SIGNS AND SYMPTOMS OF OVEREXPOSURE

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

## MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

May cause allergic skin reaction in susceptible persons or skin sensitization.

## CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

---

Section 4 -- FIRST AID MEASURES

---

EYES: Flush eyes with large amounts of water for 15 minutes.  
Get medical attention.SKIN: Wash affected area thoroughly with soap and water.  
Remove contaminated clothing and launder before re-use.INHALATION: If affected, remove from exposure. Restore breathing.  
Keep warm and quiet.INGESTION: Do not induce vomiting.  
Get medical attention immediately.

---

Section 5 -- FIRE FIGHTING MEASURES

---

## FLASH POINT

Not Applicable

LEL

N.A.

UEL

N.A.

## FLAMMABILITY CLASSIFICATION

Not Applicable

## EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Alcohol Foam

## UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

## SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

---

Section 6 -- ACCIDENTAL RELEASE MEASURES

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate the area.  
Remove with inert absorbent.

---

Section 7 -- HANDLING AND STORAGE

---

STORAGE CATEGORY

Not Applicable

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

---

Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

---

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.  
Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

---

 Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES
 

---

|  |                   |  |
|--|-------------------|--|
| PRODUCT WEIGHT   | 10.17 lb/gal      | 1218 g/l                                 |
| SPECIFIC GRAVITY   | 1.22              |  |
| BOILING POINT  | 212 - 500 F       | 100 - 260 C                              |
| MELTING POINT  | Not Available     |  |
| VOLATILE VOLUME  | 67 %              |  |
| EVAPORATION RATE   | Slower than ether |  |
| VAPOR DENSITY  | Heavier than air  |  |
| SOLUBILITY IN WATER  | N.A.              |  |
| pH   | 9.0               |  |
| VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged) |                   |  |
| 1.22 lb/gal  | 146 g/l           | Less Water and Federally Exempt Solvents |
| 0.46 lb/gal  | 55 g/l            | Emitted VOC                              |

---

 Section 10 -- STABILITY AND REACTIVITY
 

---

STABILITY -- Stable  
 CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur

---

 Section 11 -- TOXICOLOGICAL INFORMATION
 

---

CHRONIC HEALTH HAZARDS

Crystalline Silica (Quartz, Cristobalite) is listed by IARC and NTP. Long term exposure to high levels of silica dust, which can occur only when sanding or abrading the dry film, may cause lung damage (silicosis) and possibly cancer.

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

Ethylene Glycol is considered an animal teratogen. It has been shown to cause birth defects in rats and mice at high doses when given in drinking water or by gavage. There is no evidence to indicate it causes birth defects in humans.

---

TOXICOLOGY DATA

Continued on page 5

| CAS No.    | Ingredient Name  |      |     |     |               |
|------------|------------------|------|-----|-----|---------------|
| 107-21-1   | Ethylene Glycol  | LC50 | RAT | 4HR | Not Available |
|            |                  | LD50 | RAT |     | 4700 mg/kg    |
| 14808-60-7 | Quartz           | LC50 | RAT | 4HR | Not Available |
|            |                  | LD50 | RAT |     | Not Available |
| 14464-46-1 | Cristobalite     | LC50 | RAT | 4HR | Not Available |
|            |                  | LD50 | RAT |     | Not Available |
| 13463-67-7 | Titanium Dioxide | LC50 | RAT | 4HR | Not Available |
|            |                  | LD50 | RAT |     | Not Available |

---

Section 12 -- ECOLOGICAL INFORMATION

---

## ECOTOXICOLOGICAL INFORMATION

No data available.

---

Section 13 -- DISPOSAL CONSIDERATIONS

---

## WASTE DISPOSAL METHOD

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

---

Section 14 -- TRANSPORT INFORMATION

---

## US Ground (DOT)

Not Regulated for Transportation.

## Canada (TDG)

Not Regulated for Transportation.

## IMO

Not Regulated for Transportation.

---

Section 15 -- REGULATORY INFORMATION

---

## SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

| CAS No.  | CHEMICAL/COMPOUND | % by WT | % Element |
|----------|-------------------|---------|-----------|
| 107-21-1 | Ethylene Glycol   | 2       |           |

## TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

Continued on page 6

---

Section 16 -- OTHER INFORMATION

---

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.