

MATERIAL SAFETY DATA SHEET

35-917  
07 00

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER	DATE OF PREPARATION	HMIS CODES	
35-917	06-SEP-07	Health	1*
		Flammability	0
		Reactivity	0

PRODUCT NAME  
ULTRA DELUXE® Interior Acrylic Latex Semi-Gloss Enamel, Shell White

MANUFACTURER'S NAME  
DURON  
10406 Tucker St.  
Beltsville, MD 20705-2297

TELEPHONE NUMBERS and WEBSITES  
Product Information  
(800) 723-8766                      www.duron.com  
Regulatory Information  
(800) 306-8961                      www.paintdocs.com  
Medical Emergency  
(216) 566-2917  
Transportation Emergency              for Chemical Emergency ONLY (spill, leak,  
(800) 424-9300                      fire, exposure, or accident)

Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

% by WT	CAS No.	INGREDIENT	UNITS	VAPOR PRESSURE
20	13463-67-7	Titanium Dioxide		
		ACGIH TLV	10 mg/m3 as Dust	
		OSHA PEL	10 mg/m3 Total Dust	
		OSHA PEL	5 mg/m3 Respirable Fraction	

Section 3 -- HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE  
INHALATION of vapor or spray mist.  
EYE or SKIN contact with the product, vapor or spray mist.

EFFECTS OF OVEREXPOSURE  
EYES: Irritation.  
SKIN: Prolonged or repeated exposure may cause irritation.

INHALATION: Irritation of the upper respiratory system.

SIGNS AND SYMPTOMS OF OVEREXPOSURE  
Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE  
May cause allergic skin reaction in susceptible persons or skin sensitization.

CANCER INFORMATION  
For complete discussion of toxicology data refer to Section 11.

---

 Section 4 -- FIRST AID MEASURES
 

---

EYES: Flush eyes with large amounts of water for 15 minutes.  
Get medical attention.

SKIN: Wash affected area thoroughly with soap and water.

INHALATION: If affected, remove from exposure. Restore breathing.  
Keep warm and quiet.

INGESTION: Do not induce vomiting.  
Get medical attention immediately.

---

 Section 5 -- FIRE FIGHTING MEASURES
 

---

FLASH POINT	LEL	UEL
Not Applicable	N.A.	N.A.

## FLAMMABILITY CLASSIFICATION

Not Applicable

## EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Alcohol Foam

## UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

## SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

---

 Section 6 -- ACCIDENTAL RELEASE MEASURES
 

---

## STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate the area.  
Remove with inert absorbent.

---

 Section 7 -- HANDLING AND STORAGE
 

---

## STORAGE CATEGORY

Not Applicable

## PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

---

 Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION
 

---

## PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.  
Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

## VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

## RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

## PROTECTIVE GLOVES

Required for long or repeated contact.

## EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

---

 Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES
 

---

PRODUCT WEIGHT	10.10 lb/gal	1209 g/l
SPECIFIC GRAVITY	1.21	
BOILING POINT	212 - 213 F	100 - 100 C
MELTING POINT	Not Available	
VOLATILE VOLUME	70 %	
EVAPORATION RATE	Slower than ether	
VAPOR DENSITY	Heavier than air	
SOLUBILITY IN WATER	N.A.	
pH	9.0	
VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)		
0.27 lb/gal	32 g/l	Less Water and Federally Exempt Solvents
0.08 lb/gal	9 g/l	Emitted VOC

---

 Section 10 -- STABILITY AND REACTIVITY
 

---

STABILITY -- Stable

CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur

Continued on page 4

---

 Section 11 -- TOXICOLOGICAL INFORMATION
 

---

## CHRONIC HEALTH HAZARDS

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

---

 TOXICOLOGY DATA
 

---

CAS No.	Ingredient Name				
13463-67-7	Titanium Dioxide				
	LC50	RAT	4HR		Not Available
	LD50	RAT			Not Available

---

 Section 12 -- ECOLOGICAL INFORMATION
 

---

## ECOTOXICOLOGICAL INFORMATION

No data available.

---

 Section 13 -- DISPOSAL CONSIDERATIONS
 

---

## WASTE DISPOSAL METHOD

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

---

 Section 14 -- TRANSPORT INFORMATION
 

---

## US Ground (DOT)

Not Regulated for Transportation.

## Canada (TDG)

Not Regulated for Transportation.

## IMO

Not Regulated for Transportation.

---

 Section 15 -- REGULATORY INFORMATION
 

---

## SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.			

Continued on page 5

---

**TSCA CERTIFICATION**

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

---

**Section 16 -- OTHER INFORMATION**

---

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.