

	Material Safety Data Sheet	24 Hour Emergency Phone Numbers: Medical/Poison Control: In U.S.: Call 1-800-222-1222 Outside U.S.: Call your local poison control center Transportation/National Response Center: 1-800-535-5053 1-352-323-3500 •NOTE: The National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.
IMPORTANT: Provide this information to employees, customers, and users of this product. Read this MSDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this MSDS are further described in Section 16.		

Section 1 - Chemical Product / Company Information

This Material Safety Data Sheet is available in Canadian French and Hispanic American Spanish upon request.
 On peut demander cette fiche signalétique (MSDS) a la langue francaise-canadienne.
 Los Datos de Seguridad del Producto pueden obtenerse en Espanol si lo requiere.

Product Name: DAP Watertight Concrete Filler & Sealant
Product UPC Number: 070798180215
Product Use/Class: Latex Concrete Sealant
Manufacturer: DAP Inc.
 2400 Boston Street Suite 200
 Baltimore, MD 21224-4723
 888-327-8477 (non-emergency matters)

Revision Date: 09/03/2009
Supersedes: 12/23/1999
MSDS Number: 00010010001

Section 2 - Hazards Identification

Emergency Overview: A gray paste product with a very slight ammonia odor. WARNING! May cause eye, skin, nose, throat and respiratory tract irritation. Harmful if swallowed or absorbed through the skin. This product contains ethylene glycol.

Refer to other MSDS sections for other detailed information.

Effects Of Overexposure - Eye Contact: May cause eye irritation.

Effects Of Overexposure - Skin Contact: Harmful if absorbed through the skin. May cause skin irritation.

Effects Of Overexposure - Inhalation: May be harmful if inhaled. Inhalation of vapors causes irritation of the nose, throat, lungs and respiratory tract. Inhalation may cause mild irritation to the respiratory tract (nose, mouth, mucous membranes). Inhalation of high concentrations may cause headache, nausea, and dizziness.

Effects Of Overexposure - Ingestion: Harmful or fatal if swallowed. If ingested, may cause vomiting, diarrhea, and depressed respiration. Ingestion may result in obstruction when material hardens. Ingestion of ethylene glycol can cause gastrointestinal irritation, nausea, vomiting, diarrhea and if ingested in sufficient quantities, death.

Effects Of Overexposure - Chronic Hazards: Repeated or prolonged exposure may cause skin, respiratory, kidney and liver damage. Prolonged and repeated skin contact may cause irritation and possibly dermatitis.

The International Agency for Research on Cancer (IARC) has determined that crystalline silica in the form of quartz or cristobalite that is inhaled from occupational sources is carcinogenic to humans (Group 1- carcinogenic to humans). Refer

to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (published in June 1997) in conjunction with the use of these materials. The National Toxicology Program (NTP) classifies respirable crystalline silica as "known to be a human carcinogen". Refer to the 9th Report on Carcinogens (2000). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (Group A2).

Breathing dust containing respirable crystalline silica may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may have the following serious chronic health effects: Excessive inhalation of respirable dust can cause pneumoconiosis, a respiratory disease, which can result in delayed, progressive, disabling and sometimes fatal lung injury. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function. Smoking exacerbates this disease. Individuals with pneumoconiosis are predisposed to develop tuberculosis. There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by fibrosis of the lungs, skin and other internal organs) and kidney disease. Prolonged, repeated, or high exposures may cause weakness and depression of the central nervous system.

The mixture of phthalate esters contained within this product has been shown to cause developmental effects at high doses in laboratory animals when administered orally by gavage in a developmental study and developmental and fertility effects when administered at high doses by feed in a two-generation reproduction study. The potential risk from occupational and consumer exposure is considered to be very low, based on limited relevance of the rodent findings to humans and the large safety margins between exposure and the effect levels.

Ethylene Glycol may cause kidney and liver damage upon prolonged and repeated overexposures. Studies have shown that repeated inhalation of ethylene glycol has produced adverse cardiovascular changes in laboratory animals. Ethylene glycol has been shown to cause birth defects in laboratory animals.

Primary Route(s) Of Entry: Skin Contact, Inhalation, Eye Contact

Medical Conditions which May be Aggravated by Exposure: None known.

Carcinogenicity:

CAS No.	Chemical Name	ACGIH	OSHA	IARC	NTP
14808-60-7	Silica, crystalline	Suspected human carcinogen.	Not Listed.	Human carcinogen.	Known carcinogen.
13463-67-7	Titanium dioxide	Not Listed.	Not Listed.	Possible carcinogen.	Not Listed.

Section 3 - Composition / Information On Ingredients

Chemical Name	CASRN	Wt%
Limestone	1317-65-3	40-70
Branched and linear phthalates	Proprietary	1-5
Silica, crystalline	14808-60-7	0.1-1.0
Titanium dioxide	13463-67-7	0.1-1.0
Ethylene glycol	107-21-1	0.1-1.0

Section 4 - First Aid Measures

First Aid - Eye Contact: In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

First Aid - Skin Contact: Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical aid if symptoms persist. In case of contact, immediately flush skin with plenty of water while removing contaminated clothing and shoes. Remove and wash contaminated clothing. If skin irritation persists, call a physician.

First Aid - Inhalation: If inhaled, remove to fresh air. If breathing is difficult, leave the area to obtain fresh air. If continued breathing difficulty is experienced, get medical attention immediately. If inhaled, remove to fresh air. Administer oxygen if necessary. Consult a physician if symptoms persist or exposure was severe. First Aid: If you experience difficulty in

breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

First Aid - Ingestion: If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately. If ingested, drink 2 glasses of water. Immediately see a physician. Never give anything by mouth to an unconscious person.

Note to Physician: None.

COMMENTS: If over-exposure occurs, call your poison control center at 1-800-222-1222.

Section 5 - Fire Fighting Measures

Extinguishing Media: Alcohol, Carbon Dioxide, Dry Chemical, Foam, Water Fog

Unusual Fire And Explosion Hazards: None known.

Special Firefighting Procedures: Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

Section 6 - Accidental Release Measures

Steps To Be Taken If Material Is Released Or Spilled: Wear proper protective equipment as specified in Section 8. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Section 7 - Handling And Storage

Handling: KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY. Use only with adequate ventilation. Open all windows and doors or use other means to ensure cross-ventilation and fresh air entry during application and drying. Odor is not an adequate warning for hazardous conditions. Avoid breathing vapor and contact with eyes, skin and clothing. Wash thoroughly after handling.

Storage: Avoid excessive heat and freezing. Do not store at temperatures above 120 degrees F. Close container after each use. Store away from caustics and oxidizers.

Section 8 - Exposure Controls / Personal Protection

Chemical Name	CASRN	ACGIH TWA	ACGIH STEL	ACGIH CEIL	OSHA TWA	OSHA STEL	OSHA CEIL	Skin
Limestone	1317-65-3	10 MGM3	N.E.	N.E.	5 MGM3 (respirable fraction)	N.E.	N.E.	No
Branched and linear phthalates	Proprietary	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.	No
Silica, crystalline	14808-60-7	0.025 MGM.	N.E.	N.E.	10/(%SiO ₂ + 2) MGM3	N.E.	N.E.	No
Titanium dioxide	13463-67-7	10 MGM3	N.E.	N.E.	15 MGM3	N.E.	N.E.	No
Ethylene glycol	107-21-1	N.E.	N.E.	100 MGM3	N.E.	N.E.	N.E.	No

Exposure Notes:

14808-60-7 The 2002 ACGIH Threshold Limit Values for Chemical Substances and Physical Agents lists the median Respirable Particulate Mass (RPM) point for crystalline silica at 4.0 microns in terms of the particle's aerodynamic diameter.

The TLVs for crystalline silica represent the respirable fraction.

OSHA PEL TWA for Quartz is calculated using the following formula: 10 mg/m³/(% SiO₂ + 2). Both concentration and percent quartz for the application of this limit are to be determined from the fraction passing a size selector with the following characteristics.

-----|-----
 | Aerodynamic diameter (unit density sphere)| Percent passing selector |

2	90.....
2.5	75.....
3.5	50.....
5.0	25.....
10	0.....

Precautionary Measures: Contact lenses pose a special hazard; soft lenses may absorb and all lenses concentrate irritants.

Engineering Controls: Good general ventilation should be sufficient to control airborne levels. Ensure adequate ventilation, especially in confined areas. Local ventilation of emission sources may be necessary to maintain ambient concentrations below recommended exposure limits.

Respiratory Protection: No personal respiratory protective equipment normally required. In case of insufficient ventilation, wear suitable respiratory equipment. A NIOSH-approved air purifying respirator with an organic vapor cartridge or canister may be necessary under certain circumstances where airborne concentrations are expected to exceed exposure limits. A respiratory protection program that meets the OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. National Institute for Occupational Safety and Health (NIOSH) has recommended that the permissible exposure limit be changed to 50 micrograms respirable free silica per cubic meter of air (0.05 mg/m³) as determined by a full shift sample up to 10-hour work shift.

Skin Protection: Impervious gloves. Natural rubber, butyl rubber and polyvinyl chloride gloves are not suitable protection against the phthalates contained within this product; neoprene is recommended.

Eye Protection: Goggles or safety glasses with side shields.

Other protective equipment: Not required under normal use.

Hygienic Practices: Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use.

Important: Listed Permissible Exposure Levels (PEL) are from the U.S. Dept. of Labor OSHA Final Rule Limits (CFR 29 1910.1000); these limits may vary between states.

Note: An employee's skin exposure to substances having a "YES" in the "SKIN" column in the table above shall be prevented or reduced to the extent necessary under the circumstances through the use of gloves, coveralls, goggles or other appropriate personal protective equipment, engineering controls or work practices.

Section 9 - Physical And Chemical Properties

Boiling Range:	Not Established	Vapor Density:	Heavier Than Air
Odor:	Very Slight Ammonia	Odor Threshold:	Not Established
Color:	Gray	Evaporation Rate:	Slower Than n-Butyl Acetate
Solubility in H₂O:	Not Established	Specific Gravity:	1.65
Freeze Point:	Not Established	pH:	Between 7.0 and 12.0
Vapor Pressure:	Not Established	Viscosity:	Not Established
Physical State:	Paste	Flammability:	Non-Flammable
Flash Point, F:	Greater than 200	Method:	(Seta Closed Cup)
Lower Explosive Limit, %:	Not Established	Upper Explosive Limit, %:	Not Established

When reported, vapor pressure of this product has been calculated theoretically based on its constituent makeup and has not been determined experimentally.

(See section 16 for abbreviation legend)

Section 10 - Stability And Reactivity

Conditions To Avoid: Excessive heat and freezing.

Incompatibility: Incompatible with strong bases and oxidizing agents.

Hazardous Decomposition Products: Normal decomposition products, i.e., COx, NOx.

Hazardous Polymerization: Hazardous polymerization will not occur under normal conditions.

Stability: Stable under recommended storage conditions.

Section 11 - Toxicological Information

Product LD50: Not Established

Product LC50: Not Established

CASRN	Chemical Name	LD50	LC50
107-21-1	Ethylene glycol	Rat:4700 mg/kg	Rat:10876 mg/kg

Significant Data with Possible Relevance to Humans: None.

Section 12 - Ecological Information

Ecological Information: Ecological injuries are not known or expected under normal use.

Section 13 - Disposal Information

Disposal Information: Dispose of material in accordance with all federal, state and local regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

EPA Waste Code if Discarded (40 CFR Section 261): This product does not meet the definition of a hazardous waste according to U.S. EPA Hazardous Waste Management Regulation, 40 CFR Section 261.

Section 14 - Transportation Information

DOT Proper Shipping Name:	Not Regulated	Packing Group:	N.A.
DOT Technical Name:	N.A.	Hazard Subclass:	N.A.
DOT Hazard Class:	N.A.	DOT UN/NA Number:	None

Note: The shipping information provided is applicable for domestic ground transport only. Different categorization may apply if shipped via other modes of transportation and/or to non-domestic destinations.

Section 15 - Regulatory Information

CERCLA - SARA Hazard Category:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Immediate Health Hazard, Chronic Health Hazard

SARA Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

None

Toxic Substances Control Act:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

None

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product:

Chemical Name	CAS Number
Water	7732-18-5
Non-Hazardous Polymer	Proprietary
Acrylic polymer	Proprietary

Pennsylvania Right-to-Know:

The following non-hazardous ingredients are present in the product at greater than 3%:

Chemical Name	CAS Number
Water	7732-18-5
Non-Hazardous Polymer	Proprietary
Acrylic polymer	Proprietary

California Proposition 65:

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Section 16 - Other Information**HMIS Ratings:**

Health: 1 Flammability: 1 Reactivity: 0 Personal Protection: X

Volatile Organic Compounds (VOC), less water less exempts: g/L: 35.0 lb/gal: 0.29 wt:wt%: 1.54

Volatile Organic Compounds (VOC), less water less exempts, less LVP-VOCs: wt:wt%: 0.8

REASON FOR REVISION: Periodic Update

Legend:

N.A. – Not Applicable

ACGIH – American Conference of Governmental Industrial Hygienists

N.E. – Not Established

SARA – Superfund Amendments and Reauthorization Act of 1986

N.D. – Not Determined

NJRTK – New Jersey Right-to-Know Law

VOC – Volatile Organic Compound

OSHA – Occupational Safety and Health Administration

PEL – Permissible Exposure Limit

HMIS – Hazardous Materials Identification System

TLV – Threshold Limit Value

NTP – National Toxicology Program

CEIL – Ceiling Exposure Limit

STEL – Short Term Exposure Limit

LD50 – Lethal Dose 50

LC50 – Lethal Concentration 50

F – Degree Fahrenheit

MSDS – Material Safety Data Sheet

C – Degree Celsius

CASRN – The Chemical Abstracts Service Registry Number

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. **NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS.** Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.

<End of MSDS>