

AVON, OH 44011  
TELEPHONE: (440) 937-7000

MATERIAL SAFETY DATA SHEET

INST GLASS GLUE 2GR TB/CG  
IDH: 233841

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: INST GLASS GLUE 2GR TB/CG  
Product Type: Cyanoacrylate

2. COMPOSITION, INFORMATION ON INGREDIENTS

Ingredients	CAS No.	%
n-Butyl cyanoacrylate	6606-65-1	65-70
Trimellitic ester	90218-77-2	30-35
Poly (methyl methacrylate)	9011-14-7	3-5
HYDROQUINONE	123-31-9	0.1-0.5

Ingredients which have exposure limits

Exposure Limits (TWA) Ingredients	ACGIH (TLV)	OSHA (PEL)	OTHER
n-Butyl cyanoacrylate	None	None	2 ppm TWA
HYDROQUINONE	2 mg/m3 TWA	2 mg/m3 TWA	2 mg/m3 TWA 4 mg/m3 STEL

Exposure Limits (STEL) Ingredients	ACGIH (TLV)	OSHA (PEL)

3. HAZARDS IDENTIFICATION

Toxicity: Skin contact may cause burns.  
Bonds skin rapidly and strongly.  
Skin and eye irritant.

Primary Routes of Entry: None known

Signs and Symptoms  
of Exposure: Vapor is irritating to eyes and mucous membranes  
above TLV. Prolonged and repeated overexposure to  
vapors may produce symptoms of non-allergic  
asthma in sensitive individuals.

Existing Conditions  
Aggravated by Exposure: None known

Ingredients	Literature Referenced Target Organ and Other Health Effects	Carcinogen		
		NTP	IARC	OSHA
n-Butyl cyanoacrylate	ALG IRR RES	NO	NO	NO
Trimellitic ester	No Data	NO	NO	NO
Poly (methyl methacrylate)	IRR	NO	N/A	NO

AVON, OH 44011  
TELEPHONE: (440) 937-7000

MATERIAL SAFETY DATA SHEET

Product Name: INST GLASS GLUE 2GR TB/CG  
IDH: 233841

3. HAZARDS IDENTIFICATION

(continued)

HYDROQUINONE AC3 BLO BNM CNS EYE IMM IRR LIV NO N/A NO  
MUT SKI THY

Abbreviations

N/A Not Applicable	AC3 ACGIH animal carcinogen.
ALG Allergen	BLO Blood
BNM Bone Marrow	CNS Central nervous system
EYE Eyes	IMM Immune system
IRR Irritant	LIV Liver
MUT Mutagen	RES Respiratory
SKI Skin	THY Thyroid

4. FIRST AID MEASURES

Ingestion: Ingestion is not likely. See supplemental page for emergency procedures.

Inhalation: Remove to fresh air. If symptoms persist, obtain medical attention.

Skin Contact: Soak in warm water. See supplemental page for emergency procedures.

Eye Contact: Flush with water. See supplemental page for emergency procedures.

5. FIRE FIGHTING MEASURES

Flash Point: 150 - 200 øF Method: Tag Closed Cup

Recommended Extinguishing Agents: Carbon dioxide, foam, dry chemical. Do not use water.

Special Firefighting Procedures: Not available

Hazardous Products formed by Fire or Thermal Decomp: Irritating organic fragments.

Unusual Fire or Explosion Hazards: May polymerize exothermically, especially upon contact with water.

Explosive Limits:  
 (% by volume in air)Lower Not available  
 (% by volume in air)Upper Not available

AVON, OH 44011  
TELEPHONE: (440) 937-7000

## MATERIAL SAFETY DATA SHEET

Page 03 of 07

Product Name: INST GLASS GLUE 2GR TB/CG  
IDH: 233841

## 6. ACCIDENTAL RELEASE MEASURES

Steps to be taken in case  
of spill or leak: Flood with water to polymerize. Soak up with an  
inert absorbent.

## 7. HANDLING AND STORAGE

Safe Storage: Store at or below 75°F  
(Contact Loctite Customer Service 1-800-243-4874 for shelf life information)  
Handling: Avoid contact with skin and eyes. Avoid breathing  
vapor.

## 8. EXPOSURE CONTROLS, PERSONAL PROTECTION

Eyes: Safety glasses or goggles.  
Skin: Nitrile or polyethylene gloves and aprons.  
Do not use cotton.  
See supplemental page for additional information.  
Ventilation: Positive down-draft exhaust ventilation should be  
provided to maintain vapor concentration below  
TLV.  
Respiratory: NIOSH/MSHA approved respirator with organic vapors  
cartridge if ventilation is inadequate.  
  
See Section 2 for Exposure Limits.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear liquid.  
Odor: Sharp, irritating  
Boiling Point: More than 300°F  
pH: Does not apply  
Solubility in Water: Polymerized by water  
Specific Gravity: 1.05 at 75°F  
Volatile Organic Compound  
(EPA Method 24) Not available  
Vapor Pressure: Less than 0.2 mm at 75°F  
Vapor Density: Approximately 3  
Evaporation Rate  
(Ether = 1) Not available

## 10. STABILITY AND REACTIVITY

Stability: Stable  
Hazardous Polymerization: May occur  
Incompatibility: Polymerized by contact with water, alcohols,  
amines, alkalis.  
Conditions to Avoid: Not available

AVON, OH 44011  
TELEPHONE: (440) 937-7000

## MATERIAL SAFETY DATA SHEET

Page 04 of 07

Product Name: INST GLASS GLUE 2GR TB/CG  
IDH: 233841

## 10. STABILITY AND REACTIVITY (continued)

Hazardous Decomposition  
Products (non-thermal): None

## 11. TOXICOLOGICAL INFORMATION

Estimated oral LD50 more than 5000 mg/kg.  
Estimated dermal LD50 more than 2000 mg.kg.

## 12. ECOLOGICAL INFORMATION

No data available

## 13. DISPOSAL CONSIDERATIONS

Recommended methods of  
disposal: Incinerate following EPA and local regulations.  
EPA Hazardous Waste  
Number NH - Not a RCRA Hazardous Waste Material

## 14. TRANSPORTATION INFORMATION

## DOT (49 CFR 172)

## Domestic Ground Transport

Proper Shipping Name: Unrestricted (Not more than 450 liters);  
Combustible liquids, n.o.s. (Cyanoacrylate ester)  
(More than 450 liters)

Hazard Class or  
Division: Unrestricted (Not more than 450 liters)  
Combustible liquid (More than 450 liters)

Identification Number: None (Not more than 450 liters);  
NA 1993 (More than 450 liters)

Marine Pollutant: None

## IATA

Proper Shipping Name: Unrestricted (Not more than one pint);  
Aviation regulated liquid, n.o.s., (Cyanoacrylate  
Ester) (More than one pint)

Class or Division: Unrestricted (Not more than one pint);  
Class 9 (More than one pint)

UN or ID Number: None (Not more than one pint)  
UN 3334 (More than one pint)

## 15. REGULATORY INFORMATION

CA Proposition 65: No California Proposition 65 chemicals are known  
to be present.

AVON, OH 44011  
TELEPHONE: (440) 937-7000

MATERIAL SAFETY DATA SHEET

Product Name: INST GLASS GLUE 2GR TB/CG  
IDH: 233841

16. OTHER INFORMATION

Estimated NFPA(R) Code:  
Health Hazard: 2  
Fire Hazard: 2  
Reactivity Hazard: 1  
Specific Hazard: Does not apply

Estimated HMIS(R) Code:  
Health Hazard: 2\*  
Flammability Hazard: 2  
Reactivity Hazards: 1  
Personal Protection: See Section 8.

NFPA is a registered trademark of the National Fire Protection Assn.  
HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared by:  
Company: Safety, Health and Regulatory Affairs - North America,  
Loctite Corp., 1001 Tr Br Cr, Rocky Hill CT 06067  
(24hr.) Phone: (860) 571-5100

AVON, OH 44011  
TELEPHONE: (440) 937-7000

## MATERIAL SAFETY DATA SHEET

Page 06 of 07

Product Name: INST GLASS GLUE 2GR TB/CG  
IDH: 233841

Supplement

INFORMATION FOR FIRST AID AND CASUALTY ON TREATMENT FOR ADHESION OF  
HUMAN SKIN TO ITSELF IF CAUSED BY CYANOACRYLATE ADHESIVES

Cyanoacrylate adhesive is a very fast setting and strong adhesive. It bonds human tissue including skin in seconds. Experience has shown that accidents due to cyanoacrylates are handled best by passive, nonsurgical first aid. Treatment of specific types of accidents are given below.

## SKIN CONTACT

Remove excess adhesive. Soak in warm, soapy water. The adhesive will come loose from the skin in several hours. Cured adhesive does not present a health hazard even when bonded to the skin.

Avoid contact with clothes, fabrics, rags, or tissue. Contact with these materials may cause polymerization. The polymerization of large amounts of adhesive will generate heat causing smoke, skin burns, and strong, irritating vapors. Wear nitrile or polyethylene gloves and apron when handling large amounts of adhesive.

## SKIN ADHESION

First immerse the bonded surfaces in warm, soapy water. Peel or roll the surfaces apart with the aid of a blunt edge, e.g. a spatula or a teaspoon handle; then remove adhesive from the skin with soap and water. Do not try to pull surfaces apart with a direct opposing action.

## EYELID TO EYELID OR EYEBALL ADHESION

In the event that eyelids are stuck together or bonded to the eyeball, wash thoroughly with warm water and apply a gauze patch. The eye will open without further action, typically in 1-4 days. There will be no residual damage. Do not try to open the eyes by manipulation.

## ADHESIVE ON THE EYEBALL

Cyanoacrylate introduced into the eyes will attach itself to the eye protein and will disassociate from it over intermittent periods, generally covering several hours. This will cause periods of weeping until clearance is achieved. During the period of contamination, double vision may be experienced together with a lachrymatory effect, and it is important to understand the cause and realize that disassociation will normally occur within a matter of hours, even with gross contamination.

## MOUTH

If lips are accidentally stuck together, apply lots of warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth. Peel or roll lips apart. Do not try to pull the lips

AVON, OH 44011  
TELEPHONE: (440) 937-7000

MATERIAL SAFETY DATA SHEET

Page 07 of 07

Product Name: INST GLASS GLUE 2GR TB/CG  
IDH: 233841

Supplement

with direct opposing action.

It is almost impossible to swallow cyanoacrylate. The adhesive solidifies and adheres in the mouth. Saliva will lift the adhesive in one half to two days. In case a lump forms in the mouth, position the patient to prevent ingestion of the lump when it detaches.

BURNS

Cyanoacrylates give off heat on solidification. In rare cases a large drop will increase in temperature enough to cause a burn. Burns should be treated normally after the lump of cyanoacrylate is released from the tissue as described above.

SURGERY

It should never be necessary to use such a drastic method to separate accidentally bonded skin.