

MATERIAL SAFETY DATA SHEET

MSDS Name: SC-170tm VAPOR & ACOUSTICAL SOUND SEALANT
MSDS Number: 1305812
Version Number 1
Revision Date: APR-20-2009
Page Number: 1

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: SC-170tm VAPOR & ACOUSTICAL SOUND SEALANT
HMIS Hazard Rating: Health: 1 Fire: 2 Reactivity: 0 PPE: B

Company Identification: HENKEL CORPORATION
7405 PRODUCTION DRIVE
MENTOR OH 44060

Contact (24 hour): Consumer Help (800)624-7767
CHEMTREC Emergency (24 hour):(703) 527-3887 (International)
(800) 424-9300
in Canada CANUTEC 613-996-6666

Product Class SEALANT
Trade Name OSI
Product Code See above

Non-hardening sound caulk for Canada - Black color
-- SCELLANT ACOUSTIQUE

SECTION II - INGREDIENT AND HAZARD INFORMATION

Hazardous Ingredient Name	CAS Number	Percent	TSCA
MINERAL SPIRITS	8052-41-3	5 - 10	Y
SILICA, QUARTZ	14808-60-7	TRACE	Y

Ingredient Notes:
Remaining ingredients are not considered OSHA hazardous.

SECTION III - PHYSICAL AND CHEMICAL PROPERTIES

Form: Non-sag, paste-like caulk
Appearance/Color: BLACK
Solubility (in water): insoluble
pH Value, +/- .3: Not Applicable
Boiling Range: 300.°F - 394.°F (148.89°C - 201.11°C)
Vapor Pressure (mmHg): 2.@ 20.°C (68.°F)
Evaporation Rate: 0.08 times Slower than n-Butyl Acetate

Vapor Density: Heavier than air

MATERIAL SAFETY DATA SHEET

MSDS Name: SC-170tm VAPOR & ACOUSTICAL SOUND SEALANT
MSDS Number: 1305812
Version Number 1
Revision Date: APR-20-2009
Page Number: 2

% Volatile, Weight 10.%
% Volatile, Volume approx 20.%
Specific Gravity: 1.573
VOC (less H2O or exempt) 108 g/l, 0.9#/GL

NOTE:

*BOIL RANGE, EVAP RATE, VAPOR DENSITY AND PRESSURE FOR SOLVENT ONLY!

SECTION IV - FIRE FIGHTING MEASURES

Flammability Class II
Flash Point: 106.°F (41.11°C)
Tag Closed Cup
Explosive Range (LEL/UEL): 0.9%
6.%

EXTINGUISHING MEDIA:

Carbon Dioxide---Dry Chemical---Foam
Use water fog to cool material in vicinity of fire.

SPECIAL FIRE-FIGHTING PROCEDURES:

Use self-contained breathing apparatus with full facepiece
operated in pressure demand with full protective equipment.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Any closed container may rupture when exposed to extreme heat.
Solvent vapors are heavier than air and travel along the ground.
Vapors given off are flammable and may be ignited in air explosively.

SECTION V - HEALTH HAZARD DATA

Route	Species	Exposure and Dose
MINERAL SPIRITS		LC50 700. mg/kg LD50 5000. PPM

ROUTES OF ENTRY:

ENTRY THROUGH... Inhalation and skin most likely

CARCINOGENICITY...

NTP? N/E | IARC Monographs? Yes | OSHA? NO

EFFECTS OF OVEREXPOSURE

Eyes: Can cause irritation, redness, tearing and blurred vision.
Skin: Prolonged or repeated contact can cause moderate
irritation, drying of the skin, and dermatitis.
Inhalation: Excessive inhalation of vapors can cause respiratory
irritation, headache, drowsiness and fatigue. High
concentrations of vapors are anesthetic and may cause
central nervous system effects such as dizziness.

MATERIAL SAFETY DATA SHEET

MSDS Name: SC-170tm VAPOR & ACOUSTICAL SOUND SEALANT
MSDS Number: 1305812
Version Number 1
Revision Date: APR-20-2009
Page Number: 3

Ingestion: Can cause gastrointestinal irritation, nausea,
vomiting and diarrhea.

FIRST AID MEASURES

Eyes: Flush eyes gently with water for at least 15 minutes
lifting eyelids occasionally; get prompt medical attention
Skin: Wash thoroughly with soap and water; apply a mild skin cream.
Remove contaminated clothing.
Inhalation: Move affected person to fresh air; if breathing is
difficult, administer oxygen; if breathing has stopped,
give artificial respiration. Get medical attention.
Ingestion: DO NOT INDUCE VOMITING! Get immediate medical attention.

CHRONIC HAZARDS

NOTICE: Reports have associated repeated and prolonged
occupational overexposure to solvents with permanent brain,
nervous system, liver or kidney damage or may cause cardiac
arrhythmia. INTENTIONAL misuse of this product by
deliberately inhaling its vapors may be harmful or fatal.
SILICA: Normal use of this product does not produce dust. Sanding dried
material could generate trace amounts of Silica (quartz) which
is a suspect human carcinogen (IARC group 1).
Repeated and prolonged occupational overexposure to Crystalline
Silica may cause silicosis, a progressively disabling lung disease.

SECTION VI - STABILITY AND REACTIVITY

Stability: Product is stable under normal storage conditions
Hazardous Polymerization: Will not occur under normal conditions

INCOMPATIBILITY:

Keep away from strong oxidizing agents.

CONDITIONS TO AVOID:

Keep away from heat, spark, open flames and any ignition source.

HAZARDOUS DECOMPOSITION PRODUCTS:

Will produce fumes and smoke containing carbon monoxide and
dioxide under fire conditions.

SECTION VII - ACCIDENTAL RELEASE AND DISPOSAL MEASURES:

STEPS TO BE TAKEN IN CASE OF SPILL:

Eliminate all ignition sources. Ventilate confined areas.
(Open windows and doors). Wear appropriate protective clothing.
Cover with absorbent. Scoop into sealable safety container.

WASTE DISPOSAL METHOD:

Dispose of following local, state, and federal regulations.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

MATERIAL SAFETY DATA SHEET

MSDS Name: SC-170tm VAPOR & ACOUSTICAL SOUND SEALANT
MSDS Number: 1305812
Version Number 1
Revision Date: APR-20-2009
Page Number: 4

Occupational Exposure Limits

Table with 5 columns: ACGIH TLV, ACGIH TLV-C, ACGIH STEL, OSHA STEL, OSHA PEL. Rows include MINERAL SPIRITS and SILICA, QUARTZ with their respective exposure limits.

Note: The TLV for Silica is for the respirable fraction of dust only.

RESPIRATORY PROTECTION:

If TLV of the product is exceeded, a NIOSH/MSHA jointly approved air supply respirator is advised in the absence of proper ventilation. OSHA regulations also permit the use of other types of NIOSH/MSHA respirators under specified conditions. (See your safety equipment supplier for more information)

VENTILATION:

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV. Ventilate during application and curing of this product.

PROTECTIVE CLOTHING:

Rubber gloves should be worn where skin contact is likely. Wear impervious clothing and shoes.

EYE PROTECTION:

Chemical goggles or safety glasses should be worn.

HANDLING AND STORAGE PRECAUTIONS:

Keep away from heat, spark and flame. Keep out of reach of children. Keep container closed while not in use. Do not cut or burn recepticals that have contained a solvent based product. Do not reuse this container. Use only in a well ventilated area.

N/A=NOT APPLICABLE N/AV=NOT AVAILABLE N/E, N/est=NOT ESTABLISHED

SECTION IX - TRANSPORT INFORMATION: (not all sizes available)

GROUND TRANSPORT (DOT) - DOMESTIC

Units less than 5L (1.3 gallons liquid) i.e. cartridges

Proper Shipping Name: CONSUMER COMMODITY
Classification: ORM-D
DOT Label Required: ORM-D
Shipping Document: CONSUMER COMMODITY
ERG Code: 171

MATERIAL SAFETY DATA SHEET

MSDS Name: SC-170tm VAPOR & ACOUSTICAL SOUND SEALANT
MSDS Number: 1305812
Version Number 1
Revision Date: APR-20-2009
Page Number: 5

Units GREATER than 5L i.e. 5gal. pail, 50 gal.drum
Proper Shipping Name: ADHESIVE
Classification: CLASS 3
DOT Label Required: Flammable liquid, UN1133, Class 3
Shipping Document: ADHESIVE,3, UN1133, PG III
ERG Code: 128

AIR TRANSPORT (DOT) - DOMESTIC

Units less than 5L (1.3 gallons liquid) i.e. cartridges

Proper Shipping Name: CONSUMER COMMODITY
Classification: ORM-D
DOT Label Required: ORM-D-AIR
Shipping Document: Consumer Commodity, ORM-D
ERG Code: 171

Units GREATER than 5L i.e. 5gal. pail, 50 gal. drum
Proper Shipping Name: ADHESIVE
Classification: Class 3
DOT Label Required: Flammable Liquid, UN 1133, Class 3
Shipping Document: ADHESIVE, 3, UN1133, PG III
ERG Code: 128

AIR TRANSPORT (IATA) - INTERNATIONAL

Units less than 5 Liters i.e. one 12 PACK of 10oz (300gm) cartridges

Proper Shipping Name: CONSUMER COMMODITY
Classification: class 9
Label Required: ID8000
Shipping Document: Consumer Commodity,9, ID8000
ERG Code: 9L

Units GREATER than 5L i.e. 5gal. pail, 50 gal. drum
Proper Shipping Name: ADHESIVE
Classification: Class 3
Label Required: Flammable Liquid, UN 1133, Class 3
Shipping Document: ADHESIVE, 3, UN1133, PG III
ERG Code: 3L

MARINE - OCEAN TRANSPORT (IMDG)

Units less than 5L (1.3 gallons liquid) i.e. cartridges

Proper Shipping Name: ADHESIVE
Classification: Class 3
Label Required: Flammable Liquid, UN1133, Class 3, Ltd. Qty.
(on ocean container only, not req. on cartons)
Shipping Document: ADHESIVE,3, UN1133, PG III, LTD.QTY.
EMS Code: F-E, S-D

MATERIAL SAFETY DATA SHEET

MSDS Name: SC-170tm VAPOR & ACOUSTICAL SOUND SEALANT
MSDS Number: 1305812
Version Number 1
Revision Date: APR-20-2009
Page Number: 6

Units GREATER than 5L i.e. 5gal. pail, 50 gal. drum
Proper Shipping Name: ADHESIVE
Classification: Class 3
Label Required: Flammable Liquid, UN 1133, Class 3
Shipping Document: ADHESIVE, 3, UN1133, PG III
EMS Code: F-E, S-D

SECTION X - REGULATORY INFORMATION:

SARA Section 311/312 Hazard Categories met: Fire Hazard,
Immediate (Acute) and Delayed (Chronic) Health Hazards.

Chemical ingredients are listed on the TSCA inventory.

WARNING: This product contains chemicals known to the State of Cali-
fornia to cause cancer and birth defects or other reproductive harm.

CANADA Note:

This MSDS has been prepared according to the criteria of the
Controlled Products Regulation (CPR) and the MSDS contains all of the
information required by the CPR.

Oil / water coefficient: N/AP

WHMIS CLASS: When labeled as Consumer Commodity this product is
exempt from WHMIS regulations. (Sect. 12f Hazardous Products Act)

DISCLAIMER:

The information contained herein is based on data available as of the
date of preparation of this MSDS and which we believe to be reliable.
However, no warranty is expressed or implied regarding the accuracy
of the data. We shall not be responsible for the use of this infor-
mation, or of any product, method, apparatus mentioned, and user must
make his own investigation to determine the suitability of the infor-
mation or products for his particular purpose, for the protection of
the environment, and the health & safety of the users of this material.