



Form

F 7.3.29

MATERIAL SAFETY DATA SHEET

Rev: B
Page: 1 of 3
Date: 01/25/07

I. PRODUCT IDENTIFICATION

TRADE NAME (as labeled): LATICRETE Premium Acrylic Caulk

CHEMICAL FAMILY: proprietary blend

MANUFACTURER'S NAME: LATICRETE INTERNATIONAL, INC.
1 Laticrete Park, N.
Bethany, CT 06524-3423 USA

Phone number for additional information: (203) 393-0010 or website :www.laticrete.com

Date prepared or revised: 12/08 Name of preparer: S.B. Fine

II. HAZARDOUS INGREDIENTS

CHEMICAL NAMES	CAS NUMBERS	PERCENT	ACGIH TLV	OSHA PEL	OTHER (SPECIFY)
Petroleum Distillate	64742-88-7	< 1.0	100 ppm	100 ppm	N/A
Calcium Carbonate** as nuisance particulate, total)	1317-65-3	< 30	10 mg/m ³	15 mg/m ³	N/A
Aqueous TerPolymer Emulsion) (see Sec. IX)	(Mixture	< 35	N/A	N/A	N/A
Benzoate ester	proprietary	< 10	N/A	N/A	N/A
Amino Methyl Propanol 95	124-68-5	< 0.20	10	15 mg/m ³	N/A
Rutile Titanium Dioxide	13463-67-7	< 2.50	0.1 mg/m ³	0.1 mg/m ³	N/A
Silicon Dioxide as Quartz ** (Sanded Formulas Only)	14808-60-7	<30	0.1 mg/m ³	N/A	N/A

N/A = Not applicable or available

III. HEALTH HAZARD INFORMATION

SYMPTOMS OF OVEREXPOSURE for each potential route of exposure.

Inhaled: High vapor concentrations may produce headache, dizziness and nausea. May cause respiratory irritation.

Contact with skin or eyes: Prolonged or repeated contact may cause mild skin and eye irritation.

Absorbed through skin: N/A

Swallowed: N/A

SUSPECTED CANCER AGENT?

NO: This product's ingredients are not found in the lists below.

YES: Federal OSHA NTP IARC



MATERIAL SAFETY DATA SHEET

Form

F 7.3.29

Rev: B
Page: 2 of 3
Date: 01/25/07

IV. FIRST AID: EMERGENCY PROCEDURES

Eye Contact: Irrigate immediately for at least 15 minutes. See a physician if irritation persists.
Skin Contact: Wipe material from skin with cloth/paper towel; wash with soap and water. Get medical help if irritation persists.
Inhaled: Remove to fresh air. Seek medical attention if necessary.
Swallowed: Seek immediate medical attention.

V. FIRE AND EXPLOSION

Flash Point method): >200°F (Non Flam)
Auto ignition temperature, °F: N/A
Flammable limits in air, volume %: N/A Lower (LEL) _____ Upper (UEL) _____
Fire extinguishing materials:
 water spray carbon dioxide other:
 foam dry chemical

Special fire fighting procedures: Wear positive pressure self-contained breathing apparatus. Use water spray or fog to cool fire-exposed containers.
Unusual fire and explosion hazards: Closed containers may explode when exposed to extreme heat.

VI. SPILL, LEAK, AND DISPOSAL PROCEDURES

Spill response procedures (include employee protection measures): dust masks, safety glasses, and long sleeved clothing. Clean up with absorbent material.
Preparing wastes for disposal (container types, neutralization, etc.): N/A

NOTE: Dispose of all wastes in accordance with federal, state and local regulations.

VII. Handling and Storage

Wear dust masks, safety glasses, and long sleeved clothing when handling. Store in dry, well ventilated areas.

VIII. Exposure Controls and Personal Protection

Ventilation and engineering controls: Normal
Respiratory protection (type): Not normally required. TLV exceeded/symptoms of overexposure, wear NIOSH-approved respirator organic vapors
Eye protection (type): Safety glasses or goggles
Gloves (specify material): Impervious gloves
Other clothing and equipment: Long sleeved clothing
Work practices, hygienic practices: Normal Good housekeeping
Other handling and storage requirements: N/A

