



Material Safety Data Sheet

Material Name: Opticolor - Part A

ID: SAH00188

*** Section 1 - Chemical Product and Company Identification ***

Material Name: Opticolor - Part A

Product Use

Grout

Manufacturer Information

USA and Puerto Rico

MAPEI

1144 East Newport Center Drive

Deerfield Beach, FL 33442

Phone: 1-954-246-8888

Canada

MAPEI

2900 Francis-Hughes Avenue

Laval, QC H7L 3J5

Phone: 1-450-662-1212

IN THE EVENT OF A CHEMICAL EMERGENCY INVOLVING A SPILL, LEAK, FIRE, EXPLOSION, EXPOSURE OR ACCIDENT, CONTACT THE FOLLOWING NUMBERS:

Emergency 24 hour numbers:

(USA) CHEMTREC 1-800-424-9300

(Canada) CANUTEC 1-631-996-6666

*** Section 2 - Hazards Identification ***

Emergency Overview

This product has been evaluated using criteria specified in 29CFR 1910.1200 (Hazard Communication Standard).

This product is irritating to the eyes and skin. May cause sensitization by skin contact.

Hazard Statements

CAUTION! IRRITANT. ALLERGEN. Irritating to eyes and skin. May cause sensitization by skin contact. Wear suitable gloves, eye/face protection, and respiratory protection. Keep out of the reach of children.

Potential Health Effects: Eyes

This product is irritating to the eyes.

Potential Health Effects: Skin

This product is irritating to the skin. Prolonged or repeated skin contact may cause skin irritation or allergic skin sensitization reaction.

Potential Health Effects: Ingestion

Acute ingestion may result in mild gastrointestinal distress.

Potential Health Effects: Inhalation

This product may cause irritation to the respiratory system.

Medical Conditions Aggravated by Exposure

Hypersensitivity to product, allergies, and skin or respiratory disorders

Potential Environmental Effects

None identified.

HMIS Ratings: Health: 2 Fire: 1 Reactivity: 1 Pers. Prot.: Safety glasses, gloves

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

*** Section 3 - Composition / Information on Ingredients ***

CAS #	Component	Percent
28064-14-4	Epoxy resin	40-70
68609-97-2	Alkyl Epoxy Resin	10-30
25085-99-8	Epoxy Resin	10-30
100-51-6	Benzyl alcohol	3-7
67762-90-7	Dimethyl silicone polymer with silica	1-5

Material Safety Data Sheet

Material Name: Opticolor - Part A

ID: SAH00188

*** Section 4 - First Aid Measures ***

First Aid: Eyes

In case of contact, immediately flush eyes with large amounts of water, continuing to flush for 15 minutes. If irritation persists get medical attention.

First Aid: Skin

For skin contact, flush with large amounts of water. If irritation persists, get medical attention.

First Aid: Ingestion

For ingestion, flush out mouth with water. If ingestion of a large amount does occur, seek medical attention. Do not induce vomiting.

First Aid: Inhalation

If inhaled, immediately remove the affected person to fresh air. If the affected person is not breathing, apply artificial respiration. If symptoms persist, get medical attention.

First Aid: Notes to Physician

Provide general supportive measures and treat symptomatically.

*** Section 5 - Fire Fighting Measures ***

General Fire Hazards

See Section 9 for Flammability Properties.

This product is combustible at high temperatures.

Hazardous Combustion Products

Irritating and toxic gases or fumes may be released during a fire. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Extinguishing Media

Dry chemical (preferred), foam, water.

Fire Fighting Equipment/Instructions

Firefighters should wear full protective gear.

NFPA Ratings: Health: 2 Fire: 1 Reactivity: 1

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

*** Section 6 - Accidental Release Measures ***

Personal Precautions

Wear appropriate protective equipment and clothing during clean-up.

Containment Procedures

Absorb with inert absorbent such as dry clay, sand or diatomaceous earth, commercial sorbents, or recover using pumps. Scoop up used absorbent into drums or other appropriate container.

Environmental Precautions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

Clean-Up Procedures

Attempt to reclaim the free product, if this is possible. Shovel the material into waste container. Thoroughly wash the area with water after a spill or leak clean-up. Wear appropriate protective equipment and clothing during clean-up.

Evacuation Procedures

None identified.

Special Procedures

Regulations vary. Consult local authorities before disposal.

*** Section 7 - Handling and Storage ***

Handling Procedures

Avoid getting this material into contact with your skin and eyes. Use this product with adequate ventilation. Wash hands after handling and before eating. Keep out of the reach of children.

Material Safety Data Sheet

Material Name: Opticolor - Part A

ID: SAH00188

Storage Procedures

Store at ambient temperature and atmospheric pressure. Store away from strong oxidizers.

*** Section 8 - Exposure Controls / Personal Protection ***

A: Component Exposure Limits

ACGIH, OSHA, NIOSH or the provinces of Canada have not developed exposure limits for any of this product's components.

Engineering Controls

Use general ventilation.

PERSONAL PROTECTIVE EQUIPMENT

Personal Protective Equipment: Eyes/Face

Wear safety glasses with side shields.

Personal Protective Equipment: Skin

The use of nitrile-latex gloves is recommended.

Personal Protective Equipment: Respiratory

Not normally needed. If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

Personal Protective Equipment: General

Launder contaminated clothing before reuse. Use good industrial hygiene practices in handling this material.

*** Section 9 - Physical & Chemical Properties ***

Appearance:	Beige Paste	Odor:	Slight latex odor
Physical State:	Paste	pH:	6.07
Vapor Pressure:	N/A	Vapor Density:	N/A
Boiling Point:	N/A	Melting Point:	N/A
Solubility (H₂O):	Insoluble	Specific Gravity:	0.70 - 1.00
Evaporation Rate:	N/A	VOC:	16 g/L (mixture)
Octanol/H₂O Coeff.:	N/A	Flash Point:	
Flash Point Method:	>212° F (>100° C)	Upper Flammability Limit (UFL):	CC
Lower Flammability Limit (LFL):	N/A	Burning Rate:	N/A
Auto Ignition:	N/A		

Physical Properties: Additional Information

The data provided in this section is to be used for product safety handling purposes. Please refer to Product Data Sheets, Certificates of Conformity or Certificates of Analysis for chemical and physical data for determinations of quality and for formulation purposes.

*** Section 10 - Chemical Stability & Reactivity Information ***

Chemical Stability

This is a stable material.

Chemical Stability: Conditions to Avoid

Do not freeze.

Incompatibility

This product may react with strong oxidizing agents.

Hazardous Decomposition

Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Possibility of Hazardous Reactions

Will not occur.

Material Safety Data Sheet

Material Name: Opticolor - Part A

ID: SAH00188

*** Section 11 - Toxicological Information ***

Acute Dose Effects

A: General Product Information

No information available for the product.

B: Component Analysis - LD50/LC50

Alkyl Epoxy Resin (68609-97-2)

Oral LD50 Rat: 17100 mg/kg

Benzyl alcohol (100-51-6)

Inhalation LC50 Rat: 8.8 mg/L/4H; Oral LD50 Rat:1230 mg/kg; Dermal LD50 Rabbit:2000 mg/kg

Carcinogenicity

A: General Product Information

No information available for the product.

B: Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, OSHA, NIOSH, or NTP.

Sensitization

This product may be sensitizing by prolonged skin contact.

*** Section 12 - Ecological Information ***

Ecotoxicity

A: General Product Information

No information available for the product.

B: Component Analysis - Ecotoxicity - Aquatic Toxicity

Benzyl alcohol (100-51-6)

Test & Species		Conditions
96 Hr LC50 Pimephales promelas	460 mg/L	[static]
96 Hr LC50 Lepomis macrochirus	10 mg/L	[static]
3 Hr EC50 Anabaena variabilis	35 mg/L	
48 Hr EC50 water flea	23 mg/L	

*** Section 13 - Disposal Considerations ***

US EPA Waste Number & Descriptions

A: General Product Information

Waste must be handled in accordance with all federal, state, provincial, and local regulations. Consult authorities before disposal.

B: Component Waste Numbers

No EPA Waste Numbers are applicable for this product's components.

Disposal Instructions

Waste must be handled in accordance with all federal, state, provincial, and local regulations. Consult authorities before disposal.

See Section 7 for Handling Procedures. See Section 8 for Personal Protective Equipment recommendations.

*** Section 14 - Transportation Information ***

International Transportation Regulations

Not regulated as dangerous goods.

*** Section 15 - Regulatory Information ***

US Federal Regulations

A: General Product Information

All components are on the U.S. EPA TSCA Inventory List. All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List unless otherwise noted.

Material Safety Data Sheet

Material Name: Opticolor - Part A

ID: SAH00188

B: Component Analysis

None of this products components are listed under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), or CERCLA (40 CFR 302.4).

State Regulations

A: General Product Information

Other state regulations may apply. Check individual state requirements.

B: Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
Benzyl alcohol	100-51-6	No	Yes	Yes	No	Yes	No

Canadian WHMIS Information

A: General Product Information



B: Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS #	Minimum Concentration
Benzyl alcohol	100-51-6	1 %

Additional Regulatory Information

A: General Product Information

Supplier(s) of proprietary component(s) state that these components are contained on the TSCA inventory.

B: Component Analysis - Inventory

Component	CAS #	TSCA	CAN	EEC
Epoxy resin	28064-14-4	Yes	DSL	No
Alkyl Epoxy Resin	68609-97-2	Yes	DSL	EINECS
Epoxy Resin	25085-99-8	Yes	DSL	No
Benzyl alcohol	100-51-6	Yes	DSL	EINECS
Dimethyl silicone polymer with silica	67762-90-7	Yes	DSL	No

*** Section 16 - Other Information ***

Reference Version (internal)

15-2412-03

Other Information

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. However, no warranty, expressed or implied, is given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

Key/Legend

NA = Not available or Not Applicable. NFPA = National Fire Protection Association. HMIS = Hazardous Material Information System. CFR = Code of Federal Regulations. EPA = Environmental Protection Agency; TSCA = Toxic Substance Control Act; ACGIH = American Conference of Governmental Industrial Hygienists; IARC = International Agency for Research on Cancer; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration., NJTSR = New Jersey Trade Secret Registry.

Contact: Product Safety Specialist

Contact Phone: 1-954-246-8888

End of Sheet SAH00188



Material Safety Data Sheet

Material Name: Opticolor - Part B

ID: SAH00189

*** Section 1 - Chemical Product and Company Identification ***

Material Name: Opticolor - Part B

Product Use

Grout

Manufacturer Information

USA and Puerto Rico

MAPEI

1144 East Newport Center Drive

Deerfield Beach, FL 33442

Phone: 1-954-246-8888

Canada

MAPEI

2900 Francis-Hughes Avenue

Laval, QC H7L 3J5

Phone: 1-450-662-1212

IN THE EVENT OF A CHEMICAL EMERGENCY INVOLVING A SPILL, LEAK, FIRE, EXPLOSION, EXPOSURE OR ACCIDENT, CONTACT THE FOLLOWING NUMBERS:

Emergency 24 hour numbers:

(USA) CHEMTREC 1-800-424-9300

(Canada) CANUTEC 1-631-996-6666

*** Section 2 - Hazards Identification ***

Emergency Overview

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication). Causes burns to the skin and eyes. This product is combustible.

Hazard Statements

DANGER! CORROSIVE. COMBUSTIBLE. Causes burns to the skin and eyes. Irritating to respiratory system. Vapor harmful. Wear suitable gloves, eye/face protection, and respiratory protection. Keep out of the reach of children.

Potential Health Effects: Eyes

This product is severely irritating to the eyes and may cause eye burns.

Potential Health Effects: Skin

This product is severely irritating to the skin and may cause burns.

Potential Health Effects: Ingestion

Ingestion of this product may cause nausea, vomiting and diarrhea.

Potential Health Effects: Inhalation

This product may be fatal if it is inhaled.

Medical Conditions Aggravated by Exposure

Hypersensitivity to product, allergies, and skin or respiratory disorders

Potential Environmental Effects

None identified.

HMIS Ratings: Health: 3 Fire: 2 Reactivity: 1 Pers. Prot.: Safety glasses, gloves, synthetic apron, vapor respirator if airborne concentrations exceed exposure limits

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

*** Section 3 - Composition / Information on Ingredients ***

CAS #	Component	Percent
68951-85-9	Fatty acids, tall-oil, polymers with bisphenol A, diethylenetriamine, epichlorohydrin and tetraethylenepentamine	60-100
100-51-6	Benzyl alcohol	10-30
2855-13-2	Isophorone diamine	5-10

Material Safety Data Sheet

Material Name: Opticolor - Part B

ID: SAH00189

109-55-7	3-(Dimethylamino)-propylamine	1-5
----------	-------------------------------	-----

*** Section 4 - First Aid Measures ***

First Aid: Eyes

In case of contact, immediately flush eyes with large amounts of water, continuing to flush for 15 minutes. If irritation persists get medical attention.

First Aid: Skin

For skin contact, wash immediately with soap and water. If irritation persists, get medical attention.

First Aid: Ingestion

For ingestion, flush out mouth with water. Get medical attention or advice. Do not induce vomiting.

First Aid: Inhalation

If inhaled, immediately remove the affected person to fresh air. If the affected person is not breathing, apply artificial respiration. If symptoms persist, get medical attention.

First Aid: Notes to Physician

Provide general supportive measures and treat symptomatically.

*** Section 5 - Fire Fighting Measures ***

General Fire Hazards

See Section 9 for Flammability Properties.

This product is combustible. Keep this product from heat, sparks, or open flame.

Hazardous Combustion Products

Irritating and toxic gases or fumes may be released during a fire. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Extinguishing Media

Dry chemical (preferred), foam, water.

Fire Fighting Equipment/Instructions

Firefighters should wear full protective gear.

NFPA Ratings: Health: 3 Fire: 2 Reactivity: 1

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

*** Section 6 - Accidental Release Measures ***

Personal Precautions

Wear appropriate protective equipment and clothing during clean-up.

Containment Procedures

Dike the spilled material, where this is possible. Absorb with inert absorbent such as dry clay, sand or diatomaceous earth, commercial sorbents, or recover using pumps. Scoop up used absorbent into drums or other appropriate container.

Environmental Precautions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

Clean-Up Procedures

Attempt to reclaim the free product, if this is possible. Thoroughly wash the area with water after a spill or leak clean-up. Keep out of the reach of children.

Evacuation Procedures

None identified.

Special Procedures

Regulations vary. Consult local authorities before disposal.

*** Section 7 - Handling and Storage ***

Handling Procedures

Keep this product from heat, sparks, or open flame. Avoid getting this material into contact with your skin and eyes. Avoid breathing vapors or mists of this product. Wash hands after handling and before eating. Keep out of the reach of children.

Material Safety Data Sheet

Material Name: Opticolor - Part B

ID: SAH00189

Storage Procedures

Store in a cool, dry, well-ventilated area. Store at ambient temperature and atmospheric pressure. Store away from strong oxidizers.

*** Section 8 - Exposure Controls / Personal Protection ***

A: Component Exposure Limits

3-(Dimethylamino)-propylamine (109-55-7)

Ontario: 0.5 ppm TWAEV; 2 mg/m³ TWAEV

Engineering Controls

Use general ventilation.

PERSONAL PROTECTIVE EQUIPMENT

Personal Protective Equipment: Eyes/Face

Wear safety glasses with side shields.

Personal Protective Equipment: Skin

The use of nitrile-latex gloves is recommended.

Personal Protective Equipment: Respiratory

If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

Personal Protective Equipment: General

Laundry contaminated clothing before reuse. Use good industrial hygiene practices in handling this material.

*** Section 9 - Physical & Chemical Properties ***

Appearance:	Amber liquid	Odor:	Amine odor
Physical State:	Liquid	pH:	10.91
Vapor Pressure:	N/A	Vapor Density:	N/A
Boiling Point:	N/A	Melting Point:	32° F (0° C)
Solubility (H₂O):	Insoluble	Specific Gravity:	1.00 - 1.30
Evaporation Rate:	N/A	VOC:	16 g/L (mixture)
Octanol/H₂O Coeff.:	N/A	Flash Point:	164° F (73° C)
Flash Point Method:	CC	Upper Flammability Limit (UFL):	N/A
Lower Flammability Limit (LFL):	N/A	Burning Rate:	N/A
Auto Ignition:	N/A		

Physical Properties: Additional Information

The data provided in this section is to be used for product safety handling purposes. Please refer to Product Data Sheets, Certificates of Conformity or Certificates of Analysis for chemical and physical data for determinations of quality and for formulation purposes.

*** Section 10 - Chemical Stability & Reactivity Information ***

Chemical Stability

Stable under normal conditions.

Chemical Stability: Conditions to Avoid

Keep away from heat, sparks, or open flame. Do not freeze.

Incompatibility

This product may react with strong acids, bases and oxidizing agents.

Hazardous Decomposition

Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition. Upon decomposition, this product may emit fumes of carbon monoxide, carbon dioxide, oxides of nitrogen, and other organic compounds.

Material Safety Data Sheet

Material Name: Opticolor - Part B

ID: SAH00189

Possibility of Hazardous Reactions

Will not occur.

*** Section 11 - Toxicological Information ***

Acute Dose Effects

A: General Product Information

No information available for the product.

B: Component Analysis - LD50/LC50

Benzyl alcohol (100-51-6)

Inhalation LC50 Rat: 8.8 mg/L/4H; Oral LD50 Rat:1230 mg/kg; Dermal LD50 Rabbit:2000 mg/kg

Isophorone diamine (2855-13-2)

Oral LD50 Rat: 1030 mg/kg

3-(Dimethylamino)-propylamine (109-55-7)

Inhalation LC50 Rat: >4.31 mg/L/4H; Oral LD50 Rat:922 mg/kg; Dermal LD50 Rabbit:600 µL/kg

Carcinogenicity

A: General Product Information

No information available for the product.

B: Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, OSHA, NIOSH, or NTP.

Sensitization

No information available for the product.

*** Section 12 - Ecological Information ***

Ecotoxicity

A: General Product Information

No information available for the product.

B: Component Analysis - Ecotoxicity - Aquatic Toxicity

Benzyl alcohol (100-51-6)

Test & Species		Conditions
96 Hr LC50 Pimephales promelas	460 mg/L	[static]
96 Hr LC50 Lepomis macrochirus	10 mg/L	[static]
3 Hr EC50 Anabaena variabilis	35 mg/L	
48 Hr EC50 water flea	23 mg/L	

Isophorone diamine (2855-13-2)

Test & Species		Conditions
96 Hr LC50 Leuciscus idus	110 mg/L	[semi-static]
72 Hr EC50 Scenedesmus subspicatus	37 mg/L	

3-(Dimethylamino)-propylamine (109-55-7)

Test & Species		Conditions
96 Hr LC50 Leuciscus idus	122 mg/L	[static]
72 Hr EC50 Scenedesmus subspicatus	56.2 mg/L	
96 Hr EC50 Scenedesmus subspicatus	57.5 mg/L	

*** Section 13 - Disposal Considerations ***

US EPA Waste Number & Descriptions

A: General Product Information

No additional information available.

B: Component Waste Numbers

No EPA Waste Numbers are applicable for this product's components.

Material Safety Data Sheet

Material Name: Opticolor - Part B

ID: SAH00189

Disposal Instructions

Waste must be handled in accordance with all federal, state, provincial, and local regulations. Consult authorities before disposal.

See Section 7 for Handling Procedures. See Section 8 for Personal Protective Equipment recommendations.

*** Section 14 - Transportation Information ***

US DOT Information

Shipping Name: Amines, liquid, corrosive, n.o.s. (Isophorone diamine)

UN/NA #: UN2735 **Hazard Class:** 8 **Packing Group:** III

IATA Information

Shipping Name: Amines, liquid, corrosive, n.o.s. (Isophorone diamine)

UN #: UN2735 **Hazard Class:** 8 **Packing Group:** III

TDG Information

Shipping Name: Amines, liquid, corrosive, n.o.s. (Isophorone diamine)

UN/NA #: UN2735 **Hazard Class:** 8 **Packing Group:** III

*** Section 15 - Regulatory Information ***

US Federal Regulations

A: General Product Information

All components are on the U.S. EPA TSCA Inventory List. All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List unless otherwise noted.

B: Component Analysis

None of this products components are listed under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), or CERCLA (40 CFR 302.4).

State Regulations

A: General Product Information

Other state regulations may apply. Check individual state requirements.

B: Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
Benzyl alcohol	100-51-6	No	Yes	Yes	No	Yes	No
Isophorone diamine	2855-13-2	No	No	No	Yes	No	No
3-(Dimethylamino)-propylamine	109-55-7	No	Yes	No	Yes	Yes	No

Canadian WHMIS Information

A: General Product Information



B: Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS #	Minimum Concentration
Benzyl alcohol	100-51-6	1 %
Isophorone diamine	2855-13-2	1 %

Additional Regulatory Information

A: General Product Information

Supplier(s) of proprietary component(s) state that these components are contained on the TSCA inventory.

Material Safety Data Sheet

Material Name: Opticolor - Part B

ID: SAH00189

B: Component Analysis - Inventory

Component	CAS #	TSCA	CAN	EEC
Fatty acids, tall-oil, polymers with bisphenol A, diethylenetriamine, epichlorohydrin and tetraethylenepentamine	68951-85-9	Yes	DSL	No
Benzyl alcohol	100-51-6	Yes	DSL	EINECS
Isophorone diamine	2855-13-2	Yes	DSL	EINECS
3-(Dimethylamino)-propylamine	109-55-7	Yes	DSL	EINECS

*** Section 16 - Other Information ***

Reference Version (internal)

I5-2413-02

Other Information

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use.

Key/Legend

NA = Not available or Not Applicable. ACGIH = American Conference of Governmental Industrial Hygienists. NFPA = National Fire Protection Association. EPA = Environmental Protection Agency; TSCA = Toxic Substance Control Act; ACGIH = American Conference of Governmental Industrial Hygienists; IARC = International Agency for Research on Cancer; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration., NJTSR = New Jersey Trade Secret Registry.

Contact: Product Safety Specialist

Contact Phone: 1-954-246-8888

End of Sheet SAH00189



Material Safety Data Sheet

Material Name: Opticolor - Part C

ID: SAH00190

*** Section 1 - Chemical Product and Company Identification ***

Material Name: Opticolor - Part C

Product Use

Grout

Manufacturer Information

USA and Puerto Rico

MAPEI

1144 East Newport Center Drive

Deerfield Beach, FL 33442

Phone: 1-954-246-8888

Canada

MAPEI

2900 Francis-Hughes Avenue

Laval, QC H7L 3J5

Phone: 1-450-662-1212

IN THE EVENT OF A CHEMICAL EMERGENCY INVOLVING A SPILL, LEAK, FIRE, EXPLOSION, EXPOSURE OR ACCIDENT, CONTACT THE FOLLOWING NUMBERS:

Emergency 24 hour numbers:

(USA) CHEMTREC 1-800-424-9300

(Canada) CANUTEC 1-631-996-6666

*** Section 2 - Hazards Identification ***

Emergency Overview

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication). This product is irritating to the eyes. May be harmful or fatal if swallowed.

Hazard Statements

CAUTION! Irritating to eyes. Chronic lung disease (silicosis) and/or lung cancer may result from prolonged/repeated breathing of the dust of this material. Wear suitable gloves, eye/face protection, and respiratory protection. Keep out of the reach of children.

Potential Health Effects: Eyes

This product is irritating to the eyes. Symptoms can include irritation, redness, scratching of the cornea, and tearing.

Potential Health Effects: Skin

This product may cause irritation to the skin. Prolonged and/or repeated skin contact may result in mild irritation or redness. Mechanical rubbing may increase skin irritation.

Potential Health Effects: Ingestion

Ingestion of this product is unlikely. However, ingestion of product may produce gastrointestinal irritation and disturbances.

Potential Health Effects: Inhalation

This product may be harmful by inhalation. Chronic lung disease (silicosis) and/or lung cancer may result from prolonged/repeated breathing of the dust of this material. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.

Medical Conditions Aggravated by Exposure

Hypersensitivity to product, allergies, and skin or respiratory disorders

Potential Environmental Effects

None identified.

HMIS Ratings: Health: 1* **Fire:** 0 **Reactivity:** 0 **Pers. Prot.:** Safety glasses, gloves, and N95 respirator if dust exposure exceeds TLV values

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

*** Section 3 - Composition / Information on Ingredients ***

Material Safety Data Sheet

Material Name: Opticolor - Part C

ID: SAH00190

CAS #	Component	Percent
14808-60-7	Silica Sand	60-100

*** Section 4 - First Aid Measures ***

First Aid: Eyes

In case of contact, immediately flush eyes with large amounts of water, continuing to flush for 15 minutes. If irritation persists get medical attention.

First Aid: Skin

For skin contact, flush with large amounts of water. If irritation persists, get medical attention.

First Aid: Ingestion

For ingestion, flush out mouth with water. If ingestion of a large amount does occur, seek medical attention. Do not induce vomiting.

First Aid: Inhalation

If inhaled, immediately remove the affected person to fresh air. If the affected person is not breathing, apply artificial respiration. If symptoms persist, get medical attention.

First Aid: Notes to Physician

Provide general supportive measures and treat symptomatically.

*** Section 5 - Fire Fighting Measures ***

General Fire Hazards

See Section 9 for Flammability Properties.

As with all dry powders, it is advisable to ground mechanical equipment in contact with dry material to dissipate the potential buildup of static electricity.

Hazardous Combustion Products

Irritating and toxic gases or fumes may be released during a fire. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Extinguishing Media

Dry chemical (preferred), foam, water.

Fire Fighting Equipment/Instructions

Firefighters should wear full protective clothing including self contained breathing apparatus.

NFPA Ratings: Health: 1 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

*** Section 6 - Accidental Release Measures ***

Personal Precautions

Avoid the generation of dusts during clean-up. Wear appropriate protective equipment and clothing during clean-up.

Containment Procedures

Contain the discharged material.

Environmental Precautions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

Clean-Up Procedures

Attempt to reclaim the free product, if this is possible. Shovel the material into waste container. Thoroughly wash the area with water after a spill or leak clean-up. Wear appropriate protective equipment and clothing during clean-up. Keep out of the reach of children.

Evacuation Procedures

None identified.

Special Procedures

Wear a dust mask if dust is generated above exposure limits.

Material Safety Data Sheet

Material Name: Opticolor - Part C

ID: SAH00190

*** Section 7 - Handling and Storage ***

Handling Procedures

Avoid getting this material into contact with your skin and eyes. Avoid breathing dusts from this material. Wash hands after handling and before eating. Keep out of the reach of children.

Storage Procedures

Store in a cool, dry, well-ventilated area. Keep the container tightly closed. Do not freeze.

*** Section 8 - Exposure Controls / Personal Protection ***

A: Component Exposure Limits

Silica Sand (14808-60-7)

ACGIH:	0.025 mg/m3 TWA (respirable fraction)
NIOSH:	0.05 mg/m3 TWA (respirable dust)
Alberta:	0.1 mg/m3 TWA (respirable particulate)
British Columbia:	ACGIH Category A2 - Suspected Human Carcinogen; IARC Category 1 - Human Carcinogen 0.025 mg/m3 TWA (respirable)
Manitoba:	0.025 mg/m3 TWA (respirable fraction)
New Brunswick:	0.1 mg/m3 TWA (respirable fraction)
NW Territories:	0.1 mg/m3 TWA (respirable mass); 0.3 mg/m3 TWA (total mass)
Nova Scotia:	0.025 mg/m3 TWA (respirable fraction)
Nunavut:	0.1 mg/m3 TWA (respirable mass); 0.3 mg/m3 TWA (total mass)
Ontario:	0.10 mg/m3 TWAEV 0.10 mg/m3 TWAEV (designated substance regulation)
Quebec:	0.1 mg/m3 TWAEV (respirable dust)
Saskatchewan:	0.05 mg/m3 TWA (respirable fraction)
Yukon:	300 particles/mL TWA

Engineering Controls

Use general ventilation.

PERSONAL PROTECTIVE EQUIPMENT

Personal Protective Equipment: Eyes/Face

Wear safety glasses with side shields.

Personal Protective Equipment: Skin

The use of nitrile-latex gloves is recommended.

Personal Protective Equipment: Respiratory

If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

Personal Protective Equipment: General

Launder contaminated clothing before reuse. Use good industrial hygiene practices in handling this material.

*** Section 9 - Physical & Chemical Properties ***

Appearance:	White powder	Odor:	Odorless
Physical State:	Solid	pH:	N/A
Vapor Pressure:	N/A	Vapor Density:	N/A
Boiling Point:	N/A	Melting Point:	N/A
Solubility (H2O):	Soluble	Specific Gravity:	2.0 - 2.3
Evaporation Rate:	N/A	VOC:	16 g/L (mixture)
Octanol/H2O Coeff.:	N/A	Flash Point:	N/A
Flash Point Method:	N/A	Upper Flammability Limit (UFL):	N/A
Lower Flammability Limit (LFL):	N/A	Burning Rate:	N/A
Auto Ignition:	N/A		

Material Safety Data Sheet

Material Name: Opticolor - Part C

ID: SAH00190

Physical Properties: Additional Information

The data provided in this section is to be used for product safety handling purposes. Please refer to Product Data Sheets, Certificates of Conformity or Certificates of Analysis for chemical and physical data for determinations of quality and for formulation purposes.

*** Section 10 - Chemical Stability & Reactivity Information ***

Chemical Stability

Stable under normal conditions.

Chemical Stability: Conditions to Avoid

Keep away from heat, ignition sources and incompatible materials.

Incompatibility

This product may react with strong acids, bases and oxidizing agents.

Hazardous Decomposition

Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition. Upon decomposition, this product may emit fumes of carbon monoxide, carbon dioxide, oxides of nitrogen, and other organic compounds.

Possibility of Hazardous Reactions

Will not occur.

*** Section 11 - Toxicological Information ***

Acute Dose Effects

A: General Product Information

No information available for the product.

B: Component Analysis - LD50/LC50

Silica Sand (14808-60-7)

Oral LD50 Rat: 500 mg/kg

Carcinogenicity

A: General Product Information

Exposure to quartz (the most stable and common form of crystalline silica) is responsible for the majority of clinically diagnosed silicosis. Silicosis is a fibronodular lung disease that occurs after occupational exposure to crystalline silica for 5 years or longer. Inhalation of quartz dusts may cause shortness of breath, limitation of chest expansion, dry cough, and a lessened capacity for work. Individuals with a pre-existing disease in, or a history of ailments involving the skin or respiratory tract, are at a greater risk of developing adverse health effects when exposed to this material.

B: Component Carcinogenicity

Silica Sand (14808-60-7)

ACGIH:	A2 - Suspected Human Carcinogen
NIOSH:	potential occupational carcinogen
NTP:	Known Human Carcinogen (Select Carcinogen)
IARC:	Monograph 68 [1997] (listed under Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources) (Group 1 (carcinogenic to humans))

Sensitization

No information available for the product.

*** Section 12 - Ecological Information ***

Ecotoxicity

A: General Product Information

No information available for the product.

B: Component Analysis - Ecotoxicity - Aquatic Toxicity

No ecotoxicity data are available for this product's components.

Material Safety Data Sheet

Material Name: Opticolor - Part C

ID: SAH00190

*** Section 13 - Disposal Considerations ***

US EPA Waste Number & Descriptions

A: General Product Information

No additional information available.

B: Component Waste Numbers

No EPA Waste Numbers are applicable for this product's components.

Disposal Instructions

Waste must be handled in accordance with all federal, state, provincial, and local regulations. Consult authorities before disposal.

See Section 7 for Handling Procedures. See Section 8 for Personal Protective Equipment recommendations.

*** Section 14 - Transportation Information ***

International Transportation Regulations

Not regulated as dangerous goods.

*** Section 15 - Regulatory Information ***

US Federal Regulations

A: General Product Information

All components are on the U.S. EPA TSCA Inventory List. All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List unless otherwise noted.

B: Component Analysis

None of this products components are listed under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), or CERCLA (40 CFR 302.4).

State Regulations

A: General Product Information

Other state regulations may apply. Check individual state requirements.

B: Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
Silica Sand	14808-60-7	No	Yes	Yes	Yes	Yes	Yes

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause cancer.

Canadian WHMIS Information

A: General Product Information



B: Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS #	Minimum Concentration
Silica Sand	14808-60-7	1 %

Additional Regulatory Information

A: General Product Information

Supplier(s) of proprietary component(s) state that these components are contained on the TSCA inventory.

Material Safety Data Sheet

Material Name: Opticolor - Part C

ID: SAH00190

B: Component Analysis - Inventory

Component	CAS #	TSCA	CAN	EEC
Silica Sand	14808-60-7	Yes	DSL	EINECS

*** Section 16 - Other Information ***

Reference Version (internal)

I5-2416-02

Other Information

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use.

Key/Legend

NA = Not available or Not Applicable. ACGIH = American Conference of Governmental Industrial Hygienists. NFPA = National Fire Protection Association. EPA = Environmental Protection Agency; TSCA = Toxic Substance Control Act; ACGIH = American Conference of Governmental Industrial Hygienists; IARC = International Agency for Research on Cancer; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration., NJTSR = New Jersey Trade Secret Registry.

Contact: Product Safety Specialist

Contact Phone: 1-954-246-8888

End of Sheet SAH00190