



Material Safety Data Sheet

Material Name: ULTRAMASTIC ECO

ID: SAH00334

*** Section 1 - Chemical Product and Company Identification ***

Material Name: ULTRAMASTIC ECO

Product Use

Adhesive

Manufacturer Information

USA and Puerto Rico

MAPEI

1144 East Newport Center Drive

Deerfield Beach, FL 33442

Phone: 1-954-246-8888

Canada

MAPEI

2900 Francis-Hughes Avenue

Laval, QC H7L 3J5

Phone: 1-450-662-1212

IN THE EVENT OF A CHEMICAL EMERGENCY INVOLVING A SPILL, LEAK, FIRE, EXPLOSION, EXPOSURE OR ACCIDENT, CONTACT THE FOLLOWING NUMBERS:

Emergency 24 hour numbers:

(USA) CHEMTREC 1-800-424-9300

(Canada) CANUTEC 1-631-996-6666

*** Section 2 - Hazards Identification ***

Emergency Overview

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication). This product is irritating to the eyes.

Hazard Statements

CAUTION! IRRITANT. Irritating to eyes. Wear suitable gloves and eye/face protection. Keep out of the reach of children.

Potential Health Effects: Eyes

This product is irritating to the eyes.

Potential Health Effects: Skin

This product may cause irritation to the skin.

Potential Health Effects: Ingestion

Ingestion of this product may cause nausea, vomiting and diarrhea.

Potential Health Effects: Inhalation

This product may cause irritation to the respiratory system.

Medical Conditions Aggravated by Exposure

Hypersensitivity to product, allergies, and skin or respiratory disorders

Potential Environmental Effects

None identified.

HMIS Ratings: Health: 1 Fire: 0 Reactivity: 0 Pers. Prot.: Safety glasses, gloves

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

*** Section 3 - Composition / Information on Ingredients ***

| CAS # | Component | Percent |
|------------|--|---------|
| 1317-65-3 | Limestone | 30-60 |
| 25586-20-3 | Styrene acrylic polymer | 10-30 |
| 31069-81-5 | Acrylic polymer | 1-5 |
| 111-46-6 | Diethylene glycol | 1-5 |
| 68412-54-4 | Polyethylene glycol branched nonylphenyl ether | 0.5-1.5 |

Material Safety Data Sheet

Material Name: ULTRAMASTIC ECO

ID: SAH00334

*** Section 4 - First Aid Measures ***

First Aid: Eyes

In case of contact, immediately flush eyes with large amounts of water, continuing to flush for 15 minutes. If irritation persists get medical attention.

First Aid: Skin

For skin contact, flush with large amounts of water. If irritation persists, get medical attention.

First Aid: Ingestion

For ingestion, flush out mouth with water. If ingestion of a large amount does occur, seek medical attention. Do not induce vomiting.

First Aid: Inhalation

If inhaled, immediately remove the affected person to fresh air. If the affected person is not breathing, apply artificial respiration. If symptoms persist, get medical attention.

First Aid: Notes to Physician

Provide general supportive measures and treat symptomatically.

*** Section 5 - Fire Fighting Measures ***

General Fire Hazards

See Section 9 for Flammability Properties.

This product is an aqueous mixture which will not burn. If evaporated to dryness, the solid residue may pose a moderate fire hazard.

Hazardous Combustion Products

Irritating and toxic gases or fumes may be released during a fire. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Extinguishing Media

Dry chemical (preferred), foam, water.

Fire Fighting Equipment/Instructions

Firefighters should wear full protective gear.

NFPA Ratings: Health: 1 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

*** Section 6 - Accidental Release Measures ***

Personal Precautions

Wear appropriate protective equipment and clothing during clean-up.

Containment Procedures

Dike the spilled material, where this is possible. Absorb with inert absorbent such as dry clay, sand or diatomaceous earth, commercial sorbents, or recover using pumps. Scoop up used absorbent into drums or other appropriate container.

Environmental Precautions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

Clean-Up Procedures

Attempt to reclaim the free product, if this is possible. Shovel the material into waste container. Thoroughly wash the area with water after a spill or leak clean-up. Keep out of the reach of children.

Evacuation Procedures

None identified.

Special Procedures

Regulations vary. Consult local authorities before disposal.

*** Section 7 - Handling and Storage ***

Handling Procedures

Avoid getting this material into contact with your skin and eyes. Avoid breathing vapors or mists of this product. Wash hands after handling and before eating. Keep out of the reach of children.

Material Safety Data Sheet

Material Name: ULTRAMASTIC ECO

ID: SAH00334

Storage Procedures

Store in a cool, dry, well-ventilated area. Store at ambient temperature and atmospheric pressure. Keep out of sun.

*** Section 8 - Exposure Controls / Personal Protection ***

A: Component Exposure Limits

Limestone (1317-65-3)

| | |
|-------------------|---|
| OSHA: | 15 mg/m3 TWA total dust; 5 mg/m3 TWA respirable fraction |
| NIOSH: | 10 mg/m3 TWA total dust; 5 mg/m3 TWA respirable dust |
| Alberta: | 10 mg/m3 TWA |
| British Columbia: | 10 mg/m3 TWA total dust; 3 mg/m3 TWA respirable fraction 20 mg/m3 STEL total dust |
| New Brunswick: | 10 mg/m3 TWA particulate matter containing no asbestos and < 1% crystalline silica |
| NW Territories: | 5 mg/m3 TWA respirable mass; 10 mg/m3 TWA total mass |
| Nunavut: | 5 mg/m3 TWA respirable mass; 10 mg/m3 TWA total mass |
| Quebec: | 10 mg/m3 TWAEV total dust, containing no asbestos and less than 1% crystalline silica |
| Saskatchewan: | 20 mg/m3 STEL 10 mg/m3 TWA |
| Yukon: | 20 mg/m3 STEL 30 mppcf TWA; 10 mg/m3 TWA |

Engineering Controls

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits. Local exhaust is suggested for use, where possible, in enclosed or confined spaces.

PERSONAL PROTECTIVE EQUIPMENT

Personal Protective Equipment: Eyes/Face

Wear safety glasses with side shields.

Personal Protective Equipment: Skin

The use of nitrile-latex gloves is recommended.

Personal Protective Equipment: Respiratory

Not normally needed. If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

Personal Protective Equipment: General

Laundry contaminated clothing before reuse. Use good industrial hygiene practices in handling this material.

*** Section 9 - Physical & Chemical Properties ***

| | | | |
|--|-----------------|--|-------------------|
| Appearance: | Beige paste | Odor: | Slight latex odor |
| Physical State: | Paste | pH: | 8.0 - 10.0 |
| Vapor Pressure: | N/A | Vapor Density: | N/A |
| Boiling Point: | 212° F (100° C) | Melting Point: | N/A |
| Solubility (H2O): | Dispersible | Specific Gravity: | 1.30 - 1.60 |
| Evaporation Rate: | Same as water | VOC: | 57 g/L |
| Octanol/H2O Coeff.: | N/A | Flash Point: | N/A |
| Flash Point Method: | N/A | Upper Flammability Limit (UFL): | N/A |
| Lower Flammability Limit (LFL): | N/A | Burning Rate: | N/A |
| Auto Ignition: | N/A | | |

Physical Properties: Additional Information

The data provided in this section is to be used for product safety handling purposes. Please refer to Product Data Sheets, Certificates of Conformity or Certificates of Analysis for chemical and physical data for determinations of quality and for formulation purposes.

*** Section 10 - Chemical Stability & Reactivity Information ***

Chemical Stability

Stable under normal conditions.

Material Safety Data Sheet

Material Name: ULTRAMASTIC ECO

ID: SAH00334

Chemical Stability: Conditions to Avoid

Do not freeze.

Incompatibility

This product may react with strong acids, bases and oxidizing agents.

Hazardous Decomposition

Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition. Upon decomposition, this product may emit fumes of carbon monoxide, carbon dioxide, oxides of nitrogen, and other organic compounds.

Possibility of Hazardous Reactions

Will not occur.

*** Section 11 - Toxicological Information ***

Acute Dose Effects

A: General Product Information

No information available for the product.

B: Component Analysis - LD50/LC50

Diethylene glycol (111-46-6)

Oral LD50 Rat 12565 mg/kg; Dermal LD50 Rabbit 11890 mg/kg

Carcinogenicity

A: General Product Information

No information available for the product.

B: Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, OSHA, NIOSH, or NTP.

Sensitization

No information available for the product.

*** Section 12 - Ecological Information ***

Ecotoxicity

A: General Product Information

No information available for the product.

B: Component Analysis - Ecotoxicity - Aquatic Toxicity

Diethylene glycol (111-46-6)

| Test & Species | | Conditions |
|--------------------------------|------------|----------------|
| 96 Hr LC50 Pimephales promelas | 75200 mg/L | [flow-through] |
| 48 Hr EC50 Daphnia magna | 84000 mg/L | |

*** Section 13 - Disposal Considerations ***

US EPA Waste Number & Descriptions

A: General Product Information

No additional information available.

B: Component Waste Numbers

No EPA Waste Numbers are applicable for this product's components.

Disposal Instructions

Waste must be handled in accordance with all federal, state, provincial, and local regulations. Consult authorities before disposal.

See Section 7 for Handling Procedures. See Section 8 for Personal Protective Equipment recommendations.

*** Section 14 - Transportation Information ***

International Transportation Regulations

Not regulated as dangerous goods.

Material Safety Data Sheet

Material Name: ULTRAMASTIC ECO

ID: SAH00334

*** Section 15 - Regulatory Information ***

US Federal Regulations

A: General Product Information

All components are on the U.S. EPA TSCA Inventory List. All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List unless otherwise noted.

B: Component Analysis

None of this products components are listed under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), or CERCLA (40 CFR 302.4).

State Regulations

A: General Product Information

Other state regulations may apply. Check individual state requirements.

B: Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

| Component | CAS | CA | MA | MN | NJ | PA | RI |
|-------------------|-----------|----|-----|-----|-----|-----|-----|
| Limestone | 1317-65-3 | No | Yes | Yes | Yes | Yes | Yes |
| Diethylene glycol | 111-46-6 | No | No | Yes | No | Yes | Yes |

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):
WARNING! This product contains a chemical known to the state of California to cause cancer. WARNING! This product contains a chemical known to the state of California to cause reproductive/developmental effects.

Canadian WHMIS Information

A: General Product Information

Not regulated

B: Component Analysis - WHMIS IDL

No components are listed in the WHMIS IDL.

Additional Regulatory Information

A: General Product Information

Supplier(s) of proprietary component(s) state that these components are contained on the TSCA inventory.

B: Component Analysis - Inventory

| Component | CAS # | TSCA | CAN | EEC |
|--|------------|------|------|--------|
| Limestone | 1317-65-3 | Yes | NDSL | EINECS |
| Styrene acrylic polymer | 25586-20-3 | Yes | DSL | No |
| Acrylic polymer | 31069-81-5 | Yes | DSL | No |
| Diethylene glycol | 111-46-6 | Yes | DSL | EINECS |
| Polyethylene glycol branched nonylphenyl ether | 68412-54-4 | Yes | DSL | No |

*** Section 16 - Other Information ***

Reference

Q1-4293-02

Other Information

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

Key/Legend

NA = Not available or Not Applicable. ACGIH = American Conference of Governmental Industrial Hygienists. NFPA = National Fire Protection Association. EPA = Environmental Protection Agency; TSCA = Toxic Substance Control Act; ACGIH = American Conference of Governmental Industrial Hygienists; IARC = International Agency for Research on Cancer; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration., NJTSR = New Jersey Trade Secret Registry.

Contact: Product Safety Sepcialist

Contact Phone: 1-954-246-8888

End of Sheet SAH00334