

MATERIAL SAFETY DATA SHEET

NPCA

FOR COATINGS, RESINS AND RELATED MATERIALS (Approved by US Department of Labor Essentially Similar to Form OSHA 20)

Date Issued :12/21/2006

Page 1 of 2

SECTION I

MANUFACTURERS NAME

GARDNER-GIBSON

STREET ADDRESS

4161 E. 7th Ave.

EMERGENCY TELEPHONE NUMBER

1-800-247-9691

PRODUCT CLASS

ACRYLIC

CITY, STATE, AND ZIP CODE

Tampa, FL 33605

MANUFACTURES CODE IDENTIFICATION

BJ-5227

TRADE NAME

Black Jack White Elastomeric Roof Patch

SECTION II- HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	TLV PPM	PEL-TWA PPM
ETHYLENE GLYCOL CAS # - 107-21-1	1.0	50	N.E
POLYMER CAS #- 900-55-8	<40%	*	
CAS #-			
CAS #-			

N.E.= Not Established

SECTION III – PHYSICAL DATA

BOILING RANGE: 379 °F - 401°F VAPOR DENSITY HEAVIER LIGHTER, THAN AIR
VAPOR PRESSURE: .1mm @ 68°F Appearance:White Odor:Slight
EVAPORATION RATE FASTER SLOWER, THAN ETHER PERCENT VOTILE BY VOLUME 100 % WEIGHT PER GALLON BY VOLUME 11.00 LBS
SOLUBILITY IN WATER: Yes PHYSICAL STATE :Liquid Ph: 8.5

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

FLASH POINT=100 F

EXPLOSION HAZARD:Not Applicable

LEL-1% UEL

EXTINGUISHING MEDIA-

CARBON DIOXIDE, FOAM, & DRY CHEMICAL

UNUSUAL FIRE AND EXPOLSION HAZARDS-

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO

EXTREME HEAT. PRODUCTS OF COMBUSTION MAY BE TOXIC

SPECIAL FIRE FIGHTING PROCEDURES-

WEAR SELF CONTAINED BREATHING APPARATUS. WATER

MAY BE USED TO COOL CLOSED CONTAINERS. HIGH PRESSURE STREAM WILL SPREAD FIRE.

SECTION V – REACTIVITY DATA

STABILITY: UNSTABLE

STABLE

CONDITIONS TO AVOID: STORE AWAY FROM
STRONG OXIDIZING MATERIALS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE IN A COOL, DRY PLACE. KEEP CONTAINER
CLOSED WHEN NOT IN USE. PROTECT FROM FREEZING.

MATERIAL SAFETY DATA SHEET

NPCA

FOR COATINGS, RESINS AND RELATED MATERIALS

(Approved by US Department of Labor Essentially Similar to Form OSHA 20)

Date Issued :12/21/2006

Page 2 of 2

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON OXIDES AND TRACES OF INCOMPLETELY BURNED CARBON COMPOUNDS.

HAZARDOUS POLYMERIZATION: MAY OCCUR WILL NOT OCCUR

SECTION VI-HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:

ACUTE EFFECTS: SKIN: May cause slight irritation to sensitive skin. INHALATION: Overexposure may cause dizziness
INGESTION May cause nausea, consult physician immediately.

CHRONIC EXPOSURE EFFECTS: SKIN:No known applicable information INHALATION: No known applicable information
INGESTION: None known.

EMERGENCY FIRST AID PROCEDURE-

EYES: Flush with water for 15 minutes. Get medical attention if irritation persists.

SKIN: Wash with soap and water or waterless cleanser. Get medical attention if irritation develops or persists.

INHALATION: If symptoms develop, move to fresh air.

INGESTION: Don not induce vomiting. If symptoms develop, seek medical advice from a physician. No ingredient in this product is an IRAC, NTP or OSHA listed carcinogen.

SECTION VII – SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Observe all personal protection equipment recommendations described in Section VIII. Wipe up spill and contain for disposal. Final cleaning may require use of hot water and/or detergents. Dispose of saturated absorbent or cleaning materials appropriately

WASTE DISPOSAL METHOD: Dispose of unused material in accordance with Federal, State, and Local Regulations.

SECTION VIII – SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Use with adequate ventilation.

SKIN PROTECTION: Protective gloves are recommended for prolonged exposure.

EYE PROTECTION: Safety glasses with side shields.

OTHER PROTECTIVE EQUIPMENT: None required.

SECTION IX – OTHER INFORMATION

OTHER PRECAUTIONS: KEEP OUT OF THE REACH OF CHILDREN. KEEP CONTAINER CLOSED WHEN NOT IN USE. PROTECT FROM FREEZING.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

Hazardous Materials Identification System (HMIS)

Health Flammability Reactivity Personal Protection
1 0 0 B

Prepared By:
Barton Malina