

Permatex, Inc.
10 Columbus Blvd.
Hartford, CT 06106 USA
Telephone: 1-87-Permatex
(877) 376-2839
Emergency: 800-255-3924

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: NO TOUCH SERIOUSLY WET EXTREME TIRE SHINE 15 OZ AE
Item No: NTSW15-6
Product Type: Aerosol protectant

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Percent	ACGIH 8 Hr. TWA:	OSHA 8 Hr. TWA:
OCTAMETHYLCYCLOTETRASILO XANE 556-67-2	>30	Not Listed	Not Listed
PROPANE 74-98-6	5-15	simple asphyxiant; 2500 ppm TWA	1000 ppm TWA; 1800 mg/m ³ TWA
POLYBUTENE 9003-28-5	1-10	Not Listed	Not Listed
DECAMETHYLCYCLOPENTASILO XANE 541-02-6	1-10	Not Listed	Not Listed

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye, skin and respiratory irritation.
Primary Routes of Entry: Eye and skin contact, inhalation
Signs and Symptoms of Exposure: May cause redness to eyes and irritation to nasal passages. Skin redness.

Medical Conditions Recognized as Being Aggravated by Exposure: None known

4. FIRST AID MEASURES

Ingestion: If swallowed, do NOT induce vomiting. Give victim two glasses of water, Call a physician immediately. Never give anything by mouth to an unconscious person.
Inhalation: If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention..
Skin Contact: Remove contaminated clothing. Wash area with soap and water. If irritation persists, seek medical attention.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): Flammable per Flame Projection Test
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus. Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool. Silicon dioxide, Formaldehyde, Oxides of carbon.
Hazardous Products Formed by Fire or Thermal Decomposition:
Unusual Fire/Explosion Hazards: Contents under pressure. Exposure to temperatures over 120 degrees F. may cause bursting or venting. Use equipment or shielding to protect personnel from bursting containers.
Lower Explosive Limit: Not determined
Upper Explosive Limit: Not determined

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal. Flush spill or leak area with water. Prevent from entering waterways or sewers. Clean up spills thoroughly as residue is slippery.

7. HANDLING AND STORAGE

Storage: Store away from heat, sparks or open flame. Do not store at temperatures above 120 degrees F. Exposure to high temperatures may cause container to burst. Store in accordance with NFPA 30B for Level 3 Aerosols

Handling: Avoid contact with skin and eyes. Use only in a well ventilated area. Spills may cause slippery floors. Proper footwear required.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Not normally required, but wearing safety glasses will minimize exposure. Recommended if handling large spills.

Skin: Not normally required when using an aerosol. Recommended if handling large spills.

Ventilation: Mechanical ventilation.

Respiratory Protection: If handling large industrial or warehouse spills. wear NIOSH-approved respiratory protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: White liquid

Odor: SLIGHT AMINE

Boiling Point (°F): Not determined.

pH: Does not apply

Solubility in Water: Soluble

Specific Gravity: 0.9-1.0

VOC Content(Wt.%): 10% by wieght

Vapor Pressure: Not determined

Vapor Density (Air=1): >1 (air = 1)

Evaporation Rate: <1 (butyl acetate = 1)

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions

Hazardous Polymerization: WILL NOT OCCUR

Incompatabilities: Strong oxidizers.

Conditions to Avoid: Temperatures above 120 degrees F.

Hazardous Products Formed by Fire or Thermal Decomposition: Silicon dioxide, Formaldehyde, Oxides of carbon.

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations. This container may be recycled in aerosol recycling centers. Before offering for recycling, empty the can by using the product according to the label. If recycling is not available, wrap the container and discard in the trash.

US EPA Waste Number: D001 as per 40CFR 261.21

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name: CONSUMER COMMODITY

Hazard Class: ORM-D

UN/ID Number: None

Marine Pollutant: None

IATA

Proper Shipping Name: Consumer Commodity (Not more than 500 ml)

Class or Division: Class 9

UN/NA Number: ID 8000

IMDG

Product name: NO TOUCH SERIOUSLY WET
EXTREME TIRE SHINE 15 OZ AE

Item NTSW15-6

Proper Shipping: Aerosols, Limited Quantity
Hazard Class: Class 2.1
UN Number: UN 1950

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

SARA 313 Information

NONE

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present.

TSCA Inventory Status:

Listed on Inventory: **YES** All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 4, REACTIVITY 0

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 4, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Health and Safety Manager
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA
06106

Revision Date: 10/19/2004

Revision New

Number:

Telephone Number: 1-87-Permatex (877) 376-2839