

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924
 International Emergency: +01-813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: NO TOUCH TURBO WET 12 OZ.
Item No: NTTW12-6
Product Type: Aerosol coating

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
ACETONE 67-64-1	30-40	500 ppm	1000 ppm; 2400 mg/m ³
DIMETHYLCYCLOSILOXANE 69430-24-6	10-30	Not listed	Not listed
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	10-30	Not listed	Not listed
SYNTHETIC ISOPARAFFINIC HYDROCARON 64742-47-8	10-30	Not listed	Not listed
CARBON DIOXIDE 124-38-9	<10	5000 ppm	5000 ppm; 9000 mg/m ³
PROPANE 74-98-6	<10	1000 ppm	1000 ppm; 1800 mg/m ³
HEXAMETHYLCYCLOTETRA SILOXANE 541-05-9	<5	Not listed	Not listed
OCTAMETHYLCYCLOTETRA SILOXANE 556-67-2	<5	Not listed	Not listed

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye, skin and respiratory irritation.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation
Signs and Symptoms of Exposure: Overexposure may cause eye and skin redness. Excessive accidental exposure may cause headache, dizziness, nausea and mild respiratory irritation.

Component	Weight%	NTP	ACGIH Carcinogens	IARC
ACETONE 67-64-1	30-40	Not known	A4 - Not Classifiable as a Human Carcinogen	

Medical Conditions Recognized as Being Aggravated by Exposure: None known

4. FIRST AID MEASURES

Ingestion: If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.
Inhalation: Move to fresh air in case of accidental inhalation of vapours. If irritation persists or signs of toxicity occur, seek medical attention.
Skin Contact: Remove contaminated clothing. Wash area with soap and water. If irritation persists, seek medical attention.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): Extremely flammable per flame projection test
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.

5. FIRE FIGHTING MEASURES

Special Fire-Fighting Procedures:	Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.
Hazardous Products of Combustion:	Oxides of carbon
Unusual Fire/Explosion Hazards:	Contents under pressure. Exposure to temperatures over 120 degrees F. may cause bursting or venting. Use equipment or shielding to protect personnel from bursting containers.
Lower Explosive Limit:	Not determined
Upper Explosive Limit:	Not determined

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures:	Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.
--------------------------	--

7. HANDLING AND STORAGE

Storage:	Store away from heat, sparks or open flame. Do not store at temperatures above 120 degrees F. Exposure to high temperatures may cause container to burst. Store in accordance with NFPA 30B for Level 3 Aerosols.
Handling:	Avoid contact with skin and eyes. Use only in a well ventilated area. Product may cause surfaces to become slippery.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:	Not normally required, but wearing safety glasses will minimize exposure..
Skin:	Neoprene or nitrile gloves recommended.
Ventilation:	General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.
Respiratory Protection:	Not normally necessary. An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear liquid
Odor:	Solvent
Boiling Point:	>100°F
pH:	Does not apply
Solubility in Water:	Somewhat miscible
Specific Gravity:	0.85-0.87
VOC Content(Wt.%):	9.4%
Vapor Pressure:	Not determined
Vapor Density (Air=1):	>1 (air = 1)
Evaporation Rate:	>1 (butyl acetate = 1)

10. STABILITY AND REACTIVITY

Chemical Stability:	Stable at normal conditions
Hazardous Polymerization:	Will not occur.
Incompatibilities:	Strong oxidizers
Conditions to Avoid:	Keep away from heat, sparks and flame
Hazardous Products of Combustion:	Oxides of carbon

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations. This container may be recycled in aerosol recycling centers. Before offering for recycling, empty the can by using the product according to the label. If recycling is not available, wrap the container and discard in the trash.

Product Name: NO TOUCH TURBO WET 12 OZ.

Item No: NTTW12-6

13. DISPOSAL CONSIDERATIONS

US EPA Waste Number: D001 as per 40CFR 261.21

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Ground Transport (DOT)

DOT Shipping Name: CONSUMER COMMODITY
Hazard Class: ORM-D
UN/ID Number: None

IATA

Proper Shipping Name: Consumer Commodity (Not more than 1 liter)
Class or Division: Class 9
UN/ID Number: ID 8000

IMDG

Proper Shipping: Aerosols, Limited Quantity
Hazard Class: Class 2.1
UN Number: UN 1950

Marine Pollutant: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

CALIFORNIA PROP 65:

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 3, REACTIVITY 0.

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 3, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision Date: December/22/2008

Revision 1

Number:

Telephone No.: 1-87-Permatex (877) 376-2839