

Permatex, Inc.  
 10 Columbus Blvd.  
 Hartford, CT 06106 USA  
 Telephone: 1-87-Permatex  
 (877) 376-2839  
 Emergency: 800-255-3924

## Material Safety Data Sheet

### 1. PRODUCT IDENTIFICATION

**Product Name:** 36051 NO TOUCH WET N PROTECT WET TIRE FINISH 15OZ AE  
**Item No:** WPBP15-6  
**Product Type:** Aerosol protectant

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Percent	ACGIH 8 Hr. TWA:	OSHA 8 Hr. TWA:
OCTAMETHYLCYCLOTETRASILOXANE 556-67-2	15-40	Not Listed	Not Listed
POLYDIMETHYLSILOXANE 63148-62-9	15-40	Not Listed	Not Listed
ACETONE 67-64-1	10-20	500 ppm TWA; 1188 mg/m <sup>3</sup> TWA	1000 ppm TWA; 2400 mg/m <sup>3</sup> TWA
DECAMETHYLCYCLOPENTASILOXANE 541-02-6	5-15	Not Listed	Not Listed
POLYBUTENE 9003-28-5	5-15	Not Listed	Not Listed
PROPANE 74-98-6	5-15	simple asphyxiant; 2500 ppm TWA	1000 ppm TWA; 1800 mg/m <sup>3</sup> TWA
DODECAMETHYLCYCLOHEXASILOXANE 540-97-6	1-10	Not Listed	Not Listed

### 3. HAZARDS IDENTIFICATION

**Toxicity:** May cause eye, skin and respiratory irritation. High concentrations may cause central nervous system (CNS) depression. Aspiration hazard if swallowed.  
**Primary Routes of Entry:** Eye and skin contact, ingestion, inhalation.  
**Signs and Symptoms of Exposure:** Contact with eyes may cause tearing and redness. Excessive accidental exposure may cause headache, dizziness, nausea and mild respiratory irritation.

Ingredients	Percent	NTP:	ACGIH Carcinogens	IARC:
ACETONE 67-64-1	10-20	Not known	A4 - Not Classifiable as a Human Carcinogen	Not known

**Medical Conditions Recognized as Being Aggravated by Exposure:** None known

### 4. FIRST AID MEASURES

**Ingestion:** If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention. Never give fluids or induce vomiting if the victim is unconscious or having convulsions.  
**Inhalation:** If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention..  
**Skin Contact:** Remove contaminated clothing. Wash area with soap and water. If irritation persists, seek medical attention.  
**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

### 5. FIRE FIGHTING MEASURES

**Flash Point (°F/C):** Extremely flammable per flame projection test  
**Recommended Extinguishing Media:** Carbon Dioxide, Dry Chemicals, Foam.

**Special Fire-Fighting Procedures:**

Firefighters should wear self-contained breathing apparatus. Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool. Silicon dioxide, Oxides of carbon.

**Hazardous Products Formed by Fire or Thermal Decomposition:**

**Unusual Fire/Explosion Hazards:**

Contents under pressure. Exposure to temperatures over 120 degrees F. may cause bursting or venting. Use equipment or shielding to protect personnel from bursting containers.

**Lower Explosive Limit:**

1.8

**Upper Explosive Limit:**

9.5

## **6. ACCIDENTAL RELEASE MEASURES**

**Spill Procedures:**

Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal. Flush spill or leak area with water. Prevent from entering waterways or sewers. Clean up spills thoroughly as residue is slippery.

## **7. HANDLING AND STORAGE**

**Storage:**

Store away from heat, sparks or open flame. Do not store at temperatures above 120 degrees F. Exposure to high temperatures may cause container to burst. Store in accordance with NFPA 30B for Level 3 Aerosols

**Handling:**

Avoid contact with skin and eyes. Use only in a well ventilated area. Spills may cause slippery floors. Proper footwear required.

## **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Eyes:**

Safety glasses or goggles.

**Skin:**

Rubber or plastic gloves

**Ventilation:**

General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits during the use of this product.

**Respiratory Protection:**

An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the applicable limits..

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance:**

White liquid

**Odor:**

Ketone odor.

**Boiling Point (°F):**

Not determined.

**pH:**

Does not apply

**Solubility in Water:**

Soluble

**Specific Gravity:**

0.85-0.95

**VOC Content(Wt.%):**

10% by weight

**Vapor Pressure:**

Not determined

**Vapor Density (Air=1):**

>1 (air = 1)

**Evaporation Rate:**

Not determined

## **10. STABILITY AND REACTIVITY**

**Chemical Stability:**

Stable at normal conditions

**Hazardous Polymerization:**

WILL NOT OCCUR

**Incompatibilities:**

Strong oxidizers.

**Conditions to Avoid:**

Temperatures above 120 degrees F.

**Hazardous Products Formed by Fire or Thermal Decomposition:**

Silicon dioxide, Oxides of carbon.

## **11. TOXICOLOGICAL INFORMATION**

See Section 3

## **12. ECOLOGICAL INFORMATION**

No data available

## **13. DISPOSAL CONSIDERATIONS**

**Recommended Method of Disposal:** Disposal should be made in accordance with federal, state and local regulations. This container may be recycled in aerosol recycling centers. Before offering for recycling, empty the can by using the product according to the label. If recycling is not available, wrap the container and discard in the trash.

**Product name:** 36051 NO TOUCH WET N PROTECT  
WET TIRE FINISH 15OZ AE

**Item** WPBP15-6

**US EPA Waste Number:** D001 as per 40CFR 261.21

## **14. TRANSPORTATION INFORMATION**

**DOT (49CFR 172)**

### **Domestic Ground Transport**

**DOT Shipping Name:** CONSUMER COMMODITY  
**Hazard Class:** ORM-D  
**UN/ID Number:** None  
**Marine Pollutant:** None

### **IATA**

**Proper Shipping Name:** Consumer Commodity (Not more than 500 ml)  
**Class or Division:** Class 9  
**UN/NA Number:** ID 8000

### **IMDG**

**Proper Shipping:** Aerosols, Limited Quantity  
**Hazard Class:** Class 2.1  
**UN Number:** UN 1950

## **15. REGULATORY INFORMATION**

**SARA 313 Chemicals:** The following component(s) is listed as a SARA Section 313 Toxic Chemical.

**SARA 313 Information**

NONE

**CALIFORNIA PROP 65:**

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

**TSCA Inventory Status:**

**Listed on Inventory:** YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

## **16. OTHER INFORMATION**

**Estimated NFPA Rating:** HEALTH 2, FLAMMABILITY 4, REACTIVITY 0

**Estimated HMIS Classification:** HEALTH 2, FLAMMABILITY 4, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

**Prepared By:** Denise Boyd, Health and Safety Manager  
**Company:** Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA  
06106

**Revision Date:** 01/13/2005

**Revision** New

**Number:**

**Telephone Number:** 1-87-Permatex (877) 376-2839