

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924
 International Emergency: +01-813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: NOS MAX STREET OCTANE BOOSTER 16 FL.OZ.
Item No: 12003
Product Type: Fuel additive

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL:
KEROSINE (PETROLEUM) 8008-20-6	>60	200 mg/m ³ TWA	Not Listed
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT 64742-47-8	<5	Not listed	100 ppm TWA
TRICARBONYL(METHYLCYLCOPE NTADIENYL)MANGANESE 12108-13-3	0.1-1.0	0.2 mg/m ³ (Mn)	0.2 mg/m ³ TWA (as Mn)

3. HAZARDS IDENTIFICATION

Toxicity: Excessive inhalation causes headache, dizziness, nausea, and incoordination. Exposure to vapors or mist may result in irritation of the respiratory tract. Harmful if swallowed. Aspiration hazard if swallowed. May cause eye and skin irritation. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage (sometimes referred to as "solvent" or "painter's syndrome"). Symptoms include fatigue, concentration difficulties, anxiety, depression, rapid mood swings, and short-term memory loss.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation

Signs and Symptoms of Exposure: Excessive accidental exposure may cause headache, dizziness, nausea and mild respiratory irritation. Overexposure may cause eye and skin redness.

Component	Weight%	NTP	ACGIH Carcinogens	IARC
KEROSINE (PETROLEUM) 8008-20-6	>60	male mice-no evidence; female mice-no evidence	A3	Group 3 Vol 45, pg 203; 1989

Medical Conditions Recognized as Being Aggravated by Exposure: May aggravate preexisting dermatitis.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. If not breathing, give artificial respiration. Obtain medical attention.

Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician. Discard contaminated shoes.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): 110° F PMCC

Recommended Extinguishing Media: Carbon dioxide, Dry chemical, Alcohol foam

Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus.

Hazardous Products of Combustion: Oxides of carbon, Oxides of nitrogen

Unusual Fire/Explosion Hazards: Exposure to temperatures over 120 degrees F. may cause bursting or venting. Keep containers cool.

Lower Explosive Limit: Not determined.

5. FIRE FIGHTING MEASURES

Upper Explosive Limit: Not determined.

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage: Store away from heat, sparks or open flame. Do not store at temperatures above 120 degrees F.
Handling: Avoid contact with skin and eyes. Avoid breathing vapors, if exposed to high vapor concentration, leave area at once. Do not take internally. Do not use near heat, sparks or open flame. Keep container closed when not in use. Wash hands before eating and smoking.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses.
Skin: Neoprene or nitrile gloves recommended.
Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.
Respiratory Protection: An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Amber liquid
Odor: Solvent
Boiling Point: 214-580°F
pH: Not applicable
Solubility in Water: Soluble
Specific Gravity: 0.82
VOC Content(Wt.%): >90% by weight
Vapor Pressure: Not Determined
Vapor Density (Air=1): >1
Evaporation Rate: Not Determined

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions
Hazardous Polymerization: WILL NOT OCCUR.
Incompatibilities: Acids, Strong oxidizers
Conditions to Avoid: Heat
Hazardous Products of Combustion: Oxides of carbon, Oxides of nitrogen

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.
US EPA Waste Number: D001 as per 40CFR 261.21

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name: Unrestricted
Hazard Class: None
UN/ID Number: None

IATA

Proper Shipping Name: Consumer Commodity (Not more than 1 liter)
Class or Division: Class 9
UN/ID Number: ID 8000

Product Name: NOS MAX STREET OCTANE BOOSTER
16 FL.OZ.

Item No: 12003

IMDG

Proper Shipping: Petroleum Distillates, n.o.s., Limited Quantity
Hazard Class: Class 3 PGIII
UN Number: UN 1268

Marine Pollutant: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present.

TSCA Inventory Status:

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 2, REACTIVITY 0.

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 2, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision Date: October/03/2008

Revision 6

Number:

Telephone No.: 1-87-Permatex (877) 376-2839