

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924 (ChemTel)
 International Emergency: +01-813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: 195DA WHITE LITHIUM GREASE 10.75OZ AE
Item No: 81981
Product Type: Aerosol lubricant

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC 64741-96-4	15-40	Not listed	Not listed
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC 64742-52-5	15-40	Not listed	Not listed
PROPANE 74-98-6	15-40	1000 ppm	1000 ppm; 1800 mg/m ³
HEPTANE 142-82-5	10-30	400 ppm	500 ppm; 2000 mg/m ³

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye, skin and respiratory irritation. Intentional misuse by concentrating and inhaling the vapor may be harmful or fatal. High concentrations may cause central nervous system (CNS) depression.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation
Signs and Symptoms of Exposure: Excessive accidental exposure may cause headache, dizziness, nausea and mild respiratory irritation. May cause redness to eyes and irritation to nasal passages.
Medical Conditions Recognized as Being Aggravated by Exposure: Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation: Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed. Obtain medical attention.
Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): Flammable aerosol per flame projection
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus. Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.
Hazardous Products of Combustion: Oxides of carbon
Unusual Fire/Explosion Hazards: Contents under pressure. Exposure to temperatures over 120 degrees F. may cause bursting or venting. Use equipment or shielding to protect personnel from bursting containers.
Lower Explosive Limit: Not determined
Upper Explosive Limit: Not determined

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage: Store away from heat, sparks or open flame. Do not store at temperatures above 100°F (38°C). Exposure to high temperatures may cause container to burst.

Handling: Do not use near heat, sparks or open flame. Do not puncture or incinerate container. Avoid contact with skin and eyes. Avoid breathing vapors, if exposed to high vapor concentration, leave area at once. Use only in a well ventilated area. Intentionally concentrating and inhaling the vapor may be harmful or fatal. Wash thoroughly after handling.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses.

Skin: Neoprene or nitrile gloves recommended.

Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.

Respiratory Protection: An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: White liquid

Odor: Solvent

Boiling Point: >100°F

pH: Does not apply

Solubility in Water: Nil

Specific Gravity: 0.885

VOC(Wt.%): 37.8%

Vapor Pressure: Not Determined

Vapor Density (Air=1): >1

Evaporation Rate: <1 (butyl acetate = 1)

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions

Hazardous Polymerization: Will not occur

Incompatibilities: Strong oxidizers

Conditions to Avoid: Keep away from heat, sparks and open flame. - No smoking.

Hazardous Products of Combustion: Oxides of carbon

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.. This container may be recycled in aerosol recycling centers. Before offering for recycling, empty the can by using the product according to the label. If recycling is not available, wrap the container and discard in the trash.

US EPA Waste Number: D001 as per 40CFR 261.21

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Ground Transport (DOT)

DOT Shipping Name: Consumer Commodity

Hazard Class: ORM-D

UN/ID Number: None

IATA

Proper Shipping Name: Consumer Commodity (Not more than 1 liter)

Class or Division: Class 9

Product Name: 195DA WHITE LITHIUM GREASE
10.75OZ AE

Item No: 81981

14. TRANSPORTATION INFORMATION

UN/ID Number: ID 8000

IMDG

Proper Shipping: Aerosols, Limited Quantity

Hazard Class: Class 2.1

UN Number: UN 1950

Marine Pollutant: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

None

California Proposition 65: WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 4, REACTIVITY 1.

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 4, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision Date: December 16, 2010

Revision Number: 1

Telephone No.: 1-87-Permatex (877) 376-2839