

**GE25692****Acrylic Latex Caulk - Antique White****1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

**Manufactured By:** Daytona Plant  
703 South Street  
New Smyrna Beach FL 32168

**Revised:** 03/02/2011  
**Preparer:** PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS  
**CHEMTREC** 1-800-424-9300

**Chemical Family/Use:** Sealant  
**Formula:** Mixture

**HMIS**

Flammability: 0      Reactivity: 0      Health: 1

**NFPA**

Flammability: 0      Reactivity: 0      Health: 1

**2. HAZARDS IDENTIFICATION****EMERGENCY OVERVIEW**

WARNING! Harmful if swallowed, inhaled, or absorbed through the skin. May cause skin, eye, and respiratory tract irritation. Do not inhale vapors.

**Form:** Solid      **Color:** Off-white

**POTENTIAL HEALTH EFFECTS****INGESTION**

Harmful if swallowed. Irritation of the mouth, throat, and stomach. May cause irritation of the gastrointestinal tract. May cause reproductive effects based on results of animal studies.

**SKIN**

May be absorbed through the skin and contribute to the symptoms listed under "Ingestion". Can cause irritation and reddening of the skin.

**INHALATION**

High concentrations of vapors may irritate respiratory system and lead to headache, fatigue, nausea and vomiting. Can irritate mucous membranes and respiratory tract with coughing and shortness of breath. Avoid inhalation of vapors and spray mists.

**EYES**

Contact can cause severe irritation and conjunctivitis (redness and swelling).

**MEDICAL CONDITIONS AGGRAVATED**

Pre-existing skin or respiratory diseases. Kidney disorders

**GE25692****Acrylic Latex Caulk - Antique White****SUBCHRONIC (TARGET ORGAN )**

Respiratory System; Kidney

**CHRONIC EFFECTS / CARCINOGENICITY**

This product contains stoddard solvent or mineral spirits. Chronic and repeated overexposure may result in adverse liver and kidney effects, bone marrow hyperplasia, and intracerebral hemorrhage.

**ROUTES OF EXPOSURE**

dermal; Eye

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

<u>PRODUCT COMPOSITION</u>	<u>CAS REG NO.</u>	<u>WGT. %</u>
<b><u>A. HAZARDOUS</u></b>		
Butyl benzyl phthalate	85-68-7	10 - 30 %
STODDARD SOLVENT	8052-41-3	1 - 5 %
<b><u>B. NON-HAZARDOUS</u></b>		
CALCIUM CARBONATE	1317-65-3	30 - 60 %
Vendor Trade Secret Acrylic polymer	-	10 - 30 %
Water	7732-18-5	10 - 30 %
White Mineral Oil	8042-47-5	1 - 5 %

**4. FIRST AID MEASURES****INGESTION**

Do NOT induce vomiting. To avoid aspiration should vomiting occur, have the person lean forward. Get medical attention immediately. If victim is conscious, give 2-4 glasses of water. Never induce vomiting unless specifically directed by qualified medical personnel. Do not give victim anything to drink if he is unconscious.

**SKIN**

Flush skin with large amounts of water for at least 15 minutes until no evidence of chemical remains. Wash with soap and water.

**INHALATION**

Move to fresh air. If not breathing, begin artificial respiration using a barrier device. Because of

**GE25692****Acrylic Latex Caulk - Antique White**

chemical properties, do not use mouth-to-mouth contact.

**EYES**

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

**NOTE TO PHYSICIAN**

Treatment is symptomatic and supportive.

**5. FIRE-FIGHTING MEASURES**

**FLASH POINT:** > 93.3 °C; 200 °F  
**METHOD:** Estimated  
**IGNITION TEMPERATURE:** Not applicable  
**FLAMMABLE LIMITS IN AIR - LOWER (%):** Not applicable  
**FLAMMABLE LIMITS IN AIR - UPPER (%):** Not applicable

**SENSITIVITY TO MECHANICAL IMPACT:** No

**SENSITIVITY TO STATIC DISCHARGE**

Sensitivity to static discharge is not expected.

**EXTINGUISHING MEDIA**

All standard extinguishing agents are suitable. None

**SPECIAL FIRE FIGHTING PROCEDURES**

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

**6. ACCIDENTAL RELEASE MEASURES****ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED**

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section. Keep out of water supplies and sewers.

**7. HANDLING AND STORAGE****PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Avoid contact with skin and eyes. Use only in well-ventilated areas. Avoid accidental ingestion of this material. Wash hands and face before eating, drinking, smoking, using toilet facilities, or applying cosmetics.

**GE25692****Acrylic Latex Caulk - Antique White**

Keep container closed. Keep out of reach of children.

**STORAGE**

Store away from heat, sources of ignition, and incompatibles.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****ENGINEERING CONTROLS**

Showers; Eyewash stations; Ventilation and other forms of engineering controls are preferred for controlling exposures. Respiratory protection may be needed for non-routine or emergency situations.

**RESPIRATORY PROTECTION**

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

**PROTECTIVE GLOVES**

Neoprene

**EYE AND FACE PROTECTION**

Monogoggles; Safety glasses with side shields

**OTHER PROTECTIVE EQUIPMENT**

Wear suitable protective clothing and eye/face protection.

**Exposure Guidelines**

<b>Component</b>	<b>CAS RN</b>	<b>Source</b>	<b>Value</b>
STODDARD SOLVENT	8052-41-3	ACGIH, TWA	100 ppm
STODDARD SOLVENT	8052-41-3	OSHA Z1, PEL	500 ppm; 2,900 mg/m3

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average; INTL REL - Internal Recommended Exposure Limit

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

**9. PHYSICAL AND CHEMICAL PROPERTIES****BOILING POINT - C & F:**

Not applicable

**VAPOR PRESSURE (20 C) (MM HG):**

Not applicable

**GE25692****Acrylic Latex Caulk - Antique White**

<b>VAPOR DENSITY (AIR=1):</b>	Not applicable
<b>FREEZING POINT:</b>	Not applicable
<b>PHYSICAL STATE:</b>	Solid
<b>Color:</b>	Off-white
<b>SPECIFIC GRAVITY (WATER=1):</b>	ca. 1.40
<b>ACID / ALKALINITY (MEQ/G):</b>	Not applicable
<b>SOLUBILITY IN WATER (20 C):</b>	No data available.
<b>SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT):</b>	No data available.
<b>VOC EXCL. H2O &amp; EXEMPTS (G/L):</b>	47.1 g/l

**10. STABILITY AND REACTIVITY****STABILITY**

Stable

**HAZARDOUS POLYMERIZATION**

Hazardous polymerisation does not occur.

**HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS**

Carbon dioxide; Carbon Monoxide.; Nitrogen Oxides; Toxic monomer fumes.

**INCOMPATIBILITY (MATERIALS TO AVOID)**

None known.

**CONDITIONS TO AVOID**

No data available.

**11. TOXICOLOGICAL INFORMATION****ACUTE ORAL**

Remarks: No data available.

**ACUTE DERMAL**

Remarks: No data available.

**ACUTE INHALATION**

Remarks: No data available.

**OTHER**

Contains ethylene glycol which causes birth defects in laboratory animals.

**SENSITIZATION**

No data available.

**GE25692****Acrylic Latex Caulk - Antique White**

---

**SKIN IRRITATION**

No data available.

**EYE IRRITATION**

No data available.

**MUTAGENICITY**

No data available.

**OTHER EFFECTS OF OVEREXPOSURE**

This product contains butyl benzyl phthalate. Adverse reproductive effects have been reported in animals exposed to butyl benzyl phthalate through chronic feeding studies. Additionally, chronically fed rats exhibited leukemia and lymphomas, including Hodgkin's disease.

**12. ECOLOGICAL INFORMATION****ECOTOXICITY**

Ecotoxicological data for this product is not available.

**DISTRIBUTION**

No data available.

**CHEMICAL FATE**

No data available.

**13. DISPOSAL CONSIDERATIONS****DISPOSAL METHOD**

Disposal should be made in accordance with federal, state and local regulations.

**14. TRANSPORT INFORMATION****Further Information:**

This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

**15. REGULATORY INFORMATION****Inventories**

Australia Inventory of Chemical Substances (AICS)      n (Negative listing)

**GE25692****Acrylic Latex Caulk - Antique White**

---

Japan Inventory of Existing & New Chemical Substances (ENCS) n (Negative listing)  
China Inventory of Existing Chemical Substances n (Negative listing)  
Korea Existing Chemicals Inventory (KECI) n (Negative listing)  
Canada DSL Inventory n (Negative listing)  
Canada NDSL Inventory n (Negative listing)  
Philippines Inventory of Chemicals and Chemical Substances (PICCS) n (Negative listing)  
TSCA list y (positive listing)

For inventories that are marked as quantity restricted or special cases, please contact Momentive.

**US Regulatory Information****SARA (311,312) HAZARD CLASS**

Acute Health Hazard; Chronic Health Hazard

**SARA (313) CHEMICALS**

75-21-8, Ethylene Oxide. 50-00-0, Formaldehyde. 79-06-1, Acrylamide. 107-13-1, Acrylonitrile.

**CALIFORNIA PROPOSITION 65**

WARNING! This product contains a chemical known to the State of California to cause cancer.

**Canadian Regulatory Information****WHMIS HAZARD CLASS**

D2B - Toxic Material Causing Other Toxic Effects

**16. OTHER INFORMATION****OTHER**

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

,C = ceiling limit      NEGL = negligible  
EST = estimated      NF = none found  
NA = not applicable      UNKN = unknown  
NE = none established      REC = recommended  
ND = none determined      V = recommended by vendor  
SKN = skin      TS = trade secret  
R = recommended      MST = mist  
NT = not tested      STEL = short term exposure limit

**GE25692****Acrylic Latex Caulk - Antique White**

---

ppm = parts per million    ppb = parts per billion

By-product= reaction by-product, TSCA inventory status not required under 40 CFR part 720.30(h-2).