

**MSDS - Material Safety Data Sheet****Product Name: HYDRAULIC CLUTCH FLUID (UPC: 078698119090)****(AAP SKU: 7060035)****MSDS No.: M4112****I. Basic Information:****Manufacturer:** RADIATOR SPECIALTY COMPANY**Contact:** Robert Geer**Address:** 600 RADIATOR ROAD**Information Telephone Number:** 704-684--181 1**City, ST Zip:** INDIAN TRAIL, NC 28079**Emergency Contact:** Rocky Mountain Poison Control Center**Country:****Emergency Telephone Number:** 303-623-5716**Emergency Restrictions:****Product Name:** HYDRAULIC CLUTCH FLUID (UPC: 078698119090) (AAP SKU: 7060035)**MSDS No.:** M4112**Issue Date:** 04/15/2008**Supersedes Date:** 04/19/2007**II. Hazards Identification:****EMERGENCY OVERVIEW**

Danger: Harmful or fatal if swallowed. May cause CNS depression. Eye and Skin Irritant.

**OSHA Regulatory Status**

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Potential Health Effects****Route(s) of Entry:**

Absorption, Inhalation, and Ingestion.

**Health Hazards (Acute and Chronic):**

Exposure to high concentrations of mist generated at room temperature may cause lung injury and liver/kidney dysfunction. Skin contact may cause sensitization and allergic skin reaction. Components of this formulation have caused slight embryofetal toxicity (delayed development), but no increase in birth defects in laboratory animals.

**Signs and Symptoms:****EYE CONTACT:** Causes severe irritation, experienced as discomfort or pain, excess blinking and tear production, marked excess redness and swelling of the conjunctiva.**SKIN CONTACT:** Prolonged or repeated contact may cause discomfort and local redness. Prolonged or repeated contact may cause defatting and drying of the skin.**INHALATION:** Short-term health effects are not expected from vapor generated at ambient temperature.**INGESTION:** Slightly toxic. May cause abdominal discomfort, nausea, and vomiting.**Medical Conditions Generally Aggravated by Exposure:**

Skin contact may aggravate an existing dermatitis.

**Other Health Warnings:**

Vomiting and subsequent aspiration into the lungs may lead to chemical pneumonia and pulmonary edema which is a potentially fatal condition.

**Potential Environmental Effects**

Not Available

**III. Composition/Information on Ingredients:**

Chemical Name	CAS No.	% Range	Trade Secret
2-Butoxyethoxy-2-ethanol	112-34-5	<=30.0	
Diethylene Glycol	111-46-6	<=60.0	
Diethylene glycol monoethyl ether	111-90-0	<=7%	
Diethylene glycol monopropyl ether	6881-94-3	<=10.0	
Poly(ethylene oxide)	25322-68-3	<=50.0	
Polyethylene glycol monobutyl ether	9004-77-7	<=60.0	
Polyethylene glycol monomethyl ether	9004-74-4	<=50.0	
Polyethylene/polypropylene glycol ethyl ether	55068-41-2	<=60.0%	

## MSDS - Material Safety Data Sheet

**Product Name: HYDRAULIC CLUTCH FLUID (UPC: 078698119090)  
(AAP SKU: 7060035)**

MSDS No.: M4112

Polyethylene/Polypropylene Glycol Methyl Ether	9063-06-3	<=60.0
Tetraethylene Glycol	112-60-7	<=30%
Tetraethylene Glycol Monomethyl Ether	23783-42-8	<=20%
Triethylene glycol	112-27-6	<=30.0
Triethylene glycol monobutyl ether	143-22-6	<=70.0
Triethylene glycol monoethyl ether	112-50-5	<=85.0

### IV. First Aid Measures:

#### **Emergency and First Aid Procedures:**

Eye Contact: Flush eyes with clean water for 15 minutes while lifting eyelids. Get prompt medical attention.

Skin Contact: Wash with soap and water thoroughly. If adverse effects persist, get prompt medical attention. Launder contaminated clothing before reuse.

Inhalation: Remove to fresh air. If breathing becomes difficult give oxygen and get prompt medical attention. If breathing stops, give artificial respiration and get prompt medical attention.

Ingestion: DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergency room immediately. Aspiration of vomitus into the lungs can cause pneumonitis, which can be fatal.

#### **Note to Physicians:**

N/E

### V. Fire Fighting Measures:

#### **Suitable Extinguishing Media:**

Water Fog, Foam, Carbon Dioxide, Dry Chemical

#### **Unsuitable Extinguishing Media:**

Do not use forced water stream as this could cause the fire to spread.

#### **Products of Combustion:**

Carbon dioxide, carbon monoxide, nitrogen oxides and various hydrocarbons.

#### **Protection of Firefighters:**

Wear self-contained positive pressure breathing apparatus and protective clothes. Use shield to protect from rupturing and venting containers. At elevated temperatures containers may vent, rupture or burst, even violently

### VI. Accidental Release Measures:

#### **Personal Precautions:**

Persons not wearing protective equipment should be excluded from area of spill until clean up has been completed.

#### **Environmental Precautions:**

Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occurred.

#### **Methods for Containment:**

Dike or contain spill and absorb with inert materials (sand, sawdust, absorbent sweeping compounds, rags, etc).

#### **Methods for Cleanup:**

Using a scoop, place contaminated material into an approved chemical waste container. Where possible, vacuum spilled liquid using an explosion proof vacuum to recover material.

#### **Other Information:**

Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occurred.

### VII. Handling and Storage:

#### **Handling Precautions:**

Avoid contact with eyes, skin, and clothing. Avoid repeated breathing of mist. Keep containers closed. Use with adequate ventilation. Wash thoroughly after handling.

## *MSDS - Material Safety Data Sheet*

**Product Name: HYDRAULIC CLUTCH FLUID (UPC: 078698119090)**

**(AAP SKU: 7060035)**

**MSDS No.: M4112**

### Storage Precautions:

Store in cool, dry area away from heat sources. Avoid high temperatures in the presence of strong bases, acids, strong oxidizing agents. Do not mix this product with nitrites or other nitrosating agent because nitrosamines may be formed. Keep containers tightly closed.

### **VIII. Exposure Controls/Personal Protection:**

<b>Chemical Name</b>	<b>OSHA PEL</b>	<b>ACGIH TLV</b>	<b>Other Limits</b>
Triethylene glycol	N/E	N/E	100 mg/m3
Diethylene Glycol	N/E	N/E	50 ppm
Triethylene glycol monoethyl ether	N/E	N/E	Not Available
Triethylene glycol monobutyl ether	N/E	N/E	Not Available
Poly(ethylene oxide)	N/E	N/E	Not Available
Polyethylene glycol monobutyl ether	N/E	N/E	Not Available
Polyethylene glycol monomethyl ether	N/E	N/E	Not Available
2-Butoxyethoxy-2-ethanol	N/E	N/E	Not Available
Diethylene glycol monopropyl ether	N/E	N/E	Not Available
Polyethylene/Polypropylene Glycol Methyl Ether	N/E	N/E	Not Available
Diethylene glycol monoethyl ether	N/E	N/E	Not Available
Polyethylene/polypropylene glycol ethyl ether	N/E	N/E	Not Available
Tetraethylene Glycol	N/E	N/E	Not Available
Tetraethylene Glycol Monomethyl Ether	N/E	N/E	Not Available

### Engineering Controls:

General (mechanical) room ventilation is expected to be satisfactory. Avoid breathing mist.

As Ethylene Glycol Vapors ACGIH -TLV recommends a ceiling level of 39.4 ppm (v)  
OSHA - PEL recommends a ceiling level of 50 ppm (v)

### Personal Protective Equipment:

Safety glasses and goggles for bulk handling. Use nitrile or neoprene gloves. Other protective equipment: eye bath and shower.

### **IX. Physical and Chemical Properties:**

**Boiling Point:** >401°F

**Boiling Range:** N/D

**Solubility In Water:** Soluble

**Flash Point:** 212°F

**Odor Threshold:** N/D

**Melting Point:** NA

**Freezing Point:** N/D

**Evaporation Rate (Butyl Acetate = 1):** <0.01

**Flash Point Method:** TCC

**Appearance and Odor:** Transparent yellow to amber with mild ether like odor

**MSDS - Material Safety Data Sheet****Product Name: HYDRAULIC CLUTCH FLUID (UPC: 078698119090)  
(AAP SKU: 7060035)****MSDS No.: M4112****Vapor Density (AIR = 1): N/D****pH Range: N/A****Decomposition Temp: N/D****Lower Explosive Limit: ND****Specific Gravity (H2O = 1): 1.02****Other Information: N/D****Vapor Pressure (mm Hg.): <0.1****Partition Coefficient: N/D****Auto-Ignition Temp: N/D****Upper Explosive Limit: ND****X. Stability and Reactivity:****Stability:**

Stable

**Conditions to Avoid:**

Avoid heat sources.

**Incompatible Materials:**

Strong alkalis. High temperatures in the presence of strong bases, acids, strong oxidizing agents. Do not mix this product with nitrites or other nitrosating agent because nitrosamines may be formed.

**Hazardous Decomposition Products:**

Carbon monoxide and/or carbon dioxide. Oxides of nitrogen.

**Possibility of Hazardous Reactions:**

Will not occur.

**XI. Toxicological Information:**

Contains one or more amines which may react with nitrites to form nitrosamines.

**XII. Ecological Information:**

No data available

**XIII. Disposal Considerations:**

DISPOSAL: This container may be recycled in a recycling centers when empty. Before offering for recycling, empty the can or bottle by using the product according to the label. If recycling is not available, wrap the container and discard in the trash. Dispose of unused product in accordance with all local, state government and federal laws and regulations

**XIV. Transport Information:****Shipping Name:** Not Available**DOT Hazard Class:** Not Available**UN/NA#:** Not Available**Transportation Information:**

U.S. Department of Transportation (DOT)

Non-Bulk: Not Regulated

Bulk: Not Regulated

Air: IATA Regulated: no

International Information:

Vessel: IMDG Regulated: no

Air: ICAO Regulated: no

**DOT Subsidiary Hazard Class:** Not Available**Packing Group:** Not Available

# MSDS - Material Safety Data Sheet

**Product Name: HYDRAULIC CLUTCH FLUID (UPC: 078698119090)  
(AAP SKU: 7060035)**

MSDS No.: M4112

**XV. Regulatory Information:**

USA TSCA: All chemicals used are listed on the TSCA Inventory.

SARA, SECTION 313 TITLE III: This product contains glycol ethers which are subject to reporting requirement.

STATE/LOCAL:

Pennsylvania Right-to-Know Chemicals:

- Diethylene Glycol (111-46-6)
- Triethylene Glycol (112-27-6)
- Triethylene Glycol Monobutyl Ether (143-22-6)
- Diethylene Glycol Monobutyl Ether (112-34-5)
- Diisopropanolamine (110-97-4)

New Jersey Right-to-Know Chemicals:

- Triethylene Glycol (143-22-6)

**XVI. Other Information:**


- Chemical State:**     Liquid     Gas     Solid
- Chemical Type:**     Pure     Mixture
- Hazard Category:**
- Acute     Chronic     Fire
- Pressure     Reactive



**Additional Manufacturer Warnings:**

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY FROM CHILDREN AND ANIMALS!

- N/E: Not Established
- N/D: Not Determined
- N/A: Not Applicable
- N/AV: Not Available



**Additional Product Information:**

While Radiator Specialty Company believes this data is accurate as of the revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered solely for information, investigation, and verification. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.