

REJUVENOL LABORATORIES, INC

415 Bayview Avenue, Amityville, New York, USA

Phone: 631-789-1309 Fax: 631-842-4385

MATERIAL SAFETY DATA SHEET

IDENTITY REJUVENOL CHOCOLATE BRAZILIAN KERATIN TREATMENT	
---	--

SECTION I

Manufacturer's Name REJUVENOL LABORATORIES	Emergency Telephone Number CHEMTREC: (800)424-9300
Address 415 Bayview Avenue Amityville, NY 11701	Telephone Number for Information 631-789-1309
	Date Prepared 02/2011
	Signature of Preparer(Optional)

SECTION II-HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Formaldehyde	0.75 ppm	0.3 ppm	2 ppm STEL, 0.5 ppm TWA action level. Irritant and potential cancer hazard (29 CFR 1910.1048)	1-2
WATER HYDROLYZED KERATIN PROPYLENE GLYCOL AMODIMETHICONE CETRIMONIUM CHLORIDE CYCLOPENTASILOXANE DIMETHICONE CETEARYL ALCOHOL CETEARETH-20 HYDROLYZED COLLAGEN FRAGRANCE	None Established	None Established	None Established	Trade Secret

12027

SECTION III- Physical/Chemical Characteristics

Boiling Point	98 °C	Specific Gravity (H2O=1)	0.98
Vapor Pressure	N/D	Melting Point	N/A
Vapor Density	N/A	Evaporation Rate (Butyl Acetate = 1)	N/D
Solubility in Water : Soluble			
Appearance and Odor : Light Brown Viscous Lotion with Chocolate smell			

SECTION IV-Fire and Explosion Hazard Data

Flash Point (Method Used) Will not flash	Flammable limits N/A	LEL N/A	UEL N/A
Extinguishing Media Water, CO2, Dry Chemical Foam			
Special Fire Fighting Procedures None			
Unusual Fire and Explosion Hazards None			

Section V - Reactivity Data

Stability	Unstable		Conditions To Avoid
	Stable	X	None Known
Incompatibility (Materials to Avoid) N/A			
Hazardous Decomposition or Byproducts			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	N/A

Section VI- Health Hazard Data

Route(s) of Entry	Inhalation?	Yes	Skin? Yes	Ingestion?
Health Hazards (Acute and Chronic) Danger contains formaldehyde which is a potential carcinogen.				
Carcinogenicity:	NTP?	IARC Monographs	OSHA Regulated?	
Yes	Listed	Group 1, 2A or 2B	Yes	
Signs and Symptoms of Exposure Acute: Inhalation can irritate the nose, throat and lungs. Skin contact might cause				

irritation. Vapors might cause irritation to the eyes with redness, pain and blurred vision. **Chronic:** amounts of formaldehyde in the air above 25 ppm can cause severe injury. prolonged skin contact might cause allergic dermatitis (rash).

Medical Conditions

Generally Aggravated by Exposure

May aggravate existing skin, eye, respiratory, liver and kidney conditions.

Emergency and first Aid Procedures

Inhalation: If inhaled remove to fresh air, If not breathing give artificial respiration, preferable mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin Contact: Immediate wash thoroughly with soap and water, remove contaminated clothing and footwear. Wash clothing before reusing. Get medical attention if irritation should develop.

Eye contact: Remove contact lenses. immediately flush eyes with plenty of water for at least 15 minutes, holding eyelids apart to ensure flushing of the entire surface. Washing within one minute is essential to achieve maximum effectiveness. Seek immediate medical attention.

Ingestion: If swallowed , call a physician immediately. Only induce vomiting at the instruction of the physician. Never give anything by mouth to an unconscious person.

Notes To Physician: Treat symptomatically.

Section VII- Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled

Potential Cancer Hazard. May be fatal if inhaled or Swallowed .

May cause sensitization.

Waste Disposal Method

Precautions to be Taken in Handling and Storing

Avoid contact with eyes, skin and clothing. Avoid breathing vapors. If expose to high vapor concentrations , leave area at once. Use in a well ventilated area.

Other Precautions

Section VIII-Control Measures

Respiratory Protection (Specify Type)

Appropriate respiratory protection shall be worn when applied engineering controls are not adequate to protect against inhalation exposure, Use appropriate NIOSH respiratory protection if TLV exceeded or overexposure is likely. If the exposure limit is exceeded for formaldehyde, a full face-piece with a formaldehyde cartridge may be worn up to 50 times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator manufacturer.

Respirator 3M 8247 or face masque with cartridge 3M 6005 could be use when performing a treatment.

Ventilation

Local Exhaust

Special

Local exhaust ventilation is

N/A

	necessary to maintain exposures to within applicable limits.	
	Mechanical N/A	Other N/A
Protective Gloves Nitrile, Neoprene, Natural Rubber, PVC or Butyl Gloves		Eye Protection Chemical Goggles or a face shield if splashing hazard exist
Other Protective equipment N/A		
Work/Hygiene Practices Ventilate area. Isolate spill and stop leak where safe. Wear appropriate personal equipment as specified in section VIII. Contain and collect equipment in an appropriate container or absorb with an inert material. Do not flush to sewers or surface waterways.		