

**Product:** Touch-Up Paint - Force Damascus Steel Gray (Aerosol)

**Product #:** 92-802878 36

**SECTION I - MANUFACTURER INFORMATION**

**Name:** Mercury Marine  
**Address:** W6250 W. Pioneer Rd.  
PO Box 1939  
Fond du Lac WI 54936-1939

**Emergency:** 800-424-9300 (ChemTrec)  
**Information:** 920-929-5418  
**Date Prepared:** 12-04-98  
**Revised:** 01-15-99

| <b>SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION</b>   |          |                      |       |          |
|--|----------|----------------------|-------|----------|
| Hazardous Components*  | OSHA PEL | ACGIH TLV            | Other | % (Opt.) |
| Carbon Black (1333-86-4)   | N/D      | 3.5mg/m <sup>3</sup> |       | .52      |
| Ethyl Benzene (100-41-4)**                                       | N/D      | 100ppm               |       | 2        |
| N-Butane (106-97-8)  | 800ppm   | 800ppm               |       | 6        |
| Propane (74-98-6)  | N/D      | 1000ppm              |       | 18       |
| Xylene (1330-20-7)**   | 100ppm   | 100ppm               |       | 11       |
| Acetone (67-64-1)  | 750ppm   | 750ppm               |       | 37       |
| Propylene Glycol Methyl Ether Acetate (108-65-6)                 | N/D      | N/E                  |       | 7        |
| *Specific Chemical Identity, Common Name (CAS)                   |          |                      |       |          |
| **This component is listed as a SARA Section 313 Toxic Chemical. |          |                      |       |          |
| <b>SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS</b>           |          |                      |       |          |

**Boiling Point:** 1° to 999°F  
**Vapor Pressure (mmhg):** 5585.2 @ 20°C  
**Vapor Density (Air=1):** N/A  
**Solubility in Water:** N/D  
**Appearance and Odor:** Opaque liquid, solvent odor

**Specific Gravity (H<sub>2</sub>O=1):** .7570  
**Melting Point:** N/D  
**Evaporation Rate:** 7.7  
**(Butyl Acetate=1)**

| <b>SECTION IV - FIRE AND EXPLOSION HAZARD DATA</b> |
|--|
|--|

**Flash Point (Method Used):** < -25°F (No Method Listed)  
**Flammable Limits:** LEL - 1.0 UEL - 100.0  
**Extinguishing Media:** Carbon Dioxide, dry chemical, chemical foam  
**Special Fire Fighting Procedures:** Full protective equipment including SCBA to avoid inhalation should be used. Water spray should not be used except to keep down vapors or cool closed containers to prevent buildup of pressure. If water is used, fog nozzles are preferred.  
**Unusual Fire and Explosion Hazards:** Contents under pressure. Aerosol containers may explode when exposed to extreme heat. Product vapors are heavier than air and may travel a long distance to a source of ignition and flash back.

| <b>SECTION V - REACTIVITY DATA</b> |
|------------------------------------|
|------------------------------------|

**Stability:** Unstable ( ) Stable (X)  
**Conditions to Avoid:** Contact with heat, sparks, and open flame.  
**Incompatibility (Materials to Avoid):** Strong oxidizing agents.  
**Hazardous Decomposition or Byproducts (Thermal):** Carbon Dioxide, Carbon Monoxide, and unidentifiable organic materials.  
**Hazardous Polymerization:** May Occur ( ) Will Not Occur (X)

| <b>ADDITIONAL INFORMATION</b> |
|-------------------------------|
|-------------------------------|

Mercury Marine Emergency Information Number: 920-929-5000  
 Manufacturer, Raabe Corp., Emergency Number: 414-255-9500

**SECTION VI - HEALTH HAZARD DATA**

**Route(s) of Entry:** Inhalation (Y) Skin (Y) Eye (Y) Ingestion (Y)

**Health Hazards (Acute and Chronic):** Liquid or vapor may be irritating to skin, eyes, throat, and lungs.

Intentional misuse by deliberately concentrating and inhaling the contents of this product can be harmful or fatal.

Chronic overexposure to a component or components in this product has been found to cause the following effects in laboratory animals: anemia and damage to kidney, eye, and liver. Chronic exposure has also been suggested as a cause of cardiac abnormalities in humans. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

**Carcinogenicity:** Carbon Black: NTP (N) IARC Monographs (Y) OSHA Regulated (N)

Other Ingredients: NTP (N) IARC Monographs (N) OSHA Regulated (N)

**Signs and Symptoms of Exposure:** Eye - May cause severe irritation. Skin - May cause irritation. Inhalation - Exposure to high vapor concentrations may cause dizziness, breathing difficulty, headaches, or respiratory irritation. Extremely high concentrations may cause drowsiness, staggering, confusion, unconsciousness, coma, or death. Ingestion - Moderately toxic. May cause stomach discomfort, nausea, vomiting, diarrhea, and narcosis. Aspiration of material into the lungs if swallowed or if vomiting occurs can cause chemical pneumonitis, which can be fatal.

**Medical Conditions Generally Aggravated by Exposure:** N/D

**Emergency and First Aid Procedures:** Eye - Immediately flush with plenty of water for at least 15 minutes. Get medical attention if irritation persists. Skin - Remove contaminated clothing and wash affected area thoroughly with soap and water. Seek medical attention. Launder contaminated clothing before reuse. Inhalation - Move person to fresh air. If breathing stops, apply artificial respiration. Seek medical attention. Ingestion - SEEK MEDICAL ATTENTION IMMEDIATELY! The decision to induce vomiting or not must be made by a physician after careful consideration of all materials ingested.

**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE**

**Steps to be Taken in Case Material is Released or Spilled:** Remove all sources of ignition. Ventilate area of spill and adjacent low-lying areas. Avoid breathing solvent vapors. Remove with inert absorbent materials and non-sparking tools.

**Waste Disposal Method:** Place in closed containers. Dispose of product in accordance with federal, state, county, and local regulations.

**Precautions to be taken in Handling and Storing:** Store in a cool, dry area (<120°F) with ventilation suitable for storing materials shown in Section II. Keep away from heat, sparks, and flame. Store away from direct sunlight or sources of ignition. Wash hands thoroughly after handling.

**Other Precautions:** KEEP AWAY FROM CHILDREN!

**SECTION VIII - CONTROL MEASURES**

**Respiratory Protection (Specify Type):** A NIOSH/OSHA-approved respirator suitable for components listed in Section II is recommended if limits are expected to be exceeded.

**Ventilation: Local Exhaust & Mechanical** - Provide sufficient ventilation, in volume and pattern, to keep air contamination below applicable PELs and TLVs.

**Protective Gloves:** Chemical-resistant plastic or rubber gloves

**Eye Protection:** Chemical goggles with side shields or face shield

**Other Protective Clothing or Equipment:** Appropriate impervious clothing if prolonged or repeated contact is likely.

**Work/Hygiene Practices:** Always follow good housekeeping and personal hygiene practices.

N/D = NOT DETERMINED (NO DATA) N/E = NONE ESTABLISHED Y = YES  
N/A = NOT APPLICABLE N/AV = NOT AVAILABLE N = NO