

# Material Safety Data Sheet

ITW Consumer - Devcon/Versachem

1 of 5

## SUPER BLUE SILICONE GASKET MAKER

This product appears in the following stock number(s):  
61309

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Tradename:** SUPER BLUE SILICONE GASKET MAKER

**General use:** When cured, these products are not hazardous. They cure by reacting with atmospheric moisture to slowly give off acetic acid, the same substance as in vinegar. Acetic acid vapor can be an irritant

**Chemical family:** Silicones

#### MANUFACTURER

ITW Consumer - Devcon/Versachem  
2107 West Blue Heron Blvd.  
Riviera Beach, Florida 33404

#### EMERGENCY INFORMATION

Emergency telephone number  
(CHEMTEL): (800) 255-3924  
(CHEMTEL International): (+01) 813-248-0585  
Other Calls: (561) 845-2425

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Abbr.	Weight%	ACGIH; TLV-TWA	OSHA PEL:	Other Limits
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	n/e	>60		n/e	n/e
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE 64742-46-7	n/e	<40	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup> PEL (oil mist)	n/e
AMORPHOUS SILICA 7631-86-9	n/e	5-15	10 mg/m <sup>3</sup>	6 mg/m <sup>3</sup> TWA	n/e
ETHYLTRIACETOXSILANE 17689-77-9	n/e	1-5		n/e	n/e
METHYLTRIACETOXSILANE 4253-34-3	n/e	1-5		n/e	n/e
TRADE SECRET (Non-hazardous) MIXTURE	n/e	balance		n/e	n/e

"TLV" means the Threshold Limit Value exposure (eight-hour, time-weighted average, unless otherwise noted) established by the American Conference of Governmental Industrial Hygienists. "STEL" indicates a short-term exposure limit. "PEL" indicates the OSHA Permissible Exposure Limit. "n/e" indicates that no exposure limit has been established. An asterisk (\*) indicates a substance whose identify is a trade secret of our supplier and unknown to us.

### 3. HAZARDOUS IDENTIFICATION

#### Emergency Overview

**Appearance, form, odor:** paste with vinegar odor

**CAUTION!.** Eye, skin and respiratory irritant. May be harmful if swallowed.

#### Potential health effects

**Primary Routes of Exposure:** Eye and skin contact, ingestion, inhalation

#### Symptoms of acute overexposure

**Skin:** May cause moderate skin irritation.

**Eyes:** The acetic acid vapor given off during cure can cause eye irritation in poorly ventilated areas

## ITW Consumer - Devcon/Versachem

**Inhalation:** May cause mild respiratory irritation. Excessive inhalation causes headache, dizziness, nausea and incoordination.

**Ingestion:** Amounts consumed due to carelessness during normal operations should not cause injury. Ingestion of large amounts may cause discomfort.

**Effects of Chronic Exposure:** None known.

Component	Weight%	NTP	ACGIH Carcinogens	IARC
AMORPHOUS SILICA 7631-86-9	5-15			Group 3 Monograph 68, 1997

### Medical Conditions Recognized as Being Aggravated by Exposure:

Methyltriacetoxysilane: Eye, skin and pulmonary disorders.

## 4. FIRST AID MEASURES

**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

**Skin Contact:** Wipe off material with paper towel or cloth. Wash off with soap and water. If skin irritation persists, call a physician.

**Inhalation:** Move to fresh air; get medical attention if symptoms persist

**Ingestion:** If swallowed, DO NOT induce vomiting. Obtain medical attention immediately

## 5. FIRE FIGHTING MEASURES

**Recommended Extinguishing Media:** Water, Dry chemical, Carbon dioxide, foam

**Flash point:** >200°F (93.3°C)

**Method:** CC

**Lower Explosive**

**Upper Explosive**

**Limit:** n/d

**Limit:** n/d

**Special Fire-Fighting Procedures:** Firefighters should wear self-contained breathing apparatus.

### Unusual Fire/Explosion Hazards:

Toxic smoke or vapors may form during combustion.

### Hazardous Products of Combustion:

Acetic acid, Oxides of carbon, Formaldehyde, Silicon dioxide

## 6. ACCIDENTAL RELEASE MEASURES

**Spill Control:** Ventilate area. Wear the appropriate personal protective equipment.

**Containment:** Dike, contain and absorb with clay, sand or other suitable material

**Cleanup:** Wipe or scrape up spill material. Place in moisture-proof containers. Scrub areas of large spills with detergent and water to remove vinegar odor.

**Special procedures:** Spills may cause slippery floors.

## 7. HANDLING AND STORAGE

**Handling precautions:** Releases acetic acid vapor on contact with moisture or water vapor. Provide appropriate ventilation/respiratory protection against decomposition products (see Section 10) during welding/flame cutting operations and to protect against dust during sanding/grinding of cured product.

**Storage:** Store away from heat. Store away from water or moisture. Keep containers closed when not in use.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Engineering controls:

#### Ventilation:

General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.

**Other engineering controls:** Eye wash station.

### Personal protective equipment

**Eye and face protection:** Safety glasses with side shields

**Skin protection:** Chemical-resistant gloves (i.e. butyl) and other gear as required to prevent skin contact.

**Respiratory protection:** With good ventilation, none required. Use NIOSH-approved organic vapor cartridges for uncured product and dust/particle respirators during sanding/grinding operations of cured product as exposure levels dictate.

**Comments:** When heated to temperatures above 300 degrees F. in the presence of air, this product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Safe handling conditions may be maintained by keeping vapor concentrations below the OSHA permissible limit for formaldehyde

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Specific Gravity:** 0.96

**Boiling Point:** >300°F

**Melting point:** n/d

**Vapor Density (Air=1):** >1

**Vapor Pressure:** n/d

**Evaporation Rate:** <1 (butyl acetate = 1)

**VOC:** <70 g/l

**Solubility in water:** Polymerized

**pH (5% solution or slurry in water):** n/d

## 10. STABILITY AND REACTIVITY

This material is chemically stable. Hazardous polymerization will not occur.

**Conditions to Avoid:** Exposure to moisture.

**Incompatibilities:** Strong oxidizers

**Hazardous Products of Combustion:** Acetic acid, Oxides of carbon, Formaldehyde, Silicon dioxide

**Conditions under which hazardous polymerization may occur:** N/A.

## 11. TOXICOLOGICAL INFORMATION

**Eye Contact:** No data available.

**Subchronic effects:** None known.

**Carcinogenicity, tertogenicity and mutagenicity:** None known.

**Other chronic effects:** None known.

### Toxicological information on hazardous chemical constituents of this product:

Component	Oral LD50 (rat)	Dermal LD50 (rabbit)	Inhalation LC50 4hr (rat)
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	n/d	n/d	n/d

ITW Consumer - Devcon/Versachem

Component	Oral LD50 (rat)	Dermal LD50 (rabbit)	Inhalation LC50 4hr (rat)
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE 64742-46-7	n/d	n/d	n/d
AMORPHOUS SILICA 7631-86-9	n/d	n/d	n/d
ETHYLTRIACETOXSILANE 17689-77-9	n/d	n/d	n/d
METHYLTRIACETOXSILANE 4253-34-3	2060 mg/kg	n/d	n/d
TRADE SECRET (Non-hazardous) MIXTURE	n/d	n/d	n/d

'n/d' = not determined

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity:** No data available.

**Mobility and persistence:** No data available.

**Environmental fate:** No data available.

## 13. DISPOSAL CONSIDERATIONS

Please see also Section 15, Regulatory Information.

**Recommended Method of Disposal:** If material becomes a waste, it would not be a hazardous waste by RCRA criteria (40CFR 261). Dispose of according to applicable federal, state and local regulations.

**US EPA Waste Number:** NH - Not a RCRA Hazardous Waste Material.

## 14. TRANSPORT INFORMATION

**Proper shipping name:** Not regulated

**Technical name:** N/A

**Hazard class:** N/A

**UN/ID Number:** N/A

**Packing group:** N/A

**Emergency Response Guide no:** N/A

## 15. REGULATORY INFORMATION

### U.S. Federal Regulations

**TSCA:**

All ingredients of this product are listed or are exempt from listing on the TSCA Inventory.

**The following RCRA code(s) applies to this material if it becomes waste:**

None

**Regulatory status of hazardous chemical constituents of this product:**

Component	Extremely Hazardous*	Toxic Chemical**	CERCLA RQ (lbs)	12B EXPORT NOTIFICATION:
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	No	No	0.0	Not required

## ITW Consumer - Devcon/Versachem

Component	Extremely Hazardous*	Toxic Chemical**	CERCLA RQ (lbs)	12B EXPORT NOTIFICATION:
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE 64742-46-7	No	No	0.0	Not required
AMORPHOUS SILICA 7631-86-9	No	No	0.0	Not required
ETHYLTRIACETOXSILANE 17689-77-9	No	No	0.0	Not required
METHYLTRIACETOXSILANE 4253-34-3	No	No	0.0	Not required
TRADE SECRET (Non-hazardous) MIXTURE	No	No	0.0	Not required

\*Consult the appropriate regulations for emergency planning and release reporting requirements for substances on the SARA Section 301 Extremely Hazardous Substance List.

\*\*Substances for which the "Toxic Chemical" column is marked "Yes" are on the SARA Section 313 list of Toxic Chemicals, for which release reporting may be required. For specific requirements, consult the appropriate regulations.

**For purposes of SARA Section 312 hazardous materials inventory reporting, the following hazard classes apply to this material:** Immediate health hazard

**California regulations:** For purposes of the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Prop 65), this product does not contain any listed chemical at or above the No Significant Risk Limit.

### Canadian Regulations

**WHMIS Hazard Class:** D2B TOXIC MATERIALS

## 16. OTHER INFORMATION

### **Hazardous Material Information System (HMIS) rating:**

Health 1 Flammability 1 Physical Hazard 0

HMIS is a registered trademark of the National Paint and Coatings Assn.

**Revision Date:** September/08/2008

**Revision Number:** 4

The information and recommendations in this document are based on the best information available to us at the time of preparation, but we make no other warranty, express or implied, as to its correctness or completeness, or as to the results of reliance on this document.