



**The Armor All/STP Products Company**  
 39 Old Ridgebury Road  
 Danbury, CT 06810  
 Tel. 1-203-205-2900

# Material Safety Data Sheet

|                           |  |  |
|---------------------------|--|--|
| <b>I Product:</b>         | ARMOR ALL® OXI MAGIC™ CARPET & UPHOLSTERY CLEANER                                |  |
| <b>Description:</b>       | WHITE CLEAR LIQUID   |  |
| <b>Other Designations</b> | <b>Distributor</b>   | <b>Emergency Telephone Nos.</b>  |
|                           | The Armor All/STP Products Company<br>39 Old Ridgebury Road<br>Danbury, CT 06810 | For Medical Emergencies call:<br>1-866-949-6465<br>For Transportation Emergencies call:<br>1-800-424-9300 (Chemtrec) |

| <b>II Health Hazard Data</b>  | <b>III Hazardous Ingredients</b>  |                               |               |                       |                                     |      |                    |                             |      |                               |  |  |
|---|---|-------------------------------|---------------|-----------------------|-------------------------------------|------|--------------------|-----------------------------|------|-------------------------------|--|--|
| <p><u>Eye Irritant:</u> Eye contact may result in irritation. This product contains hydrogen peroxide, which may cause skin irritation or skin whitening after prolonged contact with the concentrated product.</p> <p><u>FIRST AID:</u></p> <p><u>EYE CONTACT:</u> Flush eyes with water for at least 15 minutes. Call a physician.</p> <p><u>INGESTION:</u> Drink a glassful of water to dilute. Call a physician.</p> <p><u>SKIN CONTACT:</u> Rinse thoroughly with water. If irritation persists, call a physician.</p> <p><u>INHALATION:</u> Move to fresh air. If breathing is affected or if irritation persists, call a physician.</p> <p><u>KEEP OUT OF THE REACH OF CHILDREN.</u></p> | <table border="1"> <thead> <tr> <th>Ingredient</th> <th>Concentration</th> <th>Worker Exposure Limit</th> </tr> </thead> <tbody> <tr> <td>Hydrogen peroxide<br/>CAS #7722-84-1</td> <td>1-5%</td> <td>1 ppm TLV-TWA, PEL</td> </tr> <tr> <td>Isopropanol<br/>CAS# 67-63-0</td> <td>1-5%</td> <td>400ppm TLV-TWA<br/>500ppm STEL</td> </tr> </tbody> </table> <p>None of the ingredients in this product is on the IARC, OSHA or NTP carcinogen lists.</p> <p>TLV-TWA = Threshold Limit Value - Time Weighted Average (ACGIH)<br/>         PEL = Permissible Exposure Level (OSHA)<br/>         STEL = Short term Exposure Limit (ACGIH)</p> | Ingredient                    | Concentration | Worker Exposure Limit | Hydrogen peroxide<br>CAS #7722-84-1 | 1-5% | 1 ppm TLV-TWA, PEL | Isopropanol<br>CAS# 67-63-0 | 1-5% | 400ppm TLV-TWA<br>500ppm STEL |  |  |
| Ingredient  | Concentration   | Worker Exposure Limit         |               |                       |                                     |      |                    |                             |      |                               |  |  |
| Hydrogen peroxide<br>CAS #7722-84-1   | 1-5%  | 1 ppm TLV-TWA, PEL            |               |                       |                                     |      |                    |                             |      |                               |  |  |
| Isopropanol<br>CAS# 67-63-0   | 1-5%  | 400ppm TLV-TWA<br>500ppm STEL |               |                       |                                     |      |                    |                             |      |                               |  |  |

|  |   |
|--|---|
| <b>IV Special Protection and Precautions</b>   | <b>V Transportation and Regulatory Data</b>   |
| <p>The following recommendations are given for production facilities and for other conditions and situations where there is increased potential for accidental, large-scale, or prolonged exposure:</p> <p><u>Hygienic Practices:</u> Wash hands after direct contact. Do not wear product-contaminated clothing for prolonged periods.</p> <p><u>Engineering Controls:</u> Use local exhaust to minimize exposure to product mist.</p> <p><u>Personal Protective Equipment:</u> Wear safety glasses. Wear rubber or neoprene gloves if there is the potential for repeated or prolonged skin contact.</p> | <p><u>U.S. DOT/IMDG/IATA:</u> Not Restricted</p> <p><u>EPA-CERCLA/SARA Title III:</u><br/>         This product is regulated under Sections 311/312. This product contains no chemicals which are regulated under Section 313, and contains sodium dodecylbenzene-sulfonate (CAS # 25155-30-0) which is regulated under 304/CERCLA.</p> <p><u>TSCA</u> - All chemicals in this product are listed on the TSCA Inventory</p> |

|  |  |
|--|--|
| <b>VI Spill Procedures/Waste Disposal</b>  | <b>VII Reactivity Data</b>   |
| <p><u>Spill Procedures:</u> Absorb and containerize. Wash down residual to sanitary sewer. Contact the sanitary treatment facility in advance to assure ability to process washed-down material.</p> <p><u>Waste Disposal:</u> Dispose of in accordance with all applicable federal, state, and local regulations.</p> | <p>Do not heat.<br/>         Do not mix with bleach containing products, alkalis, reducing agents, or organic liquids.</p> |

|  |   |
|--|---|
| <b>VIII Fire and Explosion Data</b>  | <b>IX Physical Data</b>   |
| <p>Flashpoint (Closed Cup) = .....&gt;199 °F</p> <p>Fire Extinguishing Agents: Dry chemical, carbon dioxide (CO<sub>2</sub>), foam or water spray.</p> | <p>pH.....~5.5<br/>         Solubility in water..... Complete<br/>         Specific Gravity..... ~ 1.00</p> |