



The Armor All/STP Products Company
 39 Old Ridgebury Road
 Danbury, CT 06810
 Tel. 1-203-205-2900

Material Safety Data Sheet

I Product: STP® ENGINE STOP LEAK	
Description: DARK BROWN LIQUID WITH A HYDROCARBON ODOR	
Other Designations	Distributor
Oil Additive	The Armor All/STP Products Company 39 Old Ridgebury Road Danbury, CT 06810
Emergency Telephone Nos.	
For Medical Emergencies call: 1-866-949-6465. For Transportation Emergencies call: 1-800-424-9300 (Chemtrec).	

II Health Hazard Data	III Hazardous Ingredients												
<p>Eye Irritant. Prolonged skin contact may cause irritation or dermatitis. Vapors or mists may cause respiratory irritation. Swallowing may cause irritation, nausea, vomiting and diarrhea. Aspiration from ingestion may cause lipid pneumonia.</p> <p>Individuals with preexisting skin disorders may be at increased risk from exposure to this product.</p> <p>Under normal consumer use and conditions, the likelihood of adverse health effects is low.</p> <p>FIRST AID: EYE CONTACT: Immediately flush eyes with plenty of water for 15 minutes. Get immediate medical attention. SKIN CONTACT: Remove contaminated clothing. Wash contact area with soap and water. If irritation persists, get medical attention. INGESTION: Do not induce vomiting. If conscious, give 1-2 glasses of water. Get medical attention by calling a poison Control or doctor. Never give anything by mouth to an unconscious or drowsy person. INHALATION: If symptoms develop, remove to fresh air. If breathing becomes difficult, give oxygen or administer artificial respiration. Get medical attention if symptoms appear.</p>	<table border="1"> <thead> <tr> <th>Ingredients</th> <th>Concentration</th> <th>Worker Exposure Limit</th> </tr> </thead> <tbody> <tr> <td>Mineral Oil CAS# Mixture</td> <td>60-100%</td> <td>5 mg/ m³ TWA PEL/TLV TWA</td> </tr> <tr> <td>Petroleum Distillates CAS# Mixture</td> <td>5-10%</td> <td>500 ppm TLV-TWA</td> </tr> <tr> <td>Zinc Compounds CAS# Proprietary</td> <td>1-5%</td> <td>None established</td> </tr> </tbody> </table> <p>TLV-TWA = ACGIH Threshold Limit Value - Time Weighted Average. PEL = Permissible Exposure Limit</p> <p>None of the ingredients in this product are on the IARC, NTP or OSHA carcinogen list.</p>	Ingredients	Concentration	Worker Exposure Limit	Mineral Oil CAS# Mixture	60-100%	5 mg/ m ³ TWA PEL/TLV TWA	Petroleum Distillates CAS# Mixture	5-10%	500 ppm TLV-TWA	Zinc Compounds CAS# Proprietary	1-5%	None established
Ingredients	Concentration	Worker Exposure Limit											
Mineral Oil CAS# Mixture	60-100%	5 mg/ m ³ TWA PEL/TLV TWA											
Petroleum Distillates CAS# Mixture	5-10%	500 ppm TLV-TWA											
Zinc Compounds CAS# Proprietary	1-5%	None established											

IV Special Protection and Precautions	V Transportation and Regulatory Data
<p>Hygienic Practices: Wash hands thoroughly after contact.</p> <p>Engineering Controls: Use local and/or general ventilation to minimize exposure to vapor or mists.</p> <p>Personal Protective Equipment: Wear safety glasses with sideshields. Wear neoprene or nitrile gloves to prevent skin contact. Use a NIOSH-approved respirator if exposure exceeds occupational limits.</p> <p>Keep container closed when not in use.</p> <p>KEEP OUT OF REACH OF CHILDREN</p>	<p>DOT/IMO/IATA: Not Restricted</p> <p>TSCA Status: All ingredients in this product are listed on the TSCA inventory.</p> <p>EPA - SARA Title III/CERCLA: This product is regulated under Sections 311/312. This product contains Zinc compounds (1-5%), which are regulated under Sara 313 and Section 304/CERCLA.</p>

VI Spill Procedures/Waste Disposal	VII Reactivity Data
<p>Spill Procedures: Wear appropriate protective equipment. Collect with suitable absorbent material and place into a container for disposal. Prevent product from entering sewer or waterways by diking or impounding. Notify National Response Center if spill of any amount enters navigable waters, contiguous zones or adjoining shorelines. Report spills as required under federal, state and local regulations.</p> <p>Waste Disposal: Dispose of in accordance with all applicable federal, state and local regulations.</p>	<p>Stability: Stable</p> <p>Hazardous Polymerization: Will not occur.</p> <p>Hazardous Decomposition: Carbon monoxide, carbon dioxide and hydrogen sulfide.</p> <p>Incompatibilities: Strong oxidizing agents.</p>

VIII Fire and Explosion Data	IX Physical Data
<p>Flash Point: 275°F (CC)</p> <p>Fire Extinguishing Agents: Foam, carbon dioxide, dry chemical or water spray (fog). Cool fire exposed containers with water.</p> <p>Products of Combustion: Carbon monoxide, carbon dioxide and hydrogen sulfide.</p>	<p>Specific Gravity 0.90 @ 15°C</p> <p>Solubility in Water Insoluble</p> <p>Viscosity 1325 cSt@ 40°C 133 cSt@ 100°C</p>