



The Armor All/STP Products Company  
 39 Old Ridgebury Road  
 Danbury, CT 06810  
 Tel. 1-203-205-2900

# Material Safety Data Sheet

<b>I Product:</b> STP® MULTIPURPOSE MOTOR TREATMENT										
<b>Description:</b> LIGHT COLORED LIQUID WITH A MILD ODOR										
<b>Other Designations</b>	<b>Distributor</b>									
	The Armor All/STP Products Company 39 Old Ridgebury Road Danbury, CT 06810									
<b>Emergency Telephone Nos.</b>										
For Medical Emergencies, call 1-866-949-6465. For Transportation Emergencies, call 1-800-424-9300 (Chemtrec).										
<b>II Health Hazard Data</b>	<b>III Hazardous Ingredients</b>									
<p>May cause eye irritation. May cause slight skin irritation. Prolonged skin contact may cause dermatitis. Vapors or mists may cause irritation to the eyes, nose, throat, and respiratory tract. High concentrations above the worker exposure limits may cause central nervous system depression (e.g. dizziness, weakness, nausea, headaches, drowsiness and stupor). Small amounts of liquid aspirated into the lungs can cause chemical pneumonitis, which can be fatal. Besides being an aspiration hazard, ingestion may cause gastrointestinal disturbances (e.g. irritation, nausea, vomiting, and diarrhea) and central nervous system depression. Repeated overexposure to petroleum naphtha can cause nervous system damage.</p> <p>Preexisting eye, skin, and respiratory disorders may be aggravated by exposure to this product.</p> <p><b>FIRST AID:</b></p> <p><b>EYE CONTACT:</b> Rinse with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If irritation persists, call a doctor.</p> <p><b>SKIN CONTACT:</b> Wash with soap and water. If irritation persists, call a doctor.</p> <p><b>INGESTION:</b> DO NOT INDUCE VOMITING. Immediately call a doctor or poison control center.</p> <p><b>INHALATION:</b> Move to fresh air. If breathing problems develop, call a doctor.</p>	<table border="1"> <thead> <tr> <th>Ingredients</th> <th>Concentration</th> <th>Worker Exposure Limit</th> </tr> </thead> <tbody> <tr> <td>Petroleum naphtha, hydrotreated light CAS # 64742-47-8</td> <td>10 - 100%</td> <td>1200 mg/m<sup>3</sup> TWA<sup>b</sup></td> </tr> <tr> <td>Diphenylamine CAS # 122-39-4</td> <td>0 - 10%</td> <td>10 mg/m<sup>3</sup> TLV-TWA<sup>a</sup></td> </tr> </tbody> </table> <p><sup>a</sup>TLV-TWA = ACGIH Threshold Limit Value - Time Weighted Average  <sup>b</sup>Based on supplier recommendation.</p> <p>None of the ingredients in the product are on the IARC, NTP, or OSHA carcinogen lists.</p>	Ingredients	Concentration	Worker Exposure Limit	Petroleum naphtha, hydrotreated light CAS # 64742-47-8	10 - 100%	1200 mg/m <sup>3</sup> TWA <sup>b</sup>	Diphenylamine CAS # 122-39-4	0 - 10%	10 mg/m <sup>3</sup> TLV-TWA <sup>a</sup>
Ingredients	Concentration	Worker Exposure Limit								
Petroleum naphtha, hydrotreated light CAS # 64742-47-8	10 - 100%	1200 mg/m <sup>3</sup> TWA <sup>b</sup>								
Diphenylamine CAS # 122-39-4	0 - 10%	10 mg/m <sup>3</sup> TLV-TWA <sup>a</sup>								
<b>IV Special Protection and Precautions</b>	<b>V Transportation and Regulatory Data</b>									
<p><b>Hygienic Practices:</b> Wash hands after direct contact. Do not wear product-contaminated clothing for prolonged periods.</p> <p><b>Engineering Controls:</b> Use local or general ventilation to minimize exposure to product vapors.</p> <p><b>Personal Protective Equipment:</b> Wear safety glasses. Wear chemical resistant (e.g. nitrile or neoprene) gloves if there is the potential for repeated or prolonged skin contact. In situations where exposure limits may be exceeded, a NIOSH-approved respirator is advised.</p>	<p><b>DOT:</b> Not regulated in non-bulk packaging (less than 119 gal).</p> <p><b>IATA:</b> Not regulated.</p> <p><b>IMDG:</b> Not regulated.</p> <p><b>EPA - SARA Title III/CERCLA:</b> This product is regulated under Sections 311/312. This product is not regulated under Section 313 or Section 304/CERCLA.</p> <p><b>TSCA 8(b):</b> All components of this product are either on the TSCA 8(b) Inventory or otherwise exempt from listing.</p> <p><b>TSCA 12(b):</b> This product is not subject to TSCA 12(b) reporting requirements.</p>									
<b>VI Spill Procedures/Waste Disposal</b>	<b>VII Reactivity Data</b>									
<p><b>Spill Procedures:</b> CAUTION - COMBUSTIBLE. Eliminate potential sources of ignition. Absorb and containerize. Prevent product from entering sewer or waterways by diking or impounding. Notify the National Response Center if a spill of any amount enters navigable waters, the contiguous zone, or adjoining shorelines.</p> <p><b>Waste Disposal:</b> Dispose of in accordance with all applicable federal, state, and local regulations.</p>	<p>Stable under normal use and storage conditions.</p> <p>Avoid contact with strong oxidizing agents.</p>									
<b>VIII Fire and Explosion Data</b>	<b>IX Physical Data</b>									
<p><b>Flashpoint:</b> 66°C (closed cup)</p> <p><b>Fire Extinguishing Agents:</b> Dry chemical, carbon dioxide (CO<sub>2</sub>), foam, or water spray.</p>	<p>Specific gravity (16°C) ..... 0.83</p> <p>Solubility in water..... Insoluble</p>									

DATA SUPPLIED IS FOR USE ONLY IN CONNECTION WITH OCCUPATIONAL SAFETY AND HEALTH

DATE PREPARED 6/2011