

**MATERIAL SAFETY DATA SHEET**

**1. Product And Company Identification**

MSDS ID: MSDS633  
PRODUCT NAME: Prestone® Power Steering Fluid for Asian Vehicles  
PRODUCT NUMBER: AS-269, AS-269Y  
FORMULA NUMBER: 2479-009

MANUFACTURER:  
Prestone Products Corporation  
Danbury, CT 06810-5109

CANADIAN OFFICE:  
FRAM Group (Canada), Inc.  
Mississauga, Ontario L5L 3S6

**MEDICAL EMERGENCIES AND ALL OTHER INFORMATION PHONE NUMBER:**

(800)890-2075 (in the US)  
(800)668-9349 (in Canada)

**TRANSPORTATION EMERGENCY PHONE NUMBER (Chemical Spills and Transport Accidents only):**

CHEMTREC 1-800-424-9300 (in the US)  
CANUTEC (613)996-6666 (in Canada)

MSDS DATE OF PREPARATION/REVISION: 12/21/11

PRODUCT USE: Automobile fluid – consumer product

**2. Hazards Identification**

Amber liquid with a mild petroleum odor.

**EMERGENCY OVERVIEW**

May cause mild transient eye and skin irritation. Prolonged skin contact may cause mild irritation. Oil injection into the skin from high-pressure hydraulic systems may cause severe injury. Most damage occurs during the first four hours. Seek medical attention immediately. Surgical removal may be necessary. Breathing high vapor concentrations may cause headache, dizziness, drowsiness or lung irritation. If the product is swallowed, aspiration may occur resulting in lipid pneumonitis.

**3. Composition/Information On Ingredients**

Component	CAS No.	Amount
Highly-refined petroleum lubricant oils	Proprietary	30 - 60%
1-Decene trimer, hydrogenated	68649-12-7	5 - 40 %
1-Decene homopolymer, hydrogenated	68037-01-4	5 - 40 %

(See Section 8 for Exposure Limits)

**4. First Aid Measures**

**INHALATION:** If symptoms of exposure develop, remove to fresh air. If symptoms persist, or breathing becomes difficult, have qualified personnel administer oxygen. Seek immediate medical attention.

**SKIN CONTACT:** If burned by hot material, Cool skin by quenching with large amounts of water. For contact at ambient temperatures: Remove contaminated clothing. Wash all affected and exposed areas with soap and water. If skin irritation or redness develops and persists, seek medical attention. High pressure injection of this product through the skin is a medical emergency. This product must be removed completely from under the skin. Seek immediate medical attention.

**PRESTONE POWER STEERING FLUID  
FOR ASIAN VEHICLES**

**Date Prepared: 12/21/11**

**EYE CONTACT:** Exposed eyes should be immediately flushed with copious amounts of water using a steady, low-pressure stream for several minutes. After the first few minutes, remove contact lenses, if present and easy to do so, then continue flushing eyes. If irritation, pain, swelling or tearing persist, seek medical attention.

**INGESTION:** If swallowed, get immediate medical attention by calling an emergency room or poison control center. Do not induce vomiting unless directed to do so by a physician. If medical advice cannot be obtained, then take the person and product to the nearest medical emergency center or hospital. If vomiting occurs spontaneously, keep head below hips to prevent aspiration into the lungs. Never give anything by mouth to a person who is unconscious or drowsy.

**NOTES TO PHYSICIAN:** There is no specific antidote. The petroleum oils and other ingredients in this product are unlikely to produce systemic symptoms following accidental ingestion. Upon ingestion, there is a slight risk of aspiration in the lungs which can lead to pneumonitis and non-cardiogenic pulmonary edema. If aspiration is suspected the patient should be observed for sign of lung injury. The viscosity range of the product represented by this MSDS is greater than 100 SUS at 100° F. Careful gastric lavage may be considered to evacuate large quantities of material. Treatment should be directed at the control of symptoms and clinical conditions. Subcutaneous or intramuscular injection requires prompt surgical debridement. There may be no signs of injury or pain initially. Failure to provide immediate treatment may result in extensive necrosis.

**5. Firefighting Measures**

**EXTINGUISHING MEDIA:** Use water fog, foam, carbon dioxide or dry chemical. Water or foam may cause frothing. Cool fire exposed containers with water.

**SPECIAL FIRE FIGHTING PROCEDURES:** Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored.

**UNUSUAL FIRE HAZARDS:** This product can burn but will not readily ignite. Vapors may be released when heated above the flashpoint that can ignite when exposed to an ignition source. In enclosed spaces, heated vapor can ignite with explosive force. Mists or sprays may burn at temperatures below the flashpoint. Containers may rupture from excessive heat.

**HAZARDOUS COMBUSTION PRODUCTS:** Burning may produce carbon monoxide, carbon dioxide, traces oxides of sulfur, and nitrogen.

**6: Accidental Release Measures**

Wear appropriate protective clothing and equipment (See Section 8). Collect material with an inert absorbent material and shovel into appropriate container for disposal. For large spill, recover free product by pumping and place in appropriate, labeled container. Use caution when walking in spilled area. This product can create a slip hazard. Keep out of sewers, watercourses and low areas.

**7. Handling and Storage**

Avoid contact with the eyes.

Avoid prolonged or repeated contact with skin and clothing.

Avoid breathing vapors or mists.

Use with adequate ventilation.

Wash exposed skin with soap and water after use.

Keep container away from excessive heat and open flames.

Keep containers closed when not in use.

Store in a cool, dry, well ventilated area.

Empty containers retain product residue and may be hazardous. Do not cut, weld, drill, etc. containers, even empty. Do not reuse empty containers unless properly cleaned.



**11. Toxicological Information**

**POTENTIAL HEALTH EFFECTS:**

**ACUTE HAZARDS:**

**INHALATION:** At elevated temperatures or in enclosed spaces, product mist or vapors may irritate the mucous membranes of the nose, the throat, bronchi, and lungs; based on data from similar products.

**SKIN CONTACT:** Prolonged contact may cause mild irritation. High pressure injection of this product through the skin may cause possible extensive tissue damage resulting in loss of a finger, hand or arm. There may be no sign of initial injury or pain.

**EYE CONTACT:** Direct eye contact may result in mild transient irritation with redness, tearing, stinging and swelling.

**INGESTION:** Ingestion of this product is not expected to result in any acute systemic toxic effects. If more than several mouthfuls are swallowed, abdominal discomfort, headache, drowsiness, belching, nausea, vomiting and diarrhea may occur. If swallowed, aspiration into the lungs during ingestion or vomiting may result in lipid pneumonitis.

**CHRONIC HAZARDS:** Prolonged or repeated skin contact may remove skin oil, leading to possible skin irritation or dermatitis. In extreme, prolonged exposures to mists, or vapors in poorly ventilated may result in lipid pneumonitis.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Prolonged or repeated skin contact may aggravate an existing skin condition such as acne, seborrhea or dermatitis. Repeated long term contact may aggravate liver, and central nervous

**CARCINOGEN:** None of the components of this product present at greater than 0.1% are listed as carcinogens by OSHA, IARC, NTP or ACGIH.

**Acute Toxicity Values:**

Highly-refined petroleum lubricant oils	Oral Rat LD50 >2,000 mg/kg Dermal Rabbit LD50 >2,000 mg/kg
1-Decene trimer, hydrogenated	Oral Rat LD50 >2,000 mg/kg Dermal Rabbit LD50 >2,000 mg/kg
1-Decene homopolymer, hydrogenated:	Oral Rat LD50 >2,000 mg/kg Dermal Rabbit LD50 >2,000 mg/kg

**12. Ecological Information**

Inherently biodegradable in aerobic conditions. Partition Coefficient (log Kow): >6 (based on similar materials)  
Analysis for ecological effects has not been conducted on this product. However, if spilled, this product and any contaminated soil or water may be harmful to human, animal, and aquatic life. Also, the coating action associated with petroleum products can be harmful or fatal to aquatic life and water fowl.

**13. Disposal Considerations**

Recycle, incinerate or landfill in accordance with all local, state/provincial and federal regulations.

**14. Transport Information**

U.S. DOT HAZARD CLASSIFICATION: Not Regulated

DOT MARINE POLLUTANTS: This product does not contain Marine Pollutants as defined in 49 CFR 171.8.

IMDG CODE SHIPPING CLASSIFICATION: Not Regulated

CANADIAN TDG CLASSIFICATION: Not Regulated

### 15. Regulatory Information

EPA SARA 311/312 HAZARD CLASSIFICATION: Not hazardous

EPA SARA 313: This Product Contains the Following Chemicals Subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None

PROTECTION OF STRATOSPHERIC OZONE: This product is not known to contain or to have been manufactured with ozone depleting substances as defined in 40 CFR Part 82, Appendix A to Subpart A.

CERCLA SECTION 103: This product is not subject to CERCLA reporting requirements, however, oil spills are reportable to the National Response Center under the Clean Water Act. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

EPA TSCA INVENTORY: All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

CALIFORNIA PROPOSITION 65:

This product does not contain chemicals at reportable levels that are regulated under California Proposition 65.

CANADIAN WHMIS CLASSIFICATION: Not a controlled product.

This MSDS has been prepared according to the criteria of the Controlled Products Regulation (CPR) and the MSDS contains all of the information required by the CPR.

### 16. Other Information

NFPA Rating: Fire: 1                      Health: 1                      Reactivity: 0

REVISION SUMMARY: Changes to Section 1: Product numbers; Section 3: Composition; Section 8: Exposure limits; Section 9: Viscosity, Boiling point, Freezing point; Section 11: Chronic hazards, and Acute toxicity; and Section 15: SARA 313.

This MSDS is directed to professional users and bulk handlers of the product. Consumer products are labeled in accordance with Federal Hazardous Substances Act regulations.

While Prestone Products Corporation believes that the data contained herein are factual and the opinions expressed are those of qualified experts regarding the results of tests conducted, the data are not to be taken as a warranty or representation for which Prestone Products Corporation assumes legal responsibility. They are offered for your consideration, investigation and verification. Any use of these data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

If more information is needed, please contact:                      Prestone Products Corporation  
69 Eagle Road  
Danbury, CT 06810  
(800) 890-2075