

**The Clorox Company**1221 Broadway
Oakland, CA 94612
Tel. 1-510-271-7000**Material Safety
Data Sheet**

I Product: CLOROX® FRAGANZIA™ AIR FRESHENER – LAVENDER WITH EUCALYPTUS & MINT / LAVANDA CON EUCALIPTO Y MENTA																
Description: CLEAR, COLORLESS, THIN LIQUID WITH A LAVENDER, EUCALYPTUS, MINT ODOR IN AN AEROSOL CAN																
	Distributor															
	The Clorox Sales Company 1221 Broadway Oakland, CA 94612															
	Emergency Telephone Nos.															
	For Medical Emergencies, call 1-800-446-1014. For Transportation Emergencies, call 1-800-424-9300 (Chemtrec).															
II Health Hazard Data	III Hazardous Ingredients															
Under normal consumer use and conditions, the likelihood of any adverse health effects is low. No medical conditions are known to be aggravated by exposure to this product. FIRST AID: EYE CONTACT: Rinse with plenty of water. If irritation persists, call a doctor. SKIN CONTACT: Rinse with plenty of water. If irritation persists, call a doctor. INGESTION: Drink a glassful of water. Call a doctor or poison control center. INHALATION: Move person to fresh air. If breathing problems develop, call a doctor.	<table border="1"> <thead> <tr> <th>Ingredients</th> <th>Concentration</th> <th>Worker Exposure Limit</th> </tr> </thead> <tbody> <tr> <td>n-Butane CAS # 106-97-8</td> <td>7 - 13%</td> <td>1000 ppm - TLV-TWA^{a,b}</td> </tr> <tr> <td>Isobutane CAS # 75-28-5</td> <td>1 - 5%</td> <td>1000 ppm - TLV-TWA^{a,b}</td> </tr> <tr> <td>Propane CAS # 74-98-6</td> <td>1 - 5%</td> <td>1000 ppm - TLV-TWA^{a,b} 1000 ppm - PEL^c</td> </tr> <tr> <td>Ethanol CAS # 64-17-5</td> <td>0.5 - 1.5%</td> <td>1000 ppm - TLV-TWA^a 1000 ppm - PEL^c</td> </tr> </tbody> </table> <p>^aTLV-TWA = ACGIH Threshold Limit Value-Time Weighted Average ^bACGIH TLV-TWA for aliphatic hydrocarbon gases (C1-C4 alkanes) ^cPEL = OSHA Permissible Exposure Limit - Time Weighted Average</p> <p>None of the materials in this product are on the IARC, OSHA, or NTP carcinogen lists.</p>	Ingredients	Concentration	Worker Exposure Limit	n-Butane CAS # 106-97-8	7 - 13%	1000 ppm - TLV-TWA ^{a,b}	Isobutane CAS # 75-28-5	1 - 5%	1000 ppm - TLV-TWA ^{a,b}	Propane CAS # 74-98-6	1 - 5%	1000 ppm - TLV-TWA ^{a,b} 1000 ppm - PEL ^c	Ethanol CAS # 64-17-5	0.5 - 1.5%	1000 ppm - TLV-TWA ^a 1000 ppm - PEL ^c
Ingredients	Concentration	Worker Exposure Limit														
n-Butane CAS # 106-97-8	7 - 13%	1000 ppm - TLV-TWA ^{a,b}														
Isobutane CAS # 75-28-5	1 - 5%	1000 ppm - TLV-TWA ^{a,b}														
Propane CAS # 74-98-6	1 - 5%	1000 ppm - TLV-TWA ^{a,b} 1000 ppm - PEL ^c														
Ethanol CAS # 64-17-5	0.5 - 1.5%	1000 ppm - TLV-TWA ^a 1000 ppm - PEL ^c														
IV Special Protection and Precautions	V Transportation and Regulatory Data															
Hygienic Practices: Wash hands after direct contact. Engineering Controls: Use general ventilation to minimize exposure to product mist. Personal Protective Equipment: Wear safety glasses. In situations where exposure limits may be exceeded, a NIOSH-approved respirator is advised. Contents under pressure. Do not expose to heat or store at temperatures above 49°C. Do not puncture or incinerate container. Store in accordance with NFPA 30B for Level 1 aerosols.	DOT: Consumer Commodity ORM-D. IMDG: Dangerous goods in limited quantities of Class 2, UN1950. IATA: Aerosols, non-flammable, n.o.s., Class 2.2, UN1950. EPA - SARA Title III/CERCLA: This product is regulated under Sections 311/312. This product contains sodium nitrite (CAS # 7632-00-0, <0.1%) that is regulated under Section 313 and under Section 304/CERCLA and sodium hydroxide (CAS # 1310-73-2, <0.1%) that is regulated under Section 304/CERCLA. TSCA 8(b): All components of this product are either on the TSCA 8(b) Inventory or otherwise exempt from listing. TSCA 12(b): This product is not subject to TSCA 12(b) reporting requirements.															
VI Spill Procedures/Waste Disposal	VII Reactivity Data															
Spill Procedures: Absorb and containerize. Wash residual down to sanitary sewer. Contact the sanitary treatment facility in advance to assure ability to process washed-down material. Waste Disposal: Dispose of in accordance with all applicable federal, state, and local regulations.	Stable under normal use and storage conditions.															
VIII Fire and Explosion Data	IX Physical Data															
Flash Point (liquid): >93°C (closed cup) Fire Extinguishing Agents: Dry chemical, carbon dioxide (CO ₂), foam, or water spray. Fire and Explosion Hazards/Protective Equipment: Containers may rupture at temperatures greater than 49°C. Cool exposed containers to avoid potential bursting or venting. Use equipment or shielding to protect personnel from bursting containers. NFPA Aerosol Classification: Level 1. CPSC Aerosol Classification: Not flammable.	pH (liquid).....~11 Specific gravity (liquid)~1.0 Solubility in water (liquid)Soluble															