

1. Product and company identification

| | |
|-----------------------------|--|
| Product name | : LN-740 WOOD PROJECTS AHE74024TN0 |
| Manufacturer | : Akzo Nobel Paints LLC 15885 West Sprague Road Strongsville, OH 44136 U.S.A. |
| Validation date | : 2013-03-12. |
| Print date | : 2013-03-12. |
| Responsible name | : Product Safety and Compliance |
| In case of emergency | : 1-800-545-2643 |

2. Hazards identification

Emergency overview

| | |
|-------------------------------|--|
| Physical state | : Liquid. |
| Signal word | : WARNING! |
| Hazard statements | CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. MAY CAUSE ALLERGIC RESPIRATORY AND SKIN REACTION. MAY BE HARMFUL IF SWALLOWED. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA. CANCER HAZARD - CONTAINS MATERIAL WHICH CAN CAUSE CANCER. |
| Precautionary measures | : Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Do not eat, drink or smoke when using this product. Avoid contact with eyes, skin and clothing. Keep container tightly closed. Use personal protective equipment as required. Wash thoroughly after handling. |

Potential acute health effects

| | |
|-------------------|--|
| Inhalation | : Irritating to respiratory system. May cause sensitization by inhalation. |
| Ingestion | : Harmful if swallowed. |
| Skin | : Irritating to skin. May cause sensitization by skin contact. |
| Eyes | : Irritating to eyes. |

Potential chronic health effects

| | |
|------------------------------|---|
| Chronic effects | : Contains material that may cause target organ damage, based on animal data. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. |
| Carcinogenicity | : Contains material which can cause cancer. Risk of cancer depends on duration and level of exposure. |
| Mutagenicity | : No known significant effects or critical hazards. |
| Teratogenicity | : No known significant effects or critical hazards. |
| Developmental effects | : No known significant effects or critical hazards. |
| Fertility effects | : No known significant effects or critical hazards. |
| Target organs | : Contains material which may cause damage to the following organs: lungs, upper respiratory tract, skin, eyes, stomach. |

Over-exposure signs/symptoms

| | |
|-------------------|--|
| Inhalation | : Adverse symptoms may include the following: respiratory tract irritation coughing wheezing and breathing difficulties asthma |
|-------------------|--|

2. Hazards identification

- Ingestion** : No specific data.
- Skin** : Adverse symptoms may include the following:
irritation
redness
- Eyes** : Adverse symptoms may include the following:
pain or irritation
watering
redness

See toxicological information (Section 11)

3. Composition/information on ingredients

| Name | CAS number | % |
|---------------------------------|------------|----------|
| Limestone | 1317-65-3 | 10-<30 |
| Acrylic (co)polymer, waterborne | | 10-<30 |
| Kaolin | 1332-58-7 | 1-<5 |
| propane-1,2-diol | 57-55-6 | 1-<5 |
| EPOXIAMINA CICLOALIFATICA | | 1-<5 |
| ethanol | 64-17-5 | 0.1-<1.0 |
| Quartz (SiO ₂) | 14808-60-7 | 0.1-<1.0 |
| vinyl acetate | 108-05-4 | 0.1-<1.0 |
| Formaldehyde | 50-00-0 | < 0.01 |
| water | 7732-18-5 | 30-<60 |

4. First aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
- Skin contact** : In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
- Inhalation** : Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
- Ingestion** : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

5. Fire-fighting measures

- Flammability of the product** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Extinguishing media**
- Suitable** : Use an extinguishing agent suitable for the surrounding fire.
- Not suitable** : None known.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides

8. Exposure controls/personal protection

| | |
|----------------------------|--|
| | <p>Appendix A -- Carcinogens. Respirable fraction; see Appendix C, paragraph C. TWA: 2 mg/m³ 8 hour(s). Form: Respirable fraction NIOSH REL (United States, 6/2009). TWA: 5 mg/m³ 10 hour(s). Form: Respirable fraction TWA: 10 mg/m³ 10 hour(s). Form: Total OSHA PEL (United States, 6/2010). TWA: 5 mg/m³ 8 hour(s). Form: Respirable fraction TWA: 15 mg/m³ 8 hour(s). Form: Total dust OSHA PEL 1989 (United States, 3/1989). TWA: 5 mg/m³ 8 hour(s). Form: Respirable fraction TWA: 10 mg/m³ 8 hour(s). Form: Total dust</p> |
| propane-1,2-diol | <p>AIHA WEEL (United States, 10/2011). TWA: 10 mg/m³ 8 hour(s).</p> |
| ethanol | <p>ACGIH TLV (United States, 1/2008). Notes: 1996 Adoption Refers to Appendix A -- Carcinogens. TWA: 1880 mg/m³ 8 hour(s). ACGIH TLV (United States, 1/2011). Notes: 1996 Adoption Refers to Appendix A -- Carcinogens. STEL: 1000 ppm 15 minute(s). NIOSH REL (United States, 6/2009). TWA: 1900 mg/m³ 10 hour(s). TWA: 1000 ppm 10 hour(s). OSHA PEL (United States, 6/2010). TWA: 1900 mg/m³ 8 hour(s). TWA: 1000 ppm 8 hour(s). OSHA PEL 1989 (United States, 3/1989). TWA: 1900 mg/m³ 8 hour(s). TWA: 1000 ppm 8 hour(s).</p> |
| Quartz (SiO ₂) | <p>OSHA PEL Z3 (United States, 9/2005). Notes: 10/(SiO₂+2) TWA: 10 mg/m³ 8 hour(s). Form: Respirable OSHA PEL Z3 (United States, 9/2005). Notes: 250/(%SiO₂+5) TWA: 250 mppcf 8 hour(s). Form: Respirable OSHA PEL 1989 (United States, 3/1989). Notes: as quartz TWA: 0.1 mg/m³, (as quartz) 8 hour(s). Form: Respirable dust ACGIH TLV (United States, 1/2011). Notes: Respirable fraction; see Appendix C, paragraph C. TWA: 0.025 mg/m³ 8 hour(s). Form: Respirable fraction OSHA PEL Z3 (United States, 9/2005). Notes: 30/(%SiO₂+2) TWA: 30 mg/m³ 8 hour(s). Form: Total dust. NIOSH REL (United States, 6/2009). Notes: See Appendix A - NIOSH Potential Occupational Carcinogen TWA: 0.05 mg/m³ 10 hour(s). Form: respirable dust</p> |
| vinyl acetate | <p>ACGIH TLV (United States, 1/2011). TWA: 10 ppm 8 hour(s). TWA: 35 mg/m³ 8 hour(s). STEL: 15 ppm 15 minute(s). STEL: 53 mg/m³ 15 minute(s). OSHA PEL 1989 (United States, 3/1989). TWA: 10 ppm 8 hour(s). TWA: 30 mg/m³ 8 hour(s). STEL: 20 ppm 15 minute(s). STEL: 60 mg/m³ 15 minute(s). NIOSH REL (United States, 6/2009). CEIL: 4 ppm 15 minute(s). CEIL: 15 mg/m³ 15 minute(s).</p> |
| Formaldehyde | <p>ACGIH TLV (United States, 1/2011). Skin sensitizer. Notes: Substance identified by other sources as a suspected or confirmed human carcinogen. Refers to Appendix A -- Carcinogens. 2000 Adoption.</p> |

8. Exposure controls/personal protection

C: 0.37 mg/m³
 C: 0.3 ppm
NIOSH REL (United States, 6/2009). Notes: See Appendix A - NIOSH Potential Occupational Carcinogen
 CEIL: 0.1 ppm 15 minute(s).
 TWA: 0.016 ppm 10 hour(s).
OSHA PEL (United States, 6/2010).
 STEL: 2 ppm 15 minute(s).
 TWA: 0.75 ppm 8 hour(s).
OSHA PEL 1989 (United States, 3/1989). Notes: See Table Z-2 for operations or sectors excluded from section 1910.1048 or for which limit(s) is(are) stayed. Sec. 1910.1048 Formaldehyde.
 STEL: 2 ppm 15 minute(s).
 TWA: 0.75 ppm 8 hour(s).
OSHA PEL Z2 (United States, 11/2006). Notes: Sec. 1910.1048 Formaldehyde.
 STEL: 2 ppm 15 minute(s).
 TWA: 0.75 ppm 8 hour(s).

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.
- Engineering measures** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Personal protection**
- Respiratory** : A NIOSH-approved, air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where air-purifying respirators may not provide adequate protection.
- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eyes** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

| | |
|-----------------------------------|--|
| Physical state | : Liquid. |
| Flash point | : Closed cup: 96°C (204.8°F) |
| Auto-ignition temperature | : Not available. |
| Flammable limits | : Not available. |
| Color | : Not available. |
| Odor | : not available |
| pH | : Not available. |
| Boiling/condensation point | : 100°C (212°F) |
| Melting/freezing point | : 0°C (32°F) |
| Specific gravity | : 1.318 |
| Density (lbs/gal) | : 10.999 |
| Vapor pressure | : Not available. |
| Vapor density | : Not available. |
| Volatility | : 54.8% (v/v), 41.29% (w/w) |
| Viscosity | : Dynamic: 99999 mPa·s (99999 cP) |
| Dispersibility properties | : Easily dispersible in the following materials: cold water. |
| Solubility | : Easily soluble in the following materials: cold water. |
| VOC g/l | : 17 g/l [Method 24] |

10. Stability and reactivity

| | |
|---|--|
| Chemical stability | : The product is stable. |
| Conditions to avoid | : No specific data. |
| Incompatible materials | : No specific data. |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |

11. Toxicological information

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|-----------------------|---------|--------------------------|----------|
| propane-1,2-diol | LD50 Dermal | Rabbit | 20800 mg/kg | - |
| | LD50 Oral | Rat | 20 g/kg | - |
| ethanol | LC50 Inhalation Vapor | Rat | 124700 mg/m ³ | 4 hours |
| | LD50 Oral | Rat | 7 g/kg | - |
| vinyl acetate | LC50 Inhalation Vapor | Rat | 11400 mg/m ³ | 4 hours |
| | LD50 Dermal | Rabbit | 2335 mg/kg | - |
| Formaldehyde | LD50 Oral | Rat | 2900 mg/kg | - |
| | LC50 Inhalation Gas. | Rat | 250 ppm | 4 hours |
| | LD50 Dermal | Rabbit | 270 mg/kg | - |
| | LD50 Oral | Rat | 100 mg/kg | - |

Conclusion/Summary : Not available.

Chronic toxicity

Conclusion/Summary : Not available.

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|--------|---------|-------|----------|-------------|
| | | | | | |

11. Toxicological information

| | | | | | |
|------------------|--------------------------|--------|---|--------------------------------------|---|
| propane-1,2-diol | Eyes - Mild irritant | Rabbit | - | 24 hours 500 milligrams | - |
| | Eyes - Mild irritant | Rabbit | - | 100 milligrams | - |
| | Skin - Moderate irritant | Child | - | 96 hours 30 Percent continuous | - |
| | Skin - Mild irritant | Human | - | 168 hours 500 milligrams | - |
| | Skin - Moderate irritant | Human | - | 72 hours 104 milligrams Intermittent | - |
| | Skin - Mild irritant | Woman | - | 96 hours 30 Percent | - |
| ethanol | Eyes - Mild irritant | Rabbit | - | 24 hours 500 milligrams | - |
| | Eyes - Moderate irritant | Rabbit | - | 0.06666667 minutes 100 milligrams | - |
| | Eyes - Moderate irritant | Rabbit | - | 100 microliters | - |
| | Eyes - Severe irritant | Rabbit | - | 500 milligrams | - |
| | Skin - Mild irritant | Rabbit | - | 400 milligrams | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 20 milligrams | - |
| Formaldehyde | Eyes - Mild irritant | Human | - | 6 minutes 1 parts per million | - |
| | Eyes - Severe irritant | Rabbit | - | 24 hours 750 Micrograms | - |
| | Eyes - Severe irritant | Rabbit | - | 750 Micrograms | - |
| | Skin - Mild irritant | Human | - | 72 hours 150 Micrograms Intermittent | - |
| | Skin - Severe irritant | Human | - | 0.01 Percent | - |
| | Skin - Mild irritant | Rabbit | - | 540 milligrams | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 50 milligrams | - |
| | Skin - Severe irritant | Rabbit | - | 24 hours 2 milligrams | - |

Conclusion/Summary : Not available.

Sensitizer

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Classification

| Product/ingredient name | ACGIH | IARC | EPA | NIOSH | NTP | OSHA |
|-------------------------|-------|------|-----|-------|---------|------|
| Kaolin | A4 | - | - | - | - | - |
| ethanol | A3 | 1 | - | None. | - | - |
| Quartz (SiO2) | A2 | 1 | - | + | Proven. | - |
| vinyl acetate | A3 | 2B | - | - | - | - |
| Formaldehyde | A2 | 1 | - | + | Proven. | + |

Mutagenicity

Conclusion/Summary : Not available.

11. Toxicological information

Teratogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

12. Ecological information

Ecotoxicity : No known significant effects or critical hazards.

Aquatic ecotoxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|--|--|----------|
| propane-1,2-diol | Acute EC50 >1000 mg/L Fresh water | Daphnia - Daphnia magna - <24 hours | 48 hours |
| | Acute LC50 1020000 ug/L Fresh water | Crustaceans - Ceriodaphnia dubia - <24 hours | 48 hours |
| | Acute LC50 710000 ug/L Fresh water | Fish - Pimephales promelas - <=7 days | 96 hours |
| ethanol | Acute EC50 17.921 mg/L Marine water | Algae - Ulva pertusa | 96 hours |
| | Acute EC50 2000 ug/L Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 25500 ug/L Marine water | Crustaceans - Artemia franchiscana - Larvae | 48 hours |
| | Acute LC50 42000 ug/L Fresh water | Fish - Oncorhynchus mykiss | 4 days |
| | Chronic NOEC <6.3 g/L Fresh water | Daphnia - Daphnia magna | 48 hours |
| vinyl acetate | Chronic NOEC 0.375 ul/L Fresh water | Fish - Gambusia holbrooki - Larvae - 3 days | 12 weeks |
| | Acute LC50 10000 to 100000 ug/L Marine water | Crustaceans - Crangon crangon - Larvae | 48 hours |
| | Acute LC50 14000 ug/L Fresh water | Fish - Pimephales promelas - 1 days | 96 hours |
| Formaldehyde | Acute EC50 0.788 mg/L Marine water | Algae - Ulva pertusa | 96 hours |
| | Acute EC50 12.98 mg/L Fresh water | Crustaceans - Ceriodaphnia dubia - Neonate - <24 hours | 48 hours |
| | Acute EC50 5800 to 7800 ug/L Fresh water | Daphnia - Daphnia pulex - Neonate - <24 hours | 48 hours |
| | Acute LC50 1.41 ppm Fresh water | Fish - Oncorhynchus mykiss | 96 hours |

Conclusion/Summary : Not available.

Persistence/degradability

Conclusion/Summary : Not available.

13. Disposal considerations

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

| Regulatory information | UN number | Proper shipping name | Classes | PG* | Label | Additional information |
|---------------------------|----------------|----------------------|----------------|-----|-------|------------------------|
| DOT Classification | Not available. | Not available. | Not available. | - | | - |
| IMDG Class | Not available. | Not available. | Not available. | - | | - |

PG* : Packing group

15. Regulatory information

U.S. Federal regulations : **United States inventory (TSCA 8b)**: All components are listed or exempted.
SARA 302/304/311/312 extremely hazardous substances: No components were found.
SARA 302/304 emergency planning and notification: No components were found.
SARA 302/304/311/312 hazardous chemicals: Limestone; Kaolin; propane-1,2-diol
SARA 311/312 MSDS distribution - chemical inventory - hazard identification:
 Limestone: Immediate (acute) health hazard; Kaolin: Delayed (chronic) health hazard;
 propane-1,2-diol: Immediate (acute) health hazard, Delayed (chronic) health hazard

State regulations

Massachusetts : The following components are listed: CALCIUM CARBONATE
New York : The following components are listed: Vinyl acetate
New Jersey : The following components are listed: CALCIUM CARBONATE; LIMESTONE; KAOLIN;
 PROPYLENE GLYCOL; 1,2-PROPANEDIOL; ETHYL ALCOHOL; ALCOHOL; SILICA,
 QUARTZ; QUARTZ (SiO₂); VINYL ACETATE; ACETIC ACID ETHENYL ESTER
Pennsylvania : The following components are listed: LIMESTONE; KAOLIN; 1,2-PROPANEDIOL;
 DENATURED ALCOHOL; QUARTZ (SiO₂); ACETIC ACID ETHENYL ESTER

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

International regulations

Canada inventory : Not determined.

16. Other information

Hazardous Material Information System (U.S.A.) :

| | | |
|------------------|---|---|
| Health | * | 2 |
| Flammability | | 1 |
| Physical hazards | | 0 |
| | | |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

Prepared by : Product Safety and Compliance Akzo Nobel Paints LLC

Notice to reader

The information contained herein is based on data available at the time of preparation of this data sheet and which Akzo Nobel Paints LLC believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. Akzo Nobel Paints LLC shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

Complies with OSHA Hazard Communication Standard 29CFR1910.1200.

16. Other information

