

Pyroil™ OCTANE TREAT OCTANE  
TREATMENT  
PYOCT12

### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone number	1-800-ASHLAND (1-800-274-5263)

Product name Pyroil™ OCTANE TREAT OCTANE TREATMENT

Product code PYOCT12

### 2. HAZARDS IDENTIFICATION

#### Emergency Overview

Appearance: liquid, yellow

CAUTION! COMBUSTIBLE LIQUID AND VAPOR. MAY AFFECT THE CENTRAL NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN AND RESPIRATORY TRACT IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE DERMATITIS AND BURNS.

#### Potential Health Effects

##### **Exposure routes**

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

##### **Eye contact**

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

##### **Skin contact**

Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, skin burns, and other skin damage.

##### **Ingestion**

Pyroil™ OCTANE TREAT OCTANE  
TREATMENT  
PYOCT12

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

### **Inhalation**

Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

### **Aggravated Medical Condition**

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: Skin, lung (for example, asthma-like conditions), Individuals with preexisting heart disorders may be more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material.

### **Symptoms**

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), Lung irritation, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), Lack of coordination, confusion, irregular heartbeat, narcosis (dazed or sluggish feeling), Convulsions, coma

### **Target Organs**

Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver effects

### **Carcinogenicity**

This product (or a component) is a petroleum-derived material. Similar materials and certain compounds occurring naturally in petroleum oils have been shown to cause skin cancer in laboratory animals following repeated exposure without washing or removal. This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

### **Reproductive hazard**

Based on the available information, risk to the fetus from maternal exposure to this material cannot be assessed.

Pyroil™ OCTANE TREAT OCTANE  
TREATMENT  
PYOCT12

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	CAS-No. / Trade Secret No.	Concentration
KEROSENE	8008-20-6	>=90-<=100%

### 4. FIRST AID MEASURES

#### Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

#### Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

#### Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

#### Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

#### Notes to physician

**Hazards:** Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard.

Pyroil™ OCTANE TREAT OCTANE  
TREATMENT  
PYOCT12

Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting.

**Treatment:** No information available.

### 5. FIREFIGHTING MEASURES

#### Suitable extinguishing media

Dry chemical, Carbon dioxide (CO<sub>2</sub>), Water spray

#### Hazardous combustion products

Aldehydes, carbon dioxide and carbon monoxide, Hydrocarbons, nitrogen oxides (NO<sub>x</sub>), sulfur oxides

#### Precautions for fire-fighting

If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

#### NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class II

### 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Ensure adequate ventilation. Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Pay attention to the spreading of gases especially at ground level (heavier than air) and to the direction of the wind.

#### Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

Pyroil™ OCTANE TREAT OCTANE  
TREATMENT  
PYOCT12

### Methods for cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### Other information

Comply with all applicable federal, state, and local regulations. Suppress (knock down) gases/vapours/mists with a water spray jet.

## 7. HANDLING AND STORAGE

### Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.

### Storage

Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in a cool, dry, ventilated area.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Guidelines

KEROSENE		8008-20-6	
ACGIH	time weighted average	200 mg/m3	Non-aerosol
NIOSH	Recommended exposure limit (REL):	100 mg/m3	

### General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect

Pyroil™ OCTANE TREAT OCTANE  
TREATMENT  
PYOCT12

exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

### Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

### Eye protection

Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

### Skin and body protection

Wear resistant gloves such as:

Neoprene

Nitrile rubber

Polyethylene

Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Discard gloves that show tears, pinholes, or signs of wear.

### Respiratory protection

Respiratory protection is not required under normal conditions of use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state</b>	liquid
<b>Colour</b>	yellow
<b>Odour</b>	hydrocarbon-like
<b>Boiling point/boiling range</b>	(>)293 °F / 145 °C
<b>Flash point</b>	120.00 °F / 48.89 °C Calculated Flash Point
<b>Evaporation rate</b>	(<)1
<b>Lower explosion limit/Upper explosion limit</b>	0.7 %(V) / 5 %(V)
<b>Vapour pressure</b>	0.639 hPa @ 68 °F / 20 °C Calculated Vapor

Pyroil™ OCTANE TREAT OCTANE  
TREATMENT  
PYOCT12

	Pressure
Density	0.8051 g/cm <sup>3</sup> @ 60.01 °F / 15.56 °C
Water solubility	insoluble

### 10. STABILITY AND REACTIVITY

#### Stability

Stable.

#### Conditions to avoid

excessive heat, Heat, flames and sparks.

#### Incompatible products

Strong oxidizing agents

#### Hazardous decomposition products

carbon dioxide and carbon monoxide, Hydrocarbons, nitrogen oxides (NO<sub>x</sub>), Sulphur oxides

#### Hazardous reactions

Product will not undergo hazardous polymerization.

### 11. TOXICOLOGICAL INFORMATION

#### Acute oral toxicity

Acute oral toxicity - : no data available  
Product

#### Acute oral toxicity - Components

KEROSENE : LD 50: > 5,000 mg/kg Species: Rat

#### Acute inhalation toxicity

Acute inhalation toxicity - : no data available  
Product

Pyroil™ OCTANE TREAT OCTANE  
TREATMENT  
PYOCT12

### Acute inhalation toxicity - Components

KEROSENE : LC 50: > 5,000 mg/m<sup>3</sup> Exposure time: 4 h Species: Rat

### Acute dermal toxicity

Acute dermal toxicity - Product : no data available

### Acute dermal toxicity - Components

KEROSENE : LD 50: > 2 g/kg Species: Rabbit

### Acute toxicity (other routes of administration)

Acute toxicity (other routes of administration) : no data available

## 12. ECOLOGICAL INFORMATION

### Biodegradability

Biodegradability - Product : no data available

### Bioaccumulation

Bioaccumulation - Product : no data available

### Ecotoxicity effects

#### Toxicity to fish

Toxicity to fish - Product : no data available

### Toxicity to daphnia and other aquatic invertebrates

Toxicity to daphnia and other aquatic invertebrates - Product : no data available

### Toxicity to algae

Toxicity to algae - Product : no data available

Pyroil™ OCTANE TREAT OCTANE  
TREATMENT  
PYOCT12

Product

### Toxicity to bacteria

Toxicity to bacteria - : no data available  
Product

## 13. DISPOSAL CONSIDERATIONS

### Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations.

## 14. TRANSPORT INFORMATION

### REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

### U.S. DOT - ROAD

Not dangerous goods

### U.S. DOT - RAIL

Not dangerous goods

### U.S. DOT - INLAND WATERWAYS

Not dangerous goods

### TRANSPORT CANADA - ROAD

Not dangerous goods

### TRANSPORT CANADA - RAIL

Not dangerous goods

### TRANSPORT CANADA - INLAND WATERWAYS

Pyroil™ OCTANE TREAT OCTANE  
TREATMENT  
PYOCT12

Not dangerous goods

### INTERNATIONAL MARITIME DANGEROUS GOODS

UN	1993	FLAMMABLE LIQUID, N.O.S. (KEROSENE)	3	III	LIMITED QUANTITY
----	------	--	---	-----	---------------------

### INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

UN	1993	Flammable liquid, n.o.s. (KEROSENE)	3	III
----	------	--	---	-----

### INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

UN	1993	Flammable liquid, n.o.s. (KEROSENE)	3	III
----	------	--	---	-----

### MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

UN	1993	LIQUIDO INFLAMABLE, N.E.P. (KEROSENE)	3	III
----	------	--	---	-----

\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

## 15. REGULATORY INFORMATION

### California Prop. 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

### SARA Hazard Classification

#### SARA 311/312 Classification

Fire Hazard

Acute Health Hazard

Chronic Health Hazard

### SARA 313 Component(s)

Pyroil™ OCTANE TREAT OCTANE  
TREATMENT  
PYOCT12

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### New Jersey RTK Label Information

KEROSENE	8008-20-6
POLYMER	

### Pennsylvania RTK Label Information

KEROSENE	8008-20-6
----------	-----------

### Notification status

US. Toxic Substances Control Act	y (positive listing)
Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)	y (positive listing)
Australia. Industrial Chemical (Notification and Assessment) Act	y (positive listing)
New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand	n (Negative listing)
Japan. Kashin-Hou Law List	n (Negative listing)
Korea. Toxic Chemical Control Law (TCCL) List	y (positive listing)
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act	y (positive listing)
China. Inventory of Existing Chemical Substances	y (positive listing)

### Reportable quantity - Product

US. EPA CERCLA Hazardous Substances (40 CFR 302)	214132 lbs
--	------------

### Reportable quantity-Components

NAPHTHALENE	91-20-3	100 lbs
-------------	---------	---------

	HMIS	NFPA
Health	2	1
Flammability	2	2
Physical hazards	0	
Instability		0
Specific Hazard	--	--

Pyroil™ OCTANE TREAT OCTANE  
TREATMENT  
PYOCT12

### 16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).