



## Material Safety Data Sheet

### 1 - Chemical Product and Company Identification

<b>Manufacturer:</b> WD-40 Company <b>Address:</b> 1061 Cudahy Place (92110) P.O. Box 80607 San Diego, California, USA 92138 -0607  <b>Telephone:</b> <b>Emergency only:</b> 1-888-324-7596 (PROSAR) <b>Information:</b> 1-888-324-7596 <b>Chemical Spills:</b> 1-800-424-9300 (Chemtrec) 1-703-527-3887 (International Calls)	<b>Chemical Name:</b> Organic Mixture  <b>Trade Name:</b> 3-IN-ONE All-Temp Silicone  <b>Product Use:</b> Lubricant, Protectant  <b>MSDS Date Of Preparation:</b> 12/8/2012
--	---

### 2 – Hazards Identification

<b>Emergency Overview:</b> <b>DANGER!</b> Harmful or fatal if swallowed. Combustible Liquid. If swallowed, may be aspirated and cause lung damage. May cause eye irritation. Avoid eye contact. Use with adequate ventilation. Keep away from heat, sparks and all other sources of ignition.  <b>Symptoms of Overexposure:</b> <b>Inhalation:</b> High concentrations may cause nasal and respiratory irritation and central nervous system effects such as headache, dizziness and nausea. Intentional abuse may be harmful or fatal. <b>Skin Contact:</b> Prolonged and/or repeated contact may produce mild irritation and defatting with possible dermatitis. <b>Eye Contact:</b> Contact may be irritating to eyes. May cause redness and tearing. <b>Ingestion:</b> This product has low oral toxicity. Swallowing may cause gastrointestinal irritation, nausea, vomiting and diarrhea. This product is an aspiration hazard. If swallowed, can enter the lungs and may cause chemical pneumonitis, severe lung damage and death. <b>Chronic Effects:</b> None expected. <b>Medical Conditions Aggravated by Exposure:</b> Preexisting eye, skin and respiratory conditions may be aggravated by exposure.  <b>Suspected Cancer Agent:</b> Yes    No X
--

### 3 - Composition/Information on Ingredients

Ingredient	CAS #	Weight Percent
LVP Petroleum Distillates, hydrotreated light	64742-47-8	85-95%
Poly(dimethylsiloxane)	63148-62-9	1-5%

See Section 8 for Exposure Limits

### 4 – First Aid Measures

<b>Ingestion (Swallowed):</b> Aspiration Hazard. DO NOT induce vomiting. Call physician, poison control center or the WD-40 Safety Hotline at 1-888-324-7596 immediately. <b>Eye Contact:</b> Flush thoroughly with water. Remove contact lenses if present after the first 5 minutes and continue flushing for several more minutes. Get medical attention if irritation persists. <b>Skin Contact:</b> Wash with soap and water. If irritation develops and persists, get medical attention. <b>Inhalation (Breathing):</b> If irritation is experienced, move to fresh air. Get medical attention if irritation or other symptoms develop and persist.
--

## 5 – Fire Fighting Measures

**Extinguishing Media:** Use water fog, dry chemical, carbon dioxide or foam. Do not use water jet or flooding amounts of water. Burning product will float on the surface and spread fire.

**Special Fire Fighting Procedures:** Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water.

**Unusual Fire and Explosion Hazards:** Combustible liquid and vapor. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back.

## 6 – Accidental Release Measures

Wear appropriate protective clothing (see Section 8). Eliminate all sources of ignition and ventilate area. Contain and collect liquid with an inert absorbent and place in a container for disposal. Clean spill area thoroughly. Report spills to authorities as required.

## 7 – Handling and Storage

**Handling:** Avoid contact with eyes. Avoid prolonged contact with skin. Avoid breathing vapors or aerosols. Use with adequate ventilation. Keep away from heat, sparks, hot surfaces and open flames. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep out of the reach of children.

**Storage:** Store in a cool, well-ventilated area, away from incompatible materials. NFPA 30 Class IIIA Liquid.

## 8 – Exposure Controls/Personal Protection

Chemical	Occupational Exposure Limits
LVP Petroleum Distillates, hydrotreated light	1200 mg/m <sup>3</sup> TWA (manufacturer recommended)
Poly(dimethylsiloxane)	None Established

### The Following Controls are Recommended for Normal Consumer Use of this Product

**Engineering Controls:** Use in a well-ventilated area.

**Personal Protection:**

**Eye Protection:** Avoid eye contact. Safety glasses or goggles recommended.

**Skin Protection:** Avoid prolonged skin contact. Chemical resistant gloves recommended for operations where skin contact is likely.

**Respiratory Protection:** None needed for normal use with adequate ventilation.

### For Bulk Processing or Workplace Use the Following Controls are Recommended

**Engineering Controls:** Use adequate general and local exhaust ventilation to maintain exposure levels below the occupational exposure limits.

**Personal Protection:**

**Eye Protection:** Safety goggles recommended where eye contact is possible.

**Skin Protection:** Wear chemical resistant gloves.

**Respiratory Protection:** None required if ventilation is adequate. If the occupational exposure limits are exceeded, wear a NIOSH approved respirator. Respirator selection and use should be based on contaminant type, form and concentration. Follow OSHA 1910.134, ANSI Z88.2 and good Industrial Hygiene practice.

**Work/Hygiene Practices:** Wash with soap and water after handling.

## 9 – Physical and Chemical Properties

Boiling Point:	430 - 520°F (221 - 271°C)	Specific Gravity:	0.8 – 0.89
Solubility in Water:	Insoluble	pH:	Not Applicable
Vapor Pressure:	0.07 mmHg @20°C	Vapor Density:	Greater than 1
Percent Volatile:	Not Determined	VOC:	<1%
Coefficient of Water/Oil Distribution:	Not Determined	Appearance/Odor	Light brown liquid/mild odor

Flash Point:	191°F (88.3°C) Tag Closed Cup	Flammable Limits: (Solvent Portion)	LEL: 0.6% UEL: 5.0%
Pour Point:	-39°C (-38°F)	Kinematic Viscosity:	3.8 cSt @ 104°F

### 10 – Stability and Reactivity

**Stability:** Stable

**Hazardous Polymerization:** Will not occur.

**Conditions to Avoid:** Avoid heat, sparks, flames and other sources of ignition.

**Incompatibilities:** Strong oxidizing agents.

**Hazardous Decomposition Products:** Carbon monoxide and carbon dioxide.

### 11 – Toxicological Information

The oral toxicity of this product is estimated to be greater than 5,000 mg/kg based on an assessment of the ingredients. This product is not classified as toxic by established criteria. It is an aspiration hazard.

None of the components of this product is listed as a carcinogen or suspected carcinogen or is considered a reproductive hazard.

### 12 – Ecological Information

LVP Petroleum Distillates, hydrotreated light: Not expected to be harmful to aquatic organisms, readily biodegradable.

Poly(dimethylsiloxane): Not expected to be harmful to aquatic organisms. Very low water solubility.

### 13 - Disposal Considerations

If this product becomes a waste, it would not be expected to meet the criteria of a RCRA hazardous waste. However, it is the responsibility of the generator to determine at the time of disposal the proper classification and method of disposal. Dispose in accordance with federal, state, and local regulations.

### 14 – Transportation Information

DOT Surface Shipping Description: Excepted from Hazmat (49CFR 173.150 (F)) in non-bulk packagings. Bulk Packagings: NA1993, Combustible Liquid, n.o.s. (contains Petroleum Distillates), PG III

IMDG Shipping Description: Not Regulated

ICAO Shipping Description: Not Regulated

### 15 – Regulatory Information

#### U.S. Federal Regulations:

**CERCLA 103 Reportable Quantity:** This product is not subject to CERCLA reporting requirements, however, oil spills are reportable to the National Response Center under the Clean Water Act and many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

#### SARA TITLE III:

**Hazard Category For Section 311/312:** Acute Health, Fire Hazard

**Section 313 Toxic Chemicals:** This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: None

Section 302 Extremely Hazardous Substances (TPQ): None

**EPA Toxic Substances Control Act (TSCA) Status:** All of the components of this product are listed on the TSCA inventory

**California Safe Drinking Water and Toxic Enforcement Act (Proposition 65):** This product does not contain chemicals regulated under California Proposition 65.

**VOC Regulations:** This product complies with the consumer product VOC limits of CARB, the US EPA and states adopting the OTC VOC rules.

**Canadian Environmental Protection Act:** One of the components is listed on the NDSL. All of the other ingredients are listed on the Canadian Domestic Substances List or exempt from notification.

**Canadian WHMIS Classification:** Class B-3 (Combustible Liquid)

This MSDS has been prepared according to the criteria of the Controlled Products Regulation (CPR) and the MSDS contains all of the information required by the CPR.

**16 – Other Information:**

**HMIS Hazard Rating:**

**Health – 1 (slight hazard), Fire Hazard – 2 (moderate hazard), Reactivity – 0 (minimal hazard)**

Revision Date: December 2012

Supercedes: New MSDS

Prepared by: Industrial Health and Safety Consultants, Inc. Shelton, CT

SIGNATURE: ASM

DATE: August 2013