



Material Safety Data Sheet

E

1. Chemical Product and Company Identification

DESCRIPTION: ELMER'S INT/EXT CARPENTER'S WOOD FILLER
 PRODUCT TYPE: MODIFIED PVAC
 APPLICATION: FOR PRODUCT CODES, SEE SECTION 16

Manufacturer/Supplier Information

MSDS Prepared by:
 Elmer's Products, Inc.
 460 Polaris Parkway
 Westerville, OH 43082
 For additional health, safety or regulatory information, call 1-888-435-6377.
 Call 1-800-848-9400 to place an order or request additional MSDSs.

Emergency Phone Number
 Poison Control Center
 1-888-516-2502

2. Composition, Information on Ingredients

The ingredients listed below have been associated with one or more immediate and/or delayed(*) health hazards. Risk of damage and effects depends upon duration and level of exposure. BEFORE USING, HANDLING, OR EXPOSURE TO THESE INGREDIENTS, READ AND UNDERSTAND THE MSDS.

	% by weight
546-93-0 Magnesium Carbonate (MgCO ₃)	5-10
1317-65-3 *Limestone	50-70
1318-59-8 Chlorite (Mineral Class)	1-5
13397-26-7 *Calcite (Ca(CO ₃))	1-5
14808-60-7 *Quartz (SiO ₂)	0.1-0.99

3. Hazards Identification

3.1 Emergency Overview

Appearance Light Tan, paste
 Odor Mild
 CAUTION!
 Not a significant fire hazard.
 May cause eye irritation

HMIS Rating

HEALTH = 1 (slight)
 FLAMMABILITY = 0 (minimal)
 REACTIVITY = 0 (minimal)
 CHRONIC = *

3.2 Potential Health Effects

Immediate Hazards

INGESTION: Not expected to be harmful under normal conditions of use.
 INHALATION: Not expected to be harmful under normal conditions of use. However, if allowed to become airborne, may cause irritation of nose, throat and lungs.
 SKIN: May cause irritation on prolonged or repeated contact.
 EYES: May cause irritation on prolonged or repeated contact.

Delayed Hazards

Limestone 1317-65-3
 Can cause lung damage. Pre-existing respiratory disorders may be aggravated by exposure.
 -- See Footnote C.
 Calcite (Ca(CO₃)) 13397-26-7
 Can cause lung damage. Pre-existing respiratory disorders may be aggravated by exposure.
 -- See Footnote C.
 Quartz (SiO₂) 14808-60-7
 CANCER HAZARD. Can cause cancer. Use of this product may generate silica dust (which may be invisible). Inhaled silica has been classified by IARC as a human carcinogen.
 Footnote C: As of the date of issuance of this document, this material has not been listed by NTP, classified by IARC nor regulated by OSHA as a carcinogen.

4. First Aid Measures

INGESTION: If accidentally swallowed, dilute by drinking large quantities of water. Immediately contact poison control center or hospital emergency room for any other additional treatment directions.
 INHALATION: Remove to fresh air.
 SKIN: In case of irritation, flush with water.
 EYES: Immediately flush eyes with plenty of water. Call a physician if irritation persists.

5. Fire Fighting Measures

Autoignition Temperature Not available
 Upper/Lower Flammable Limits Not applicable
 Up/Lower Explosive Limits, % by Vol Not applicable
 Flash Point Not applicable
 Will not burn unless water has evaporated. Dried material may burn.
 In case of fire, water should be used to keep fire-exposed containers cool.

6. Accidental Release Measures

Sweep (scoop) up and remove to a chemical disposal area. Prevent entry into natural bodies of water.

7. Handling and Storage

7.1 Handling

Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of the material from eyes, skin and clothing. Wash thoroughly after handling. Always use appropriate Personal Protective Equipment (PPE).
INHALATION: Avoid prolonged or repeated breathing of vapor.
SKIN: Avoid prolonged or repeated contact with skin and clothing.
EYES: Avoid prolonged or repeated contact with eyes.

7.2 Storage

Keep from freezing.
Store in a cool, dry place.
Keep containers tightly closed.

8. Exposure Controls/Personal Protection

8.1 Exposure Controls

If airborne contaminants are generated when the material is heated or handled, sufficient ventilation in volume and air flow patterns should be provided to keep air contaminant concentration levels below acceptable criteria.

8.2 Personal Protection

Where air contaminants can exceed acceptable criteria, use NIOSH/MSHA approved respiratory protection equipment. Respirators should be selected based on the form and concentration of contaminants in air in accordance with OSHA laws and regulations or other applicable standards or guidelines, including ANSI standards regarding respiratory protection. Use goggles if contact is likely. Wear impervious gloves as required to prevent skin contact.

8.3 Exposure Guidelines

Magnesium Carbonate (MgCO₃) 546-93-0
ACGIH TLV: 10 mg/m³ TWA, inhalable particulate
OSHA PEL: 5 mg/m³ TWA, particulates respirable; 15 mg/m³ TWA
total dust
Limestone 1317-65-3

ACGIH TLV: 10 mg/m³ TWA, inhalable particulate
 OSHA PEL: 5 mg/m³ TWA, respirable particulates; 15 mg/m³ TWA
 total dust
 Chlorite (Mineral Class) 1318-59-8
 ACGIH TLV: 10 mg/m³ TWA, (as Al₂O₃)
 OSHA PEL: 5 mg/m³ TWA, respirable dust (as Al₂O₃); 15 mg/m³ TWA,
 total dust (as Al₂O₃)
 REMANDED PEL: 5 mg/m³ TWA, respirable dust (as Al₂O₃); 10 mg/m³ TWA,
 total dust (as Al₂O₃)
 OSHA 1989 PEL remanded, but in effect in some states
 Calcite (Ca(CO₃)) 13397-26-7
 ACGIH TLV: 10 mg/m³ TWA, inhalable particulate
 OSHA PEL: 5 mg/m³ TWA, respirable particulates; 15 mg/m³ TWA
 total dust
 Quartz (SiO₂) 14808-60-7
 ACGIH TLV: 0.05 mg/m³ TWA, respirable fraction, A2 - See Appendix A
 OSHA PEL: 10/(%SiO₂ + 2) mg/m³ TWA, respirable dust;
 30/(%SiO₂ + 2) mg/m³ TWA, total dust
 REMANDED PEL: 0.1 mg/m³ TWA, respirable dust
 OSHA 1989 PEL remanded, but in effect in some states
 OTHER: NIOSH has recommended a permissible exposure limit of 50 micrograms
 respirable free silica per cubic meter of air (0.05 mg/m³) averaged
 over a workshift of up to 10 hours per day, 40 hours per week. NIOSH
 publications, including the NIOSH Criteria Document for Crystalline
 Silica, should be consulted for more detailed information.

9. Physical and Chemical Properties

Percent Volatiles	22
pH @ 25 C	8.5
Specific Gravity	1.38
Appearance	Light Tan, paste
Autoignition Temperature	Not available
Boiling Point	100°C (212°F)
Vapor Density (Air=1)	<1
Vapor Pressure, mm Hg @ 20 C	17
Evaporation Rate (Butyl Acetate=1)	<1
Upper/Lower Flammable Limits	Not applicable
Up/Lower Explosive Limits, % by Vol	Not applicable
Flash Point	Not applicable
Freezing Point	0°C (32°F)
Odor	Mild
Odor Threshold, ppm	Not available
Solubility in Water	Dispersible

10. Stability and Reactivity

Normally stable as defined in NFPA 704-12(4-3.1).

· Incompatibilities:

None known to company.

· Decomposition products may include:

Acrylic monomers by thermal decomposition.

· Hazardous polymerization:

Will not occur.

Other Hazards:

None known to company.

11. Toxicological Information

See Section 3 Hazards Identification information.

Magnesium Carbonate (MgCO₃) 546-93-0

LC50: Not available

LD50: Not available

Limestone 1317-65-3

LC50: Not available

LD50: Not available

Chlorite (Mineral Class) 1318-59-8

LC50: Not available

LD50: Not available

Calcite (Ca(CO₃)) 13397-26-7

LC50: Not available

LD50: Not available

Quartz (SiO₂) 14808-60-7

LC50: Not available

LD50: Not available

12. Ecological Information

Not determined.

13. Disposal Considerations

Dispose of according to local, state/provincial, and federal requirements.

14. Transport Information

14.1 U.S. Department of Transportation (DOT)

The data provided in this section is for information only and may not be specific to your package size. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

Non-Regulated.

14.2 Canadian Transportation of Dangerous Goods (TDG)

Non-Regulated.

15. Regulatory Information (Selected Regulations)

15.1 U.S. Federal Regulations

- OSHA Hazard Communication Standard 29CFR1910.1200

This material presents possible health hazards as determined when reviewed according to the requirements of the Occupational Safety and Health Administration 29 CFR Part 1910.1200 "Hazard Communication" Standard.

- SARA Title III: Section 311/312

Delayed health hazard

- SARA Title III Section 313 and 40 CFR Part 372

This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986, and Subpart C-Supplier Notification Requirement of 40 CFR Part 372.
None required per SARA TITLE III SECTION 313.

- TSCA Section 8(b) Inventory

All reportable chemical substances are listed on the TSCA Inventory. We rely on certifications of compliance from our suppliers for chemical substances not manufactured by us.

15.2 Canadian Regulations

- Workplace Hazardous Materials Information System (WHMIS)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulation (CPR) and the MSDS contains all the information required by the CPR.
CLASS D, DIV 2A, 2B

- Canadian Environmental Protection Act (CEPA)

All reportable chemical substances are listed on the Domestic Substances List (DSL) or otherwise comply with CEPA new substance notification requirements.

- National Pollutant Release Inventory (NPRI)

This product contains the following chemical(s) subject to the

reporting requirements of the Canadian Environmental Protection Act (CEPA) subsection 16(1), National Pollutant Release Inventory.
None required.

16. Other Information

CL (Cautionary Labeling): Products bearing the CL (Cautionary Labeling) Seal of The Art & Creative Materials Institute, Inc. (ACMI) are certified to be properly labeled in a program of toxicological evaluation by a medical expert. This program is reviewed by ACMI's Toxicological Advisory Board. These products are certified by ACMI to be labeled in accordance with the chronic hazard labeling standard, ASTM D-4236 and Federal Law, P.L. 100-695.

MSDS covers items:

U.S.: E842, E847, E848, E849, E842L, E847DL, E848DL, E849DL
Canada: 60842, 60848, 60849, 63842, 63846, 63847, 63848, 63849

User's Responsibility

The OSHA Hazard Communication Standard 29CFR 1910.1200 and the Workplace Hazardous Materials Information System (WHMIS) require that the information contained on these sheets be made available to your workers. Educate and train your workers regarding OSHA and WHMIS precautions. Instruct your workers to handle this product properly. Consult with appropriate experts to guard against hazards associated with use of this product and its ingredients.

Disclaimer

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE, except that the product shall conform to contracted specifications, and that the product does not infringe any valid United States or Canadian patent. No claim of any kind shall be greater in amount than the purchase price of the quantity of product in respect of which damages are claimed. In no event shall Seller be liable for incidental or consequential damages, whether Buyer's claim is based on contract, breach of warranty, negligence or otherwise.

CURRENT ISSUE: 19-APR-11
PREVIOUS ISSUE: 01-DEC-10