



# Material Safety Data Sheet

**E**

## 1. Chemical Product and Company Identification

DESCRIPTION: ELMER'S SLIDE-ALL  
 PRODUCT TYPE: TEFLON BASED LUBRICANT  
 APPLICATION: FOR PRODUCT CODES, SEE SECTION 16

### • Manufacturer/Supplier Information

MSDS Prepared by:

Elmer's Products, Inc.

1 Easton Oval

Columbus, OH 43219

Emergency Phone Number

Poison Control Center

1-888-516-2502

For additional health, safety or regulatory information, call 1-888-435-6377.

Call 1-800-848-9400 to place an order or request additional MSDSs.

## 2. Composition, Information on Ingredients

The ingredients listed below have been associated with one or more immediate and/or delayed(\*) health hazards. Risk of damage and effects depends upon duration and level of exposure. BEFORE USING, HANDLING, OR EXPOSURE TO THESE INGREDIENTS, READ AND UNDERSTAND THE MSDS.

	% by weight
67-63-0 *Isopropanol	5-10
67-64-1 *Acetone	5-10
74-98-6 Propane	10-30
75-28-5 Isobutane	10-30
107-83-5 2-Methylpentane	30-50
109-66-0 Pentane	1-5

---

### 3. Hazards Identification

---

#### 3.1 Emergency Overview

Appearance White powder

Odor Mild mint

DANGER!

EXTREMELY FLAMMABLE

May be harmful if inhaled. May cause irritation of nose, throat and lungs.

Can cause central nervous system depression.

Causes skin irritation.

Causes eye irritation.

---

- **HMIS Rating**

HEALTH = 2 (moderate)

FLAMMABILITY = 4 (severe)

REACTIVITY = 0 (minimal)

CHRONIC = \*

---

#### 3.2 Potential Health Effects

---

- **Immediate Hazards**

INGESTION: Not expected to be harmful under normal conditions of use.

INHALATION: May be harmful if inhaled. Liquid or vapor may cause irritation of nose, throat and lungs.

Can cause central nervous system depression.

SKIN: Causes irritation.

EYES: Causes irritation.

Isopropanol 67-63-0

Can cause central nervous system depression. Signs and symptoms may include headache, dizziness, nausea, vomiting, unconsciousness and even asphyxiation.

Acetone 67-64-1

Can cause central nervous system depression. Signs and symptoms may include headache, dizziness, nausea, vomiting, unconsciousness and even asphyxiation.

Propane 74-98-6

This material is a simple asphyxiant. Signs and symptoms of overexposure include cyanosis, respiratory distress, headache, dizziness, drowsiness, unconsciousness and asphyxiation. Can cause central nervous system depression.

2-Methylpentane 107-83-5

Can cause central nervous system depression. Signs and symptoms may include headache, dizziness, nausea, vomiting and drowsiness.

Pentane 109-66-0

Can cause central nervous system depression. Signs and symptoms may include headache, dizziness, nausea, vomiting, unconsciousness and even asphyxiation.

## • Delayed Hazards

Isopropanol 67-63-0

Suspect reproductive hazard. May cause reproductive disorders based on animal data.

May cause liver damage based on animal data.

May cause kidney damage based on animal data.

-- See Footnote C.

Acetone 67-64-1

Ingestion may cause liver damage.

Ingestion may cause kidney damage.

-- See Footnote C.

Poly(difluoromethylene), .alpha.-(cyclohexylmethyl)-. 65530-85-0  
omega.-hydro

Inhalation of fumes or smoke may cause polymer fume fever, a temporary flu-like illness. Repeated episodes of polymer fume fever may cause lung damage.

-- See Footnote C.

Footnote C: As of the date of issuance of this document, this material has not been listed by NTP, classified by IARC nor regulated by OSHA as a carcinogen.

---

#### 4. First Aid Measures

INGESTION: If accidentally swallowed, dilute by drinking large quantities of water. Immediately contact poison control center or hospital emergency room for any other additional treatment directions.

INHALATION: If inhaled, remove to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Call a physician.

SKIN: Flush with plenty of water. Remove contaminated clothing. Call a physician if irritation persists.

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held apart during irrigation to insure water contact with entire surface of eyes and lids. Call a physician.

---

#### 5. Fire Fighting Measures

Autoignition Temperature	Not available
Upper/Lower Flammable Limits	Not available
Up/Lower Explosive Limits, % by Vol	12.8/1.0 %
Flash Point	-104.5°C (-156°F) pensky-martens c.c.

EXTREMELY FLAMMABLE.

DO NOT INCINERATE (BURN) CONTAINER. AVOID HEAT. KEEP CONTAINER BELOW 120 F (50 C). High temperatures may cause bursting. Do not place container on radiator, stove, in direct sunlight or near other heat sources. DO NOT PUNCTURE CONTAINER. Contents under pressure will discharge. AVOID OPEN FLAMES, SPARKS, PILOT LIGHTS. DO NOT SMOKE. Vapor may ignite explosively. Spray mist or vapor evaporating from a deposited film is heavier than air and may settle in low places or travel outward to a source of ignition and flashback. In case of fire, use dry chemical, foam or CO<sub>2</sub>. Water may be ineffective, but should be used to keep fire-exposed containers

cool.

---

## 6. Accidental Release Measures

Eliminate all ignition sources. Soak up with absorbent material and remove to a chemical disposal area. Prevent entry into natural bodies of water.

---

## 7. Handling and Storage

---

### 7.1 Handling

Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of the material from eyes, skin and clothing.

Wash thoroughly after handling. Always use appropriate Personal Protective Equipment (PPE).

INHALATION: USE WITH ADEQUATE VENTILATION. To avoid breathing vapors or spray mist, open windows and doors or use other means, such as an exhaust fan to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, increase fresh air, wear respiratory protection (NIOSH/MSHA TC23C or equivalent), or leave the area.

SKIN: Avoid contact with skin and clothing.

EYES: Avoid contact with eyes.

---

### 7.2 Storage

Store in a cool, dry place.

Keep containers tightly closed.

Do not store at temperatures above 50 C.

Keep away from heat, sparks, flame and other ignition sources.

---

## 8. Exposure Controls/Personal Protection

---

## 8.1 Exposure Controls

ENGINEERING CONTROLS: The following exposure control techniques may be used to effectively minimize employee exposure: local exhaust ventilation, enclosed system design, process isolation and remote control in combination with appropriate use of personal protective equipment and prudent work practices. These techniques may not necessarily address all issues pertaining to your operations. We, therefore, recommend that you consult with experts of your choice to determine whether or not your programs are adequate.

If airborne contaminants are generated when the material is heated or handled, sufficient ventilation in volume and air flow patterns should be provided to keep air contaminant concentration levels below acceptable criteria.

---

## 8.2 Personal Protection

Where air contaminants can exceed acceptable criteria, use NIOSH/MSHA approved respiratory protection equipment. Respirators should be selected based on the form and concentration of contaminants in air in accordance with OSHA laws and regulations or other applicable standards or guidelines, including ANSI standards regarding respiratory protection. Use goggles if contact is likely. Wear impervious gloves as required to prevent skin contact.

---

## 8.3 Exposure Guidelines

Isopropanol            67-63-0

ACGIH TLV: 400 ppm (983 mg/m<sup>3</sup>) TWA; 500 ppm (1230 mg/m<sup>3</sup>) STEL

OSHA PEL: 400 ppm (980 mg/m<sup>3</sup>) TWA

REMANDED PEL: 400 ppm (980 mg/m<sup>3</sup>) TWA; 500 ppm (1225 mg/m<sup>3</sup>) STEL

OSHA 1989 PEL remanded, but in effect in some states

Acetone                67-64-1

ACGIH TLV: 500 ppm (1188 mg/m<sup>3</sup>) TWA; 750 ppm (1782 mg/m<sup>3</sup>) STEL

OSHA PEL: 1000 ppm (2400 mg/m<sup>3</sup>) TWA

REMANDED PEL: 750 ppm (1800 mg/m<sup>3</sup>) TWA; 1000 ppm (2400 mg/m<sup>3</sup>) STEL

OSHA 1989 PEL remanded, but in effect in some states

Propane 74-98-6

ACGIH TLV: 2500 ppm (4508 mg/m<sup>3</sup>) TWA

OSHA PEL: 1000 ppm (1800 mg/m<sup>3</sup>) TWA

Isobutane 75-28-5

ACGIH TLV: NONE ESTABLISHED

OSHA PEL: NONE ESTABLISHED

2-Methylpentane 107-83-5

ACGIH TLV: HexIso.500ppm(1760mg/m<sup>3</sup>)TWA;1000ppm(3500mg/m<sup>3</sup>)STEL

OSHA PEL: REMANDED PEL: HexIso.500ppm(1800mg/m<sup>3</sup>)TWA;1000ppm(3600mg/m<sup>3</sup>)STEL

OSHA 1989 PEL remanded, but in effect in some states

Pentane 109-66-0

ACGIH TLV: 600 ppm (1770 mg/m<sup>3</sup>) TWA

OSHA PEL: 1000 ppm (2950 mg/m<sup>3</sup>) TWA

REMANDED PEL: 600 ppm (1800 mg/m<sup>3</sup>) TWA; 750 ppm (2250 mg/m<sup>3</sup>)STEL

OSHA 1989 PEL remanded, but in effect in some states

Poly(difluoromethylene), .alpha.-(cyclohexylmethyl)-. 65530-85-0

omega.-hydro

ACGIH TLV: NONE ESTABLISHED

OSHA PEL: NONE ESTABLISHED

## 9. Physical and Chemical Properties

Percent Volatiles	99.5
pH @ 25 C	Not available
Specific Gravity	0.61
Appearance	White powder
Autoignition Temperature	Not available
Boiling Point	-42.2 to 83.3°C (-44 to 182°F)
Vapor Density (Air=1)	>1
Vapor Pressure, mm Hg @ 20 C	Not available
Evaporation Rate (Butyl Acetate=1)	>1
Upper/Lower Flammable Limits	Not available
Up/Lower Explosive Limits, % by Vol	12.8/1.0 %
Flash Point	-104.5°C (-156°F) pensky-martens c.c.
Freezing Point	Not applicable
Odor	Mild mint
Odor Threshold, ppm	Not available
Solubility in Water	Negligible

Coefficient of Water/Oil Distrib. Not applicable

---

## 10. Stability and Reactivity

Normally stable as defined in NFPA 704-12(4-3.1).

---

- **Incompatibilities:**

None known to company.

---

- **Decomposition products may include:**

CO, CO2.

---

- **Hazardous polymerization:**

Will not occur.

---

- **Other Hazards:**

None known to company.

---

## 11. Toxicological Information

See Section 3 Hazards Identification information.

Isopropanol            67-63-0

LC50: rat=16000 ppm/8H (Sax)

LD50: orl-rat=5.8 g/kg (Merck); skn-rbt=13 g/kg (Sax)

Acetone                67-64-1

LC50: Not available

LD50: oral-rat=5800 mg/kg (RTECS); skin-rabbit=20 g/kg (RTECS)

Propane                74-98-6

LC50: Not available

LD50: Not available

Isobutane             75-28-5

LC50: Not available

LD50: Not available

2-Methylpentane 107-83-5

LC50: Not available

LD50: Not available

Pentane 109-66-0

LC50: Not available

LD50: Not available

Poly(difluoromethylene), .alpha.-(cyclohexylmethyl)-. 65530-85-0  
omega.-hydro

LC50: Not available

LD50: Not available

---

## 12. Ecological Information

Not determined.

---

## 13. Disposal Considerations

Dispose of according to local, state/provincial, and federal requirements.

Empty container: May contain explosive vapors. DO NOT cut, puncture or weld on or nearby. Incineration will cause container to burst violently.

---

## 14. Transport Information

---

### 14.1 U.S. Department of Transportation (DOT)

The data provided in this section is for information only and may not be specific to your package size. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

ORM-D Consumer Commodity.

---

### 14.2 Canadian Transportation of Dangerous Goods (TDG)

Not determined.

---

## 15. Regulatory Information (Selected Regulations)

---

### 15.1 U.S. Federal Regulations

---

- **OSHA Hazard Communication Standard 29CFR1910.1200**

This material is a "health hazard" and/or a "physical hazard" as determined when reviewed according to the requirements of the Occupational Safety and Health Administration 29 CFR Part 1910.1200 "Hazard Communication" Standard.

---

- **SARA Title III: Section 311/312**

Fire hazard  
Sudden release of pressure (explosion) hazard  
Immediate health hazard  
Delayed health hazard

---

- **SARA Title III Section 313 and 40 CFR Part 372**

This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986, and Subpart C-Supplier Notification Requirement of 40 CFR Part 372.  
None required per SARA TITLE III SECTION 313.

---

- **TSCA Section 8(b) Inventory**

All reportable chemical substances are listed on the TSCA Inventory. We rely on certifications of compliance from our suppliers for chemical substances not manufactured by us.

---

## 15.2 Canadian Regulations

---

- **Workplace Hazardous Materials Information System (WHMIS)**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulation (CPR) and the MSDS contains all the information required by the CPR.

CLASS D, DIV 2B

CLASS B, DIV 2

---

- **Canadian Environmental Protection Act (CEPA)**

All reportable chemical substances are listed on the Domestic Substances List (DSL) or otherwise comply with CEPA new substance notification requirements.

---

- **National Pollutant Release Inventory (NPRI)**

This product contains the following chemical(s) subject to the reporting requirements of the Canadian Environmental Protection Act (CEPA) subsection 16(1), National Pollutant Release Inventory.

Isopropyl alcohol	67-63-0	10.00%
-------------------	---------	--------

---

## 16. Other Information

MSDS covers items:

U.S.: E450, E459

Canada: 60450, 60459

---

- **User's Responsibility**

The OSHA Hazard Communication Standard 29CFR 1910.1200 and the Workplace Hazardous Materials Information System (WHMIS) require that the information contained on these sheets be made available to your workers. Educate and train your workers regarding OSHA and WHMIS precautions. Instruct your

workers to handle this product properly. Consult with appropriate experts to guard against hazards associated with use of this product and its ingredients.

---

- **Disclaimer**

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE, except that the product shall conform to contracted specifications, and that the product does not infringe any valid United States or Canadian patent. No claim of any kind shall be greater in amount than the purchase price of the quantity of product in respect of which damages are claimed. In no event shall Seller be liable for incidental or consequential damages, whether Buyer's claim is based on contract, breach of warranty, negligence or otherwise.

---

CURRENT ISSUE: 03-JUN-09

PREVIOUS ISSUE: 30-JUN-06