

Valvoline™ FUEL INJECTOR PLUS INTAKE
VALVE CLEANER
602376

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone number	1-800-ASHLAND (1-800-274-5263)
Product name	Valvoline™ FUEL INJECTOR PLUS INTAKE VALVE CLEANER	
Product code	602376	

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid

CAUTION! COMBUSTIBLE LIQUID AND VAPOR. MAY AFFECT THE CENTRAL NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN AND RESPIRATORY TRACT IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE DERMATITIS AND BURNS.

Potential Health Effects

Exposure routes

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye contact

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

Skin contact

Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, skin burns, and other skin damage.

Ingestion

Valvoline™ FUEL INJECTOR PLUS INTAKE
VALVE CLEANER
602376

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: Skin, Upper respiratory tract, lung (for example, asthma-like conditions), Kidney, urinary system, Exposure to this material may aggravate any preexisting condition sensitive to a decrease in available oxygen, such as chronic lung disease, coronary artery disease or anemias., Individuals with preexisting heart disorders maybe more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material., Individuals with erythrocyte glucose-6-phosphate dehydrogenase deficiency are particularly susceptible to hemolytic agents and rapidly develop hemolytic anemia from ingestion or inhalation of this material (or a component).

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: sweating, Fever, stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), Lung irritation, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), Abdominal pain, Lack of coordination, confusion, irregular heartbeat, blood abnormalities (breakage of red blood cells), narcosis (dazed or sluggish feeling), kidney damage, lung damage, Convulsions, coma

Target Organs

Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans., Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver effects, cataracts, anemia, nasal damage, eye damage, Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans: cataracts, eye damage

Carcinogenicity

In a National Toxicology Program (NTP) study, lifetime inhalation exposure to naphthalene resulted in increases in tumors of the nose in rats. In a previous NTP study, lifetime exposure to

Valvoline™ FUEL INJECTOR PLUS INTAKE
VALVE CLEANER
602376

naphthalene caused lung tumors in female mice. Male mice with the same exposure did not develop tumors. The relevance of this finding to humans is uncertain. Naphthalene is listed as carcinogenic by IARC (International Agency for Research on Cancer) and the National Toxicology Program (NTP). This product (or a component) is a petroleum-derived material. Similar materials and certain compounds occurring naturally in petroleum oils have been shown to cause skin cancer in laboratory animals following repeated exposure without washing or removal.

Reproductive hazard

This material (or a component) causes harm to the fetus.

Other information

Infants are more sensitive than adults to the toxic effects of naphthalene. Diapers or cloths stored with mothballs and used directly on infants have caused skin rashes and illness. Naphthalene vapors from clothing or blankets that had been stored in or near the infant's room have caused illness and death.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	CAS-No. / Trade Secret No.	Concentration
KEROSENE	8008-20-6	>=80-<90%
DISTILLATES (PETROLEUM), SWEETENED MIDDLE	64741-86-2	>=1.5-<5%
PETROLEUM NAPHTHA	64742-94-5	>=1.5-<5%
NAPHTHALENE	91-20-3	>=0.1-<0.5%

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Valvoline™ FUEL INJECTOR PLUS INTAKE
VALVE CLEANER
602376

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting. Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities. Inhalation or ingestion of high levels of this material (or a component) may cause a hemolytic reaction. Complications of acute intravascular hemolysis include anemia, leukocytosis, fever, hemoglobinuria, jaundice, renal insufficiency, and sometimes disturbances in liver function. Fats, for example, baby oil on the skin or ingested oil, facilitate absorption of naphthalene.

Treatment: No information available.

5. FIREFIGHTING MEASURES

Suitable extinguishing media

Dry chemical, Carbon dioxide (CO₂), Water spray

Valvoline™ FUEL INJECTOR PLUS INTAKE
VALVE CLEANER
602376

Hazardous combustion products

Aldehydes, carbon dioxide and carbon monoxide, Hydrocarbons, nitrogen oxides (NOx), sulfur oxides

Precautions for fire-fighting

If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class II

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Ensure adequate ventilation. Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Pay attention to the spreading of gases especially at ground level (heavier than air) and to the direction of the wind.

Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

Methods for cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Other information

Comply with all applicable federal, state, and local regulations. Suppress (knock down) gases/vapours/mists with a water spray jet.

Valvoline™ FUEL INJECTOR PLUS INTAKE
VALVE CLEANER
602376

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.

Storage

Store in a cool, dry, ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

KEROSENE		8008-20-6	
ACGIH	time weighted average	200 mg/m ³	Non-aerosol
NIOSH	Recommended exposure limit (REL):	100 mg/m ³	

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Valvoline™ FUEL INJECTOR PLUS INTAKE
VALVE CLEANER
602376

Skin and body protection

Wear resistant gloves such as:

Neoprene

Nitrile rubber

Polyethylene

Discard gloves that show tears, pinholes, or signs of wear.

Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Respiratory protection

Respiratory protection is not required under normal conditions of use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Boiling point/boiling range	347 °F / 175 °C Calculated Phase Transition Liquid/Gas
Flash point	120.00 °F / 48.89 °C Calculated Flash Point
Lower explosion limit/Upper explosion limit	0.7 %(V) / 5 %(V) Calculated Explosive Limit
Vapour pressure	0.639 hPa @ 68 °F / 20 °C Calculated Vapor Pressure
Density	0.8085 g/cm ³ @ 60.01 °F / 15.56 °C

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to avoid

excessive heat, Heat, flames and sparks.

Incompatible products

Valvoline™ FUEL INJECTOR PLUS INTAKE
VALVE CLEANER
602376

Strong oxidizing agents

Hazardous decomposition products

Aldehydes, carbon dioxide and carbon monoxide, Hydrocarbons, nitrogen oxides (NOx), Sulphur oxides

Hazardous reactions

Product will not undergo hazardous polymerization.

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

Acute oral toxicity - Product : no data available

Acute oral toxicity - Components

KEROSENE	: LD 50: > 5,000 mg/kg Species: Rat
DISTILLATES (PETROLEUM), SWEETENED MIDDLE	: LD 50: > 5,000 mg/kg Species: Rat
PETROLEUM NAPHTHA	: LD 50: 3,000 mg/kg Species: Rat
NAPHTHALENE	: LD50 Oral: 2,200 mg/kg Species: Rat

Acute inhalation toxicity

Acute inhalation toxicity - Product : no data available

Acute inhalation toxicity - Components

KEROSENE	: LC 50: > 5,000 mg/m3 Exposure time: 4 h Species: Rat
PETROLEUM NAPHTHA	: LC 50: > 3,800 mg/m3 Exposure time: 4 h Species: Rat

Acute dermal toxicity

Valvoline™ FUEL INJECTOR PLUS INTAKE
VALVE CLEANER
602376

Acute dermal toxicity - Product : no data available

Acute dermal toxicity - Components

KEROSENE : LD 50: > 2 g/kg Species: Rabbit

PETROLEUM : LD 50: > 3,000 mg/kg Species: Rabbit

NAPHTHA

NAPHTHALENE : LD50 Dermal: > 2.0 g/kg Species: Rabbit

Acute toxicity (other routes of administration)

Acute toxicity (other routes of administration) : no data available

12. ECOLOGICAL INFORMATION

Biodegradability

Biodegradability - Product : no data available

Bioaccumulation

Bioaccumulation - Product : no data available

Bioaccumulation - Components

NAPHTHALENE : Species: Rainbow trout,donaldson trout (Oncorhynchus mykiss) Exposure time: 16 d Concentration: 0.023 mg/l Bioconcentration factor (BCF): 25 Method: Flow through

Ecotoxicity effects

Toxicity to fish

Toxicity to fish - Product : no data available

Toxicity to fish - Components

NAPHTHALENE : LC 50: 0.91 - 2.82 mg/l
Exposure time: 96 h
Species: Rainbow trout,donaldson trout (Oncorhynchus mykiss)
Test Type: static test

Valvoline™ FUEL INJECTOR PLUS INTAKE
VALVE CLEANER
602376

Toxicity to daphnia and other aquatic invertebrates

Toxicity to daphnia and other aquatic invertebrates
- Product : no data available

Toxicity to daphnia and other aquatic invertebrates - Components

NAPHTHALENE : EC 50: 1.09 - 3.4 mg/l
Exposure time: 48 h
Species: Water flea (Daphnia magna)
Test Type: static test

Toxicity to algae

Toxicity to algae - Product : no data available

Toxicity to bacteria

Toxicity to bacteria - Product : no data available

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

Valvoline™ FUEL INJECTOR PLUS INTAKE
VALVE CLEANER
602376

U.S. DOT - ROAD

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

UN	1993	FLAMMABLE LIQUID, N.O.S. (KEROSENE)	3	III	LIMITED QUANTITY
----	------	----------------------------------------	---	-----	---------------------

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

UN	1993	Flammable liquid, n.o.s. (KEROSENE)	3	III
----	------	----------------------------------------	---	-----

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

UN	1993	Flammable liquid, n.o.s. (KEROSENE)	3	III
----	------	----------------------------------------	---	-----

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

UN	1993	LIQUIDO INFLAMABLE, N.E.P. (KEROSENE)	3	III
----	------	------------------------------------------	---	-----

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

Valvoline™ FUEL INJECTOR PLUS INTAKE
VALVE CLEANER
602376

15. REGULATORY INFORMATION

California Prop. 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

SARA Hazard Classification

SARA 311/312 Classification

Fire Hazard
Acute Health Hazard
Chronic Health Hazard

SARA 313 Component(s)

NAPHTHALENE	0.19 %
-------------	--------

New Jersey RTK Label Information

KEROSENE	8008-20-6
POLYMER	
DISTILLATES (PETROLEUM), SWEETENED MIDDLE	64741-86-2
ADDITIVE	
PETROLEUM NAPHTHA	64742-94-5
NAPHTHALENE	91-20-3

Pennsylvania RTK Label Information

KEROSENE	8008-20-6
POLYMER	
DISTILLATES (PETROLEUM), SWEETENED MIDDLE	64741-86-2
PETROLEUM NAPHTHA	64742-94-5

Notification status

US. Toxic Substances Control Act	y (positive listing)
Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)	y (positive listing)
Australia. Industrial Chemical (Notification and Assessment) Act	y (positive listing)

Valvoline™ FUEL INJECTOR PLUS INTAKE
VALVE CLEANER
602376

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand	n (Negative listing)
Japan. Kashin-Hou Law List	n (Negative listing)
Korea. Toxic Chemical Control Law (TCCL) List	y (positive listing)
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act	y (positive listing)
China. Inventory of Existing Chemical Substances	y (positive listing)

Reportable quantity - Product

US. EPA CERCLA Hazardous Substances (40 CFR 302)	52631 lbs
--------------------------------------------------	-----------

Reportable quantity-Components

NAPHTHALENE	91-20-3	100 lbs
-------------	---------	---------

	HMIS	NFPA
Health	2*	2
Flammability	2	2
Physical hazards	0	
Instability		0
Specific Hazard	--	--

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).