



Revision Number: 004.2

Issue date: 10/28/2014

**1. PRODUCT AND COMPANY IDENTIFICATION**

|   |  |                             |               |
|---|--|-----------------------------|---------------|
| <b>Product name:</b>  | <b>OSI 100Z H2U 201 BRN 12CC</b>   | <b>IDH number:</b>          | 1584644       |
| <b>Product type:</b>  | Sealant  | <b>Region:</b>              | United States |
| <b>Restriction of Use:</b>  | None identified  | <b>Contact information:</b> |               |
| <b>Company address:</b>   | Telephone: (860) 571-5100<br>MEDICAL EMERGENCY Phone: Poison Control Center<br>1-877-671-4608 (toll free) or 1-303-592-1711<br>TRANSPORT EMERGENCY Phone: CHEMTREC<br>1-800-424-9300 (toll free) or 1-703-527-3887<br>Internet: www.henkelna.com |                             |               |
| Henkel Corporation<br>One Henkel Way<br>Rocky Hill, Connecticut 06067 |  |                             |               |

**2. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

**WARNING:** CAUSES SERIOUS EYE IRRITATION.

**HAZARD CLASS**

**HAZARD CATEGORY**

EYE IRRITATION

2A

**PICTOGRAM(S)**



**Precautionary Statements**

|                    |   |
|--------------------|---|
| <b>Prevention:</b> | Wash thoroughly after handling. Wear eye and face protection.   |
| <b>Response:</b>   | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. If eye irritation persists: Get medical attention. |
| <b>Storage:</b>    | Not prescribed  |
| <b>Disposal:</b>   | Not prescribed  |

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

| Hazardous Component(s)                        | CAS Number  | Percentage* |
|---|-------------|-------------|
| Limestone                                     | 1317-65-3   | 10 - 30     |
| Ethylene glycol                               | 107-21-1    | 1 - 5       |
| White mineral oil (petroleum), highly refined | 8042-47-5   | 1 - 5       |
| Diiron trioxide                               | 1309-37-1   | 1 - 5       |
| Silica, amorphous, fumed, crystal-free        | 112945-52-5 | 1 - 5       |
| Ammonium hydroxide                            | 1336-21-6   | 0.1 - 1     |
| Substituted silane                            | Proprietary | 0.1 - 1     |
| 2-Butoxyethanol                               | 111-76-2    | 0.1 - 1     |

\* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

|                            |  |
|----------------------------|--|
| <b>Inhalation:</b>         | If inhaled, immediately remove the affected person to fresh air. Get immediate medical attention.                            |
| <b>Skin contact:</b>       | Wash affected area immediately with soap and water.  |
| <b>Eye contact:</b>        | Immediately flush eyes with plenty of water for at least 15 minutes. If symptoms develop and persist, get medical attention. |
| <b>Ingestion:</b>          | Consult a physician if necessary.  |
| <b>Symptoms:</b>           | See Section 11.  |
| <b>Notes to physician:</b> | Treat symptomatically and supportively.  |

#### 5. FIRE FIGHTING MEASURES

|   |  |
|---|--|
| <b>Extinguishing media:</b>               | Water spray (fog), foam, dry chemical or carbon dioxide.   |
| <b>Special firefighting procedures:</b>   | Use water spray to keep fire exposed containers cool and disperse vapors.                                |
| <b>Unusual fire or explosion hazards:</b> | May liberate large quantities of dense, foul-smelling smoke which may contain unidentified toxic gasses. |
| <b>Hazardous combustion products:</b>     | Oxides of carbon. Oxides of nitrogen.  |

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

|                                   |   |
|-----------------------------------|---|
| <b>Environmental precautions:</b> | Prevent further leakage or spillage if safe to do so. Do not allow product to enter sewer or waterways.   |
| <b>Clean-up methods:</b>          | Scrape up spilled material and place in a closed container for disposal. Dispose of according to Federal, State and local governmental regulations. |

#### 7. HANDLING AND STORAGE

|                  |   |
|------------------|---|
| <b>Handling:</b> | Avoid prolonged or repeated skin contact with this material. Keep out of the reach of children.   |
| <b>Storage:</b>  | For safe storage, store at or above 0 °C (32°F)<br>Keep from freezing. Store in a cool, dry area. |

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s)                        | ACGIH TLV  | OSHA PEL   | AIHA WEEL | OTHER |
|---|--|--|-----------|-------|
| Limestone                                     | 10 mg/m3 TWA Total dust.   | 5 mg/m3 PEL Respirable fraction.<br>15 mg/m3 PEL Total dust. | None      | None  |
| Ethylene glycol                               | 100 mg/m3 Ceiling Aerosol.                                       | None   | None      | None  |
| White mineral oil (petroleum), highly refined | 5 mg/m3 TWA Inhalable fraction.                                  | 5 mg/m3 TWA mist<br>5 mg/m3 PEL Mist.                        | None      | None  |
| Diiron trioxide                               | 5 mg/m3 TWA Respirable fraction.                                 | 10 mg/m3 PEL Fume.   | None      | None  |
| Silica, amorphous, fumed, crystal-free        | 10 mg/m3 TWA Inhalable dust.<br>3 mg/m3 TWA Respirable fraction. | 20 MPPCF TWA<br>0.8 mg/m3 TWA                                | None      | None  |
| Ammonium hydroxide                            | None   | None   | None      | None  |
| Substituted silane                            | None   | None   | None      | None  |
| 2-Butoxyethanol                               | 20 ppm TWA   | 50 ppm (240 mg/m3) PEL (SKIN)                                | None      | None  |

**Engineering controls:**

Ventilation should effectively remove and prevent buildup of any dust generated from the handling of this product.

**Respiratory protection:**

When dusts or thermal processing fumes are generated and ventilation is not sufficient to effectively remove them, appropriate NIOSH/MSHA approved respiratory protection must be provided.

**Eye/face protection:**

Safety goggles or safety glasses with side shields.

**Skin protection:**

Use impermeable gloves and protective clothing as necessary to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|   |  |
|---|--|
| <b>Physical state:</b>                          | Paste  |
| <b>Color:</b>                                   | Brown  |
| <b>Odor:</b>                                    | Mild, Acrylic  |
| <b>Odor threshold:</b>                          | Not available.   |
| <b>pH:</b>                                      | 7.3 - 8.5  |
| <b>Vapor pressure:</b>                          | 15 mm hg (20.0 °C (68°F))  |
| <b>Boiling point/range:</b>                     | 100 °C (212°F)   |
| <b>Melting point/ range:</b>                    | Not available.   |
| <b>Specific gravity:</b>                        | 1.267  |
| <b>Vapor density:</b>                           | Heavier than air   |
| <b>Flash point:</b>                             | Not applicable   |
| <b>Flammable/Explosive limits - lower:</b>      | Not available.   |
| <b>Flammable/Explosive limits - upper:</b>      | Not available.   |
| <b>Autoignition temperature:</b>                | Not available.   |
| <b>Evaporation rate:</b>                        | < 0.5 (Butyl acetate = 1)  |
| <b>Solubility in water:</b>                     | Soluble  |
| <b>Partition coefficient (n-octanol/water):</b> | Not available.   |
| <b>VOC content:</b>                             | 0.3 %; 42 g/l (by weight, calculated using CARB method; g/L less water, less exempts calculated using SCAQMD method) |
| <b>Viscosity:</b>                               | 200,000 - 300,000 cp   |
| <b>Decomposition temperature:</b>               | Not available.   |

## 10. STABILITY AND REACTIVITY

|  |  |
|--|--|
| <b>Stability:</b>                        | Stable under normal conditions of storage and use. |
| <b>Hazardous reactions:</b>              | Will not occur.                                    |
| <b>Hazardous decomposition products:</b> | Oxides of carbon. Oxides of nitrogen.              |
| <b>Incompatible materials:</b>           | This product may react with oxidizing agents.      |
| <b>Reactivity:</b>                       | Not available.                                     |
| <b>Conditions to avoid:</b>              | Do not freeze.                                     |

## 11. TOXICOLOGICAL INFORMATION

**Relevant routes of exposure:** Inhalation, Skin contact

**Potential Health Effects/Symptoms**

|                      |   |
|----------------------|---|
| <b>Inhalation:</b>   | May cause irritation to nose and throat.  |
| <b>Skin contact:</b> | May cause slight irritation to skin. May cause allergic skin reaction in susceptible individuals.   |
| <b>Eye contact:</b>  | May cause slight irritation to eyes on contact.   |
| <b>Ingestion:</b>    | Not expected to be harmful by ingestion. Ingestion of large amounts may produce gastrointestinal disturbances including irritation, nausea, and diarrhea. |

| Hazardous Component(s)                        | LD50s and LC50s  | Immediate and Delayed Health Effects  |
|---|--|---|
| Limestone                                     | None   | Nuisance dust   |
| Ethylene glycol                               | Oral LD50 (RAT) = 5.89 g/kg<br>Dermal LD50 (RABBIT) = 9,530 mg/kg  | Blood, Bone Marrow, Central nervous system, Developmental, Eyes, Irritant, Kidney, Liver, Metabolic |
| White mineral oil (petroleum), highly refined | None   | Irritant  |
| Diiron trioxide                               | None   | Allergen, Cardiac, Central nervous system, Irritant, Kidney, Liver, Lung                            |
| Silica, amorphous, fumed, crystal-free        | None   | Nuisance dust   |
| Ammonium hydroxide                            | Oral LD50 (RAT) = 350 mg/kg  | Irritant, Corrosive   |
| Substituted silane                            | None   | Allergen, Irritant  |
| 2-Butoxyethanol                               | Oral LD50 (RAT) = 560 mg/kg<br>Oral LD50 (RABBIT) = 0.32 g/kg<br>Oral LD50 (RAT) = 1.48 g/kg<br>Dermal LD50 (RABBIT) = 400 mg/kg<br>Inhalation LC50 (RAT, 4 h) = 486 ppm<br>Inhalation LC50 (RAT, 4 h) = 450 ppm | Blood, Central nervous system, Irritant, Kidney, Liver  |

| Hazardous Component(s)                        | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|---|----------------|-----------------|--|
| Limestone                                     | No             | No              | No                                       |
| Ethylene glycol                               | No             | No              | No                                       |
| White mineral oil (petroleum), highly refined | No             | No              | No                                       |
| Diiron trioxide                               | No             | No              | No                                       |
| Silica, amorphous, fumed, crystal-free        | No             | No              | No                                       |
| Ammonium hydroxide                            | No             | No              | No                                       |
| Substituted silane                            | No             | No              | No                                       |
| 2-Butoxyethanol                               | No             | No              | No                                       |

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose of according to Federal, State and local governmental regulations.

**Hazardous waste number:** It is the responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics Leaching Procedure (TCLP) 40 CFR 261.20-24.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

### Water Transportation (IMO/IMDG)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

## 15. REGULATORY INFORMATION

### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

**TSCA 12 (b) Export Notification:** None above reporting de minimis

**CERCLA/SARA Section 302 EHS:** None above reporting de minimis  
**CERCLA/SARA Section 311/312:** Immediate Health, Delayed Health

**CERCLA/SARA Section 313:** This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Ethylene glycol (CAS# 107-21-1).

**California Proposition 65:** This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

### Canada Regulatory Information

**CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

## 16. OTHER INFORMATION

**This safety data sheet contains changes from the previous version in sections:** New Material Safety Data Sheet format.

**Prepared by:** Mary Ellen Roddy, Sr. Regulatory Affairs Specialist

**Issue date:** 10/28/2014

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.