



MATERIAL SAFETY DATA SHEET

Page 1 of 6

HE289 - WHITE ROOFING SEALANT

1. Product And Company Identification	
Supplier HENRY COMPANY 999 N. Sepulveda Blvd., Suite 800 El Segundo, CA 90245-2716 Company Contact: Technical Services Telephone Number: (800) 486-1278 Web Site: www.henry.com www.bakor.com	Manufacturer HENRY COMPANY 999 N. Sepulveda Blvd., Suite 800 El Segundo, CA 90245-2716 Company Contact: Technical Services Telephone Number: (800) 486-1278 Web Site: www.henry.com www.bakor.com
Supplier Emergency Contacts & Phone Number CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666	Manufacturer Emergency Contacts & Phone Number CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666
Issue Date: 06/24/2014 Product Name: HE289 - WHITE ROOFING SEALANT Product Code: HE289	

2. Composition/Information On Ingredients			
Ingredient Name	CAS Number		Percent Of Total Weight
acrylic polymer blend	NA - Mixture		20 - 40
benzyl butyl phthalate	85-68-7		5 - 10
calcium carbonate	1317-65-3		20 - 40
silica, quartz	14808-60-7		0.1 - 1
titanium dioxide	13463-67-7		1 - 5
water	7732-18-5		10 - 30

EMERGENCY OVERVIEW	
CAUTION! Direct skin and eye contact may cause irritation. Ingestion may cause gastric distress. Inhalation may cause irritation to the respiratory tract.	
Appearance/Odor: White, creamy liquid, paint-like odor	

3. Hazards Identification
Primary Routes(s) Of Entry Inhalation, Skin Contact and Ingestion
Eye Hazards May cause eye irritation (burning, tearing, redness or swelling).
Skin Hazards May cause skin irritation. Dermal absorption hazards are similar to ingestion hazards, after long term or repeated exposures.
Ingestion Hazards May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea.



HE289 - WHITE ROOFING SEALANT

<p>3. Hazards Identification - Continued</p> <p><u>Inhalation Hazards</u> May cause minor irritation of the nose and throat. Certain individuals may experience minor nausea or headaches.</p> <p><u>Chronic/Carcinogenicity Effects</u> This product or one of its ingredients present at 0.1% or more is listed as a carcinogen by NTP, IARC or OSHA. See Section 11 (Toxicological Information) for more details.</p>
<p>4. First Aid Measures</p> <p><u>Eye</u> In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.</p> <p><u>Skin</u> Remove contaminated clothing and shoes. Wash affected areas with soap and water.</p> <p><u>Ingestion</u> Get medical attention immediately. DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious victim.</p> <p><u>Inhalation</u> Remove the person from the contaminated area to fresh air. If breathing is difficult, give oxygen. Contact a physician if symptoms develop.</p>
<p>5. Fire Fighting Measures</p> <p>Flash Point: >212 °F >100 °C Flash Point Method: Setaflash Lower Explosive Limit: not available Upper Explosive Limit: not available</p> <p><u>Fire And Explosion Hazards</u> Product is not considered flammable or combustible. Products of combustion (cured material) include compounds of carbon, hydrogen, oxygen, including carbon monoxide.</p> <p><u>Extinguishing Media</u> Carbon dioxide, water, water fog, dry chemical, chemical foam.</p> <p><u>Fire Fighting Instructions</u> Keep containers cool with water spray to prevent container rupture due to steam buildup; floor will become slippery if material is released. Firefighters should wear self-contained breathing apparatus and full protective gear.</p>
<p>6. Accidental Release Measures</p> <p>Contain and/or absorb spill with inert material (e.g. sand, vermiculite). Collect and dispose in accordance with applicable regulations. Avoid runoff to waterways and sewers.</p>
<p>7. Handling And Storage</p> <p><u>Handling And Storage Precautions</u> Keep containers tightly closed. Store in a cool, dry, well-ventilated area. Protect from physical damage. Protect from extreme temperatures. Keep out of reach of children.</p>
<p>8. Exposure Controls/Personal Protection</p> <p><u>Engineering Controls</u> Use with adequate general and local exhaust ventilation. When used outdoors, stay well away from building air intakes or close and seal the intakes to prevent product from entering building.</p>



HE289 - WHITE ROOFING SEALANT

8. Exposure Controls/Personal Protection - Continued

Eye/Face Protection

Safety glasses with side shields or goggles recommended.

Skin Protection

Use with chemical-protective gloves to prevent skin contact.

Respiratory Protection

This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

The level of respiratory protection needed should be based on the evaluation of chemical exposures by a health or safety professional. If required, use a NIOSH-approved air purifying respirator with organic vapor cartridge and particulate filter or supplied air respirator.

Occupational Exposure Limits for individual ingredients (if available) are listed below.

Ingredient(s) - Exposure Limits

calcium carbonate

OSHA PEL-TWA 15 mg/m3 (total dust)

OSHA PEL-TWA 5 mg/m3 (respirable dust)

silica, quartz

ACGIH TLV-TWA 0.025 mg/m3

OSHA PEL-TWA 30mg/m3 / (%SiO₂+2) (total dust)

OSHA PEL-TWA 10 mg/m3/ (%SiO₂+2) (respirable dust)

titanium dioxide

ACGIH TLV-TWA 10 mg/m3 (respirable)

OSHA PEL-TWA 15 mg/m3 (total dust)

9. Physical And Chemical Properties

Appearance

White, creamy liquid

Odor

Paint-like odor

Chemical Type: Mixture

Physical State: Liquid

Boiling Point: 212 °F

Specific Gravity: 1.37

Percent Volatiles: 45

Vapor Pressure: 760 @ 212°F

Vapor Density: >1

pH Factor: not available

Solubility: dispersible

Evaporation Rate: <1

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Conditions To Avoid (Stability)

Extreme temperatures



HE289 - WHITE ROOFING SEALANT

10. Stability And Reactivity - Continued

Incompatible Materials

Strong oxidizers, strong acids

Hazardous Decomposition Products

Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons and smoke may be produced.

Conditions To Avoid (Polymerization)

none

11. Toxicological Information

Chronic/Carcinogenicity

IARC has concluded that the following chemicals in this product are carcinogenic to humans (Group 1): silica, quartz

IARC has concluded that the following chemicals in this product are possibly carcinogenic to humans (Group 2B): titanium dioxide

ACGIH has designated the following chemicals in this product as suspected human carcinogens (A2): silica, quartz

NTP has listed the following chemicals in this product as known human carcinogens: silica, quartz

Risk of cancer depends on duration and level of exposure to this product as a dust or aerosol mist.

Miscellaneous Toxicological Information

Toxicological testing has not been conducted for this product overall. Available toxicological data for individual ingredients are summarized below.

Ingredient(s) - Toxicological Data

benzyl butyl phthalate

LD50 (oral, rat): 2330 mg/kg

LD50 (dermal, rabbit): >10000 mg/kg

calcium carbonate

oral-rat LD50: 6450 mg/kg

silica, quartz

iv-rat LD50: 500 mg/kg bw/Quartz (10-200 um)

12. Ecological Information

Do not allow into any sewer, on the ground, or into any body of water.

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

14. Transport Information

Ground Not Restricted

IMDG Not Restricted

IATA Not Restricted

15. Regulatory Information

U.S. Regulatory Information

Warning: This product contains a substance known to the State of California to cause cancer.

HE289 - WHITE ROOFING SEALANT

15. Regulatory Information - Continued

SARA Hazard Classes

Acute Health Hazard

Ingredient(s) - State Regulations

benzyl butyl phthalate

- New Jersey - Workplace Hazard
- New Jersey - Environmental Hazard
- Pennsylvania - Workplace Hazard
- Pennsylvania - Environmental Hazard
- New York City - Hazardous Substance

calcium carbonate

- Pennsylvania - Workplace Hazard

silica, quartz

- New Jersey - Workplace Hazard
- Pennsylvania - Workplace Hazard
- California - Proposition 65
- Massachusetts - Hazardous Substance

titanium dioxide

- New Jersey - Workplace Hazard
- Pennsylvania - Workplace Hazard
- New York City - Hazardous Substance

Canadian Regulatory Information

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR. WHMIS Classification: D2A - Very Toxic


Ingredient(s) - Canadian Regulatory Information

silica, quartz

- WHMIS - Ingredient Disclosure List

WHMIS - Canada (Pictograms)



<u>NFPA</u>	<u>HMIS</u>								
	<table border="1"> <tr> <td>HEALTH</td> <td style="text-align: center;">1</td> </tr> <tr> <td>FLAMMABILITY</td> <td style="text-align: center;">0</td> </tr> <tr> <td>REACTIVITY</td> <td style="text-align: center;">0</td> </tr> <tr> <td>PERSONAL PROTECTION</td> <td style="text-align: center;"> </td> </tr> </table>	HEALTH	1	FLAMMABILITY	0	REACTIVITY	0	PERSONAL PROTECTION	
HEALTH	1								
FLAMMABILITY	0								
REACTIVITY	0								
PERSONAL PROTECTION									

16. Other Information

Revision/Preparer Information

This MSDS Supersedes A Previous MSDS Dated: 04/22/2011

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the



HE289 - WHITE ROOFING SEALANT

Disclaimer - Continued

consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

HENRY COMPANY