



# MATERIAL SAFETY DATA SHEET

Page 1 of 7

## HE552 - ELASTIC ROOF SEALER

1. Product And Company Identification	
<b>Supplier</b> HENRY COMPANY 999 N. Sepulveda Blvd., Suite 800 El Segundo, CA 90245-2716  <b>Company Contact:</b> Technical Services <b>Telephone Number:</b> (800) 486-1278 <b>Web Site:</b> www.henry.com www.bakor.com	<b>Manufacturer</b> HENRY COMPANY 999 N. Sepulveda Blvd., Suite 800 El Segundo, CA 90245-2716  <b>Company Contact:</b> Technical Services <b>Telephone Number:</b> (800) 486-1278 <b>Web Site:</b> www.henry.com www.bakor.com
<b>Supplier Emergency Contacts &amp; Phone Number</b> CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666	<b>Manufacturer Emergency Contacts &amp; Phone Number</b> CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666
<b>Issue Date:</b> 06/24/2014  <b>Product Name:</b> HE552 - ELASTIC ROOF SEALER <b>Product Code:</b> HE552	

2. Composition/Information On Ingredients			
Ingredient Name	CAS Number		Percent Of Total Weight
1,2,4-trimethylbenzene	95-63-6		1 - 5
aromatic petroleum distillates	64742-95-6		1 - 5
petroleum asphalt	8052-42-4		30 - 50
attapulgite	12174-11-7		5 - 15
calcium carbonate	1317-65-3		5 - 10
cellulose fiber	9004-34-6		7 - 13
silica, quartz	14808-60-7		0.1 - 1
stoddard solvent	8052-41-3		10 - 30
xylene	1330-20-7		0.5 - 1.5

EMERGENCY OVERVIEW	
<b>CAUTION! Combustible Liquid. Central nervous system depressant. Vapor may cause light-headedness, headache, nausea, loss of coordination and respiratory tract irritation. Causes skin irritation.</b>	
<b>Appearance/Odor: Black fibrous paste, strong petroleum solvent odor</b>	

3. Hazards Identification
<b>Primary Routes(s) Of Entry</b> Inhalation
<b>Eye Hazards</b> May cause eye irritation (burning, tearing, redness or swelling).
<b>Skin Hazards</b> May cause skin irritation and contact dermatitis upon prolonged contact.



HE552 - ELASTIC ROOF SEALER

3. Hazards Identification - Continued

**Ingestion Hazards**

May be harmful if swallowed. May cause gastric distress, vomiting and diarrhea.

**Inhalation Hazards**

Exposure to vapors may cause respiratory tract irritation. Inhalation of vapors or mists may cause central nervous system depression, light-headedness, headache, nausea and loss of coordination.

**Chronic/Carcinogenicity Effects**

This product or one of its ingredients present at 0.1% or more is listed as a carcinogen by NTP, IARC or OSHA. See Section 11 (Toxicological Information) for more details.

4. First Aid Measures

**Eye**

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

**Skin**

Remove contaminated clothing and shoes. Wash affected areas with soap and water.

**Ingestion**

Get medical attention immediately. DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious victim. Call a physician or poison control center immediately.

**Inhalation**

Remove the person from the contaminated area to fresh air. If breathing is difficult, give oxygen. Get medical attention immediately.

5. Fire Fighting Measures

**Flash Point:** 120 °F 48.9 °C

**Flash Point Method:** Setaflash

**Flammability Class:** Class II

**Lower Explosive Limit:** 0.9

**Upper Explosive Limit:** 6.0

**Fire And Explosion Hazards**

Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.

**Extinguishing Media**

Chemical foam, carbon dioxide (CO2), water fog or dry chemical.

**Fire Fighting Instructions**

Firefighters should wear self-contained breathing apparatus and full protective gear.

6. Accidental Release Measures

Collect and dispose in accordance with applicable regulations.

7. Handling And Storage

**Handling And Storage Precautions**

Keep containers tightly closed. Store in a cool, dry, well-ventilated area. Do not handle or store near strong oxidants or strong acids. Use only with adequate ventilation.



HE552 - ELASTIC ROOF SEALER

8. Exposure Controls/Personal Protection

**Engineering Controls**

Use with adequate general and local exhaust ventilation. When used outdoors, stay well away from building air intakes or close and seal the intakes to prevent product from entering building.

**Eye/Face Protection**

Safety glasses with side shields or goggles recommended.

**Skin Protection**

Use with chemical-protective gloves to prevent skin contact.

**Respiratory Protection**

This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

The level of respiratory protection needed should be based on the evaluation of chemical exposures by a health or safety professional. If required, use a NIOSH-approved air purifying respirator with organic vapor cartridge and particulate filter or supplied air respirator.

Occupational Exposure Limits for individual ingredients (if available) are listed below.

**Ingredient(s) - Exposure Limits**

- 1,2,4-trimethylbenzene  
ACGIH TLV-TWA 25 ppm
- aromatic petroleum distillates  
OSHA PEL-TWA 500 ppm
- petroleum asphalt  
ACGIH TLV-TWA 0.5 mg/m3 (inhalable fraction, as benzene-soluble aerosol)
- calcium carbonate  
OSHA PEL-TWA 15 mg/m3 (total dust)  
OSHA PEL-TWA 5 mg/m3 (respirable dust)
- cellulose fiber  
ACGIH TLV-TWA 10 mg/m3
- silica, quartz  
ACGIH TLV-TWA 0.025 mg/m3  
OSHA PEL-TWA 30mg/m3 / (%SiO2+2) (total dust)  
OSHA PEL-TWA 10 mg/m3/ (%SiO2+2) (respirable dust)
- stoddard solvent  
ACGIH TLV-TWA 100 ppm  
OSHA PEL-TWA 500 ppm
- xylene  
ACGIH TLV-STEL 150 ppm  
ACGIH TLV-TWA 100 ppm  
OSHA PEL-TWA 100 ppm

9. Physical And Chemical Properties

**Appearance**

Black Fibrous Paste

**Odor**

Strong Petroleum Solvent Odor

**Chemical Type:** Mixture


**Physical State:** Liquid

**Boiling Point:** 310-400 °F 154-204 °C

**HE552 - ELASTIC ROOF SEALER**

<p>9. Physical And Chemical Properties - Continued</p>
<p><b><u>Odor - Continued</u></b>  <b>Specific Gravity:</b> 1.03  <b>Percent Volatiles:</b> &lt;30  <b>Vapor Pressure:</b> 2@68°F  <b>Vapor Density:</b> &gt;1  <b>pH Factor:</b> not applicable  <b>Solubility:</b> insoluble in water  <b>Evaporation Rate:</b> &lt;1</p>
<p>10. Stability And Reactivity</p>
<p><b>Stability:</b> Stable  <b>Hazardous Polymerization:</b> Will not occur</p> <p><b><u>Incompatible Materials</u></b>          Avoid contact with strong oxidizing agents and acids.</p> <p><b><u>Hazardous Decomposition Products</u></b>          Toxic and irritating gases, vapors or fumes, carbon monoxide (CO), carbon dioxide (CO2).</p>
<p>11. Toxicological Information</p>
<p><b><u>Chronic/Carcinogenicity</u></b>          IARC has concluded that the following chemicals in this product are carcinogenic to humans (Group 1): silica, quartz          ACGIH has designated the following chemicals in this product as suspected human carcinogens (A2): silica, quartz          NTP has listed the following chemicals in this product as known human carcinogens: silica, quartz</p> <p>Risk of cancer depends on duration and level of exposure to this product as a dust.</p> <p><b><u>Miscellaneous Toxicological Information</u></b>          Toxicological testing has not been conducted for this product overall. Available toxicological data for individual ingredients are summarized below.</p> <p><b><u>Ingredient(s) - Toxicological Data</u></b>          1,2,4-trimethylbenzene              LD50 (oral, rat): 5000 mg/kg              LC50 (rat): 18 g/m3 (4-hour exposure)          aromatic petroleum distillates              LD50 (oral, rat): 2900 mg/kg          calcium carbonate              oral-rat LD50: 6450 mg/kg          cellulose fiber              LD50 (oral, rat): &gt;2000 mg/kg              LC50 (rat): &gt;5800 mg/m3 (4-hour exposure)          silica, quartz              iv-rat LD50: 500 mg/kg bw/Quartz (10-200 um)          stoddard solvent              oral-rat LD50: &gt;5000 mg/kg              dermal-rabbit LD50: &gt;3000 mg/kg              inhal-rat LC50: &gt;5500 mg/m3 (880 ppm)              inhal-rat LC50: &gt;1300 ppm          xylene              LD50 (oral, rat): 5400 mg/kg              LD50 (dermal, rabbit): 12180 mg/kg</p>

**HE552 - ELASTIC ROOF SEALER**

11. Toxicological Information - Continued
<b><u>Ingredient(s) - Toxicological Data - Continued</u></b> LC50 (rat): 6350 ppm (4-hour exposure)
12. Ecological Information
No specific information available.
13. Disposal Considerations
Dispose in accordance with applicable federal, state and local government regulations.
14. Transport Information
Ground or Water Domestic Voyage  Not restricted if shipped in containers <450L (119 gallons) Restricted if shipped in containers >450L (119 gallons)  US      NA1993, Combustible liquid, n.o.s., (Petroleum Distillates mixture), Combustible liquid, III  Canada UN1999, Tars liquid, 3, III  Unless departs >flash point:  Both UN3256, Elevated Temperature liquid, flammable, n.o.s., (Petroleum Distillates mixture), 3, III  IMDG      IMDG Code 2.3.2.5 - exempted from marking, labeling & testing of packages  IATA      UN1999, Tars liquid, 3, III
<b><u>DOT (Pictograms)</u></b>

15. Regulatory Information
<b><u>U.S. Regulatory Information</u></b> Asphalt may contain detectable amounts of chemicals known to the State of California to cause cancer or reproductive harm.
<b><u>Ingredient(s) - U.S. Regulatory Information</u></b> 1,2,4-trimethylbenzene SARA Title III - Section 313 Form "R"/TRI Reportable Chemical xylene SARA Title III - Section 313 Form "R"/TRI Reportable Chemical
<b><u>Ingredient(s) - State Regulations</u></b> 1,2,4-trimethylbenzene New Jersey - Workplace Hazard New Jersey - Environmental Hazard Massachusetts - Hazardous Substance New York City - Hazardous Substance aromatic petroleum distillates New Jersey - Workplace Hazard

## HE552 - ELASTIC ROOF SEALER

### 15. Regulatory Information - Continued

#### **Ingredient(s) - State Regulations - Continued**

Pennsylvania - Workplace Hazard  
petroleum asphalt  
New Jersey - Workplace Hazard  
Pennsylvania - Workplace Hazard  
Massachusetts - Hazardous Substance  
New York City - Hazardous Substance  
attapulgite  
California - Proposition 65  
calcium carbonate  
Pennsylvania - Workplace Hazard  
cellulose fiber  
Pennsylvania - Workplace Hazard  
silica, quartz  
New Jersey - Workplace Hazard  
Pennsylvania - Workplace Hazard  
California - Proposition 65  
Massachusetts - Hazardous Substance  
stoddard solvent  
New Jersey - Workplace Hazard  
Pennsylvania - Workplace Hazard  
Massachusetts - Hazardous Substance  
New York City - Hazardous Substance  
xylene  
New Jersey - Workplace Hazard  
New Jersey - Environmental Hazard  
New Jersey - Special Hazard  
Pennsylvania - Workplace Hazard  
Pennsylvania - Environmental Hazard  
Massachusetts - Hazardous Substance  
New York City - Hazardous Substance

#### **Canadian Regulatory Information**

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR. WHMIS Classification: B3 - Combustible Liquid, D2A - Very Toxic


#### **Ingredient(s) - Canadian Regulatory Information**

1,2,4-trimethylbenzene  
WHMIS - Ingredient Disclosure List  
silica, quartz  
WHMIS - Ingredient Disclosure List  
stoddard solvent  
WHMIS - Ingredient Disclosure List

#### **WHMIS - Canada (Pictograms)**



### HE552 - ELASTIC ROOF SEALER

<b>NFPA</b>	<b>HMIS</b>								
	<table border="1"><tr><td>HEALTH</td><td style="text-align: center;">2</td></tr><tr><td>FLAMMABILITY</td><td style="text-align: center;">2</td></tr><tr><td>REACTIVITY</td><td style="text-align: center;">0</td></tr><tr><td>PERSONAL PROTECTION</td><td style="text-align: center;"><input type="text"/></td></tr></table>	HEALTH	2	FLAMMABILITY	2	REACTIVITY	0	PERSONAL PROTECTION	<input type="text"/>
HEALTH	2								
FLAMMABILITY	2								
REACTIVITY	0								
PERSONAL PROTECTION	<input type="text"/>								

16. Other Information

**Revision/Preparer Information**

**This MSDS Supersedes A Previous MSDS Dated: 04/20/2011**

**Disclaimer**

**Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).**