



SAFETY DATA SHEET

Revision Date 14-Apr-2016

Version 2

1. IDENTIFICATION

Product identifier

Product Name SPRAY SEALANT 9.25 OZ

Other means of identification

Product Code 82099

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Flammable Aerosol Sealant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex
6875 Parkland Blvd.
Solon, OH 44139 USA

Distributor

ITW Permatex Canada
35 Brownridge Road, Unit 1
Halton Hills, ON Canada L7G 0C6
Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency:

00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Liquefied gas

Label elements

Emergency Overview

Danger

Causes skin irritation

Causes serious eye irritation
 Suspected of causing cancer
 Suspected of damaging fertility or the unborn child
 May cause drowsiness or dizziness
 May cause damage to organs through prolonged or repeated exposure
 May be fatal if swallowed and enters airways
 Extremely flammable aerosol
 Contains gas under pressure; may explode if heated



Appearance Clear

Physical state Liquid Flammable Aerosol

Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Wear eye/face protection
 Do not breathe dust/fume/gas/mist/vapors/spray
 Do not eat, drink or smoke when using this product
 Use only outdoors or in a well-ventilated area
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking
 Do not spray on an open flame or other ignition source
 Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 Specific treatment (see supplemental first aid instructions on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 IF ON SKIN: Wash with plenty of soap and water
 If skin irritation occurs: Get medical advice/attention
 Take off contaminated clothing and wash before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- Toxic to aquatic life with long lasting effects
 - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0.1 % w/w 1,3-butadiene (EINECS No. 203-450-8). If the substance is not classified as a carcinogen or mutagen, at least the S-phrases (2)-9-16 (Table 3.2) should apply. This note applies only to certain complex oil-derived substances in Part 3

Unknown acute toxicity

15.2 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
ACETONE	67-64-1	15 - 40	*
TOLUENE	108-88-3	7 - 13	*
SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH.	64742-88-7	7 - 13	*
2-PROPANOL	67-63-0	7 - 13	*
PROPANE	74-98-6	5 - 10	*
BUTANE	106-97-8	5 - 10	*
XYLENE	1330-20-7	1 - 5	*
N-HEXANE	110-54-3	<3	*
ETHYL BENZENE	100-41-4	0.1 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	Get medical advice/attention if you feel unwell.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin contact	IF ON SKIN: Wash skin with soap and water. If skin irritation persists, call a physician. Wash contaminated clothing before reuse.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
Ingestion	IF SWALLOWED: Call a physician or poison control center immediately. Do NOT induce vomiting.
Self-protection of the first aider	Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO₂), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Extremely flammable. Contents under pressure and can explode when exposed to heat or flames.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Remove all sources of ignition. Ensure adequate ventilation, especially in confined areas. Avoid contact with skin, eyes or clothing.

Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation, especially in confined areas. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Contents under pressure. Do not puncture or incinerate cans. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store locked up. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Incompatible materials Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ACETONE 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³
TOLUENE 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³

		Ceiling: 300 ppm	
2-PROPANOL 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³
PROPANE 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
BUTANE 106-97-8	STEL: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	TWA: 800 ppm TWA: 1900 mg/m ³
XYLENE 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	-
N-HEXANE 110-54-3	TWA: 50 ppm S*	TWA: 500 ppm TWA: 1800 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 180 mg/m ³	IDLH: 1100 ppm TWA: 50 ppm TWA: 180 mg/m ³
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³

NIOSH IDLH *Immediately Dangerous to Life or Health*

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin and body protection

Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Respiratory protection

Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid; Flammable Aerosol
Appearance	Clear
Odor	Solvent
Odor threshold	No information available

Property	Values	Remarks • Method
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	No information available	

Flash point	-29 °C / -20.2 °F	Gives a flame projection at full valve opening or flashback at any degree of valve opening
Evaporation rate	> 9.1	Butyl acetate = 1
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	12.8%	
Lower flammability limit:	1.0%	
Vapor pressure	13.5 kPa (101.325 mm Hg)	
Vapor density	1.55	Air = 1
Relative density	0.76	
Water solubility	No information available	
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	<0.205 cm ² /s	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	54.4%
Density	No information available
Bulk density	No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks. Temperatures >50 °C / 122 °F.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	Harmful by inhalation. May cause drowsiness or dizziness.
Eye contact	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
Skin contact	May cause skin irritation and/or dermatitis.
Ingestion	Harmful if swallowed. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
---------------	-----------	-------------	-----------------

ACETONE 67-64-1	= 5800 mg/kg (Rat)	-	= 50100 mg/m ³ (Rat) 8 h
TOLUENE 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. 64742-88-7	> 5000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
2-PROPANOL 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat) 4 h
PROPANE 74-98-6	-	-	= 658 mg/L (Rat) 4 h
BUTANE 106-97-8	-	-	= 658 g/m ³ (Rat) 4 h
XYLENE 1330-20-7	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit) > 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
N-HEXANE 110-54-3	= 25 g/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h
ETHYL BENZENE 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
TOLUENE 108-88-3	-	Group 3	-	-
XYLENE 1330-20-7	-	Group 3	-	-
ETHYL BENZENE 100-41-4	A3	Group 2B	-	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Chronic toxicity May cause adverse liver effects.

Target Organ Effects Central nervous system, Eyes, kidney, Liver, Peripheral Nervous System (PNS), Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	4525 mg/kg
ATEmix (dermal)	8568 mg/kg
ATEmix (inhalation-gas)	1796133 mg/l
ATEmix (inhalation-dust/mist)	20.5 mg/l
ATEmix (inhalation-vapor)	2035200 mg/l

12. ECOLOGICAL INFORMATION**Ecotoxicity**

30.2 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
ACETONE 67-64-1	-	4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50
TOLUENE	433: 96 h Pseudokirchneriella	15.22 - 19.05: 96 h Pimephales	5.46 - 9.83: 48 h Daphnia magna

108-88-3	subcapitata mg/L EC50 12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	promelas mg/L LC50 flow-through 12.6: 96 h Pimephales promelas mg/L LC50 static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 54: 96 h Oryzias latipes mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static	mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50
SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. 64742-88-7	450: 96 h Pseudokirchneriella subcapitata mg/L EC50	800: 96 h Pimephales promelas mg/L LC50 static	100: 48 h Daphnia magna mg/L EC50
2-PROPANOL 67-63-0	1000: 96 h Desmodemus subspicatus mg/L EC50 1000: 72 h Desmodemus subspicatus mg/L EC50	9640: 96 h Pimephales promelas mg/L LC50 flow-through 11130: 96 h Pimephales promelas mg/L LC50 static 1400000: 96 h Lepomis macrochirus µg/L LC50	13299: 48 h Daphnia magna mg/L EC50
XYLENE 1330-20-7	-	13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50
N-HEXANE 110-54-3	-	2.1 - 2.98: 96 h Pimephales promelas mg/L LC50 flow-through	1000: 24 h Daphnia magna mg/L EC50
ETHYL BENZENE 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 32: 96 h Lepomis macrochirus mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
ACETONE 67-64-1	-0.24
TOLUENE 108-88-3	2.65
2-PROPANOL 67-63-0	0.05

PROPANE 74-98-6	2.3
BUTANE 106-97-8	2.89
XYLENE 1330-20-7	2.77 - 3.15
ETHYL BENZENE 100-41-4	3.118

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment methods**

Disposal of wastes This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated packaging Do not reuse container.

US EPA Waste Number D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
ACETONE 67-64-1	-	Included in waste stream: F039	-	U002
TOLUENE 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151	-	U220
XYLENE 1330-20-7	-	Included in waste stream: F039	-	U239
ETHYL BENZENE 100-41-4	-	Included in waste stream: F039	-	-

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
TOLUENE 108-88-3	-	-	Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	-

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
ACETONE 67-64-1	Ignitable
TOLUENE 108-88-3	Toxic Ignitable
2-PROPANOL 67-63-0	Toxic Ignitable
XYLENE 1330-20-7	Toxic Ignitable

N-HEXANE 110-54-3	Toxic Ignitable
ETHYL BENZENE 100-41-4	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID no 1950
Proper shipping name: Aerosols, Limited Quantity (LQ)
Hazard Class 2.1
Emergency Response Guide Number 126

IATA

UN/ID no UN 8000
Proper shipping name: Consumer commodity
Hazard Class 9
ERG Code 9L

IMDG

UN/ID no 1950
Proper shipping name: Aerosols, Limited Quantity (LQ)
Hazard Class 2.1
EmS-No F-D, S-U

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL/NDSL Complies
EINECS/ELINCS Complies
ENCS Complies
IECSC Complies
KECL Complies
PICCS Complies
AICS Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
TOLUENE - 108-88-3	1.0
2-PROPANOL - 67-63-0	1.0
XYLENE - 1330-20-7	1.0
N-HEXANE - 110-54-3	1.0
ETHYL BENZENE - 100-41-4	0.1

SARA 311/312 Hazard Categories

Acute health hazard Yes

Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TOLUENE 108-88-3	1000 lb	X	X	X
XYLENE 1330-20-7	100 lb	-	-	X
ETHYL BENZENE 100-41-4	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
ACETONE 67-64-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
TOLUENE 108-88-3	1 lb	-	RQ 1 lb final RQ RQ 0.454 kg final RQ
XYLENE 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ
N-HEXANE 110-54-3	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
TOLUENE - 108-88-3	Developmental Female Reproductive
ETHYL BENZENE - 100-41-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ACETONE 67-64-1	X	X	X
TOLUENE 108-88-3	X	X	X
SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. 64742-88-7	X	-	-
2-PROPANOL 67-63-0	X	X	X
PROPANE 74-98-6	X	X	X
BUTANE 106-97-8	X	X	X
XYLENE 1330-20-7	X	X	X
N-HEXANE 110-54-3	X	X	X
ETHYL BENZENE 100-41-4	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

A Compressed gases, B5 - Flammable aerosol, D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 3	Instability 0	-
HMIS	Health hazards 2	Flammability 3	Physical hazards 0	Personal protection B

NFPA (National Fire Protection Association)
HMIS (Hazardous Material Information System)

Revision Date 14-Apr-2016

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet