



SAFETY DATA SHEET

Revision Date 19-May-2016

Version 2

1. IDENTIFICATION

Product identifier

Product Name WHITE LITHIUM GREASE 10.75OZ AE

Other means of identification

Product Code 81981

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Flammable Aerosol, Lubricant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex
6875 Parkland Blvd.
Solon, OH 44139 USA

Distributor

ITW Permatex Canada
35 Brownridge Road, Unit 1
Halton Hills, ON Canada L7G 0C6
Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency:

00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Liquefied gas

Label elements

Emergency Overview

Danger

May be fatal if swallowed and enters airways
Extremely flammable aerosol
Contains gas under pressure; may explode if heated

**Appearance** White**Physical state** Liquid Flammable Aerosol**Odor** Solvent**Precautionary Statements - Prevention**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking
 Do not spray on an open flame or other ignition source
 Pressurized container: Do not pierce or burn, even after use

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346. This note applies only to certain complex oil derived substances in Annex I

3. COMPOSITION/INFORMATION ON INGREDIENTS

substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC	64742-52-5	5-25	*
PROPANE	74-98-6	10 - 30	*
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC	64741-96-4	5-25	*
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	10 - 30	*
HEPTANE	142-82-5	5 - 10	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures**General advice**

Get medical advice/attention if you feel unwell.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin contact

IF ON SKIN: Wash skin with soap and water. If skin irritation persists, call a physician.

Wash contaminated clothing before reuse.

Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
Ingestion	IF SWALLOWED: Call a physician or poison control center immediately. Rinse mouth.
Self-protection of the first aider	Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO₂), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Extremely flammable. Keep product and empty container away from heat and sources of ignition. Vapors may travel to source of ignition and flash back.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin. Use personal protective equipment as required. Remove all sources of ignition. Contents under pressure. Do not puncture or incinerate cans.

Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required. Take precautionary measures against static discharges. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Contents under pressure. Do not puncture or incinerate cans.

Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store locked up.

Incompatible materials Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
PROPANE 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
HEPTANE 142-82-5	STEL: 500 ppm TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m ³	IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m ³ 15 min TWA: 85 ppm TWA: 350 mg/m ³

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Respiratory protection Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid; Flammable Aerosol
Appearance White
Odor Solvent
Odor threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	> 38 °C / >100 °F	
Flash point	< -18 °C / < 0 °F	Gives a flame projection at full valve opening or flashback at any degree of valve opening
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	>1	Air = 1
Relative density	0.905-0.915	
Water solubility	Negligible	
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	
<u>Other Information</u>		
Softening point	No information available	
Molecular weight	No information available	
VOC Content (%)	24.5%	
Density	No information available	
Bulk density	No information available	

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks. Temperatures >50 °C / 122 °F.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	May cause irritation of respiratory tract.
Eye contact	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
Skin contact	Harmful in contact with skin. Prolonged contact may cause redness and irritation.

Ingestion

Harmful if swallowed. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
PROPANE 74-98-6	-	-	= 658 mg/L (Rat) 4 h
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
HEPTANE 142-82-5	-	= 3000 mg/kg (Rabbit)	= 103 g/m ³ (Rat) 4 h

Information on toxicological effects**Symptoms**

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Sensitization**

No information available.

Germ cell mutagenicity

No information available.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC 64742-52-5	A2	Group 1	-	X
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC 64741-96-4	A2	Group 1	-	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Target Organ Effects

Central nervous system, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	23833 mg/kg
ATEmix (dermal)	8006 mg/kg
ATEmix (inhalation-gas)	1824461 mg/l
ATEmix (inhalation-dust/mist)	1373 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

20 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC 64742-52-5	-	5000: 96 h Oncorhynchus mykiss mg/L LC50	1000: 48 h Daphnia magna mg/L EC50
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC 64741-96-4	-	5000: 96 h Oncorhynchus mykiss mg/L LC50	1000: 48 h Daphnia magna mg/L EC50
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT 64742-47-8	-	45: 96 h Pimephales promelas mg/L LC50 flow-through 2.2: 96 h Lepomis macrochirus mg/L LC50 static 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static	4720: 96 h Den-dronereides heteropoda mg/L LC50
HEPTANE	-	375.0: 96 h Cichlid fish mg/L LC50	10: 24 h Daphnia magna mg/L

142-82-5			EC50
----------	--	--	------

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
PROPANE 74-98-6	2.3
HEPTANE 142-82-5	4.66

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated packaging Do not reuse container.

US EPA Waste Number D001

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
HEPTANE 142-82-5	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID no 1950
Proper shipping name: Aerosols, Limited Quantity (LQ)
Hazard Class 2.1
Emergency Response Guide Number 126

IATA

UN/ID no ID 8000
Proper shipping name: Consumer commodity
Hazard Class 9
ERG Code 9L

IMDG

UN/ID no 1950
Proper shipping name: Aerosols, Limited Quantity (LQ)
Hazard Class 2
EmS-No F-D, S-U

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
ZINC OXIDE - 1314-13-2	1.0

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
PROPANE 74-98-6	X	X	X
HEPTANE 142-82-5	X	X	X
ZINC OXIDE 1314-13-2	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

A Compressed gases, B5 - Flammable aerosol, D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 3	Instability 0	-
HMIS	Health hazards 2	Flammability 3	Physical hazards 0	Personal protection B

NFPA (National Fire Protection Association)
HMIS (Hazardous Material Information System)

Revision Date 19-May-2016

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet