



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Surf City Garage Black Max

Version number: GHS 2.0  
Replaces version of: 2015-03-27 (GHS 1)

Date of compilation: 2015-04-27

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **Surf City Garage Black Max**

#### 1.1.6 Other means of identification

Product number SCG 183

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses exterior rubber dressing

#### 1.3 Details of the supplier of the safety data sheet

Surf City Garage  
5872 Engineer Dr.  
Hunting Beach, CA 92649  
Ph. 1-866-970-7872

#### 1.4 Emergency telephone number

Emergency information service **USA 1.800.535.5053, INTL 1.352.323.3500**  
24 hour emergency telephone number.

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Annex	Hazard class and category	Hazard statement code(s)
A.5	germ cell mutagenicity	Cat. 1B (Muta. 1B) H340
A.6	carcinogenicity	Cat. 1B (Carc. 1B) H350

##### Remarks

For full text of H-phrases: see SECTION 16.

#### 2.2 Label elements

##### Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

**Signal word** danger

##### Pictograms

GHS08



##### Hazard statements



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Surf City Garage Black Max

Version number: GHS 2.0  
Replaces version of: 2015-03-27 (GHS 1)

Date of compilation: 2015-04-27

H340 May cause genetic defects.  
H350 May cause cancer.

### Precautionary statements

#### Precautionary statements - prevention

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Wear protective gloves/protective clothing/eye protection/face protection.

#### Precautionary statements - response

IF exposed or concerned: get medical advice/attention.

#### Precautionary statements - storage

Store locked up.

#### Precautionary statements - disposal

Dispose of contents/container to industrial combustion plant.

**Hazardous ingredients for labelling** Stoddard Solvent

### 2.3 Other hazards

Special danger of slipping by leaking/spilling product.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

not relevant (mixture)

### 3.2 Mixtures

#### Description of the mixture

Name of substance	Identifier	Wt%	Hazard class and category		Hazard statement
petroleum distillate	CAS No 64742-82-1	< 1	B.6 A.2 A.7 A.8D A.10	Flam. Liq. 1 Skin Irrit. 2 Repr. 2 STOT SE 3 Asp. Tox. 1	H224 H315 H361f H336 H304
Stoddard Solvent	CAS No 8052-41-3	< 1	B.6 A.5 A.6 A.9 A.10	Flam. Liq. 3 Muta. 1B Carc. 1B STOT RE 1 Asp. Tox. 1	H226 H340 H350 H372 H304



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Surf City Garage Black Max

Version number: GHS 2.0  
Replaces version of: 2015-03-27 (GHS 1)

Date of compilation: 2015-04-27

Name of substance	Identifier	Wt%	Hazard class and category		Hazard statement
morpholine	CAS No 110-91-8	< 1	B.6	Flam. Liq. 3	H226
			A.10	Acute Tox. 4	H302
			A.1D	Acute Tox. 3	H311
			A.1I	Acute Tox. 4	H332
			A.2	Skin Corr. 1B	H314
			A.3	Eye Dam. 1	H318

For full text of abbreviations: see SECTION 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

##### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

##### Following inhalation

Provide fresh air.

##### Following skin contact

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.

##### Following eye contact

Irrigate copiously with clean, fresh water, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing.

##### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

water spray, alcohol resistant foam, BC-powder, carbon dioxide (CO<sub>2</sub>)

##### Unsuitable extinguishing media

water jet

#### 5.2 Special hazards arising from the substance or mixture

Explosive when mixed with combustible material.



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Surf City Garage Black Max

Version number: GHS 2.0  
Replaces version of: 2015-03-27 (GHS 1)

Date of compilation: 2015-04-27

### **Hazardous combustion products**

nitrogen oxides (NOx), carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>)

### **5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

#### **For non-emergency personnel**

Remove persons to safety.

#### **For emergency responders**

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

### **6.2 Environmental precautions**

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose it.

### **6.3 Methods and material for containment and cleaning up**

#### **Advices on how to contain a spill**

Covering of drains.

#### **Advices on how to clean up a spill**

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage (sawdust, kieselgur (diatomite), sand, universal binder).

#### **Appropriate containment techniques**

Use of adsorbent materials.

#### **Other information relating to spills and releases**

Place in appropriate containers for disposal. Ventilate affected area.

#### **Reference to other sections**

Hazardous combustion products: see section 5. Personal precautions: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Surf City Garage Black Max

Version number: GHS 2.0  
Replaces version of: 2015-03-27 (GHS 1)

Date of compilation: 2015-04-27

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

##### Recommendations

##### Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

##### Advice on general occupational hygiene

Wash hands after use. Do not to eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feeding-stuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities

##### Managing of associated risks

##### Incompatible substances or mixtures

Observe compatible storage of chemicals.

##### Control of the effects

##### Protect against external exposure, such as

frost

#### 7.3 Specific end use(s)

See section 16 for a general overview.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### National limit values

##### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Source
US	isopropyl alcohol	67-63-0	PEL	400	980			29 CFR OSHA
US	morpholine	110-91-8	PEL	20	70			29 CFR OSHA
US	stoddard solvent	8052-41-3	PEL	500	2,900			29 CFR OSHA

##### Notation

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period unless otherwise specified.

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average.



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Surf City Garage Black Max

Version number: GHS 2.0  
Replaces version of: 2015-03-27 (GHS 1)

Date of compilation: 2015-04-27

### Relevant DNELs/DMELs/PNECs and other threshold levels

No data available.

### 8.2 Exposure controls

#### Appropriate engineering controls

General ventilation.

#### Individual protection measures (personal protective equipment)

##### Eye/face protection

Wear eye/face protection.

##### Skin protection

###### • hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

###### • other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

##### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

##### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state	liquid (viscous)
Color	light blue
Odor	fresh

#### Other physical and chemical parameters

pH (value)	6.5 - 8 at 25 °C
Melting point/freezing point	not determined
Initial boiling point and boiling range	>65 °C at 1 atm
Flash point	not determined (closed cup)
Evaporation rate	not determined
Flammability (solid, gas)	not relevant (fluid)



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Surf City Garage Black Max

Version number: GHS 2.0  
Replaces version of: 2015-03-27 (GHS 1)

Date of compilation: 2015-04-27

Explosive limits	not determined
Vapor pressure	31.69 hPa at 25 °C
Density	1 - 1.2 g/cm <sup>3</sup> at 25 °C
Solubility(ies)	not determined
Partition coefficient	
n-octanol/water (log KOW)	This information is not available.
Auto-ignition temperature	not determined
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

#### 10.2 Chemical stability

See below "Conditions to avoid".

#### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

#### Physical stresses which might result in a hazardous situation and have to be avoided

strong shocks

#### 10.5 Incompatible materials

There is no additional information.

#### Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Surf City Garage Black Max

Version number: GHS 2.0  
Replaces version of: 2015-03-27 (GHS 1)

Date of compilation: 2015-04-27

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

#### Acute toxicity

Shall not be classified as acutely toxic.

#### Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	ATE
morpholine	110-91-8	oral	1,900
morpholine	110-91-8	dermal	500
morpholine	110-91-8	inhalation: vapor	11

#### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

#### Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

#### Summary of evaluation of the CMR properties

May cause genetic defects.

May cause cancer.

Shall not be classified as a reproductive toxicant.

#### Carcinogenicity

- National Toxicology Program (United States): none of the ingredients are listed
- IARC Monographs

Name of substance	Name acc. to inventory	CAS No	wt%	Classification	Remarks	Number
morpholine	Morpholine	110-91-8	0.13	3		Volume 47, 71
propan-2-ol	Isopropyl alcohol	67-63-0	0.3784	3		Volume 15, Sup 7, 71

#### Legend

3 Not classifiable as to carcinogenicity in humans.



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Surf City Garage Black Max

Version number: GHS 2.0  
Replaces version of: 2015-03-27 (GHS 1)

Date of compilation: 2015-04-27

### Specific target organ toxicity (STOT)

Shall not be classified as a specific target organ toxicant.

### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity (acute)

Shall not be classified as hazardous to the aquatic environment.

#### Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
morpholine	110-91-8	LC50	179 mg/l	fish	96 hours
morpholine	110-91-8	EC50	45 mg/l	aquatic invertebrates	48 hours

#### Aquatic toxicity (chronic)

#### Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
petroleum distillate	64742-82-1	EC50	15.41 mg/l	microorganisms	40 h
morpholine	110-91-8	EC50	12 mg/l	aquatic invertebrates	21 d

### 12.2 Process of degradability

Data are not available.

#### Degradability of components of the mixture

Name of substance	CAS No	Process	Degradation rate	Time
morpholine	110-91-8	DOC removal	93 %	25 d

### 12.3 Bioaccumulative potential

Data are not available.



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Surf City Garage Black Max

Version number: GHS 2.0  
Replaces version of: 2015-03-27 (GHS 1)

Date of compilation: 2015-04-27

### Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Stoddard Solvent	8052-41-3		7.15	
morpholine	110-91-8	0.65	-2.55	

#### 12.4 Mobility in soil

Data are not available.

#### 12.5 Results of PBT and vPvB assessment

Data are not available.

#### 12.6 Other adverse effects

Data are not available.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

##### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

##### Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### 13.3 Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

### SECTION 14: Transport information

- |      |                                     |  |
|------|-------------------------------------|--|
| 14.1 | UN number                           | (not subject to transport regulations)                                       |
| 14.2 | UN proper shipping name             | not relevant   |
| 14.3 | Transport hazard class(es)<br>Class | -  |
| 14.4 | Packing group                       | not relevant   |
| 14.5 | Environmental hazards               | none (non-environmentally hazardous acc. to the dangerous goods regulations) |



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Surf City Garage Black Max

Version number: GHS 2.0  
Replaces version of: 2015-03-27 (GHS 1)

Date of compilation: 2015-04-27

### 14.6 Special precautions for user

There is no additional information.

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

The cargo is not intended to be carried in bulk.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations specific for the product in question

#### National regulations (United States)

#### SARA TITLE III (Superfund Amendment and Reauthorization Act)

List of Extremely Hazardous Substances (40 CFR 355) (EPCRA Section 302 and 304) none of the ingredients are listed

Specific Toxic Chemical Listings (40 CFR 372) (EPCRA Section 313) none of the ingredients are listed

#### Industry or sector specific available guidance(s)

#### NPCA-HMIS® III

Hazardous Materials Identification System (American Coatings Association)

Category	Rating	Description
Chronic	*	Chronic (long-term) health effects may result from repeated overexposure.
Health	0	No significant risk to health.
Flammability	0	Materials that will not burn under typical fire conditions.
Physical hazard	0	Materials that are normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosives.
Personal protective equipment	-	

#### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States) - National Fire Protection Association (United States)

Category	Degree of hazard	Description
Flammability	1	Materials that must be preheated before ignition can occur.
Health	0	Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material.
Instability	0	Materials that are normally stable, even under fire conditions.
Special hazard		



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Surf City Garage Black Max

Version number: GHS 2.0  
Replaces version of: 2015-03-27 (GHS 1)

Date of compilation: 2015-04-27

### Right to Know Hazardous Substance List

Name of substance	CAS No	Remarks	Classifications
morpholine	110-91-8		CO F3 R1
Stoddard Solvent	8052-41-3		F2

#### Legend

CO	Corrosive.
F2	Flammable - Second Degree.
F3	Flammable - Third Degree.
R1	Reactive - First Degree.

### Proposition 65 List of chemicals

none of the ingredients are listed

### Relevant European Union (EU) safety, health and environmental provisions

#### Classification according to GHS (1272/2008/EC, CLP)

#### Hazard class

germ cell mutagenicity  
carcinogenicity

#### Category Hazard class and category

1B (Muta. 1B)  
1B (Carc. 1B)

## SECTION 16: Other information

### 16.1 Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)
15.1		List of Extremely Hazardous Substances (40 CFR 355) (EPCRA Section 302 and 304): none of the ingredients are listed
15.1		Specific Toxic Chemical Listings (40 CFR 372) (EPCRA Section 313): none of the ingredients are listed
15.1		NPCA-HMIS® III: change in the listing (table)
15.1		Right to Know Hazardous Substance List: change in the listing (table)
15.1		Proposition 65 List of chemicals: none of the ingredients are listed

### 16.2 Abbreviations and acronyms



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Surf City Garage Black Max

Version number: GHS 2.0  
Replaces version of: 2015-03-27 (GHS 1)

Date of compilation: 2015-04-27

Abbr.	Descriptions of used abbreviations
29 CFR OSHA	29 CFR §1910.1001 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
Acute Tox.	acute toxicity
Asp. Tox.	aspiration hazard
ATE	Acute Toxicity Estimate
BCF	BioConcentration Factor
BOD	Biochemical Oxygen Demand
Carc.	carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures
CMR	Carcinogenic, Mutagenic or toxic for Reproduction
COD	chemical oxygen demand
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
Eye Dam.	seriously damaging to the eye
Eye Irrit.	irritant to the eye
Flam. Liq.	flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IARC Monographs	IARC Monographs on the Evaluation of Carcinogenic Risks to Humans
log KOW	n-octanol/water
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
Muta.	germ cell mutagenicity
NFPA® 704	National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States)
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	parts per million
Repr.	reproductive toxicity
Skin Corr.	corrosive to skin
Skin Irrit.	irritant to skin
STOT RE	specific target organ toxicity - repeated exposure
STOT SE	specific target organ toxicity - single exposure



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Surf City Garage Black Max

Version number: GHS 2.0  
Replaces version of: 2015-03-27 (GHS 1)

Date of compilation: 2015-04-27

Abbr.	Descriptions of used abbreviations
vPvB	very Persistent and very Bioaccumulative

### 16.3 Key literature references and sources for data

- OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200
- 49 CFR § 172.101 Hazardous Materials Table (DOT)

### 16.4 Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards/Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### 16.5

#### List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H224	extremely flammable liquid and vapor
H226	flammable liquid and vapor
H302	harmful if swallowed
H304	may be fatal if swallowed and enters airways
H311	toxic in contact with skin
H314	causes severe skin burns and eye damage
H315	causes skin irritation
H318	causes serious eye damage
H332	harmful if inhaled
H336	may cause drowsiness or dizziness
H340	may cause genetic defects
H350	may cause cancer
H361f	suspected of damaging fertility
H372	causes damage to organs through prolonged or repeated exposure

### 16.7

#### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.