

Magic Sizing - Aerosol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations
Revision Date: 05/29/2018 Date of issue: 11/7/2017

Version: 2.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Magic Sizing & Extra Crisp - Aerosol

Product Code: 00502, 00519, 00530, 09502, 00512

1.2. Intended Use of the Product

Fabric Finish

1.3. Name, Address, and Telephone of the Responsible Party

Faultless Starch/ Bon Ami Co.

1025 W 8th St.

Kansas City, MO 64101 USA

T: 1-816-842-1230

www.faultless.com

1.4. Emergency Telephone Number

Emergency Number : 1-800-424-9300 (for emergencies) CHEMTREC

*This document is intended to be used for safety in the workplace only, and is not a consumer document.

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Classification (GHS-US)

Press. Gas (Liq.) H280

Full text of H-phrases: see section 16

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US) :



GHS04

Signal Word (GHS-US) : Warning

Hazard Statements (GHS-US) : H280 - Contains gas under pressure; may explode if heated.

Precautionary Statements (GHS-US) : P410+P403 - Protect from sunlight. Store in a well-ventilated place.

2.3. Other Hazards

No additional information available.

2.4. Unknown Acute Toxicity (GHS-US) No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable

3.2. Mixture

Name	Product Identifier	% (w/w)
Butane	(CAS No) 106-97-8	1 - 5
Propane	(CAS No) 74-98-6	0.1 - 1
Isobutane	(CAS No) 75-28-5	0.1 - 1

The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret [29 CFR 1910.1200].

A range of concentration as prescribed by the Controlled Products Regulations has been used where necessary, due to varying composition.

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Magic Sizing - Aerosol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Gently wash with plenty of soap and water followed by rinsing with water for at least 15 minutes. Call a POISON CENTER or doctor/physician if you feel unwell. Wash contaminated clothing before reuse.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Ingestion is not an anticipated route of exposure. If accidental ingestion occurs, flush mouth out with water and get medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: None expected under normal conditions of use.

Inhalation: Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Skin Contact: Prolonged exposure may cause skin irritation.

Eye Contact: Prolonged exposure to liquid may cause a mild irritation.

Ingestion: Not expected to be a primary route of exposure.

Chronic Symptoms: None expected under normal conditions of use.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂).

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Contains gas under pressure; may explode if heated.

Explosion Hazard: Pressurized container: may burst if heated.

Reactivity: Stable at ambient temperature and under normal conditions of use.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Do not allow run-off from fire fighting to enter drains or water sources. Do not breathe fumes from fires or vapors from decomposition. Closed containers exposed to heat may explode. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon dioxide, carbon monoxide and low molecular weight hydrocarbons.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all unnecessary exposure. Do not breathe vapor, mist or spray.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

6.2. Environmental Precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Ventilate area.

Methods for Cleaning Up: Stop the source of the release, if safe to do so. Consider the use of water spray to disperse vapors. Isolate the area until gas has dispersed. Ventilate and gas test area before entering.

Other information: Dispose of materials or solid residues at an authorized site.

Magic Sizing - Aerosol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

6.4. Reference to Other Sections

See Section 8, Exposure Controls and Personal Protection. See Section 13, Disposal Considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Do not puncture or incinerate container.

Precautions for Safe Handling: Keep away from heat, sparks, open flames, hot surfaces. – No smoking.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from Heat sources. Extremely high or low temperatures, Direct sunlight. Do not expose to temperatures exceeding 50°C/ 122°F. Keep in fireproof place. Protect from light.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Water reactive materials. Halogens.

Special Rules on Packaging: Keep only in the original container.

7.3. Specific End Use(s)

Fabric Finish

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Isobutane (75-28-5)		
USA ACGIH	ACGIH STEL (ppm)	1000 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	1900 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	800 ppm
Manitoba	OEL STEL (ppm)	1000 ppm
Newfoundland & Labrador	OEL STEL (ppm)	1000 ppm
Nova Scotia	OEL STEL (ppm)	1000 ppm
Ontario	OEL TWA (ppm)	800 ppm
Prince Edward Island	OEL STEL (ppm)	1000 ppm
Saskatchewan	OEL STEL (ppm)	1250 ppm
Saskatchewan	OEL TWA (ppm)	1000 ppm
Butane (106-97-8)		
Mexico	OEL TWA (mg/m ³)	1900 mg/m ³
Mexico	OEL TWA (ppm)	800 ppm
USA ACGIH	ACGIH STEL (ppm)	1000 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	1900 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	800 ppm
Alberta	OEL TWA (ppm)	1000 ppm
British Columbia	OEL STEL (ppm)	750 ppm
British Columbia	OEL TWA (ppm)	600 ppm
Manitoba	OEL STEL (ppm)	1000 ppm
New Brunswick	OEL TWA (mg/m ³)	1900 mg/m ³
New Brunswick	OEL TWA (ppm)	800 ppm
Newfoundland & Labrador	OEL STEL (ppm)	1000 ppm
Nova Scotia	OEL STEL (ppm)	1000 ppm
Nunavut	OEL STEL (mg/m ³)	2576 mg/m ³
Nunavut	OEL STEL (ppm)	1000 ppm
Nunavut	OEL TWA (mg/m ³)	1901 mg/m ³
Nunavut	OEL TWA (ppm)	800 ppm

Magic Sizing - Aerosol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Northwest Territories	OEL STEL (mg/m ³)	2576 mg/m ³
Northwest Territories	OEL STEL (ppm)	1000 ppm
Northwest Territories	OEL TWA (mg/m ³)	1901 mg/m ³
Northwest Territories	OEL TWA (ppm)	800 ppm
Ontario	OEL TWA (ppm)	800 ppm
Prince Edward Island	OEL STEL (ppm)	1000 ppm
Québec	VEMP (mg/m ³)	1900 mg/m ³
Québec	VEMP (ppm)	800 ppm
Saskatchewan	OEL STEL (ppm)	1250 ppm
Saskatchewan	OEL TWA (ppm)	1000 ppm
Yukon	OEL STEL (mg/m ³)	1600 mg/m ³
Yukon	OEL STEL (ppm)	750 ppm
Yukon	OEL TWA (mg/m ³)	1400 mg/m ³
Yukon	OEL TWA (ppm)	600 ppm
Propane (74-98-6)		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1800 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	1800 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
USA IDLH	US IDLH (ppm)	2100 ppm (10% LEL)
Alberta	OEL TWA (ppm)	1000 ppm
British Columbia	OEL TWA (ppm)	1000 ppm
Ontario	OEL TWA (ppm)	1000 ppm
Québec	VEMP (mg/m ³)	1800 mg/m ³
Québec	VEMP (ppm)	1000 ppm
Saskatchewan	OEL STEL (ppm)	1250 ppm
Saskatchewan	OEL TWA (ppm)	1000 ppm

8.2. Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Gas detectors should be used when flammable gases or vapors may be released. Ensure all national/local regulations are observed.

Personal Protective Equipment: Dust/aerosol mask. Safety glasses.



Hand Protection: None required under normal product handling conditions.

Eye Protection: Safety glasses.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

Environmental Exposure Controls: Avoid release to the environment.

Consumer Exposure Controls: Do not eat, drink or smoke during use

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Clear aerosol
Odor	: Pleasant
Odor Threshold	: Not available
pH	: 9.8
Evaporation Rate	: Not available

Magic Sizing - Aerosol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: 100 °C (212 °F)
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available
Specific Gravity	: 1.005 g/ml
Solubility	: Water: 95 - 96%
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available
Explosive Properties	: Pressurized container: may burst if heated
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Stable at ambient temperature and under normal conditions of use.
- 10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Ignition sources. Incompatible materials. Heat. Sparks. Open flame. Overheating.
- 10.5. Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers. Water reactive materials. Halogens.
- 10.6. Hazardous Decomposition Products:** Thermal decomposition generates: Carbon oxides (CO, CO₂). Low molecular weight hydrocarbon fragments.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity: Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Not classified

pH: 9.8

Serious Eye Damage/Irritation: Not classified

pH: 9.8

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: Prolonged exposure to liquid may cause a mild irritation.

Symptoms/Injuries After Ingestion: Not expected to be a primary route of exposure.

Chronic Symptoms: None expected under normal conditions of use.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Magic Sizing - Aerosol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Isobutane (75-28-5)	
LC50 Inhalation Rat	658 mg/l/4h
LC50 Inhalation Rat	11000 ppm
Butane (106-97-8)	
LC50 Inhalation Rat	30957 mg/m ³ (Exposure time: 4 h)
Propane (74-98-6)	
LC50 Inhalation Rat	658 mg/l/4h

SECTION 12: ECOLOGICAL INFORMATION

- 12.1. Toxicity** No additional information available
12.2. Persistence and Degradability Not available
12.3. Bioaccumulative Potential

Isobutane (75-28-5)	
BCF Fish 1	1.57 - 1.97
Log Pow	2.88 (at 20 °C)
Butane (106-97-8)	
Log Pow	2.89
Propane (74-98-6)	
Log Pow	2.3

- 12.4. Mobility in Soil** Not available
12.5. Other Adverse Effects Not available

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Sewage Disposal Recommendations: Do not empty into drains; dispose of this material and its container in a safe way.

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

Additional Information: Do not pressurize, cut, or weld containers.

SECTION 14: TRANSPORT INFORMATION

14.1. In Accordance with DOT

Proper Shipping Name : AEROSOLS, non-flammable, (each not exceeding 1 L capacity)
Hazard Class : 2.2
Identification Number : UN1950
Label Codes : 2.2



ERG Number : 126

Shipped under 49 CFR, Packaging Exception 173.306 - Consumer Commodities, Limited Quantities of Compressed Gases

14.2. In Accordance with IMDG

Proper Shipping Name : AEROSOLS, non-flammable
Hazard Class : 2
Division : 2.2
Identification Number : UN1950
Label Codes : 2.2
EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U



MFAG Number : 126

14.3. In Accordance with IATA

Proper Shipping Name : AEROSOLS, non-flammable
Identification Number : UN1950
Hazard Class : 2
Label Codes : 2.2
Division : 2.2



Magic Sizing - Aerosol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

ERG Code (IATA) : 2L

14.4. In Accordance with TDG

Proper Shipping Name : AEROSOLS, non-flammable

Hazard Class : 2.2

Identification Number : UN1950

Label Codes : 2.2



SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

Magic Sizing - Aerosol	
SARA Section 311/312 Hazard Classes	Sudden release of pressure hazard
Isobutane (75-28-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Butane (106-97-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Propane (74-98-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2. US State Regulations

Isobutane (75-28-5)
U.S. - Delaware - Accidental Release Prevention Regulations - Sufficient Quantities
U.S. - Delaware - Accidental Release Prevention Regulations - Threshold Quantities
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Maine - Chemicals of High Concern
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
RTK - U.S. - Massachusetts - Right To Know List
U.S. - Minnesota - Chemicals of High Concern
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - TCPA - Extraordinarily Hazardous Substances (EHS)
U.S. - Ohio - Accidental Release Prevention - Threshold Quantities
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
Butane (106-97-8)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Delaware - Accidental Release Prevention Regulations - Sufficient Quantities
U.S. - Delaware - Accidental Release Prevention Regulations - Threshold Quantities
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Maine - Chemicals of High Concern
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
RTK - U.S. - Massachusetts - Right To Know List

Magic Sizing - Aerosol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Minnesota - Chemicals of High Concern
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - TCPA - Extraordinarily Hazardous Substances (EHS)
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - Ohio - Accidental Release Prevention - Threshold Quantities
U.S. - Oregon - Permissible Exposure Limits - TWAs
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs

Propane (74-98-6)

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Delaware - Accidental Release Prevention Regulations - Sufficient Quantities
U.S. - Delaware - Accidental Release Prevention Regulations - Threshold Quantities
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
RTK - U.S. - Massachusetts - Right To Know List
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - TCPA - Extraordinarily Hazardous Substances (EHS)
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - Ohio - Accidental Release Prevention - Threshold Quantities
U.S. - Oregon - Permissible Exposure Limits - TWAs
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs

Magic Sizing - Aerosol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

15.3. Canadian Regulations

Magic Sizing - Aerosol	
WHMIS Classification	Class A - Compressed Gas
	
Isobutane (75-28-5)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas
Butane (106-97-8)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas
Propane (74-98-6)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 05/29/2018 Added Extra Crisp to name and list of SKUs.
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Press. Gas (Liq.)	Gases under pressure Liquefied gas
H280	Contains gas under pressure; may explode if heated

Party Responsible for the Preparation of This Document

Faultless Starch/ Bon Ami Co.: 1-816-842-1230 (for product information); 1-800-424-9300 (for emergencies)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS