



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 5.0
Replaces version of: 2020-10-12 (4)

Revision: 2020-10-21

SECTION 1: Identification

1.1 Product identifier

Trade name **STP Tire Fix Sealant and Inflator**
Alternative number(s) 071153190610, 071153190658

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses General use
Uses advised against Do not use for squirting or spraying. Do not use for products which come into direct contact with the skin.

1.3 Details of the supplier of the safety data sheet

Energizer Manufacturing, Inc.
25225 Detroit Rd.
Westlake OH 44145
United States

Telephone: 800-383-7323; 314-985-2000 (USA / CANADA)
Website: <http://data.energizer.com>

Energizer Trading Ltd.
Sword House, Totteridge Road, High Wycombe, HP13 6DG, UK

Telephone: +44(0)8000353376
e-mail: ConsumerServiceEU@energizer.com

1.4 Emergency telephone number

Emergency information service 1-314-985-1511 Int'l: 1-800-526-4727
This number is only available during the following office hours: Mon-Fri 09:00 AM - 05:00 PM

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.2	skin corrosion/irritation	1	Skin Corr. 1	H314
A.3	serious eye damage/eye irritation	1	Eye Dam. 1	H318
A.9	specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
B.5	gases under pressure	C	Press. Gas C	H280

STP Tire Fix Sealant and Inflator

Version number: 5.0
Replaces version of: 2020-10-12 (4)

Revision: 2020-10-21

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis. Delayed or immediate effects can be expected after short or long-term exposure. Contains gas under pressure; may explode if heated.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS04, GHS05, GHS08



- Hazard statements

H280 Contains gas under pressure; may explode if heated.
H314 Causes severe skin burns and eye damage.
H373 May cause damage to organs through prolonged or repeated exposure.

- Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P260 Do not breathe dusts or mists.
P280 Wear eye protection/face protection.
P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a poison center/doctor.
P321 Specific treatment (see on this label).
P363 Wash contaminated clothing before reuse.
P405 Store locked up.
P410+P403 Protect from sunlight. Store in a well-ventilated place.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

This material is combustible, but will not ignite readily.

Hazards not otherwise classified

Harmful to aquatic life (GHS category 3: aquatic toxicity - acute).

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

STP Tire Fix Sealant and Inflator

Version number: 5.0
Replaces version of: 2020-10-12 (4)

Revision: 2020-10-21




SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
R-134a	CAS No 811-97-2	25 – < 50	Press. Gas C / H280	
1-butoxypropan-2-ol	CAS No 5131-66-8	5 – < 10	Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Flam. Liq. 3 / H226	
sodium nitrite	CAS No 7632-00-0	< 1	Acute Tox. 3 / H301 Ox. Sol. 3 / H272	

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Thaw frosted parts with lukewarm water. Do not rub affected area.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 5.0
Replaces version of: 2020-10-12 (4)

Revision: 2020-10-21

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Contact with the product can cause burns and/or frostbite. Contains gas under pressure; may explode if heated.

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 5.0
Replaces version of: 2020-10-12 (4)

Revision: 2020-10-21

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Managing of associated risks

- Flammability hazards

Protect from sunlight.

Control of the effects

Protect against external exposure, such as

Frost

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

This information is not available.

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
R-134a	811-97-2	DNEL	13,936 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
1-butoxypropan-2-ol	5131-66-8	DNEL	147 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
1-butoxypropan-2-ol	5131-66-8	DNEL	52 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 5.0
Replaces version of: 2020-10-12 (4)

Revision: 2020-10-21

Relevant DNELs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
sodium nitrite	7632-00-0	DNEL	2 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
sodium nitrite	7632-00-0	DNEL	2 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
R-134a	811-97-2	PNEC	0.1 mg/l	aquatic organisms	freshwater	short-term (single instance)
R-134a	811-97-2	PNEC	0.01 mg/l	aquatic organisms	marine water	short-term (single instance)
R-134a	811-97-2	PNEC	73 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
R-134a	811-97-2	PNEC	0.75 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
1-butoxypropan-2-ol	5131-66-8	PNEC	0.525 mg/l	aquatic organisms	freshwater	short-term (single instance)
1-butoxypropan-2-ol	5131-66-8	PNEC	0.052 mg/l	aquatic organisms	marine water	short-term (single instance)
1-butoxypropan-2-ol	5131-66-8	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
1-butoxypropan-2-ol	5131-66-8	PNEC	2.36 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
1-butoxypropan-2-ol	5131-66-8	PNEC	0.236 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
1-butoxypropan-2-ol	5131-66-8	PNEC	0.16 mg/kg	terrestrial organisms	soil	short-term (single instance)
sodium nitrite	7632-00-0	PNEC	0.0054 mg/l	aquatic organisms	freshwater	short-term (single instance)
sodium nitrite	7632-00-0	PNEC	0.00616 mg/l	aquatic organisms	marine water	short-term (single instance)
sodium nitrite	7632-00-0	PNEC	21 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
sodium nitrite	7632-00-0	PNEC	0.0195 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 5.0
Replaces version of: 2020-10-12 (4)

Revision: 2020-10-21

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
sodium nitrite	7632-00-0	PNEC	0.0223 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
sodium nitrite	7632-00-0	PNEC	0.000733 mg/kg	terrestrial organisms	soil	short-term (single instance)
sodium nitrite	7632-00-0	PNEC	0.0054 mg/l	aquatic organisms	water	intermittent release

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear protective gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	aerosol (foam aerosol)
Color	various
Odor	characteristic



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 5.0
Replaces version of: 2020-10-12 (4)

Revision: 2020-10-21

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	100 °C
Flash point	63 °C
Evaporation rate	not determined
Flammability (solid, gas)	
Explosive limits	not determined
Vapor pressure	5.74 bar at 20 °C
Density	not determined
Vapor density	this information is not available
Relative density	information on this property is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	>743 °C (auto-ignition temperature (liquids and gases))
Viscosity	not relevant (aerosol)
Explosive properties	none
Oxidizing properties	none

9.2 Other information

Propellant content	32.52 %
Temperature class (USA, acc. to NEC 500)	T1 (maximum permissible surface temperature on the equipment: 450°C)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 5.0
Replaces version of: 2020-10-12 (4)

Revision: 2020-10-21

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Gas under pressure.

If heated:

Danger of explosion, Gas under pressure, Danger of bursting container

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

Hints to prevent fire or explosion

Protect from sunlight.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
sodium nitrite	7632-00-0	oral	100 mg/kg



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 5.0
Replaces version of: 2020-10-12 (4)

Revision: 2020-10-21

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
R-134a	811-97-2	LC50	560 mg/l	fish	24 h
R-134a	811-97-2	EC50	960 mg/l	aquatic invertebrates	24 h
1-butoxypropan-2-ol	5131-66-8	LC50	<1,000 mg/l	fish	96 h
1-butoxypropan-2-ol	5131-66-8	EC50	<320 mg/l	fish	96 h
sodium nitrite	7632-00-0	LC50	26.3 mg/l	fish	96 h
sodium nitrite	7632-00-0	EC50	15.4 mg/l	aquatic invertebrates	48 h
sodium nitrite	7632-00-0	ErC50	>100 mg/l	algae	72 h



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 5.0
Replaces version of: 2020-10-12 (4)

Revision: 2020-10-21

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Endocrine disrupting potential

None of the ingredients are listed.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1	UN number	3159
14.2	UN proper shipping name	Refrigerant gas R 134a
14.3	Transport hazard class(es)	
	Class	2.2 (gases)
14.4	Packing group	not assigned to a packing group
14.5	Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations
14.6	Special precautions for user	
		There is no additional information.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 5.0
Replaces version of: 2020-10-12 (4)

Revision: 2020-10-21

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

DOT

Transport of dangerous goods by road or rail (49 CFR US DOT)

Index number	3159
Proper shipping name	Refrigerant gas R 134a
- Particulars in the shipper's declaration	UN3159, Refrigerant gas R 134a, 2.2
- Reportable quantity (RQ)	12,300 lbs (5,584 kg) (sodium nitrite) (ammonia ... %)
Class	2.2
Danger label(s)	2.2



Special provisions (SP)	T50
ERG No	126

International Maritime Dangerous Goods Code (IMDG)

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR)

UN number	3159
Proper shipping name	Refrigerant gas R 134a
- Particulars in the shipper's declaration	UN3159, Refrigerant gas R 134a, 2.2
Class	2.2
Danger label(s)	2.2



Excepted quantities (EQ)	E1
--------------------------	----



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 5.0
Replaces version of: 2020-10-12 (4)

Revision: 2020-10-21

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) all ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings

Name of substance	CAS No	Remarks	Effective date
sodium nitrite	7632-00-0		1995-01-01

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
sodium nitrite	7632-00-0		1	100 (45,4)

Legend

1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	Name acc. to inventory	CAS No	Functional-ity	Authoritative Lists
Water		7732-18-5	solvents	
R-134a		811-97-2	propellant	
1-Butoxypropan-2-ol		5131-66-8	solvents	
Sodium nitrite		7632-00-0	preservative	
Diethylene glycol		111-46-6	solvents	



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 5.0
Replaces version of: 2020-10-12 (4)

Revision: 2020-10-21

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	Name acc. to inventory	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Thres hold	De Minimis Concentration Threshold
ammonia ... %	Ammonium hydroxide	1336-21-6				1.0 %
ammonia ... %	Ammonia	7664-41-7				1.0 %
sodium nitrite	Sodium nitrite	7632-00-0				1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	Name acc. to inventory	CAS No	References	Remarks
R-134a	1,1,1,2-Tetrafluoroethane	811-97-2	I	

Legend

I American Industrial Hygiene Association (AIHA), "Workplace Environmental Exposure Level Guides" (1992), available from AIHA

- Hazardous Substance List (NJ-RTK)

Name of substance	Name acc. to inventory	CAS No	Remarks	Classifications
ammonia ... %	ammonium hydroxide	1336-21-6		CO
sodium nitrite	sodium nitrite	7632-00-0		

Legend

CO Corrosive

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name of substance	Name acc. to inventory	CAS No	Classification
ammonia ... %	AMMONIUM HYDROXIDE ((NH ₄)(OH))	1336-21-6	E
sodium nitrite	NITROUS ACID, SODIUM SALT	7632-00-0	E

Legend

E Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	Name acc. to inventory	CAS No	References
diethylene glycol	Diethylene glycol	111-46-6	F

Legend

F Flammability (NFPA®)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 5.0
Replaces version of: 2020-10-12 (4)

Revision: 2020-10-21

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

none of the ingredients are listed

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
AU	AICS	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	all ingredients are listed



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 5.0
Replaces version of: 2020-10-12 (4)

Revision: 2020-10-21

Country	Inventory	Status
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

Legend

AICS	Australian Inventory of Chemical Substances
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
14.7	International Maritime Dangerous Goods Code (IMDG)	International Maritime Dangerous Goods Code (IMDG): Not subject to IMDG.	yes
14.7	UN number: 3159		yes
14.7	Proper shipping name: 1,1,1,2-TETRAFLUOROETHANE		yes
14.7	Particulars in the shipper's declaration: UN3159, 1,1,1,2-TETRAFLUOROETHANE, 2.2		yes



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 5.0
Replaces version of: 2020-10-12 (4)

Revision: 2020-10-21

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
14.7	Class: 2.2		yes
14.7	Marine pollutant: -		yes
14.7	Danger label(s): 2.2		yes
14.7		Danger label(s): change in the listing (table)	yes
14.7	Special provisions (SP): -		yes
14.7	Excepted quantities (EQ): E1		yes
14.7	Limited quantities (LQ): 120 mL		yes
14.7	EmS: F-C, S-V		yes
14.7	Stowage category: A		yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
49 CFR US DOT	49 CFR U.S. Department of Transportation
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 5.0
Replaces version of: 2020-10-12 (4)

Revision: 2020-10-21

Abbr.	Descriptions of used abbreviations
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LHS	Lower hazard substance
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NFPA®	National Fire Protection Association (United States)
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
Ox. Sol.	Oxidizing solid
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
Press. Gas	Gas under pressure
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 5.0
Replaces version of: 2020-10-12 (4)

Revision: 2020-10-21

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H226	Flammable liquid and vapor.
H272	May intensify fire; oxidizer.
H280	Contains gas under pressure; may explode if heated.
H301	Toxic if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.