



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix

Version number: 7.0
Replaces version of: 2020-09-15 (6)

Revision: 2020-12-15

SECTION 1: Identification

1.1 Product identifier

Trade name **STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix**
Alternative number(s) 071153185906

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses General use
Uses advised against Do not use for squirting or spraying.

1.3 Details of the supplier of the safety data sheet

Energizer Manufacturing, Inc.
25225 Detroit Rd.
Westlake OH 44145
United States

Telephone: 800-383-7323; 314-985-2000 (USA / CANADA)
Website: <http://data.energizer.com>

Energizer Trading Ltd.
Sword House, Totteridge Road, High Wycombe, HP13 6DG, UK

Telephone: +44(0)8000353376
e-mail: ConsumerServiceEU@energizer.com

1.4 Emergency telephone number

Emergency information service 1-314-985-1511 Int'l: 1-800-526-4727
This number is only available during the following office hours: Mon-Fri 09:00 AM - 05:00 PM

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.1I	acute toxicity (inhal.)	1	Acute Tox. 1	H330
A.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
A.5	germ cell mutagenicity	1B	Muta. 1B	H340
A.6	carcinogenicity	1A	Carc. 1A	H350
A.7	reproductive toxicity	2	Repr. 2	H361d

STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix

Version number: 7.0
Replaces version of: 2020-09-15 (6)

Revision: 2020-12-15

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
A.9	specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
A.10	aspiration hazard	1	Asp. Tox. 1	H304
B.6	flammable liquid	1	Flam. Liq. 1	H224

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS02, GHS06, GHS07, GHS08



- Hazard statements

- H224 Extremely flammable liquid and vapor.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H330 Fatal if inhaled.
- H336 May cause drowsiness or dizziness.
- H340 May cause genetic defects.
- H350 May cause cancer.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.

- Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/eye protection/face protection.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix

Version number: 7.0
Replaces version of: 2020-09-15 (6)

Revision: 2020-12-15

- Precautionary statements

P284	In case of inadequate ventilation wear respiratory protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P302+P352	If on skin: Wash with plenty of water.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	If inhaled: Remove person to fresh air and keep comfortable for breathing.
P320	Specific treatment is urgent (see on this label).
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P362	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with national regulations.

2.2.1.7- Hazardous ingredients for labelling

Naphtha, petroleum, full-range alkylate, toluene, Isopentane, Residual oils (petroleum), solvent-dewaxed

2.3 Other hazards

Hazards not otherwise classified

May be harmful in contact with skin (GHS category 5: acutely toxic - dermal).
Toxic to aquatic life with long lasting effects (GHS category 2: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.






SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures




Description of the mixture

Name of substance	CAS No	Wt%	Classification acc. to GHS	Pictograms
Naphtha, petroleum, full-range alkylate	64741-64-6	50 - < 75	Muta. 1B / H340 Carc. 1A / H350 Asp. Tox. 1 / H304 Flam. Liq. 1 / H224	 
Isopentane	78-78-4	10 - < 25	STOT SE 3 / H336 Asp. Tox. 1 / H304 Flam. Liq. 1 / H224	  

STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix

Version number: 7.0
Replaces version of: 2020-09-15 (6)

Revision: 2020-12-15

Name of substance	CAS No	Wt%	Classification acc. to GHS	Pictograms
toluene	108-88-3	10 - < 25	Acute Tox. 1 / H330 Skin Irrit. 2 / H315 Repr. 2 / H361d STOT SE 3 / H336 STOT RE 2 / H373 Asp. Tox. 1 / H304 Flam. Liq. 2 / H225	
Residual oils (petroleum), solvent-dewaxed	64742-62-7	< 1	Acute Tox. 4 / H332 Carc. 1B / H350	
Distillates (petroleum), hydrotreated light	64742-47-8	< 1	Acute Tox. 3 / H331 STOT SE 3 / H336 STOT RE 2 / H373 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

4.3 Indication of any immediate medical attention and special treatment needed

none



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix

Version number: 7.0
Replaces version of: 2020-09-15 (6)

Revision: 2020-12-15

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix

Version number: 7.0
Replaces version of: 2020-09-15 (6)

Revision: 2020-12-15

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Keep any substance that emits harmful vapors or gases in a place that allows these to be permanently extracted. Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix

Version number: 7.0
Replaces version of: 2020-09-15 (6)

Revision: 2020-12-15

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	toluene	108-88-3	REL	100 (10 h)	375 (10 h)	150	560				NIOSH REL
US	toluene	108-88-3	TLV®	20							ACGIH® 2019
US	toluene	108-88-3	PEL	200		500 (10 min)		300			29 CFR 1910.1000
US	toluene (toluol)	108-88-3	PEL (CA)	10	37	150	560	500			Cal/OSHA PEL
US	isopentane	78-78-4	TLV®	1,000							ACGIH® 2019

Notation

Ceiling-C
STEL

ceiling value is a limit value above which exposure should not occur
short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Biological limit values

Country	Name of agent	Parameter	Notation	Identifier	Value	Source
US	toluene	toluene		BEI®	0.02 mg/l	ACGIH® 2019
US	toluene	toluene		BEI®	0.03 mg/l	ACGIH® 2019
US	toluene	o-cresol	hydr, crea	BEI®	0.3 mg/g	ACGIH® 2019

Notation

crea
hydr

creatinine
hydrolysis



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix

Version number: 7.0
Replaces version of: 2020-09-15 (6)

Revision: 2020-12-15

Relevant DNELs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Isopentane	78-78-4	DNEL	3,000 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Isopentane	78-78-4	DNEL	432 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
toluene	108-88-3	DNEL	192 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
toluene	108-88-3	DNEL	384 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
toluene	108-88-3	DNEL	192 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
toluene	108-88-3	DNEL	384 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
toluene	108-88-3	DNEL	384 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
toluene	108-88-3	PNEC	0.68 mg/l	aquatic organisms	freshwater	short-term (single instance)
toluene	108-88-3	PNEC	0.68 mg/l	aquatic organisms	marine water	short-term (single instance)
toluene	108-88-3	PNEC	13.61 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
toluene	108-88-3	PNEC	16.39 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
toluene	108-88-3	PNEC	16.39 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
toluene	108-88-3	PNEC	2.89 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls
General ventilation.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix

Version number: 7.0
Replaces version of: 2020-09-15 (6)

Revision: 2020-12-15

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	various
Odor	characteristic

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	≥-20 °C at 101.3 kPa
Flash point	not determined
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix

Version number: 7.0
Replaces version of: 2020-09-15 (6)

Revision: 2020-12-15

Explosive limits

- Lower explosion limit (LEL)	1.1 vol%
- Upper explosion limit (UEL)	7.6 vol%
Vapor pressure	≤240 kPa at 37.8 °C
Density	not determined
Vapor density	this information is not available
Relative density	Information on this property is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	≥280 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

9.2 Other information

Temperature class (USA, acc. to NEC 500)	T2B (maximum permissible surface temperature on the equipment: 260°C)
--	---

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix

Version number: 7.0
Replaces version of: 2020-09-15 (6)

Revision: 2020-12-15

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Fatal if inhaled.

GHS of the United Nations, annex 4: May be harmful in contact with skin.

- Acute toxicity estimate (ATE)

Inhalation: gas 38.78 ppmV_{/4h}

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
toluene	108-88-3	inhalation: gas	7.6 ppmV _{/4h}
Distillates (petroleum), hydrotreated light	64742-47-8	inhalation: vapor	5.28 mg _{/l} /4h
Residual oils (petroleum), solvent-dewaxed	64742-62-7	inhalation: vapor	11 mg _{/l} /4h
Residual oils (petroleum), solvent-dewaxed	64742-62-7	inhalation: dust/mist	2.18 mg _{/l} /4h

Skin corrosion/irritation

Causes skin irritation.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix

Version number: 7.0
Replaces version of: 2020-09-15 (6)

Revision: 2020-12-15

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

May cause genetic defects.

Carcinogenicity

May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
toluene	108-88-3	3	

Legend

3 Not classifiable as to carcinogenicity in humans

Reproductive toxicity

Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Naphtha, petroleum, full-range alkylate	64741-64-6	LL50	8.2 mg/l	fish	96 h
Naphtha, petroleum, full-range alkylate	64741-64-6	EL50	4.5 mg/l	aquatic invertebrates	48 h
Isopentane	78-78-4	LL50	34.05 mg/l	fish	96 h



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix

Version number: 7.0
Replaces version of: 2020-09-15 (6)

Revision: 2020-12-15

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Isopentane	78-78-4	EL50	59.44 mg/l	aquatic invertebrates	48 h
toluene	108-88-3	LC50	5.5 mg/l	fish	96 h
toluene	108-88-3	EC50	84 mg/l	microorganisms	24 h
Distillates (petroleum), hydrotreated light	64742-47-8	LC50	>1,000 mg/l	rainbow trout (<i>Oncorhynchus mykiss</i>)	96 h
Distillates (petroleum), hydrotreated light	64742-47-8	LC50	>1,000 mg/l	goldfish (<i>Carassius auratus</i>)	72 h
Distillates (petroleum), hydrotreated light	64742-47-8	EC50	>1,000 mg/l	water flea (<i>Daphnia</i>)	48 h
Distillates (petroleum), hydrotreated light	64742-47-8	EC50	>1,000 mg/l	algae	72 h
Distillates (petroleum), hydrotreated light	64742-47-8	LL50	5 mg/l	fish	96 h
Distillates (petroleum), hydrotreated light	64742-47-8	EL50	1.4 mg/l	aquatic invertebrates	48 h
Distillates (petroleum), hydrotreated light	64742-47-8	LOEL	1 mg/l	algae	72 h
Residual oils (petroleum), solvent-dewaxed	64742-62-7	LL50	>100 mg/l	fish	96 h
Residual oils (petroleum), solvent-dewaxed	64742-62-7	EL50	>10,000 mg/l	aquatic invertebrates	24 h

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Naphtha, petroleum, full-range alkylate	64741-64-6	EL50	10 mg/l	fish	21 d
Naphtha, petroleum, full-range alkylate	64741-64-6	EC50	15.41 mg/l	microorganisms	40 h
toluene	108-88-3	LC50	3.78 mg/l	aquatic invertebrates	2 d
toluene	108-88-3	EC50	3.23 mg/l	aquatic invertebrates	7 d
toluene	108-88-3	LOEC	2.77 mg/l	fish	40 d



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix

Version number: 7.0
Replaces version of: 2020-09-15 (6)

Revision: 2020-12-15

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
toluene	108-88-3	NOEC	1.39 mg/l	fish	40 d
Distillates (petroleum), hydrotreated light	64742-47-8	EL50	0.89 mg/l	aquatic invertebrates	21 d
Distillates (petroleum), hydrotreated light	64742-47-8	LOEL	1.2 mg/l	aquatic invertebrates	21 d

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix

Version number: 7.0
Replaces version of: 2020-09-15 (6)

Revision: 2020-12-15

SECTION 14: Transport information

14.1 UN number

DOT	1203
IMDG-Code	1203
ICAO-TI	1203

14.2 UN proper shipping name

DOT	Gasoline
IMDG-Code	GASOLINE
ICAO-TI	Gasoline

14.3 Transport hazard class(es)

DOT	3
IMDG-Code	3
ICAO-TI	3

14.4 Packing group

DOT	II
IMDG-Code	II
ICAO-TI	II

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration	UN1203, Gasoline, 3, II
Reportable quantity (RQ)	5,102 lbs (2,316 kg) (toluene) (benzene)
Danger label(s)	3



Special provisions (SP)	144, 177, B1, B33, IB2, T4
-------------------------	----------------------------





Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix

Version number: 7.0
Replaces version of: 2020-09-15 (6)

Revision: 2020-12-15

ERG No	128
International Maritime Dangerous Goods Code (IMDG) - Additional information	
Particulars in the shipper's declaration	UN1203, GASOLINE, 3, II, <23°C c.c.
Marine pollutant	-
Danger label(s)	3
	
Special provisions (SP)	243
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
EmS	F-E, S-E
Stowage category	E
International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information	
Particulars in the shipper's declaration	UN1203, Gasoline, 3, II
Danger label(s)	3
	
Special provisions (SP)	A100
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) all ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings

Name of substance	CAS No	Remarks	Effective date
toluene	108-88-3		1987-01-01



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix

Version number: 7.0
Replaces version of: 2020-09-15 (6)

Revision: 2020-12-15

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
toluene	108-88-3		1 2 3 4	1000 (454)

Legend

- 1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act
- 2 "2" indicates that the source is section 307(a) of the Clean Water Act
- 3 "3" indicates that the source is section 112 of the Clean Air Act
- 4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)

Clean Air Act

Name of substance	CAS No	Type of registration	Basis for listing	Threshold quantity (lbs)
Isopentane	78-78-4	Flammable substance	g	10000

Legend

- g Volatile flammable liquid

Right to Know Hazardous Substance List

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	Name acc. to inventory	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
toluene	Toluene	108-88-3				1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	Name acc. to inventory	CAS No	References	Remarks
Isopentane	Alkanes		N	
toluene	Toluene	108-88-3	A, N, O	skin

Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix

Version number: 7.0
Replaces version of: 2020-09-15 (6)

Revision: 2020-12-15

Legend

skin If a potential for absorption from skin contact merits special consideration, the word "skin" follows the substance name.

- Hazardous Substance List (NJ-RTK)

Name of substance	Name acc. to inventory	CAS No	Remarks	Classifications
Isopentane	isopentane	78-78-4		F4
toluene	toluene (benzene, methyl-) (tolu-ol)	108-88-3		TE F3

Legend

F3 Flammable - Third Degree
F4 Flammable - Fourth Degree
TE Teratogenic

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name of substance	Name acc. to inventory	CAS No	Classification
Isopentane	BUTANE, 2-METHYL-	78-78-4	
toluene	BENZENE, METHYL-	108-88-3	E

Legend

E Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	Name acc. to inventory	CAS No	References
toluene	Methylbenzene	108-88-3	T, F

Legend

F Flammability (NFPA®)
T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
benzene	71-43-2		cancer
benzene	71-43-2		developmental, male
naphthalene	91-20-3		cancer
toluene	108-88-3		developmental



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix

Version number: 7.0
Replaces version of: 2020-09-15 (6)

Revision: 2020-12-15

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Health	4	material that, under emergency conditions, can be lethal
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
AU	AICS	all ingredients are listed
CA	DSL	all ingredients are listed
CA	NDSL	not all ingredients are listed
CN	IECSC	not all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix

Version number: 7.0
Replaces version of: 2020-09-15 (6)

Revision: 2020-12-15

Country	Inventory	Status
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	not all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

Legend

AICS	Australian Inventory of Chemical Substances
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NDSL	Non-domestic Substances List (NDSL)
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.2		- Precautionary statements: change in the listing (table)	yes
3.2		Description of the mixture: change in the listing (table)	yes
12.1		Aquatic toxicity (acute) of components of the mixture: change in the listing (table)	yes
12.1		Aquatic toxicity (chronic) of components of the mixture: change in the listing (table)	yes



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix

Version number: 7.0
Replaces version of: 2020-09-15 (6)

Revision: 2020-12-15

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
12.7	Other adverse effects	Other adverse effects: Data are not available.	yes
14.1	UN number: 1203	UN number	yes
14.1		DOT: 1203	yes
14.1		IMDG-Code: 1203	yes
14.1		ICAO-TI: 1203	yes
14.2	UN proper shipping name: Gasoline	UN proper shipping name	yes
14.2		DOT: Gasoline	yes
14.2		IMDG-Code: GASOLINE	yes
14.2		ICAO-TI: Gasoline	yes
14.3	Class: 3 (flammable liquids)		yes
14.3		DOT: 3	yes
14.3		IMDG-Code: 3	yes
14.3		ICAO-TI: 3	yes
14.4	Packing group: II (substance presenting medium danger)	Packing group	yes
14.4		DOT: II	yes
14.4		IMDG-Code: II	yes
14.4		ICAO-TI: II	yes
14.7	Index number: 1203		yes



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix

Version number: 7.0
Replaces version of: 2020-09-15 (6)

Revision: 2020-12-15

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
14.7	Proper shipping name: Gasoline		yes
14.7	Class: 3		yes
14.7	Packing group: II		yes
14.7		Danger label(s): change in the listing (table)	yes
14.7	UN number: 1203		yes
14.7	Proper shipping name: GASOLINE		yes
14.7	Class: 3		yes
14.7	Packing group: II		yes
14.7	UN number: 1203		yes
14.7	Proper shipping name: Gasoline		yes
14.7	Class: 3		yes
14.7	Packing group: II		yes
15.1		NPCA-HMIS® III: change in the listing (table)	yes
15.1		NFPA® 704: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix

Version number: 7.0
Replaces version of: 2020-09-15 (6)

Revision: 2020-12-15

Abbr.	Descriptions of used abbreviations
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ERG No	Emergency Response Guidebook - Number
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix

Version number: 7.0
Replaces version of: 2020-09-15 (6)

Revision: 2020-12-15

Abbr.	Descriptions of used abbreviations
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LHS	Lower hazard substance
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest Observed Effect Level
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
Muta.	Germ cell mutagenicity
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
NOEC	No Observed Effect Concentration
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Repr.	Reproductive toxicity
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Premium 2-Cycle Oil 50:1 Fuel Oil Pre-Mix

Version number: 7.0
Replaces version of: 2020-09-15 (6)

Revision: 2020-12-15

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H224	Extremely flammable liquid and vapor.
H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.