



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 8.0  
Replaces version of: 2020-06-09 (GHS 7)

Revision: 2020-10-21

### SECTION 1: Identification

#### 1.1 Product identifier

Trade name **Eagle One Etching Mag Wheel Cleaner**  
Alternative number(s) 079933998661, 012844040227

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Consumer uses  
Uses advised against Do not use for squirting or spraying. Do not use for products which come into direct contact with the skin.

#### 1.3 Details of the supplier of the safety data sheet

Energizer Manufacturing, Inc.  
25225 Detroit Rd.  
Westlake OH 44145  
United States

Telephone: 800-383-7323; 314-985-2000 (USA / CANADA)  
Website: <http://data.energizer.com>

Energizer Trading Ltd.  
Sword House, Totteridge Road, High Wycombe, HP13 6DG, UK

Telephone: +44(0)8000353376  
e-mail: [ConsumerServiceEU@energizer.com](mailto:ConsumerServiceEU@energizer.com)

#### 1.4 Emergency telephone number

Emergency information service 1-314-985-1511 Int'l: 1-800-526-4727  
This number is only available during the following office hours: Mon-Fri 09:00 AM - 05:00 PM

### SECTION 2: Hazard(s) identification

#### 2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.2	skin corrosion/irritation	1	Skin Corr. 1	H314
A.3	serious eye damage/eye irritation	1	Eye Dam. 1	H318
A.6	carcinogenicity	1A	Carc. 1A	H350
B.6	flammable liquid	4	Flam. Liq. 4	H227

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 8.0  
Replaces version of: 2020-06-09 (GHS 7)

Revision: 2020-10-21

Section	Hazard class	Category	Hazard class and category	Hazard statement
B.16	substance or mixture corrosive to metals	1	Met. Corr. 1	H290

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis. The product is combustible and can be ignited by potential ignition sources.

### 2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS05, GHS08



- Hazard statements

H227 Combustible liquid.  
H290 May be corrosive to metals.  
H314 Causes severe skin burns and eye damage.  
H350 May cause cancer.

- Precautionary statements

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P234 Keep only in original container.  
P260 Do not breathe dusts or mists.  
P280 Wear protective gloves/eye protection/face protection.  
P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.  
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a poison center/doctor.  
P321 Specific treatment (see on this label).  
P363 Wash contaminated clothing before reuse.  
P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.  
P390 Absorb spillage to prevent material damage.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.  
P406 Store in corrosive resistant container with a resistant inner liner.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 8.0  
Replaces version of: 2020-06-09 (GHS 7)

Revision: 2020-10-21

### 2.2.1.7 - Hazardous ingredients for labelling

sulphuric acid ... %, ammonium bifluoride, Sodium Caprylyl Sulfonate, phosphoric acid

### 2.3 Other hazards

This material is combustible, but will not ignite readily.

Hazards not otherwise classified

May be harmful if swallowed (GHS category 5: acutely toxic - oral).

Harmful to aquatic life with long lasting effects (GHS category 3: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.








## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture)

### 3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
phosphoric acid	CAS No 7664-38-2	10 - <25	Skin Corr. 1B / H314 Eye Dam. 1 / H318 Met. Corr. 1 / H290	
Sodium Caprylyl Sulfonate	CAS No 5324-84-5	1 - <5	Skin Irrit. 2 / H315 Eye Dam. 1 / H318	
ammonium bifluoride	CAS No 1341-49-7	1 - <5	Acute Tox. 3 / H301 Skin Corr. 1B / H314 Eye Dam. 1 / H318	 
sulphuric acid ... %	CAS No 7664-93-9	1 - <5	Acute Tox. 3 / H331 Skin Corr. 1A / H314 Eye Dam. 1 / H318 Carc. 1A / H350	  
C9-C11 Alcohol Ethoxylate	CAS No 68439-46-3 160901-09-7	1 - <5	Eye Irrit. 2B / H320	

For full text of abbreviations: see SECTION 16.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 8.0  
Replaces version of: 2020-06-09 (GHS 7)

Revision: 2020-10-21

### SECTION 4: First-aid measures

#### 4.1 Description of first- aid measures

##### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

##### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

##### Following skin contact

Wash with plenty of soap and water.

##### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

##### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

#### 4.3 Indication of any immediate medical attention and special treatment needed

none

### SECTION 5: Fire-fighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO<sub>2</sub>)

##### Unsuitable extinguishing media

Water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Substance or mixture corrosive to metals.

##### Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Phosphorus oxides (P<sub>x</sub>O<sub>y</sub>)



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 8.0  
Replaces version of: 2020-06-09 (GHS 7)

Revision: 2020-10-21

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 8.0  
Replaces version of: 2020-06-09 (GHS 7)

Revision: 2020-10-21

### - Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

### - Handling of incompatible substances or mixtures

#### - Keep away from

Caustic solutions

### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

## 7.2 Conditions for safe storage, including any incompatibilities

### Managing of associated risks

#### - Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

#### - Corrosive conditions

Store in corrosive resistant container with a resistant inner liner.

#### - Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

### Control of the effects

#### Protect against external exposure, such as

Frost

#### - Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

#### - Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

## 7.3 Specific end use(s)

See section 16 for a general overview.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 8.0  
Replaces version of: 2020-06-09 (GHS 7)

Revision: 2020-10-21

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
US	phosphoric acid	7664-38-2	PEL (CA)		1		3				Cal/ OSHA PEL
US	phosphoric acid	7664-38-2	REL		1 (10 h)		3				NIOSH REL
US	phosphoric acid	7664-38-2	TLV®		1		3				AC-GIH® 2019
US	phosphoric acid	7664-38-2	PEL		1						29 CFR 1910.1000
US	sulfuric acid	7664-93-9	PEL (CA)		0.1		3				Cal/ OSHA PEL
US	sulfuric acid	7664-93-9	REL		1 (10 h)						NIOSH REL
US	sulfuric acid	7664-93-9	PEL		1						29 CFR 1910.1000
US	sulfuric acid	7664-93-9	TLV®		0.2					t	AC-GIH® 2019

**Notation**

Ceiling-C  
STEL

ceiling value is a limit value above which exposure should not occur  
short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

t  
TWA

thoracic fraction  
time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Sodium Caprylyl Sulfonate	5324-84-5	DNEL	15.16 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 8.0  
Replaces version of: 2020-06-09 (GHS 7)

Revision: 2020-10-21

### Relevant DNELs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Sodium Caprylyl Sulfonate	5324-84-5	DNEL	215 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
sulphuric acid ... %	7664-93-9	DNEL	0.05 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
sulphuric acid ... %	7664-93-9	DNEL	0.1 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
C9-C11 Alcohol Ethoxylate	68439-46-3 160901-09-7	DNEL	294 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
C9-C11 Alcohol Ethoxylate	68439-46-3 160901-09-7	DNEL	2,080 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

### Relevant PNECs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
sulphuric acid ... %	7664-93-9	PNEC	0.003 mg/l	aquatic organisms	freshwater	short-term (single instance)
sulphuric acid ... %	7664-93-9	PNEC	0 mg/l	aquatic organisms	marine water	short-term (single instance)
sulphuric acid ... %	7664-93-9	PNEC	8.8 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
sulphuric acid ... %	7664-93-9	PNEC	0.002 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
sulphuric acid ... %	7664-93-9	PNEC	0.002 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
C9-C11 Alcohol Ethoxylate	68439-46-3 160901-09-7	PNEC	0.104 mg/l	aquatic organisms	freshwater	short-term (single instance)
C9-C11 Alcohol Ethoxylate	68439-46-3 160901-09-7	PNEC	0.104 mg/l	aquatic organisms	marine water	short-term (single instance)
C9-C11 Alcohol Ethoxylate	68439-46-3 160901-09-7	PNEC	1.4 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
C9-C11 Alcohol Ethoxylate	68439-46-3 160901-09-7	PNEC	13.7 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
C9-C11 Alcohol Ethoxylate	68439-46-3 160901-09-7	PNEC	13.7 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
C9-C11 Alcohol Ethoxylate	68439-46-3 160901-09-7	PNEC	1 mg/kg	terrestrial organisms	soil	short-term (single instance)



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 8.0  
Replaces version of: 2020-06-09 (GHS 7)

Revision: 2020-10-21

### 8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state	liquid
Color	colorless
Odor	Pleasant

#### Other safety parameters

pH (value)	2 - 3
Melting point/freezing point	not determined
Initial boiling point and boiling range	90.6 °C at 1,013 hPa
Flash point	70 °C



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 8.0  
Replaces version of: 2020-06-09 (GHS 7)

Revision: 2020-10-21

Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)
Explosive limits	not determined
Vapor pressure	not determined
Density	1.1 g/cm <sup>3</sup> at 20 °C
Vapor density	this information is not available
Relative density	1.1 at 20 °C (air = 1)
Solubility(ies)	not determined
Partition coefficient	
- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none
<b>9.2 Other information</b>	there is no additional information

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition. Substance or mixture corrosive to metals.

If heated:

Risk of ignition

#### 10.2 Chemical stability

See below "Conditions to avoid".

#### 10.3 Possibility of hazardous reactions

No known hazardous reactions.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 8.0  
Replaces version of: 2020-06-09 (GHS 7)

Revision: 2020-10-21

### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

### 10.5 Incompatible materials

Oxidizers

### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

#### Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if swallowed.

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
ammonium bifluoride	1341-49-7	oral	100 mg/kg
sulphuric acid ... %	7664-93-9	inhalation: vapor	3 mg/l/4h
sulphuric acid ... %	7664-93-9	inhalation: dust/mist	0.85 mg/l/4h

#### Skin corrosion/irritation

Causes severe skin burns and eye damage.

#### Serious eye damage/eye irritation

Causes serious eye damage.

#### Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

#### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 8.0  
Replaces version of: 2020-06-09 (GHS 7)

Revision: 2020-10-21

### Carcinogenicity

May cause cancer.

#### IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
sulphuric acid ... %	7664-93-9	1	

#### Legend

1 Carcinogenic to humans

#### National Toxicology Program (United States): Report on Carcinogens

Name of substance	CAS No	Classification	Number
sulphuric acid ... %	7664-93-9	Known to be a human carcinogen	9th Report on Carcinogens

### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

## SECTION 12: Ecological information

### 12.1 Toxicity

Harmful to aquatic life with long lasting effects.

#### Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
phosphoric acid	7664-38-2	EC50	>100 mg/l	aquatic invertebrates	48 h
phosphoric acid	7664-38-2	ErC50	>100 mg/l	algae	72 h
Sodium Caprylyl Sulfonate	5324-84-5	LC50	>100 mg/l	fish	96 h



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 8.0  
Replaces version of: 2020-06-09 (GHS 7)

Revision: 2020-10-21

### Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Sodium Caprylyl Sulfonate	5324-84-5	EC50	421 mg/l	aquatic invertebrates	48 h
Sodium Caprylyl Sulfonate	5324-84-5	ErC50	>100 mg/l	algae	72 h
sulphuric acid ... %	7664-93-9	LC50	16 – 28 mg/l	bluegill (Lepomis macrochirus)	96 h
sulphuric acid ... %	7664-93-9	EC50	>100 mg/l	aquatic invertebrates	48 h
sulphuric acid ... %	7664-93-9	ErC50	>100 mg/l	algae	72 h
C9-C11 Alcohol Ethoxylate	68439-46-3 160901-09-7	LC50	7 mg/l	fish	96 h
C9-C11 Alcohol Ethoxylate	68439-46-3 160901-09-7	EC50	2.5 mg/l	aquatic invertebrates	48 h

### Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
phosphoric acid	7664-38-2	EC50	>1,000 mg/l	microorganisms	3 h
C9-C11 Alcohol Ethoxylate	68439-46-3 160901-09-7	EC50	140 mg/l	microorganisms	3 h

#### 12.2 Persistence and degradability

Data are not available.

#### 12.3 Bioaccumulative potential

Data are not available.

#### 12.4 Mobility in soil

Data are not available.

#### 12.5 Results of PBT and vPvB assessment

Data are not available.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 8.0  
Replaces version of: 2020-06-09 (GHS 7)

Revision: 2020-10-21

### 12.6 Other adverse effects

Endocrine disrupting potential  
None of the ingredients are listed.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Waste treatment-relevant information  
Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

## SECTION 14: Transport information

14.1	<b>UN number</b>	3264
14.2	<b>UN proper shipping name</b>	Corrosive liquid, acidic, inorganic, n.o.s.
	Technical name (hazardous ingredients)	phosphoric acid, ammonium bifluoride
14.3	<b>Transport hazard class(es)</b>	
	Class	8 (corrosive substances)
14.4	<b>Packing group</b>	III (substance presenting low danger)
14.5	<b>Environmental hazards</b>	non-environmentally hazardous acc. to the dangerous goods regulations
14.6	<b>Special precautions for user</b>	
	There is no additional information.	
14.7	<b>Transport in bulk according to Annex II of MARPOL and the IBC Code</b>	
	The cargo is not intended to be carried in bulk.	

### Information for each of the UN Model Regulations

DOT



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 8.0  
Replaces version of: 2020-06-09 (GHS 7)

Revision: 2020-10-21

### Transport of dangerous goods by road or rail (49 CFR US DOT)

Index number	3264
Proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s.
- Particulars in the shipper's declaration	UN3264, Corrosive liquid, acidic, inorganic, n.o.s., (contains: phosphoric acid, ammonium bifluoride), 8, III
- Reportable quantity (RQ)	4,065 lbs (1,846 kg) (ammonium bifluoride) (phosphoric acid)
Class	8
Packing group	III
Danger label(s)	8



Special provisions (SP)	IB3, T7, TP1, TP28
ERG No	154

### International Maritime Dangerous Goods Code (IMDG)

UN number	3264
Proper shipping name	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
- Particulars in the shipper's declaration	UN3264, CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S., (contains: phosphoric acid, ammonium bifluoride), 8, III
Class	8
Marine pollutant	-
Packing group	III
Danger label(s)	8



Special provisions (SP)	223, 274
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-A, S-B
Stowage category	A
Segregation group	1 - Acids



# Safety Data Sheet


acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 8.0  
Replaces version of: 2020-06-09 (GHS 7)

Revision: 2020-10-21

### International Civil Aviation Organization (ICAO-IATA/DGR)

UN number	3264
Proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s.
- Particulars in the shipper's declaration	UN3264, Corrosive liquid, acidic, inorganic, n.o.s., (contains: phosphoric acid, ammonium bifluoride), 8, III
Class	8
Packing group	III
Danger label(s)	8
	
Special provisions (SP)	A3
Excepted quantities (EQ)	E1
Limited quantities (LQ)	1 L

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations specific for the product in question

##### National regulations (United States)

**Toxic Substance Control Act (TSCA)** all ingredients are listed

##### Superfund Amendment and Reauthorization Act (SARA TITLE III )

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

The List of Extremely Hazardous Substances and Their Threshold Planning Quantities				
Name of substance	CAS No	Notes	Reportable quantity (pounds)	Threshold planning quantity (pounds)
sulphuric acid ... %	7664-93-9		1,000	1000

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings			
Name of substance	CAS No	Remarks	Effective date
sulphuric acid ... %	7664-93-9	acid aerosols including mists, vapors, gas, fog, and other airborne forms of any particle size	1987-01-01



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 8.0  
Replaces version of: 2020-06-09 (GHS 7)

Revision: 2020-10-21

### Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
sulphuric acid ... %	7664-93-9		1	1000 (454)
ammonium bifluoride	1341-49-7		1	100 (45,4)
phosphoric acid	7664-38-2		1	5000 (2270)

Legend

1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act

### Clean Air Act

none of the ingredients are listed

### Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	Name acc. to inventory	CAS No	Functional-ity	Authoritative Lists
Water		7732-18-5	solvents	
Phosphoric acid	Phosphoric acid	7664-38-2	cleaning agent	OEHHA RELS
Sodium Caprylyl Sulfonate		5324-84-5	surfactant	
Ammonium bifluoride		1341-49-7	cleaning agent	
Sulphuric acid ... %	Sulfuric Acid	7664-93-9	pH Adjuster	IARC Carcinogens - 1 NTP 13th RoC - known OEHHA RELS Prop 65
C9-C11 Alcohol Ethoxylate		68439-46-3 160901-09-7	surfactant	
Sodium alkyl sulfate		trade secret	stabilizer	
Quaternary coco alkylamine ethoxylate		61791-10-4	emulsifier	
Isopropyl alcohol	Isopropanol	67-63-0	diluent	OEHHA RELS
2-Aminoethanol		141-43-5	pH Adjuster	
Prop-2-yn-1-ol		107-19-7	fragrance	



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 8.0  
Replaces version of: 2020-06-09 (GHS 7)

Revision: 2020-10-21

### - Toxic or Hazardous Substance List (MA-TURA)

Name of substance	Name acc. to inventory	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Thres hold	De Minimis Concentration Threshold
sulphuric acid ... %	Sulfuric acid	7664-93-9				1.0 %
ammonium bifluoride	Ammonium bifluoride	1341-49-7				1.0 %
ammonium bifluoride	Ammonia	7664-41-7				1.0 %
phosphoric acid	Phosphoric acid	7664-38-2				1.0 %

### - Hazardous Substances List (MN-ERTK)

Name of substance	Name acc. to inventory	CAS No	References	Remarks
sulphuric acid ... %	Sulfuric acid	7664-93-9	A, N, O	
phosphoric acid	Phosphoric acid	7664-38-2	A, O	

#### Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

### - Hazardous Substance List (NJ-RTK)

Name of substance	Name acc. to inventory	CAS No	Remarks	Classifications
sulphuric acid ... %	sulfuric acid	7664-93-9		CA CO R2
ammonium bifluoride	ammonium bifluoride	1341-49-7		CO
phosphoric acid	phosphoric acid	7664-38-2		CO

#### Legend

- CA Carcinogenic
- CO Corrosive
- R2 Reactive - Second Degree



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 8.0  
Replaces version of: 2020-06-09 (GHS 7)

Revision: 2020-10-21

### - Hazardous Substance List (Chapter 323) (PA-RTK)

Name of substance	Name acc. to inventory	CAS No	Classification
sulphuric acid ... %	SULFURIC ACID	7664-93-9	E
ammonium bifluoride	AMMONIUM FLUORIDE ((NH <sub>4</sub> )(HF <sub>2</sub> ))	1341-49-7	E
phosphoric acid	PHOSPHORIC ACID	7664-38-2	E

#### Legend

E Environmental hazard

### - Hazardous Substance List (RI-RTK)

Name of substance	Name acc. to inventory	CAS No	References
sulphuric acid ... %	Sulfuric acid	7664-93-9	T, F
phosphoric acid	Orthophosphoric acid	7664-38-2	T, F

#### Legend

F Flammability (NFPA®)  
T Toxicity (ACGIH®)

### California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

none of the ingredients are listed

### Industry or sector specific available guidance(s)

#### NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

#### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 8.0  
Replaces version of: 2020-06-09 (GHS 7)

Revision: 2020-10-21

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

### National inventories

Country	Inventory	Status
AU	AICS	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

#### Legend

AICS	Australian Inventory of Chemical Substances
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 8.0  
Replaces version of: 2020-06-09 (GHS 7)

Revision: 2020-10-21

### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information, including date of preparation or last revision

#### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
3.2		Description of the mixture: change in the listing (table)	yes
8.1		Relevant DNELs of components of the mixture: change in the listing (table)	yes
8.1		Relevant PNECs of components of the mixture: change in the listing (table)	yes
9.2	Other information	other information: there is no additional information	yes
9.2	Solvent content: 82.71 %		yes
9.2	Solid content: 17.29 %		yes
12.1		Aquatic toxicity (acute) of components of the mixture: change in the listing (table)	yes
12.1		Aquatic toxicity (chronic) of components of the mixture: change in the listing (table)	yes
15.1		Cleaning Product Right to Know Act Substance List (CA-RTK): change in the listing (table)	yes
15.1		Toxic or Hazardous Substance List (MA-TURA): change in the listing (table)	yes
15.1		Hazardous Substances List (MN-ERTK): change in the listing (table)	yes
15.1		Hazardous Substance List (NJ-RTK): change in the listing (table)	yes
15.1		Hazardous Substance List (Chapter 323) (PA-RTK): change in the listing (table)	yes
15.1		Hazardous Substance List (RI-RTK): change in the listing (table)	yes



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 8.0  
Replaces version of: 2020-06-09 (GHS 7)

Revision: 2020-10-21

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: <a href="http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement">http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement</a>
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IATA	International Air Transport Association



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 8.0  
Replaces version of: 2020-06-09 (GHS 7)

Revision: 2020-10-21

Abbr.	Descriptions of used abbreviations
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LHS	Lower hazard substance
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
Met. Corr.	Substance or mixture corrosive to metals
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
TLV®	Threshold Limit Values
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

### Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 8.0  
Replaces version of: 2020-06-09 (GHS 7)

Revision: 2020-10-21

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H227	Combustible liquid.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H320	Causes eye irritation.
H331	Toxic if inhaled.
H350	May cause cancer.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.