



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Eagle One All WHEEL & TIRE CLEANER Aerosol

Version number: 4.0
Replaces version of: 2020-10-12 (3)

Revision: 2020-10-21

SECTION 1: Identification

1.1 Product identifier

Trade name **Eagle One All WHEEL & TIRE CLEANER Aerosol**
Alternative number(s) 012844040067, 012844686272

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Consumer uses

1.3 Details of the supplier of the safety data sheet

Energizer Manufacturing, Inc.
25225 Detroit Rd.
Westlake OH 44145
United States

Telephone: 800-383-7323; 314-985-2000 (USA / CANADA)
Website: <http://data.energizer.com>

Energizer Trading Ltd.
Sword House, Totteridge Road, High Wycombe, HP13 6DG, UK

Telephone: +44(0)8000353376
e-mail: ConsumerServiceEU@energizer.com

1.4 Emergency telephone number

Emergency information service 1-314-985-1511 Int'l: 1-800-526-4727
This number is only available during the following office hours: Mon-Fri 09:00 AM - 05:00 PM

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
A.3	serious eye damage/eye irritation	1	Eye Dam. 1	H318
A.9	specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
B.3	flammable aerosol	2	Flam. Aerosol 2	H223
B.5	gases under pressure	D	Press. Gas D	H280

For full text of abbreviations: see SECTION 16.

Eagle One All WHEEL & TIRE CLEANER Aerosol

Version number: 4.0
Replaces version of: 2020-10-12 (3)

Revision: 2020-10-21

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. Contains gas under pressure; may explode if heated.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS02, GHS04, GHS05,
GHS08



- Hazard statements

H223	Flammable aerosol.
H280	Contains gas under pressure; may explode if heated.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H373	May cause damage to organs through prolonged or repeated exposure.

- Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P280	Wear protective gloves.
P302+P352	If on skin: Wash with plenty of water.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a poison center/doctor.
P321	Specific treatment (see on this label).
P362	Take off contaminated clothing and wash it before reuse.
P410+P403	Protect from sunlight. Store in a well-ventilated place.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

2.2.1.7- Hazardous ingredients for labelling

Alcohols, C6-12, ethoxylated, Tetrasodium ethylenediamine tetraacetate

Eagle One All WHEEL & TIRE CLEANER Aerosol

Version number: 4.0
Replaces version of: 2020-10-12 (3)

Revision: 2020-10-21

2.3 Other hazards

Hazards not otherwise classified

May be harmful if swallowed (GHS category 5: acutely toxic - oral).
Harmful to aquatic life (GHS category 3: aquatic toxicity - acute).

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.







SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Alcohols, C6-12, ethoxylated	CAS No 68439-45-2	10 - < 25	Acute Tox. 4 / H302 Eye Dam. 1 / H318	
Sodium xylenesulphonate	CAS No 1300-72-7	10 - < 25	Eye Irrit. 2 / H319	
Tetrasodium ethylene-diamine tetraacetate	CAS No 64-02-8	1 - < 5	Acute Tox. 4 / H302 Acute Tox. 4 / H332 Eye Dam. 1 / H318	
Sodium metasilicate pentahydrate	CAS No 10213-79-3	1 - < 5	Skin Corr. 1B / H314 STOT SE 3 / H335 Met. Corr. 1 / H290	
butane (containing ≥ 0,1 % butadiene (203-450-8))	CAS No 106-97-8	1 - < 5	Flam. Gas 1 / H220 Press. Gas C / H280	
propane	CAS No 74-98-6	1 - < 5	sA / OSHA002 Flam. Gas 1 / H220 Press. Gas C / H280	

For full text of abbreviations: see SECTION 16.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Eagle One All WHEEL & TIRE CLEANER Aerosol

Version number: 4.0
Replaces version of: 2020-10-12 (3)

Revision: 2020-10-21

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Thaw frosted parts with lukewarm water. Do not rub affected area.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Contact with the product can cause burns and/or frostbite. Contains gas under pressure; may explode if heated.

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Eagle One All WHEEL & TIRE CLEANER Aerosol

Version number: 4.0
Replaces version of: 2020-10-12 (3)

Revision: 2020-10-21

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Managing of associated risks

- Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight.

Control of the effects

Protect against external exposure, such as

Frost



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Eagle One All WHEEL & TIRE CLEANER Aerosol

Version number: 4.0
Replaces version of: 2020-10-12 (3)

Revision: 2020-10-21

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	butane	106-97-8	PEL (CA)	800	1,900						Ca/ OSHA PEL
US	n-butane	106-97-8	REL	800 (10 h)	1,900 (10 h)						NIOSH REL
US	n-butane	106-97-8	TLV®			1,000				E	AC-GIH® 2019
US	propane	74-98-6	PEL (CA)	1,000	1,800						Ca/ OSHA PEL
US	propane	74-98-6	REL	1,000 (10 h)	1,800 (10 h)						NIOSH REL
US	propane	74-98-6	PEL	1,000	1,800						29 CFR 1910.1000
US	propane	74-98-6	TLV®							oxygen, Simple Asp., E	AC-GIH® 2019

Notation

Ceiling-C	ceiling value is a limit value above which exposure should not occur
E	explosive
oxygen	Adequate oxygen delivery to the tissues is necessary for sustaining life
Simple Asp.	simple asphyxiants
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Eagle One All WHEEL & TIRE CLEANER Aerosol

Version number: 4.0
Replaces version of: 2020-10-12 (3)

Revision: 2020-10-21

Relevant DNELs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Sodium xylenesulphonate	1300-72-7	DNEL	26.9 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Sodium xylenesulphonate	1300-72-7	DNEL	136.3 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Tetrasodium ethylenediamine tetraacetate	64-02-8	DNEL	1.5 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
Tetrasodium ethylenediamine tetraacetate	64-02-8	DNEL	3 mg/m ³	human, inhalatory	worker (industry)	acute - local effects

Relevant PNECs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Sodium xylenesulphonate	1300-72-7	PNEC	0.23 mg/l	aquatic organisms	freshwater	short-term (single instance)
Sodium xylenesulphonate	1300-72-7	PNEC	0.023 mg/l	aquatic organisms	marine water	short-term (single instance)
Sodium xylenesulphonate	1300-72-7	PNEC	2.3 mg/l	aquatic organisms	water	intermittent release
Sodium xylenesulphonate	1300-72-7	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Sodium xylenesulphonate	1300-72-7	PNEC	0.862 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Sodium xylenesulphonate	1300-72-7	PNEC	0.086 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Sodium xylenesulphonate	1300-72-7	PNEC	0.037 mg/kg	terrestrial organisms	soil	short-term (single instance)
Tetrasodium ethylenediamine tetraacetate	64-02-8	PNEC	1.2 mg/l	aquatic organisms	water	intermittent release
Tetrasodium ethylenediamine tetraacetate	64-02-8	PNEC	2.2 mg/l	aquatic organisms	freshwater	short-term (single instance)
Tetrasodium ethylenediamine tetraacetate	64-02-8	PNEC	0.22 mg/l	aquatic organisms	marine water	short-term (single instance)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Eagle One All WHEEL & TIRE CLEANER Aerosol

Version number: 4.0
Replaces version of: 2020-10-12 (3)

Revision: 2020-10-21

Relevant PNECs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Tetrasodium ethylenediamine tetraacetate	64-02-8	PNEC	43 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Tetrasodium ethylenediamine tetraacetate	64-02-8	PNEC	0.72 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear protective gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

During spraying wear suitable respiratory equipment.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	aerosol (spray aerosol)
Color	clear
Odor	characteristic



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Eagle One All WHEEL & TIRE CLEANER Aerosol

Version number: 4.0
Replaces version of: 2020-10-12 (3)

Revision: 2020-10-21

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	-161.5 °C at 1,013 hPa
Flash point	not determined
Evaporation rate	not determined
Flammability (solid, gas)	flammable aerosol in accordance with GHS criteria

Explosive limits

- Lower explosion limit (LEL)	5 vol%
- Upper explosion limit (UEL)	15 vol%

Vapor pressure	0 hPa at 25 °C
Density	not determined
Vapor density	this information is not available
Relative density	information on this property is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
-----------------------------	-----------------------------------

Auto-ignition temperature	
Viscosity	not relevant (aerosol)
Explosive properties	none
Oxidizing properties	none

9.2 Other information

Propellant content	5 %
--------------------	-----



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Eagle One All WHEEL & TIRE CLEANER Aerosol

Version number: 4.0
Replaces version of: 2020-10-12 (3)

Revision: 2020-10-21

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Gas under pressure. Risk of ignition.

If heated:

Danger of explosion, Gas under pressure, Danger of bursting container

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if swallowed.

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
Alcohols, C6-12, ethoxylated	68439-45-2	oral	500 mg/kg



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Eagle One All WHEEL & TIRE CLEANER Aerosol

Version number: 4.0
Replaces version of: 2020-10-12 (3)

Revision: 2020-10-21

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
Tetrasodium ethylenediamine tetraacetate	64-02-8	oral	1,913 mg/kg
Tetrasodium ethylenediamine tetraacetate	64-02-8	inhalation: dust/mist	1.5 mg/l/4h

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Sodium xylenesulphonate	1300-72-7	LC50	>1,000 mg/l	fish	96 h



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Eagle One All WHEEL & TIRE CLEANER Aerosol

Version number: 4.0
Replaces version of: 2020-10-12 (3)

Revision: 2020-10-21

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Sodium xylenesulphonate	1300-72-7	EC50	>1,000 mg/l	aquatic invertebrates	48 h
Tetrasodium ethylenediamine tetraacetate	64-02-8	LC50	41 mg/l	fish	96 h
Tetrasodium ethylenediamine tetraacetate	64-02-8	EC50	140 mg/l	aquatic invertebrates	48 h
butane (containing ≥ 0,1 % butadiene (203-450-8))	106-97-8	LC50	49.9 mg/l	fish	96 h
butane (containing ≥ 0,1 % butadiene (203-450-8))	106-97-8	EC50	19.37 mg/l	algae	96 h
propane	74-98-6	LC50	49.9 mg/l	fish	96 h
propane	74-98-6	EC50	19.37 mg/l	algae	96 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Endocrine disrupting potential

None of the ingredients are listed.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Eagle One All WHEEL & TIRE CLEANER Aerosol

Version number: 4.0
Replaces version of: 2020-10-12 (3)

Revision: 2020-10-21

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.



SECTION 14: Transport information

14.1 UN number	1950
14.2 UN proper shipping name	Aerosols
14.3 Transport hazard class(es)	
Class	2.1 (gases) (aerosol) (flammable)
Subsidiary risk(s)	8 (corrosive effects)
14.4 Packing group	not assigned to a packing group
14.5 Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations
14.6 Special precautions for user	
There is no additional information.	
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code	
The cargo is not intended to be carried in bulk.	

Information for each of the UN Model Regulations

DOT

Transport of dangerous goods by road or rail (49 CFR US DOT)

Index number	1950
Proper shipping name	Aerosols
- Particulars in the shipper's declaration	UN1950, Aerosols, 2.1 (8)
Class	2.1
Subsidiary risk(s)	8
Danger label(s)	2.1+8
 	
Special provisions (SP)	N82
ERG No	126



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Eagle One All WHEEL & TIRE CLEANER Aerosol

Version number: 4.0
Replaces version of: 2020-10-12 (3)

Revision: 2020-10-21

International Maritime Dangerous Goods Code (IMDG)

UN number	1950
Proper shipping name	AEROSOLS
- Particulars in the shipper's declaration	UN1950, AEROSOLS, 2.1 (8)
Class	2.1
Subsidiary risk(s)	8
Marine pollutant	-
Danger label(s)	2.1+8



Special provisions (SP)	63, 190, 277, 327, 344, 381, 959
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
EmS	F-D, S-U
Stowage category	-

International Civil Aviation Organization (ICAO-IATA/DGR)

UN number	1950
Proper shipping name	Aerosols, flammable, containing substances in class 8, packing group III
- Particulars in the shipper's declaration	UN1950, Aerosols, flammable, containing substances in class 8, packing group III, 2.1 (8)
Class	2.1
Subsidiary risk(s)	8
Danger label(s)	2.1+8



Special provisions (SP)	A145, A167
Excepted quantities (EQ)	E0
Limited quantities (LQ)	30 kg



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Eagle One All WHEEL & TIRE CLEANER Aerosol

Version number: 4.0
Replaces version of: 2020-10-12 (3)

Revision: 2020-10-21

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA)

all ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

none of the ingredients are listed

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

none of the ingredients are listed

Clean Air Act

Name of substance	CAS No	Type of registration	Basis for listing	Threshold quantity (lbs)
propane	74-98-6	Flammable substance	f	10000
butane (containing $\geq 0,1$ % butadiene (203-450-8))	106-97-8	Flammable substance	f	10000

Legend

f Flammable gas.

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	Name acc. to inventory	CAS No	Functionality	Authoritative Lists
Water		7732-18-5	solvents	
Sodium xylenesulphonate		1300-72-7	surfactant	
Alcohols, C6-12, ethoxylated		68439-45-2	surfactant	
Tetrasodium ethylenediamine tetraacetate		64-02-8	chelating agent	
Sodium metasilicate pentahydrate		10213-79-3	cleaning agent	
Propane		74-98-6	propellant	



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Eagle One All WHEEL & TIRE CLEANER Aerosol

Version number: 4.0
Replaces version of: 2020-10-12 (3)

Revision: 2020-10-21

Name of substance	Name acc. to inventory	CAS No	Functional-ity	Authoritative Lists
Butane (containing $\geq 0,1$ % butadiene (203-450-8))	Butane (containing = 0,1 % butadiene (203-450-8))	106-97-8	propellant	EC Annex VI CMRs - Cat. 1A EC Annex VI CMRs - Cat. 1B

- Toxic or Hazardous Substance List (MA-TURA)

none of the ingredients are listed

- Hazardous Substances List (MN-ERTK)

Name of substance	Name acc. to inventory	CAS No	References	Remarks
propane	Propane	74-98-6	A, O	
propane	Alkanes		N	
propane	Gases, Simple Asphyxiants		A	gases
butane (containing $\geq 0,1$ % butadiene (203-450-8))	Alkanes		N	

Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- gases Refers to displacement of air asphyxiation hazard.
- N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

- Hazardous Substance List (NJ-RTK)

Name of substance	Name acc. to inventory	CAS No	Remarks	Classifications
propane	propane	74-98-6		F4
butane (containing $\geq 0,1$ % butadiene (203-450-8))	butane	106-97-8		F4

Legend

- F4 Flammable - Fourth Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name of substance	Name acc. to inventory	CAS No	Classification
propane	PROPANE	74-98-6	
butane (containing $\geq 0,1$ % butadiene (203-450-8))	BUTANE	106-97-8	



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Eagle One All WHEEL & TIRE CLEANER Aerosol

Version number: 4.0
Replaces version of: 2020-10-12 (3)

Revision: 2020-10-21

- Hazardous Substance List (RI-RTK)

Name of substance	Name acc. to inventory	CAS No	References
propane	liquefied petroleum gas	74-98-6	T
butane (containing $\geq 0,1$ % butadiene (203-450-8))	Butane	106-97-8	T, F

Legend

F Flammability (NFPA®)
T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

none of the ingredients are listed

Proposition 65 List of chemicals

Name acc. to inventory	CAS No	Remarks	Type of the toxicity
ethylene oxide	75-21-8		developmental, male

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	4	material that rapidly or completely vaporizes at atmospheric pressure and normal ambient temperature or that is readily dispersed in air and burn readily
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Eagle One All WHEEL & TIRE CLEANER Aerosol

Version number: 4.0
Replaces version of: 2020-10-12 (3)

Revision: 2020-10-21

Category	Degree of hazard	Description
Flammability	4	material that rapidly or completely vaporizes at atmospheric pressure and normal ambient temperature or that is readily dispersed in air and burn readily
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
AU	AICS	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

Legend

AICS	Australian Inventory of Chemical Substances
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Eagle One All WHEEL & TIRE CLEANER Aerosol

Version number: 4.0
Replaces version of: 2020-10-12 (3)

Revision: 2020-10-21

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
3.2		Description of the mixture: change in the listing (table)	yes
8.1		Relevant PNECs of components of the mixture: change in the listing (table)	yes
12.1		Aquatic toxicity (acute) of components of the mixture: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Eagle One All WHEEL & TIRE CLEANER Aerosol

Version number: 4.0
Replaces version of: 2020-10-12 (3)

Revision: 2020-10-21

Abbr.	Descriptions of used abbreviations
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Gas	Flammable gas
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
Met. Corr.	Substance or mixture corrosive to metals
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Press. Gas	Gas under pressure
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
sA	Simple asphyxiants
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Eagle One All WHEEL & TIRE CLEANER Aerosol

Version number: 4.0
Replaces version of: 2020-10-12 (3)

Revision: 2020-10-21

Abbr.	Descriptions of used abbreviations
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H220	Extremely flammable gas.
H223	Flammable aerosol.
H280	Contains gas under pressure; may explode if heated.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
OSHA002	May displace oxygen and cause rapid suffocation.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Eagle One All WHEEL & TIRE CLEANER Aerosol

Version number: 4.0
Replaces version of: 2020-10-12 (3)

Revision: 2020-10-21

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.