



Power Out Odor-X Blast Air & Fabric Refresher

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

US GHS SDS

Revision Date: 08/26/2020

Date of Issue: 08/26/2020

Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Power Out Odor-X Blast Air & Fabric Refresher

Product Code: 50942

Formulation Identification Number: 40551

1.2. Intended Use of the Product

Use of the Substance/Mixture: Air Freshener (Liquid / Pump Spray)

1.3. Name, Address, and Telephone of the Responsible Party

Manufacturer

Turtle Wax, Inc.

2250 W. Pinehurst Blvd., Suite 150

Addison, IL 60101-6103

Phone Number: 1(630)455-3700

Toll-Free Number: 1(800)887-8539

1.4. Emergency Telephone Number

Emergency Number : CHEMTREC

Within USA and Canada: 1-800-424-9300 or +1-703-527-3887 (collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Flam. Aerosol 1 H222

Press. Gas (Comp.) H280

Skin Sens. 1 H317

Simple Asphy

Aquatic Acute 3 H402

Aquatic Chronic 3 H412

Full text of hazard classes and H-statements : see section 16

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H222 - Extremely flammable aerosol.
H280 - Contains gas under pressure; may explode if heated.
H317 - May cause an allergic skin reaction.
H402 - Harmful to aquatic life.
H412 - Harmful to aquatic life with long lasting effects.
May displace oxygen and cause rapid suffocation.

Precautionary Statements (GHS-US)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Pressurized container: Do not pierce or burn, even after use.
P261 - Avoid breathing vapors, mist, or spray.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, and eye protection.
P302+P352 - If on skin: Wash with plenty of water.
P321 - Specific treatment (see section 4 on this SDS).

Power Out Odor-X Blast Air & Fabric Refresher

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P363 - Wash contaminated clothing before reuse.

P410+P403 - Protect from sunlight. Store in a well-ventilated place.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions. Contact with gas escaping the container can cause frostbite.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Synonyms	Product Identifier	%	GHS US classification
1,1-Difluoroethane	Ethane, 1,1-difluoro- / Ethylidene difluoride / Fluorocarbon 152a / Freon	(CAS-No.) 75-37-6	80 - 100	Simple Asphy Flam. Gas 1, H220 Press. Gas (Liq.), H280
Isopropyl alcohol	2-Hydroxypropane / 2-Propyl alcohol / 2-Propanol	(CAS-No.) 67-63-0	3.9 – 5.2	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Ethanone, 1-(1,2,3,4,5,6,7,8-octahydro-2,3,8,8-tetramethyl-2-naphthyl)-	1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthyl)ethan-1-one / 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone / OTNE	(CAS-No.) 54464-57-2	0.8 – 1.2	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Aquatic Acute 2, H401 Aquatic Chronic 1, H410
Terpenes and Terpenoids, sweet orange-oil	Orange oil terpenes / Orange oil, terpenes / Terpenes and terpenoids, orange oil	(CAS-No.) 68647-72-3	0.04 – 0.1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl-	2,6-Di-tert-butyl-p-cresol / BHT / 2,6-Bis(1,1-dimethylethyl)-4-methylphenol	(CAS-No.) 128-37-0	≤ 0.01	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Comb. Dust
Benzyl alcohol	Benzenecarbinol / Benzenemethanol / Methanol, phenyl-	(CAS-No.) 100-51-6	≤ 0.004	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Eye Irrit. 2A, H319 Aquatic Acute 2, H401
Citral	3,7-Dimethyl-2,6-octadienal / 2,6-Octadienal, 3,7-dimethyl- / CITRAL	(CAS-No.) 5392-40-5	≤ 0.004	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1B, H317 Aquatic Acute 2, H401

Full text of H-phrases: see section 16

The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret [29 CFR 1910.1200].

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Power Out Odor-X Blast Air & Fabric Refresher

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

First-aid Measures After Inhalation: Obtain medical attention if breathing difficulty persists. First, take proper precautions to ensure your own safety before attempting rescue (e.g. wear appropriate respiratory protective equipment, use the buddy system), then remove the exposed person to fresh air. Keep at rest in a position comfortable for breathing.

First-aid Measures After Skin Contact: Immediately remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation/rash develops or persists. If frostbite or freezing occurs from exposure to gas occurs: For brief contact with a small amount: Rewarm with body heat. Get immediate medical advice/attention. For extensive contact or a large amount: Immediately call a poison center/doctor and follow their advice. Specific treatment is urgent, incorrect first-aid practices will aggravate the injury. Protect affected area with a loose cover until proper medical treatment is received.

First-aid Measures After Eye Contact: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for at least 15 minutes. Obtain medical attention.

First-aid Measures After Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injuries: Skin sensitization. Contact with gas escaping the container can cause frostbite. Asphyxia by lack of oxygen: risk of death.

Symptoms/Injuries After Inhalation: In elevated concentrations may cause asphyxiation, central nervous system effects, and increased breathing rate. Symptoms of asphyxiation include headache, dizziness, rapid breathing, increased pulse, mood changes, tremors, cyanosis, muscular weakness, narcosis, numbness of the extremities, unconsciousness and death.

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction. Contact with gas escaping the container can cause frostbite and freeze burns.

Symptoms/Injuries After Eye Contact: Contact with gas escaping the container can cause frostbite, freeze burns, and permanent eye damage.

Symptoms/Injuries After Ingestion: Not considered a potential route of exposure, but contact with gas escaping the container can cause freeze burns and frostbite.

Chronic Symptoms: None expected under normal conditions of use. Repeated exposure may cause skin dryness or cracking.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, dry chemical, or sand.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Flammable aerosol.

Explosion Hazard: Container may explode in heat of fire. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

Reactivity: Reacts violently with strong oxidizers. Increased risk of fire or explosion.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. Fight fire remotely due to the risk of explosion. DO NOT fight fire when fire reaches containers. Evacuate area.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Hydrogen Fluoride (HF). Carbon oxides (CO, CO₂).

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe vapors, mist, or spray. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

Evacuate unnecessary personnel, isolate, and ventilate area. Eliminate ignition sources.

Power Out Odor-X Blast Air & Fabric Refresher

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Stop leak, if possible without risk. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Stop the source of the release, if safe to do so. Consider the use of water spray to disperse vapors. Isolate the area until gas has dispersed. Ventilate and gas test area before entering. Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Asphyxiating gas at high concentrations. Pressurized container: may burst if heated. Do not pierce or burn, even after use. Do not pressurize, cut, or weld containers.

Precautions for Safe Handling: Avoid prolonged contact with eyes, skin and clothing. Do not breathe gas. Do not spray on an open flame or other ignition source. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.

Storage Conditions: Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Keep only in the original container in a cool, well ventilated place away from ignition sources. Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Air Freshener (Liquid / Pump Spray)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl- (128-37-0)		
USA ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ (inhalable fraction and vapor)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³
Benzyl alcohol (100-51-6)		
USA AIHA	WEEL TWA (ppm)	10 ppm
Citral (5392-40-5)		
USA ACGIH	ACGIH TWA (ppm)	5 ppm (inhalable fraction and vapor)
USA ACGIH	ACGIH chemical category	dermal sensitizer, Skin - potential significant contribution to overall exposure by the cutaneous route, Not Classifiable as a Human Carcinogen
Isopropyl alcohol (67-63-0)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	400 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA ACGIH	Biological Exposure Indices (BEI)	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift at end of workweek (background, nonspecific)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	980 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	400 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	1225 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	500 ppm
USA IDLH	US IDLH (ppm)	2000 ppm (10% LEL)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	980 mg/m ³

Power Out Odor-X Blast Air & Fabric Refresher

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm
1,1-Difluoroethane (75-37-6)		
USA AIHA	WEEL TWA (ppm)	1000 ppm

8.2. Exposure Controls

Appropriate Engineering Controls

: Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Use explosion-proof equipment. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Oxygen detectors should be used when asphixiating gases may be released.

Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection. Respiratory protection of the dependent type.



Materials for Protective Clothing

: Chemically resistant materials and fabrics. Wear fire/flame resistant/retardant clothing.

Hand Protection

: Wear protective gloves. If material is cold, wear thermally resistant protective gloves.

Eye and Face Protection

: Chemical safety goggles.

Skin and Body Protection

: Wear suitable protective clothing.

Respiratory Protection

: Use a NIOSH-approved self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

Thermal Hazard Protection

: Wear thermally resistant protective clothing.

Other Information

: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Gas
Appearance	: Clear Pale Straw
Odor	: Fresh
Odor Threshold	: No data available
pH	: No data available
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: No data available
Flash Point	: No data available
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20°C	: No data available
Relative Density	: No data available
Specific Gravity	: 0.95 (liquid phase)
Solubility	: No data available
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available
Explosive Properties	: Contains gas under pressure; may explode if heated.
9.2. Other Information	
VOC content (California)	: 5.2 %
% NVM by Weight	: 4 %
Gas Group	: Compressed gas

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity: Reacts violently with strong oxidizers. Increased risk of fire or explosion.

Power Out Odor-X Blast Air & Fabric Refresher

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

- 10.2. Chemical Stability:** Contains gas under pressure; may explode if heated. Flammable aerosol. Pressurized container: may burst if heated.
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.
- 10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- 10.6. Hazardous Decomposition Products:** Not expected to decompose under ambient conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl- (128-37-0)	
LD50 Oral Rat	> 2930 mg/kg (Species: Sprague-Dawley)
LD50 Dermal Rat	> 2000 mg/kg
Benzyl alcohol (100-51-6)	
LD50 Oral Rat	1230 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 4.178 mg/l/4h
ATE (Dust/Mist)	1.50 mg/l/4h
Citral (5392-40-5)	
LD50 Oral Rat	4960 mg/kg
LD50 Dermal Rabbit	2250 mg/kg
Isopropyl alcohol (67-63-0)	
LD50 Dermal Rabbit	12956 mg/kg (16.4 mL/kg bw)
LC50 Inhalation Rat	72600 mg/m ³ (Exposure time: 4 h)

Skin Corrosion/Irritation: Not classified

Serious Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl- (128-37-0)	
IARC group	3
Isopropyl alcohol (67-63-0)	
IARC group	3

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: In elevated concentrations may cause asphyxiation, central nervous system effects, and increased breathing rate. Symptoms of asphyxiation include headache, dizziness, rapid breathing, increased pulse, mood changes, tremors, cyanosis, muscular weakness, narcosis, numbness of the extremities, unconsciousness and death.

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction. Contact with gas escaping the container can cause frostbite and freeze burns.

Symptoms/Injuries After Eye Contact: Contact with gas escaping the container can cause frostbite, freeze burns, and permanent eye damage.

Symptoms/Injuries After Ingestion: Not considered a potential route of exposure, but contact with gas escaping the container can cause freeze burns and frostbite.

Chronic Symptoms: None expected under normal conditions of use. Repeated exposure may cause skin dryness or cracking.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General : Harmful to aquatic life with long lasting effects.

Ethanone, 1-(1,2,3,4,5,6,7,8-octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)- (54464-57-2)	
LC50 Fish 1	1.3 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [Semi-static])

Power Out Odor-X Blast Air & Fabric Refresher

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

EC50 Daphnia 1	1.38 mg/l (Exposure time: 48 h - Species: Daphnia magna [Semi-static])
ErC50 (Algae)	2.6 mg/l (Exposure time: 72 h - Species: Scenedesmus subspicatus [Static])
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl- (128-37-0)	
EC50 Daphnia 1	0.48 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 2	0.43 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)
NOEC Chronic Fish	0.053 mg/l
NOEC Chronic Crustacea	0.069 mg/l (Species: Daphnia magna)
Benzyl alcohol (100-51-6)	
LC50 Fish 1	460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	23 mg/l (Exposure time: 48 h - Species: water flea)
LC50 Fish 2	10 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
ErC50 (Algae)	770 mg/l
Citral (5392-40-5)	
LC50 Fish 1	4.1 mg/l
EC50 Daphnia 1	7 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Isopropyl alcohol (67-63-0)	
LC50 Fish 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 1	1000 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)
LC50 Fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Other Aquatic Organisms 2	1000 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)
1,1-Difluoroethane (75-37-6)	
LC50 Fish 1	733 mg/l
EC50 Daphnia 1	720 mg/l
ErC50 (Algae)	419 mg/l

12.2. Persistence and Degradability

Power Out Odor-X Blast Air & Fabric Refresher	
Persistence and Degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative Potential

Power Out Odor-X Blast Air & Fabric Refresher	
Bioaccumulative Potential	Not established.

Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl- (128-37-0)	
BCF Fish 1	230 – 2500
Partition coefficient n-octanol/water (Log Pow)	4.17

Benzyl alcohol (100-51-6)	
Partition coefficient n-octanol/water (Log Pow)	1.1

Citral (5392-40-5)	
Partition coefficient n-octanol/water (Log Pow)	2.76 (at 25 °C)

Isopropyl alcohol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0.05 (at 25 °C)

12.4. **Mobility in Soil** No additional information available

12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations. Do not pierce or burn, even after use.

Additional Information: Do not puncture or incinerate container.

Power Out Odor-X Blast Air & Fabric Refresher

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

Ecology - Waste Materials: Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Proper Shipping Name : AEROSOLS
Hazard Class : 2.1
Identification Number : UN1950
Label Codes : 2.1
ERG Number : 126



14.2. In Accordance with IMDG

Proper Shipping Name : AEROSOLS
Hazard Class : 2
Division : 2.1
Identification Number : UN1950
Label Codes : 2.1
EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U



14.3. In Accordance with IATA

Proper Shipping Name : AEROSOLS, FLAMMABLE
Identification Number : UN1950
Hazard Class : 2
Label Codes : 2.1
Division : 2.1
ERG Code (IATA) : 10L



SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

All components in this mixture are listed on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, have been exempted, are not listed, not disclosed due to CBI requirements or disclosure rules according to the relevant regulation.

Power Out Odor-X Blast Air & Fabric Refresher	
SARA Section 311/312 Hazard Classes	Physical hazard - Gas under pressure Health hazard - Respiratory or skin sensitization Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Simple asphyxiant
Isopropyl alcohol (67-63-0)	
Subject to reporting requirements of United States SARA Section 313	
SARA Section 313 - Emission Reporting	1 % (only if manufactured by the strong acid process, no supplier notification)

15.2. US State Regulations

Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl- (128-37-0)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Benzyl alcohol (100-51-6)
U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List
Isopropyl alcohol (67-63-0)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List
1,1-Difluoroethane (75-37-6)

Power Out Odor-X Blast Air & Fabric Refresher

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision : 08/26/2020

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

GHS Full Text Phrases:

Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Comb. Dust	Combustible Dust
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Aerosol 1	Flammable aerosol Category 1
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Press. Gas (Comp.)	Gases under pressure Compressed gas
Press. Gas (Liq.)	Gases under pressure Liquefied gas
Simple Asphy	Simple Asphyxiant
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
Skin Sens. 1B	Skin sensitization, category 1B
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects


Power Out Odor-X Blast Air & Fabric Refresher

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

US GHS SDS

NFPA Health Hazard	: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA Fire Hazard	: 4 - Materials that rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and burn readily.
NFPA Reactivity Hazard	: 0 - Material that in themselves are normally stable, even under fire conditions.
HMIS III Rating	
Health	: 2 Moderate Hazard
Flammability	: 2 Moderate Hazard
Physical	: 0 Minimal Hazard



Legal disclaimer: ©Turtle Wax, Inc. All rights reserved.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any particular conditions or process. Such information is, to the best of our knowledge and belief, accurate and reliable as of the date issued. No warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the responsibility of the user or processor to satisfy themselves as to the suitability of such information for their own particular circumstances, conditions or use, including transportation, storage and disposal which are outside of our control.

SDS US (GHS HazCom)