



# SAFETY DATA SHEET

## 1. Identification

**Product identifier:** CARPET SPOTTER PLUS - SW-676

**Other means of identification**

**SDS number:** RE1000009834

**Recommended restrictions**

**Product use:** Cleaner

**Restrictions on use:** Not known.

**Manufacturer/Importer/Distributor Information**

**Manufacturer**

Company Name: Sprayway, Inc.  
Address: 1000 INTEGRAM DR.  
Pacific, MO 63069  
Telephone: 1-630-628-3000  
Fax:

**Emergency telephone number:** 1-866-836-8855

## 2. Hazard(s) identification

**Hazard Classification**

**Physical Hazards**

Flammable aerosol Category 1

**Health Hazards**

Skin Corrosion/Irritation Category 2

Serious Eye Damage/Eye Irritation Category 2A

**Label Elements**

**Hazard Symbol:**



**Signal Word:** Danger

**Hazard Statement:** Extremely flammable aerosol.  
Causes skin irritation.  
Causes serious eye irritation.

**Precautionary Statements**



- Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.
- Response:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water/# If skin irritation occurs: Get medical advice/attention. Specific treatment (see on this label). Take off contaminated clothing.
- Storage:** Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Hazard(s) not otherwise classified (HNOC):** None.

### 3. Composition/information on ingredients

#### Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Ethanol, 2-(2-butoxyethoxy)-	112-34-5	5 - <10%
Ethanol, 2-butoxy-	111-76-2	5 - <10%
Butane	106-97-8	1 - <5%
Propane	74-98-6	1 - <5%
Morpholine	110-91-8	0.1 - <1%

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### 4. First-aid measures

- Ingestion:** Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
- Inhalation:** Move to fresh air.
- Skin Contact:** Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.
- Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

#### Most important symptoms/effects, acute and delayed

- Symptoms:** No data available.
- Hazards:** No data available.

#### Indication of immediate medical attention and special treatment needed

- Treatment:** No data available.

### 5. Fire-fighting measures



**General Fire Hazards:** Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

**Suitable (and unsuitable) extinguishing media**

**Suitable extinguishing media:** Use fire-extinguishing media appropriate for surrounding materials.

**Unsuitable extinguishing media:** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical:** Vapors may travel considerable distance to a source of ignition and flash back.

**Special protective equipment and precautions for firefighters**

**Special fire fighting procedures:** No data available.

**Special protective equipment for fire-fighters:** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

**6. Accidental release measures**

**Personal precautions, protective equipment and emergency procedures:** Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

**Methods and material for containment and cleaning up:** Absorb spill with vermiculite or other inert material, then place in a container for chemical waste.

**Notification Procedures:** Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk.

**Environmental Precautions:** Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

**7. Handling and storage**

**Precautions for safe handling:** Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin.

**Conditions for safe storage, including any incompatibilities:** Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Aerosol Level 1

**8. Exposure controls/personal protection**

**Control Parameters**

**Occupational Exposure Limits**



Chemical Identity	Type	Exposure Limit Values	Source
Ethanol, 2-(2-butoxyethoxy)- - Inhalable fraction and vapor.	TWA	10 ppm	US. ACGIH Threshold Limit Values (03 2013)
Ethanol, 2-butoxy-	TWA	20 ppm	US. ACGIH Threshold Limit Values (2008)
	TWA	25 ppm 120 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	REL	5 ppm 24 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	50 ppm 240 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Butane	REL	800 ppm 1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	STEL	1,000 ppm	US. ACGIH Threshold Limit Values (03 2018)
	TWA	800 ppm 1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Propane	REL	1,000 ppm 1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	1,000 ppm 1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	1,000 ppm 1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Morpholine	REL	20 ppm 70 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	STEL	30 ppm 105 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	20 ppm	US. ACGIH Threshold Limit Values (2008)
	TWA	20 ppm 70 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	30 ppm 105 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	PEL	20 ppm 70 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Sodium hydroxide (Na(OH))	Ceiling	2 mg/m3	US. ACGIH Threshold Limit Values (2008)
	Ceiling	2 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	Ceil_Time	2 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	2 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethanol, 2-methoxy-	TWA	0.1 ppm	US. ACGIH Threshold Limit Values (2008)
	REL	0.1 ppm 0.3 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	25 ppm 80 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	PEL	25 ppm 80 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
1,2-Ethanediamine	TWA	10 ppm	US. ACGIH Threshold Limit Values (2008)
	PEL	10 ppm 25 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	10 ppm 25 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	REL	10 ppm 25 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Morpholine, 4-ethyl-	REL	5 ppm 23 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	5 ppm 23 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	PEL	20 ppm 94 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	5 ppm	US. ACGIH Threshold Limit Values (2008)

**Biological Limit Values**

Chemical Identity	Exposure Limit Values	Source
Ethanol, 2-butoxy- (Butoxyacetic acid (BAA), with hydrolysis: Sampling time: End of shift.)	200 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethanol, 2-methoxy- (2-Methoxyacetic acid: Sampling time: End of shift at end of work week.)	1 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)



**Appropriate Engineering Controls** No data available.

**Individual protection measures, such as personal protective equipment**

- General information:** Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If exposure limits have not been established, maintain airborne levels to an acceptable level.
- Eye/face protection:** Wear safety glasses with side shields (or goggles).
- Skin Protection**
- Hand Protection:** No data available.
- Other:** Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
- Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
- Hygiene measures:** Avoid contact with eyes. Observe good industrial hygiene practices. When using do not smoke. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands before breaks and immediately after handling the product.

**9. Physical and chemical properties**

**Appearance**

- Physical state:** liquid
- Form:** Spray Aerosol
- Color:** No data available.
- Odor:** No data available.
- Odor threshold:** No data available.
- pH:** No data available.
- Melting point/freezing point:** No data available.
- Initial boiling point and boiling range:** No data available.
- Flash Point:** -104.44 °C
- Evaporation rate:** No data available.
- Flammability (solid, gas):** No data available.
- Upper/lower limit on flammability or explosive limits**
- Flammability limit - upper (%):** No data available.
- Flammability limit - lower (%):** No data available.
- Explosive limit - upper (%):** No data available.
- Explosive limit - lower (%):** No data available.
- Vapor pressure:** 3,447.3786 - 4,136.8544 hPa (20 °C)
- Vapor density:** No data available.
- Density:** No data available.
- Relative density:** No data available.



**Solubility(ies)**

**Solubility in water:** No data available.  
**Solubility (other):** No data available.  
**Partition coefficient (n-octanol/water):** No data available.

**Auto-ignition temperature:** No data available.  
**Decomposition temperature:** No data available.  
**Viscosity:** No data available.

**10. Stability and reactivity**

**Reactivity:** No data available.  
**Chemical Stability:** Material is stable under normal conditions.  
**Possibility of hazardous reactions:** No data available.  
**Conditions to avoid:** Avoid heat or contamination.  
**Incompatible Materials:** No data available.  
**Hazardous Decomposition Products:** No data available.

**11. Toxicological information**

**Information on likely routes of exposure**

**Inhalation:** No data available.  
**Skin Contact:** No data available.  
**Eye contact:** No data available.  
**Ingestion:** No data available.

**Symptoms related to the physical, chemical and toxicological characteristics**

**Inhalation:** No data available.  
**Skin Contact:** No data available.  
**Eye contact:** No data available.  
**Ingestion:** No data available.

**Information on toxicological effects**

**Acute toxicity (list all possible routes of exposure)**

**Oral**  
**Product:** ATEmix: 20,189.64 mg/kg  
**Dermal**  
**Product:** ATEmix: 7,539.59 mg/kg  
**Inhalation**  
**Product:** ATEmix: 231.27 mg/l  
ATEmix : 48.82 mg/l



**Repeated dose toxicity**

**Product:** No data available.

**Specified substance(s):**

Ethanol, 2-(2-butoxyethoxy)-	NOAEL (Rat(Female, Male), Oral, 90 d): 250 mg/kg Oral Experimental result, Key study NOAEL (Rat(Female, Male), Dermal, 13 Weeks): > 2,000 mg/kg Dermal Experimental result, Key study NOAEL (Rat(Female, Male), Inhalation, 90 - 120 d): 14 ppm(m) Inhalation Experimental result, Key study
Ethanol, 2-butoxy-	NOAEL (Rabbit(Female, Male), Dermal, 90 d): > 150 mg/kg Dermal Experimental result, Key study NOAEL (Rat(Female), Oral, 90 d): < 82 mg/kg Oral Experimental result, Key study NOAEL (Rat(Female), Inhalation, 2 yr): < 31 ppm(m) Inhalation Experimental result, Key study
Butane	NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study
Propane	NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study
Morpholine	NOAEL (Rat(Female, Male), Inhalation): 36 ppm(m) Inhalation Experimental result, Key study LOAEL (Rat(Female), Oral, 56 d): 500 mg/kg Oral Experimental result, Key study

**Skin Corrosion/Irritation**

**Product:** No data available.

**Specified substance(s):**

Ethanol, 2-(2-butoxyethoxy)-	in vivo (Rabbit): Not irritant Experimental result, Supporting study
Ethanol, 2-butoxy-	in vivo (Rabbit): Irritating Experimental result, Key study
Morpholine	in vivo (Rabbit): Corrosive Experimental result, Key study

**Serious Eye Damage/Eye Irritation**

**Product:** No data available.

**Specified substance(s):**

Ethanol, 2-(2-butoxyethoxy)-	Rabbit, 24 - 72 hrs: Highly irritating
Ethanol, 2-butoxy-	Rabbit, 24 - 72 hrs: Irritating

**Respiratory or Skin Sensitization**

**Product:** No data available.

**Specified substance(s):**

Ethanol, 2-(2-butoxyethoxy)-	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Ethanol, 2-butoxy-	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Morpholine	Skin sensitization:, in vivo (Guinea pig): Non sensitising



**Carcinogenicity**

**Product:** No data available.

**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

No carcinogenic components identified

**US. National Toxicology Program (NTP) Report on Carcinogens:**

No carcinogenic components identified

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):**

No carcinogenic components identified

**Germ Cell Mutagenicity**

**In vitro**

**Product:** No data available.

**In vivo**

**Product:** No data available.

**Reproductive toxicity**

**Product:** No data available.

**Specific Target Organ Toxicity - Single Exposure**

**Product:** No data available.

**Specific Target Organ Toxicity - Repeated Exposure**

**Product:** No data available.

**Aspiration Hazard**

**Product:** No data available.

**Other effects:** No data available.

**12. Ecological information**

**Ecotoxicity:**

**Acute hazards to the aquatic environment:**

**Fish**

**Product:** No data available.

**Specified substance(s):**

Ethanol, 2-(2-butoxyethoxy)-	LC 50 (Lepomis macrochirus, 96 h): 1,300 mg/l Experimental result, Key study LC 50 (Pimephales promelas, 96 h): 2,400 mg/l Experimental result, Supporting study
Ethanol, 2-butoxy-	LC 50 (Oncorhynchus mykiss, 96 h): 1,474 mg/l Experimental result, Key study
Butane	LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study
Propane	LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study
Morpholine	LC 50 (Oncorhynchus mykiss, 96 h): 180 mg/l Experimental result, Key study



#### Aquatic Invertebrates

<b>Product:</b>	No data available.
<b>Specified substance(s):</b> Ethanol, 2-(2-butoxyethoxy)-	LC 50 (Daphnia magna, 48 h): +/- 1,743 mg/l QSAR QSAR, Supporting study
Ethanol, 2-butoxy-	EC 50 (Daphnia magna, 48 h): 1,550 mg/l Experimental result, Key study
Butane	LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study
Morpholine	EC 50 (Daphnia magna, 48 h): 45 mg/l Experimental result, Key study

#### Chronic hazards to the aquatic environment:

##### Fish

<b>Product:</b>	No data available.
<b>Specified substance(s):</b> Ethanol, 2-butoxy-	NOAEL (Danio rerio): > 100 mg/l Experimental result, Key study

##### Aquatic Invertebrates

<b>Product:</b>	No data available.
<b>Specified substance(s):</b> Ethanol, 2-butoxy-	EC 50 (Daphnia magna): 297 mg/l Experimental result, Key study EC 10 (Daphnia magna): 134 mg/l Experimental result, Key study
Morpholine	EC 50 (Daphnia magna): 12 mg/l Experimental result, Key study NOAEL (Daphnia magna): 5 mg/l Experimental result, Key study

##### Toxicity to Aquatic Plants

<b>Product:</b>	No data available.
-----------------	--------------------

#### Persistence and Degradability

##### Biodegradation

<b>Product:</b>	No data available.
<b>Specified substance(s):</b> Ethanol, 2-(2-butoxyethoxy)-	85 % (28 d) Detected in water. Experimental result, Key study
Ethanol, 2-butoxy-	90.4 % Detected in water. Experimental result, Key study
Butane	100 % (385.5 h) Detected in water. Experimental result, Key study 50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study
Propane	100 % (385.5 h) Detected in water. Experimental result, Key study 50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study
Morpholine	> 90 % (24 h) Sediment Experimental result, Key study 80 - 94 % (24 h) Sediment Experimental result, Key study

##### BOD/COD Ratio

<b>Product:</b>	No data available.
-----------------	--------------------

#### Bioaccumulative potential

##### Bioconcentration Factor (BCF)

<b>Product:</b>	No data available.
-----------------	--------------------





Class:	2.1
Label(s):	-
Packing Group:	-
Environmental Hazards:	No
Marine Pollutant	No
Special precautions for user:	Not regulated.

**15. Regulatory information**

**US Federal Regulations**

**Restrictions on use:** Not known.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**  
**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

None present or none present in regulated quantities.

**CERCLA Hazardous Substance List (40 CFR 302.4):**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Butane	lbs. 100
Propane	lbs. 100
Phosphoric acid, sodium salt (1:3)	lbs. 5000
Morpholine	lbs. 100
Sodium hydroxide (Na(OH))	lbs. 1000
1,2-Ethanediamine	lbs. 5000
Morpholine, 4-ethyl-	lbs. 100

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories**

- Fire Hazard
- Immediate (Acute) Health Hazards
- Flammable aerosol
- Skin Corrosion/Irritation
- Serious Eye Damage/Eye Irritation

**SARA 302 Extremely Hazardous Substance**

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
1,2-Ethanediamine	lbs. 5000	lbs. 10000

**SARA 304 Emergency Release Notification**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Ethanol, 2-(2-butoxyethoxy)-	
Ethanol, 2-butoxy-	
Butane	lbs. 100
Propane	lbs. 100
Phosphoric acid, sodium salt (1:3)	lbs. 5000
Morpholine	lbs. 100
Sodium hydroxide (Na(OH))	lbs. 1000
Ethanol, 2-methoxy-	
1,2-Ethanediamine	lbs. 5000
Morpholine, 4-ethyl-	lbs. 100



**SARA 311/312 Hazardous Chemical**

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
1,2-Ethanediamine	lbs
Ethanol, 2-(2-butoxyethoxy)-	10000 lbs
Ethanol, 2-butoxy-	10000 lbs
Butane	10000 lbs
Propane	10000 lbs
Morpholine	10000 lbs
Sodium hydroxide (Na(OH))	10000 lbs
Ethanol, 2-methoxy-	10000 lbs
Morpholine, 4-ethyl-	10000 lbs

**SARA 313 (TRI Reporting)**

<u>Chemical Identity</u>	<u>Reporting threshold for other users</u>	<u>Reporting threshold for manufacturing and processing</u>
Ethanol, 2-(2-butoxyethoxy)-	N230 lbs	N230 lbs.
Ethanol, 2-butoxy-	N230 lbs	N230 lbs.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):**

**Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)**

**US State Regulations**

**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Ethanol, 2-methoxy-	Developmental toxin. 03 2008
Ethanol, 2-methoxy-	Male reproductive toxin. 03 2008

**US. New Jersey Worker and Community Right-to-Know Act**

<u>Chemical Identity</u>
Ethanol, 2-(2-butoxyethoxy)-
Ethanol, 2-butoxy-
Butane
Propane

**US. Massachusetts RTK - Substance List**

<u>Chemical Identity</u>
1,2-Ethanediamine

**US. Pennsylvania RTK - Hazardous Substances**

<u>Chemical Identity</u>
Ethanol, 2-(2-butoxyethoxy)-
Ethanol, 2-butoxy-
Butane
Propane

**US. Rhode Island RTK**

No ingredient regulated by RI Right-to-Know Law present.

**International regulations**

**Montreal protocol**

Not applicable

**Stockholm convention**

Not applicable



**Rotterdam convention**

Not applicable

**Kyoto protocol**

Not applicable

**Inventory Status:**

Australia AICS:	On or in compliance with the inventory
Canada DSL Inventory List:	Not in compliance with the inventory.
EINECS, ELINCS or NLP:	Not in compliance with the inventory.
Japan (ENCS) List:	Not in compliance with the inventory.
China Inv. Existing Chemical Substances:	On or in compliance with the inventory
Korea Existing Chemicals Inv. (KECI):	Not in compliance with the inventory.
Canada NDSL Inventory:	Not in compliance with the inventory.
Philippines PICCS:	On or in compliance with the inventory
US TSCA Inventory:	Not in compliance with the inventory.
New Zealand Inventory of Chemicals:	On or in compliance with the inventory
Japan ISHL Listing:	Not in compliance with the inventory.
Japan Pharmacopoeia Listing:	Not in compliance with the inventory.
Mexico INSQ:	On or in compliance with the inventory
Ontario Inventory:	Not in compliance with the inventory.
Taiwan Chemical Substance Inventory:	On or in compliance with the inventory

**16. Other information, including date of preparation or last revision**

**Issue Date:** 09/11/2019

**Revision Information:** No data available.

**Version #:** 1.0

**Further Information:** No data available.

**Disclaimer:** This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.