

SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards

SDS Revision: 1.0

SDS Revision Date: 1/5/2022

1. PRODUCT & COMPANY IDENTIFICATION

1.1	Product Name:	PAUL MITCHELL® EXTRA BODY SCULPTING FOAM
1.2	Chemical Name:	Aerosol
1.3	Synonyms:	1802A-166C
1.4	Trade Names:	Paul Mitchell® Extra Body Sculpting Foam
1.5	Product Uses & Restrictions:	Aerosol Sculpting Foam
1.6	Distributor's Name:	John Paul Mitchell Systems
1.7	Distributor's Address:	20705 Centre Pointe Parkway, Santa Clarita, CA 91350 USA
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300
1.9	Business Phone / Fax:	+1 (661) 298-0400 / +1 (661) 298-0390

2. HAZARDS IDENTIFICATION

2.1	Hazard Identification:	Prepared in accordance with UN Globally Harmonized standards. Intended to comply with OSHA 29 CFR 1910.1200, Canadian WHMIS and Australian Work Health and Safety standards. WARNING! PRESSURIZED CONTAINER MAY BURST IF HEATED. CAUSES EYE IRRITATION. Classification: Aerosol 3; Eye Irrit. 2B
2.2	Label Elements:	<u>Hazard Statements</u> (H): H229 – Pressurized container: may burst if heated. H320 – Causes eye irritation. <u>Precautionary Statements</u> (P): P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P251 – Do not pierce or burn, even after use. P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 – If eye irritation persists get medical advice/attention. P410+P412 – Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).
2.3	Other Warnings:	KEEP OUT OF REACH OF CHILDREN.

3. COMPOSITION & INGREDIENT INFORMATION

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m ³)								OTHER
					ACGIH		NOHSC			OSHA			
					TLV	STEL	ppm	ppm	ppm	PEL	STEL	IDLH	
PROPRIETARY	NA	NA	NA	80-100	NA	NA	NF	NF	NF	NA	NA	NA	
ISOBUTANE	75-28-5	TZ4300000	200-857-2	1-5	600	750	NF	NF	NF	NA	NA	NA	
	Press. Gas, Flam. Gas 1; H229, H220												
PROPANE	74-98-6	TX2275000	200-827-9	1-5	1000	NA	1000	NF	NF	1000	NA	2100	
	Flam. Gas 1; Press. Gas; H220												

4. FIRST AID MEASURES

4.1	First Aid:	<u>Ingestion:</u> If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. <u>Eyes:</u> Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. If irritation occurs, contact a physician. <u>Skin:</u> If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately. <u>Inhalation:</u> Remove victim to fresh air at once.
4.2	Effects of Exposure:	<u>Ingestion:</u> If product is swallowed, may cause nausea, vomiting and/or diarrhea. <u>Eyes:</u> Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. <u>Skin:</u> May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals. <u>Inhalation:</u> None expected.
4.3	Symptoms of Overexposure:	Overexposure in eyes may cause redness, itching and watering. Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.
4.4	Acute Health Effects:	Moderate irritation to eyes.

SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards


SDS Revision: 1.0

SDS Revision Date: 1/5/2022

4. FIRST AID MEASURES – cont'd

4.5	Chronic Health Effects:	No harmful or chronic health effects are expected to occur from a single accidental ingestion.			
4.6	Target Organs:	Eyes			
4.7	Medical Conditions Aggravated by Exposure:	Pre-existing dermatitis, other skin conditions, and disorders of the target organs (eyes, skin, and respiratory system).	HEALTH		1
			FLAMMABILITY		1
			PHYSICAL HAZARDS		0
			PROTECTIVE EQUIPMENT		B
			EYES	SKIN	

5. FIREFIGHTING MEASURES

5.1	Fire & Explosion Hazards:	PRESSURIZED CONTAINER MAY BURST IF HEATED. Level 1 Aerosol (NFPA 30B). Aerosols may burst at temperatures above 120 °F. Cool uninvolved containers to prevent possible bursting. Aerosols may be projectile hazards when bursting. If aerosols are bursting, stay clear until bursting is complete. Containers may rupture and release flammable liquids or/ or exposed gases if exposed to the heat of fire. Keep containers cool by spraying them with water until the fire has been extinguished. Keep away from heat, lit cigarettes, sparks & open flame. Keep container closed. When exposed to high temperatures, may produce hazardous decomposition products such as oxides of carbon (e.g., CO, CO ₂) and nitrogen (e.g., NO _x) and smoke.	
5.2	Extinguishing Methods:	Water, Foam, CO ₂ , Dry Chemical, Halon (if authorized)	
5.3	Firefighting Procedures:	As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.	

6. ACCIDENTAL RELEASE MEASURES

6.1	Spills:	Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment (PPE). For <u>small spills</u> (e.g., < 1 gallon (3.8 L)) or <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals, wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows). Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.
-----	---------	---

7. HANDLING & STORAGE INFORMATION

7.1	Work & Hygiene Practices:	Do not eat, drink or smoke when handling this product. Wash unintentional residues with soap and warm water
7.2	Storage & Handling:	Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Avoid temperatures above 120 °F. Keep away from incompatible substances. Keep away from excessive heat and open flames.
7.3	Special Precautions:	Clean all spills promptly. Spilled material may present a slipping hazard.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	Exposure Limits: ppm (mg/m ³)		ACGIH		NOHSC			OSHA			OTHER
		CHEMICAL NAME(S)	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		ISOBUTANE	600	750	NF	NF	NF	NA	NA	NA	
		PROPANE	1000	NA	1000	NF	NF	1000	NA	2100	
8.2	Ventilation & Engineering Controls:	General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.									
8.3	Respiratory Protection:	No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia.									



SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards

SDS Revision: 1.0

SDS Revision Date: 1/5/2022

8. EXPOSURE CONTROLS & PERSONAL PROTECTION – cont'd

8.4	Eye Protection:	Avoid eye contact. Protective eyewear recommended. Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling large quantities (of this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants.	
8.5	Hand Protection:	None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states.	
8.6	Body Protection:	No special body protection is required under typical circumstances of use and handling. If necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA.	

9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Appearance:	Aerosol white foam
9.2	Odor:	Floral odor
9.3	Odor Threshold:	NA
9.4	pH:	5.0-6.0
9.5	Melting Point/Freezing Point:	NA
9.6	Initial Boiling Point/Boiling Range:	NA
9.7	Flashpoint:	-34°C (-30 °F) TCC for propellant only
9.8	Upper/Lower Flammability Limits:	NA
9.9	Vapor Pressure:	@ 20°C (68°F) Aerosol can pressure not to exceed 180 psig @ 55°C (131°F) 12.4 bar
9.10	Vapor Density:	>1
9.11	Relative Density:	0.91-0.99
9.12	Solubility in Water:	Soluble
9.13	Partition Coefficient (log Pow):	NA
9.14	Autoignition Temperature:	NA
9.15	Decomposition Temperature:	NA
9.16	Viscosity:	NA
9.17	Other Information:	VOC: 6%. Evaporation rate >1.

10. STABILITY & REACTIVITY

10.1	Stability:	This product is stable.
10.2	Hazardous Decomposition Products:	Oxides of carbon (CO, CO ₂) and sulfur (SO ₂).
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid:	Open flames, sparks and high heat.
10.5	Incompatible Substances:	None known.

11. TOXICOLOGICAL INFORMATION

11.1	Routes of Entry:	Inhalation: YES	Absorption: YES	Ingestion: YES
11.2	Toxicity Data:	This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product.		
11.3	Acute Toxicity:	See section 4.4		
11.4	Chronic Toxicity:	See section 4.5		
11.5	Suspected Carcinogen:	No.		
11.6	Reproductive Toxicity:	This product is not reported to produce reproductive toxicity in humans.		
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.		
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.		
	Teratogenicity:	This product is not reported to cause teratogenic effects in humans.		
	Reproductive Toxicity:	This product is not reported to cause reproductive effects in humans.		
11.7	Irritancy of Product:	See Section 4.3.		
11.8	Biological Exposure Indices:	NE		
11.9	Physician Recommendations:	Treat symptomatically.		

12. ECOLOGICAL INFORMATION

12.1	Environmental Stability:	There are no specific data available for this product.
12.2	Effects on Plants & Animals:	There are no specific data available for this product.
12.3	Effects on Aquatic Life:	There are no specific data available for this product.

SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards

SDS Revision: 1.0

SDS Revision Date: 1/5/2022

13. DISPOSAL CONSIDERATIONS

13.1	Waste Disposal:	Waste disposal must be in accordance with appropriate Federal, state, and local regulations.
13.2	Special Considerations:	U.S. EPA Waste Number: D001 (characteristic - ignitable).

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND):	UN1950, AEROSOLS, 2.2 (LTD QTY, IP VOL ≤ 1.0 L)	
14.2	IATA (AIR):	ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 820 mL) UN1950, AEROSOLS, NONFLAMMABLE, 2.2 (LTD QTY, IP VOL ≤ 820 mL)	
14.3	IMDG (OCN):	UN1950, AEROSOLS, 2.2 (LTD QTY, IP VOL ≤ 1.0 L)	
14.4	TDGR (Canadian GND):	UN1950, AEROSOLS, 2.2 (LTD QTY, IP VOL ≤ 1000 mL) or MARK PACKAGE "LIMITED QUANTITY," "LTD QTY," or "QUANT LTÉE" or "QUANTITÉ LIMITÉE"	
14.5	ADR/RID (EU):	UN1950, AEROSOLS, 2.2 (LTD QTY, IP VOL ≤ 1.0 L)	
14.6	SCT (MEXICO):	UN1950, AEROSOLS, 2.2 (CANT. LTDA., IP VOL ≤ 1.0 L)	
14.7	ADGR (AUS):	UN1950, AEROSOLS, 2.2 (LTD QTY, IP VOL ≤ 1.0 L)	

15. REGULATORY INFORMATION

15.1	SARA Reporting Requirements:	This product does not contain any substances subject to SARA Title III, section 313 reporting requirements.	
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.	
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.	
15.4	CERCLA Reportable Quantity (RQ):	NA	
15.5	Other Federal Requirements:	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics). This material does not contain any hazardous air pollutants. None of the components in this product are listed as priority pollutants under the CWA. None of the components in this product are listed as toxic pollutants under the CWA.	
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the HPR and the MSDS contains all of the information required by the HPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS B5, D2B (Flammable Aerosol, Other Toxic Effects)	
15.7	State Regulatory Information:	<p><u>Isobutane</u> is found on the following state criteria list: Massachusetts Hazardous Substances List (MA), New Jersey Right-to-Know List (NJ) and Pennsylvania Right-to-Know List (PA).</p> <p><u>Propane</u> is found on the following state criteria list: MA, MN, PA, and WA.</p> <p>No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).</p>	
15.8	Other Requirements:	This product does not contain any chemicals known to the State of California to cause cancer or other reproductive harm. For more information go to www.P65Warnings.ca.gov	


SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards

SDS Revision: 1.0

SDS Revision Date: 1/5/2022

16. OTHER INFORMATION

16.1	Other Information:	<p>WARNING! PRESSURIZED CONTAINER MAY BURST IF HEATED. CAUSES EYE IRRITATION. Use as directed. Discontinue use if irritation develops. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists get medical advice/attention. Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F). KEEP OUT OF REACH OF CHILDREN.</p>	
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	
16.3	Disclaimer:	<p>This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & John Paul Mitchell Systems', knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. ShipMate, Inc. and John Paul Mitchell Systems', are not liable for any claims, losses, or damages of any third party, special, indirect, incidental, consequential or exemplary damages from reliance on the information in this document. Data may be changed from time to time. Be sure to consult the latest edition.</p>	
16.4	Prepared for:	<p>John Paul Mitchell Systems 20705 Centre Pointe Parkway Santa Clarita, CA 91350 USA Tel: +1 (661) 298-0400 Fax: +1 (661) 298-0390</p>	<p>JOHN PAUL MITCHELL SYSTEMS</p>
16.5	Prepared by:	<p>ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com</p>	

SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards

SDS Revision: 1.0

SDS Revision Date: 1/5/2022

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
RTECS No.	Registry of Toxic Effects of Chemical Substances Number
EINECS No.	European Inventory of Existing Commercial Chemical Substances Number

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
IDLH	Immediately Dangerous to Life and Health
NOHSC	National Occupational Health and Safety Commission (Australia)
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
-----	--

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard

HEALTH
FLAMMABILITY
PHYSICAL HAZARDS
PERSONAL PROTECTION

PERSONAL PROTECTION RATINGS:

A	
B	
C	
D	
E	
F	

G	
H	
I	
J	
K	
X	Consult your supervisor or SOPs for special handling directions.

Safety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves
Boots	Protective Apron	Protective Clothing & Full Suit	Dust Respirator
Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:

Carc	Carcinogenic
Irrit	Irritant
NA	Not Available
NR	No Results
ND	Not Determined
NE	Not Established
NF	Not Found
SCBA	Self-Contained Breathing Apparatus
Sens	Sensitization
STOT RE	Specific Target Organ Toxicity – Repeat Exposure

STOT SE Specific Target Organ Toxicity – Single Exposure


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD ₁₀	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD ₁₀ , LD ₁₀ , & LD ₅₀ or TC, TC ₁₀ , LC ₁₀ , & LC ₅₀	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL _m	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

CLP/GHS (1272/2008/EC) PICTOGRAMS:

GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment