



Hybrid Solutions Trim Restorer

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations
US GHS SDS

Revision Date: 03/05/2024

Date of Issue: 06/17/2022

Supersedes Date: 06/17/2022

Version: 1.1

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Hybrid Solutions Trim Restorer

Product Code: 53838, 53860

1.2. Intended Use of the Product

Use of the Substance/Mixture: Rubber/Vinyl Protectant - Non-Aerosol

1.3. Name, Address, and Telephone of the Responsible Party

Manufacturer

Turtle Wax, Inc.

948 Springer Dr.

Lombard, IL 60148

Phone Number: 1(630)455-3700

Toll-Free Number: 1(800)887-8539

1.4. Emergency Telephone Number

Emergency Number : Velocity EHS
1-800-255-392 (US and Canada)
1-813-248-0585 (International)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US Classification

Skin Sens. 1 H317

Carc. 2 H351

Full text of hazard classes and H-statements : see section 16

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Warning

Hazard Statements (GHS-US)

: H317 - May cause an allergic skin reaction.
H351 - Suspected of causing cancer.

Precautionary Statements (GHS-US)

: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P261 - Avoid breathing vapors, mist, or spray.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves, protective clothing, and eye protection.
P302+P352 - If on skin: Wash with plenty of water.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P321 - Specific treatment (see section 4 on this SDS).
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P363 - Wash contaminated clothing before reuse.
P405 - Store locked up.
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

Hybrid Solutions Trim Restorer

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Synonyms	Product Identifier	%	GHS US classification
Propylene Glycol	1,2-Propylene glycol / 1,2-Dihydroxypropane / Propane-1,2-diol / Propylene glycol	(CAS-No.) 57-55-6	3.2 – 3.6	Not classified
Carbon black	C.I. 77266 / C.I. Pigment Black 6 / C.I. Pigment Black 7 / Lampblack	(CAS-No.) 1333-86-4	1.2 – 1.3	Carc. 2, H351 Comb. Dust
Hydrated silica	Precipitated silica / Silica gel / Silica gel, precipitated, crystalline free / Silica, amorphous, gel	(CAS-No.) 112926-00-8	0.8 – 1.1	Not classified
Butoxydiglycol	Butoxydiglycol / Butyl carbitol / Butyl dioxitol / Diethylene glycol butyl ether	(CAS-No.) 112-34-5	0.007 – 0.04	Eye Irrit. 2A, H319
Benzisothiazolinone	1,2-Benzisothiazolin-3-one / Benzisothiazolinone / 1,2-Benzisothiazolone / 1,2-Benzisothiazol-3-one	(CAS-No.) 2634-33-5	0.027– 0.033	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Comb. Dust
Sodium Hydroxide	Caustic soda / Sodium hydroxide (Na(OH)) / SODIUM HYDROXIDE / LYE	(CAS-No.) 1310-73-2	0.0076 – 0.011	Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 3, H402
Methoxyisopropyl Acetate	Acetate, 1-methoxy-2-propyl / Acetic acid, 2-methoxy-1-methylethyl ester / 2-Methoxy-1-methylethyl acetate / 1-Methoxy-2-acetoxypropane	(CAS-No.) 108-65-6	0.0003 – 0.0007	Flam. Liq. 3, H226 STOT SE 3, H336
Graphite	C.I. Pigment Black 10 / C.I. 77265 / graphite	(CAS-No.) 7782-42-5	0.0006	Comb. Dust
Cyclohexane	Benzene, hexahydro- / CYCLOHEXANE / Hexahydrobenzene	(CAS-No.) 110-82-7	0.0000002 – 0.0000001	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Ethyl Acetate	Acetic acid, ethyl ester / Ethyl ethanoate / ETHYL ACETATE	(CAS-No.) 141-78-6	≤ 0.0000002	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Acrylic Acid	Acroleic acid / Propenoic acid / 2-Propenoic acid / Acrylic acid, stabilized	(CAS-No.) 79-10-7	≤ 0.0000002	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Chronic 2, H411

Full text of H-phrases: see section 16

Hybrid Solutions Trim Restorer

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

First-aid Measures After Skin Contact: Remove contaminated clothing. Wash affected area with soap and water for at least 15 minutes. Obtain medical attention if irritation/rash develops or persists.

First-aid Measures After Eye Contact: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for at least 15 minutes. Obtain medical attention.

First-aid Measures After Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injuries: Skin sensitization. Suspected of causing cancer.

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: Suspected of causing cancer. May cause an allergic skin reaction.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, or dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Irritating fumes. Silica Oxides.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe vapor, mist or spray.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

Hybrid Solutions Trim Restorer

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Do not breathe dust/fume/gas/mist/vapors/spray.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Rubber/Vinyl Protectant - Non-Aerosol

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

Cyclohexane (110-82-7)		
USA ACGIH	ACGIH OEL TWA [ppm]	100 ppm
USA NIOSH	NIOSH REL (TWA)	1050 mg/m ³
USA NIOSH	NIOSH REL TWA [ppm]	300 ppm
USA IDLH	IDLH [ppm]	1300 ppm (10% LEL)
USA OSHA	OSHA PEL (TWA) [1]	1050 mg/m ³
USA OSHA	OSHA PEL (TWA) [2]	300 ppm
Ethyl acetate (141-78-6)		
USA ACGIH	ACGIH OEL TWA [ppm]	400 ppm
USA NIOSH	NIOSH REL (TWA)	1400 mg/m ³
USA NIOSH	NIOSH REL TWA [ppm]	400 ppm
USA IDLH	IDLH [ppm]	2000 ppm (10% LEL)
USA OSHA	OSHA PEL (TWA) [1]	1400 mg/m ³
USA OSHA	OSHA PEL (TWA) [2]	400 ppm
Acrylic acid (79-10-7)		
USA ACGIH	ACGIH OEL TWA [ppm]	2 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen, Skin - potential significant contribution to overall exposure by the cutaneous route
USA NIOSH	NIOSH REL (TWA)	6 mg/m ³
USA NIOSH	NIOSH REL TWA [ppm]	2 ppm
Sodium hydroxide (1310-73-2)		
USA ACGIH	ACGIH OEL Ceiling	2 mg/m ³
USA NIOSH	NIOSH REL (Ceiling)	2 mg/m ³
USA IDLH	IDLH	10 mg/m ³
USA OSHA	OSHA PEL (TWA) [1]	2 mg/m ³
Graphite (7782-42-5)		
USA ACGIH	ACGIH OEL TWA	2 mg/m ³ (all forms except graphite fibers-respirable particulate matter)
USA NIOSH	NIOSH REL (TWA)	2.5 mg/m ³ (natural-respirable dust)
USA IDLH	IDLH	1250 mg/m ³ (Graphite (natural))
USA OSHA	OSHA PEL (TWA) [1]	15 mg/m ³ (synthetic-total dust) 5 mg/m ³ (synthetic-respirable fraction)
USA OSHA	OSHA PEL (TWA) [2]	15 mppcf (natural) (See 29 CFR 1910.1000 TABLE Z-3)
Propylene glycol monomethyl ether acetate (108-65-6)		
USA AIHA	WEEL TWA [ppm]	50 ppm

Hybrid Solutions Trim Restorer

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

1,2-Propanediol (57-55-6)		
USA AIHA	WEEL TWA	10 mg/m ³
Carbon black (1333-86-4)		
USA ACGIH	ACGIH OEL TWA	3 mg/m ³ (inhalable particulate matter)
USA ACGIH	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
USA NIOSH	NIOSH REL (TWA)	3.5 mg/m ³ 0.1 mg/m ³ (Carbon black in presence of Polycyclic aromatic hydrocarbons)
USA IDLH	IDLH	1750 mg/m ³
USA OSHA	OSHA PEL (TWA) [1]	3.5 mg/m ³
Silica, amorphous, precipitated and gel (112926-00-8)		
USA OSHA	OSHA PEL (TWA) [1]	20 mppcf
USA OSHA	OSHA PEL (TWA) [2]	20 mppcf , 80/(SiO ₂) mg/m ³ (See 29 CFR 1910.1000 TABLE Z-3)
Diethylene glycol monobutyl ether (112-34-5)		
USA ACGIH	ACGIH OEL TWA [ppm]	10 ppm (inhalable fraction and vapor)


8.2. Exposure Controls

Appropriate Engineering Controls

: Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing

: Chemically resistant materials and fabrics.

Hand Protection

: Wear protective gloves.

Eye and Face Protection

: Chemical safety goggles.

Skin and Body Protection

: Wear suitable protective clothing.

Respiratory Protection

: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information

: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Clear
Odor	: Fruity
Odor Threshold	: No data available
pH	: 8.0
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: No data available
Flash Point	: > 93 °C (199.4 °F) (Closed cup)
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapor Pressure	: No data available
Heat Of Combustion	: No data available
Relative Vapor Density at 20°C	: No data available
Relative Density	: 0.995
Relative gas density	: No data available

Hybrid Solutions Trim Restorer

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

Solubility	: No data available
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: Liquid
Viscosity, Dynamic	: 150 cP
9.2. Other Information	
VOC content (California)	: 0 %
% NVM by Weight	: 29 %

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Hazardous reactions will not occur under normal conditions.

10.2. Chemical Stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

10.4. Conditions to Avoid

Direct sunlight, extremely high or low temperatures, and incompatible materials.

10.5. Incompatible Materials

Strong acids, strong bases, strong oxidizers.

10.6. Hazardous Decomposition Products

Not expected to decompose under ambient conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

Cyclohexane (110-82-7)	
LD50 Oral Rat	12705 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 32880 mg/m ³ (Exposure time: 4 h)
Ethyl acetate (141-78-6)	
LD50 Oral Rat	5620 mg/kg
LD50 Dermal Rabbit	> 18000 mg/kg
LC50 Inhalation Rat	> 7348 mg/l/4h (calculated off of 6hr test results)
LC50 Inhalation Rat	4000 ppm/4h
Acrylic acid (79-10-7)	
LD50 Oral Rat	1337 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	11.1 mg/l (Exposure time: 1 h)
LC50 Inhalation Rat	2.75 mg/l/4h
1,2-Benzisothiazol-3(2H)-one (2634-33-5)	
LD50 Oral Rat	1020 mg/kg
LD50 Dermal Rat	> 2000 mg/kg
Sodium hydroxide (1310-73-2)	
LD50 Oral Rat	325 mg/kg
Graphite (7782-42-5)	
LD50 Oral Rat	> 2000 mg/kg
LC50 Inhalation Rat	> 2000 mg/m ³ (Exposure time: 4 h)
Propylene glycol monomethyl ether acetate (108-65-6)	
LD50 Oral Rat	8532 mg/kg
LD50 Dermal Rabbit	> 5 g/kg
LC50 Inhalation Rat	16000 mg/m ³ (Exposure time: 6 h)
1,2-Propanediol (57-55-6)	
LD50 Oral Rat	20 g/kg

Hybrid Solutions Trim Restorer

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

LD50 Dermal Rabbit	20800 mg/kg
Carbon black (1333-86-4)	
LD50 Oral Rat	> 8000 mg/kg
LC50 Inhalation Rat	> 4.6 mg/m ³ (Exposure time: 4 h)
Diethylene glycol monobutyl ether (112-34-5)	
LD50 Oral Rat	5660 mg/kg
LD50 Dermal Rabbit	2700 mg/kg

Skin Corrosion/Irritation: Not classified

pH: 8.0

Serious Eye Damage/Irritation: Not classified

pH: 8.0

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Suspected of causing cancer.

Acrylic acid (79-10-7)	
IARC group	3
Carbon black (1333-86-4)	
IARC group	2B
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Silica, amorphous, precipitated and gel (112926-00-8)	
IARC group	3

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: Suspected of causing cancer. May cause an allergic skin reaction.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General : Not classified.

Cyclohexane (110-82-7)	
LC50 Fish 1	3.96 – 5.18 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	0.9 mg/l
LC50 Fish 2	23.03 – 42.07 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
NOEC Chronic Algae	0.94 mg/l
Ethyl acetate (141-78-6)	
LC50 Fish 1	220 – 250 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	560 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 Fish 2	484 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
NOEC Chronic Crustacea	2.4 mg/l
Acrylic acid (79-10-7)	
LC50 Fish 1	222 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])
EC50 - Crustacea [1]	95 mg/l (Exposure time: 48 h - Species: Daphnia magna)
ErC50 (Algae)	0.13 mg/l
NOEC Chronic Algae	0.016 mg/l
1,2-Benzisothiazol-3(2H)-one (2634-33-5)	
EC50 - Crustacea [1]	0.99 mg/l
Sodium hydroxide (1310-73-2)	
LC50 Fish 1	45.4 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])

Hybrid Solutions Trim Restorer

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

EC50 - Crustacea [1]	40 mg/l
Graphite (7782-42-5)	
LC50 Fish 1	> 100 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static])
EC50 - Crustacea [1]	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna [static])
ErC50 (Algae)	> 100 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata [static])
NOEC Chronic Fish	> 100 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static])
NOEC Chronic Crustacea	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna [static])
NOEC Chronic Algae	> 100 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata [static])
Propylene glycol monomethyl ether acetate (108-65-6)	
LC50 Fish 1	161 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [1]	> 500 mg/l (Exposure time: 48 h - Species: Daphnia magna)
1,2-Propanediol (57-55-6)	
LC50 Fish 1	51600 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 - Crustacea [1]	10000 mg/l (Exposure time: 24 h - Species: Daphnia magna)
LC50 Fish 2	41 – 47 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 - Crustacea [2]	1000 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
NOEC Chronic Crustacea	1000 mg/l
NOEC Chronic Algae	1000 mg/l
Carbon black (1333-86-4)	
EC50 - Crustacea [1]	5600 mg/l (Exposure time: 24 h - Species: Daphnia magna)
Silica, amorphous, precipitated and gel (112926-00-8)	
LC50 Fish 1	10000 mg/l
Diethylene glycol monobutyl ether (112-34-5)	
LC50 Fish 1	1300 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 - Crustacea [1]	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna)
12.2. Persistence and Degradability	
Hybrid Solutions Graphene Acrylic Trim Restorer	
Persistence and Degradability	Not established.
12.3. Bioaccumulative Potential	
Hybrid Solutions Graphene Acrylic Trim Restorer	
Bioaccumulative Potential	Not established.
Cyclohexane (110-82-7)	
Partition coefficient n-octanol/water (Log Pow)	3.44
Ethyl acetate (141-78-6)	
BCF Fish 1	30
Partition coefficient n-octanol/water (Log Pow)	0.6
Acrylic acid (79-10-7)	
Partition coefficient n-octanol/water (Log Pow)	0.38 – 0.46 (at 25 °C)
1,2-Benzisothiazol-3(2H)-one (2634-33-5)	
Partition coefficient n-octanol/water (Log Pow)	1.3 (at 25 °C)
Propylene glycol monomethyl ether acetate (108-65-6)	
Partition coefficient n-octanol/water (Log Pow)	0.43
1,2-Propanediol (57-55-6)	
BCF Fish 1	< 1
Partition coefficient n-octanol/water (Log Pow)	-0.92
Diethylene glycol monobutyl ether (112-34-5)	

Hybrid Solutions Trim Restorer

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

BCF Fish 1	(no bioconcentration expected)
-------------------	--------------------------------

12.4. Mobility in Soil

No additional information available

12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, and international regulations.

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Not regulated for transport

14.2. In Accordance with IMDG

Not regulated for transport

14.3. In Accordance with IATA

Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

All components in this mixture are listed on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, have been exempted, are not listed, not disclosed due to CBI requirements or disclosure rules according to the relevant regulation.

Hybrid Solutions Trim Restorer	
SARA Section 311/312 Hazard Classes	Health hazard - Respiratory or skin sensitization Health hazard - Carcinogenicity
Cyclohexane (110-82-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	1000 lb
SARA Section 313 - Emission Reporting	1 %
Ethyl acetate (141-78-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
CERCLA RQ	5000 lb
Acrylic acid (79-10-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	5000 lb
SARA Section 313 - Emission Reporting	1 %
1,2-Benzisothiazol-3(2H)-one (2634-33-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Sodium hydroxide (1310-73-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
CERCLA RQ	1000 lb
Graphite (7782-42-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Propylene glycol monomethyl ether acetate (108-65-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
EPA TSCA Regulatory Flag	PMN - PMN - indicates a commenced PMN substance.
1,2-Propanediol (57-55-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	

Hybrid Solutions Trim Restorer

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

Carbon black (1333-86-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Diethylene glycol monobutyl ether (112-34-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. US State Regulations

Cyclohexane (110-82-7)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Ethyl acetate (141-78-6)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Acrylic acid (79-10-7)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Sodium hydroxide (1310-73-2)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Graphite (7782-42-5)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

1,2-Propanediol (57-55-6)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Carbon black (1333-86-4)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

Silica, amorphous, precipitated and gel (112926-00-8)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision : 03/05/2024
Formula Identification Number : 40881
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200
The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret [29 CFR 1910.1200].

GHS Full Text Phrases:

Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1

Hybrid Solutions Trim Restorer

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 2	Carcinogenicity Category 2
Comb. Dust	Combustible Dust
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
Skin Sens. 1A	Skin sensitization, category 1A
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H290	May be corrosive to metals
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

NFPA Health Hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA Fire Hazard

: 1 - Materials that must be preheated before ignition can occur.

NFPA Reactivity Hazard

: 0 - Material that in themselves are normally stable, even under fire conditions.



HMIS III Rating

Health : 2 Moderate Hazard

Flammability : 1 Slight Hazard

Physical : 0 Minimal Hazard

Legal disclaimer: Turtle Wax, Inc. All rights reserved.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any particular conditions or process. Such information is, to the best of our knowledge and belief, accurate and reliable as of the date issued. No warranty, guarantee or representation is made to its accuracy, reliability or

Hybrid Solutions Trim Restorer

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

US GHS SDS

completeness. It is the responsibility of the user or processor to satisfy themselves as to the suitability of such information for their own particular circumstances, conditions or use, including transportation, storage and disposal which are outside of our control.

SDS US (GHS HazCom)