



Valvoline™
Global

SAFETY DATA SHEET
ZEREX™ G05® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:
04/12/2025

SECTION 1. IDENTIFICATION

Product name : ZEREX™ G05® 50/50
Antifreeze Coolant

Product code : 3658

Manufacturer or supplier's details

Company name of supplier : Valvoline Global Operations

Address : 100 Valvoline Way
Lexington, KY 40509
United States of America (USA)

Telephone : 1-800-TEAMVAL (1-800-832-6825)

E-mail address : SDS@valvolineglobal.com

Emergency telephone number : +1-800-VALVOLINE (+1-800-825-8654)

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity (Oral) : Category 4

Carcinogenicity : Category 1B

Reproductive toxicity : Category 1B

Specific target organ toxicity : Category 2 (Kidney, Liver)
- repeated exposure (Oral)

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H302 Harmful if swallowed.
H350 May cause cancer.
H360 May damage fertility or the unborn child.



SAFETY DATA SHEET
ZEREX™ G05® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:
04/12/2025

H373 May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.

Precautionary statements

:

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe mist or vapours.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

:

Mixture

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|---------------------------|-----------|-----------------------|
| ETHYLENE GLYCOL | 107-21-1 | >= 50 - < 60 |
| SODIUM BENZOATE | 532-32-1 | >= 1 - < 1.5 |
| SODIUM BORATE DECAHYDRATE | 1303-96-4 | >= 0.5 - < 1 |
| SODIUM NITRITE | 7632-00-0 | >= 0.1 - < 0.5 |
| SODIUM NITRATE | 7631-99-4 | >= 0.1 - < 0.5 |

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice

:

Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.



Valvoline™
Global

SAFETY DATA SHEET
ZEREX™ G05® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:
04/12/2025

| | |
|---|--|
| | Do not leave the victim unattended. |
| If inhaled | : If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician. |
| In case of eye contact | : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. |
| If swallowed | : Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital. |
| Most important symptoms and effects, both acute and delayed | : No symptoms known or expected. Harmful if swallowed. May cause cancer. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure if swallowed. |
| Notes to physician | : No hazards which require special first aid measures. Treat symptomatically. |

SECTION 5. FIREFIGHTING MEASURES

| | |
|---|---|
| Suitable extinguishing media | : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. |
| Unsuitable extinguishing media | : High volume water jet |
| Specific hazards during firefighting | : Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : No hazardous combustion products are known |
| Further information | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus for firefighting if necessary. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

| | |
|--|--------------------------------------|
| Personal precautions, protective equipment and | : Use personal protective equipment. |
|--|--------------------------------------|



SAFETY DATA SHEET
 ZEREX™ G05® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:
04/12/2025

emergency procedures

Environmental precautions : Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.
 If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
 Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours/dust.
 Avoid exposure - obtain special instructions before use.
 Avoid contact with skin and eyes.
 For personal protection see section 8.
 Smoking, eating and drinking should be prohibited in the application area.
 Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
 Observe label precautions.
 Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|-----------------|----------|-------------------------------|--|-------|
| ETHYLENE GLYCOL | 107-21-1 | TWA (Vapour) | 25 ppm | ACGIH |
| | | STEL (Vapour) | 50 ppm | ACGIH |
| | | STEL (Inhalable) | 10 mg/m3 | ACGIH |



ValvolineTM
Global

SAFETY DATA SHEET
ZEREXTM G05® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:
04/12/2025

| | | | | |
|------------------------------|-----------|--|---------------------------------|-----------|
| | | fraction, Aerosol only) | | |
| | | C | 50 ppm 125 mg/m ³ | OSHA P0 |
| SODIUM BENZOATE | 532-32-1 | TWA (Inhalable particulate matter) | 2.5 mg/m ³ | ACGIH |
| SODIUM BORATE DECAHYDRATE | 1303-96-4 | TWA | 5 mg/m ³ | NIOSH REL |
| | | TWA | 10 mg/m ³ | OSHA P0 |
| | | TWA (Inhalable particulate matter) | 2 mg/m ³ (Borate) | ACGIH |
| | | STEL (Inhalable particulate matter) | 6 mg/m ³ (Borate) | ACGIH |

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : light yellow

Odour : No data available

Odour Threshold : No data available

pH : Average 8.0

Melting point/freezing point : No data available



Valvoline™
Global

SAFETY DATA SHEET
ZEREX™ G05® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:
04/12/2025

| | | |
|--|---|---|
| Boiling point/boiling range | : | 225 °F / 107 °C (1013.3 hPa) |
| Flash point | : | > 250.0 °F / > 121.1 °C Method: Cleveland open cup |
| Evaporation rate | : | No data available |
| Flammability (solid, gas) | : | No data available |
| Self-ignition | : | No data available |
| Upper explosion limit / Upper flammability limit | : | 15.3 %(V) |
| Lower explosion limit / Lower flammability limit | : | 1.7 %(V) |
| Vapour pressure | : | 1.800 mmHg (68.00 °F / 20.00 °C) |
| Relative vapour density | : | > 1.000 AIR=1 |
| Relative density | : | No data available |
| Density | : | 1.0779 g/cm ³ (60.01 °F / 15.56 °C) |
| Solubility(ies) | : | |
| Water solubility | : | No data available |
| Solubility in other solvents | : | No data available |
| Partition coefficient: n-octanol/water | : | No data available |
| Decomposition temperature | : | No data available |
| Viscosity | : | |
| Viscosity, dynamic | : | No data available |
| Viscosity, kinematic | : | No data available |
| Oxidizing properties | : | No data available |

SECTION 10. STABILITY AND REACTIVITY

| | | |
|------------|---|---|
| Reactivity | : | No decomposition if stored and applied as directed. |
|------------|---|---|



Valvoline™
Global

SAFETY DATA SHEET
ZEREX™ G05® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:
04/12/2025

| | | |
|------------------------------------|---|---|
| Chemical stability | : | No decomposition if stored and applied as directed. |
| Possibility of hazardous reactions | : | No decomposition if stored and applied as directed. |
| Conditions to avoid | : | excessive heat Exposure to moisture |
| Incompatible materials | : | Acids Aldehydes Alkali metals Alkaline earth metals aluminum Fluorine Hydrogen fluoride iron salts Lead lithium sodium strong bases Strong oxidizing agents Sulphur compounds Zinc Peroxides |
| Hazardous decomposition products | : | No hazardous decomposition products are known. |

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity : Acute toxicity estimate: 977.4 mg/kg
Method: Calculation method

Components:

ETHYLENE GLYCOL:

Acute oral toxicity : LD0 (Human): estimated 1.56 g/kg

Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : LC50 (Rat): 10.9 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): 9,530 mg/kg



SAFETY DATA SHEET
ZEREX™ G05® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:
04/12/2025

Acute toxicity (other routes of administration) : LD50 (Rat): 5,010 mg/kg
Application Route: Intraperitoneal

LD50 (Rat): 3,260 mg/kg
Application Route: Intravenous

SODIUM BENZOATE:

Acute oral toxicity : LD50 (Rat, male and female): 3,450 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 12.2 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Remarks: The toxicological data has been taken from products of similar composition.

SODIUM BORATE DECAHYDRATE:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity
Remarks: The toxicological data has been taken from products of similar composition.
No mortality observed at this dose.

Acute inhalation toxicity : LC50 (Rat): > 2.04 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
GLP: yes
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: The toxicological data has been taken from products of similar composition.
No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
GLP: yes
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: The toxicological data has been taken from products of similar composition.
No mortality observed at this dose.

SODIUM NITRITE:

Acute oral toxicity : LD50 (Rat): 180 mg/kg

Acute inhalation toxicity : LC50 (Rat): 5.5 mg/l



Valvoline™
Global

SAFETY DATA SHEET
ZEREX™ G05® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:
04/12/2025

Exposure time: 4 h
Test atmosphere: dust/mist

SODIUM NITRATE:

Acute oral toxicity : LD50 (Rat): ca. 3,430 mg/kg
Method: OECD Test Guideline 401

Skin corrosion/irritation

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Species : Rabbit
Result : No skin irritation

SODIUM BENZOATE:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

SODIUM BORATE DECAHYDRATE:

Species : Rabbit
Result : Slight, transient irritation

SODIUM NITRITE:

Assessment : No skin irritation
Result : No skin irritation

SODIUM NITRATE:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : The toxicological data has been taken from products of similar composition.

Serious eye damage/eye irritation

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Result : Slight, transient irritation



ValvolineTM
Global

SAFETY DATA SHEET
ZEREXTM G05® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:
04/12/2025

SODIUM BENZOATE:

Species : Rabbit
Result : Irritating to eyes.
Method : OECD Test Guideline 405

SODIUM BORATE DECAHYDRATE:

Species : Rabbit
Result : Irritating to eyes.

SODIUM NITRITE:

Result : Irritating to eyes.
Assessment : Irritating to eyes.

SODIUM NITRATE:

Species : Rabbit
Result : Irritating to eyes.
Method : OECD Test Guideline 405

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Test Type : Maximisation Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.

SODIUM BORATE DECAHYDRATE:

Test Type : Buehler Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Remarks : The toxicological data has been taken from products of similar composition.

Germ cell mutagenicity

Not classified based on available information.

Components:

ETHYLENE GLYCOL:



ValvolineTM
Global

SAFETY DATA SHEET
ZEREXTM G05® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:
04/12/2025

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Carcinogenicity

May cause cancer.

IARC Group 2A: Probably carcinogenic to humans
SODIUM NITRITE 7632-00-0
(nitrite (ingested) under conditions that result in endogenous nitrosation)
Group 2A: Probably carcinogenic to humans
SODIUM NITRATE 7631-99-4
(nitrate (ingested) under conditions that result in endogenous nitrosation)

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

May damage fertility or the unborn child.

Components:

SODIUM BORATE DECAHYDRATE:

Reproductive toxicity - Assessment : Clear evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.

Components:

ETHYLENE GLYCOL:

Exposure routes : Ingestion
Target Organs : Kidney, Liver
Assessment : May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.



SAFETY DATA SHEET
ZEREX™ G05® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:
04/12/2025

Experience with human exposure

Components:

ETHYLENE GLYCOL:

Ingestion : Target Organs: Kidney

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 27,540 mg/l
Exposure time: 96 h
Test Type: static test

LC50 (Pimephales promelas (fathead minnow)): 8,050 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 6,500 - 13,000 mg/l
End point: Growth inhibition
Exposure time: 7 Days

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 32,000 mg/l
Exposure time: 7 d

Toxicity to daphnia and other aquatic invertebrates : NOEC (Daphnia magna (Water flea)): 24,000 mg/l
Exposure time: 7 d



Valvoline™
Global

SAFETY DATA SHEET
ZEREX™ G05® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:
04/12/2025

(Chronic toxicity)

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

SODIUM BENZOATE:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Method: Static
Remarks: Mortality

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Method: Static
Remarks: Mortality

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

SODIUM BORATE DECAHYDRATE:

Toxicity to fish : LC50 (Fish): > 100 mg/l
Exposure time: 96 h
Remarks: The toxicological data has been taken from products of similar composition.

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 133 mg/l
Exposure time: 48 h
Test Type: static test
Remarks: The toxicological data has been taken from products of similar composition.

Toxicity to algae/aquatic plants : NOEC (Dunaliella tertiolecta (marine algae)): 50 mg/l
End point: Growth inhibition
Exposure time: 240 h
Test Type: static test
Remarks: Information refers to the main component.

Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): 13 mg/l
Exposure time: 4 d
Remarks: Information refers to the main component.



SAFETY DATA SHEET
ZEREX™ G05® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:
04/12/2025

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 16.6 mg/l
Exposure time: 28 d
Test Type: flow-through test
Remarks: Information refers to the main component.

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

SODIUM NITRITE:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.35 - 3.81 mg/l
Exposure time: 96 h
Test Type: flow-through test

LC50 (Oncorhynchus mykiss (rainbow trout)): 0.54 - 26.3 mg/l
Exposure time: 96 h
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 15.4 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC (Ictalurus catus (catfish)): 6.16 mg/l
Exposure time: 31 d
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 9.86 mg/l
Exposure time: 80 d
Test Type: static test

Toxicity to microorganisms : EC10 (activated sludge): 210 mg/l
Exposure time: 3 h
Test Type: Static
Method: OECD Test Guideline 209

Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 1; Very toxic to aquatic life.

Chronic aquatic toxicity : Not classified based on available information.



Valvoline™
Global

SAFETY DATA SHEET
ZEREX™ G05® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:
04/12/2025

SODIUM NITRATE:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1,355 - 2,063 mg/l
Exposure time: 96 h
Method: Static
Remarks: Mortality

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 3,581 mg/l
Exposure time: 48 h
Method: Static

LC50 (Daphnia magna (Water flea)): 665 mg/l
Exposure time: 96 h
Method: Static

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Persistence and degradability

Components:

ETHYLENE GLYCOL:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90 - 100 %
Exposure time: 10 d
Method: OECD Test Guideline 301

SODIUM BENZOATE:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 88 %
Exposure time: 28 d
Method: OECD Test Guideline 301

Bioaccumulative potential

Components:

ETHYLENE GLYCOL:

Bioaccumulation : Species: Crayfish (Procambarus)
Bioconcentration factor (BCF): 0.27
Exposure time: 61 d
Concentration: 1000 mg/l



Valvoline™
Global

SAFETY DATA SHEET
ZEREX™ G05® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:
04/12/2025

Method: Flow through

Partition coefficient: n-octanol/water : log Pow: -1.36

SODIUM NITRITE:

Partition coefficient: n-octanol/water : log Pow: -3.700 (77 °F / 25 °C)

Mobility in soil

Components:

SODIUM NITRITE:

Stability in soil : Remarks: Not expected to adsorb on soil.

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

Global warming potential

Assessment Report of the Intergovernmental Panel on Climate Change (IPCC) of the United Nations Framework Convention on Climate Change (UNFCCC)

Components:

OCTAMETHYLCYCLOTETRASILOXANE:

20-year global warming potential: 2.66
100-year global warming potential: 0.739
500-year global warming potential: 0.211
Atmospheric lifetime: 0.027 yr
Radiative efficiency: 0.12 Wm²ppb
Further information: Miscellaneous compounds

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.



SAFETY DATA SHEET
ZEREX™ G05® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:
04/12/2025

Contaminated packaging : Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|------------|----------|--------------------|-----------------------------|
| METHANOL | 67-56-1 | 100 | 100 (F003) |
| TOLUENE | 108-88-3 | 100 | 100 (F005) |

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.



SAFETY DATA SHEET
ZEREX™ G05® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:
04/12/2025

SARA 311/312 Hazards : Acute toxicity (any route of exposure)
Carcinogenicity
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

| | | |
|----------|----------|----------------|
| ETHYLENE | 107-21-1 | >= 50 - < 70 % |
| GLYCOL | | |

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

| | | |
|-----------------|----------|----------------|
| ETHYLENE GLYCOL | 107-21-1 | >= 50 - < 70 % |
|-----------------|----------|----------------|

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

| | | |
|-----------------|----------|----------------|
| ETHYLENE GLYCOL | 107-21-1 | >= 50 - < 70 % |
| SODIUM BENZOATE | 532-32-1 | >= 1 - < 5 % |

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

| | | |
|------------------|-----------|----------------|
| SODIUM NITRITE | 7632-00-0 | >= 0.1 - < 1 % |
| SODIUM HYDROXIDE | 1310-73-2 | >= 0 - < 0.1 % |
| TOLUENE | 108-88-3 | >= 0 - < 0.1 % |

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

| | | |
|------------------|-----------|----------------|
| SODIUM NITRITE | 7632-00-0 | >= 0.1 - < 1 % |
| SODIUM HYDROXIDE | 1310-73-2 | >= 0 - < 0.1 % |
| TOLUENE | 108-88-3 | >= 0 - < 0.1 % |

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

| | |
|-----------------|-----------|
| ETHYLENE GLYCOL | 107-21-1 |
| WATER | 7732-18-5 |

Pennsylvania Right To Know

| | |
|-----------------|-----------|
| ETHYLENE GLYCOL | 107-21-1 |
| WATER | 7732-18-5 |



SAFETY DATA SHEET
 ZEREX™ G05® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:
04/12/2025

| | |
|------------------|-----------|
| SODIUM NITRITE | 7632-00-0 |
| SODIUM HYDROXIDE | 1310-73-2 |

Maine Chemicals of High Concern

| | |
|------------------------------|-----------|
| WATER | 7732-18-5 |
| TOLUENE | 108-88-3 |
| OCTAMETHYLCYCLOTETRASILOXANE | 556-67-2 |

Vermont Chemicals of High Concern

| | |
|------------------------------|-----------|
| ETHYLENE GLYCOL | 107-21-1 |
| WATER | 7732-18-5 |
| TOLUENE | 108-88-3 |
| OCTAMETHYLCYCLOTETRASILOXANE | 556-67-2 |

Washington Chemicals of High Concern

| | |
|-----------------|-----------|
| ETHYLENE GLYCOL | 107-21-1 |
| WATER | 7732-18-5 |
| TOLUENE | 108-88-3 |

California Prop. 65

WARNING: This product can expose you to chemicals including ETHYLENE GLYCOL, TOLUENE, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

| | |
|-----------------|----------|
| ETHYLENE GLYCOL | 107-21-1 |
|-----------------|----------|

California Permissible Exposure Limits for Chemical Contaminants

| | |
|-----------------|----------|
| ETHYLENE GLYCOL | 107-21-1 |
|-----------------|----------|

The components of this product are reported in the following inventories:

- TCSI : Not in compliance with the inventory
- TSCA : All substances listed as active on the TSCA inventory
- AIIC : All components are listed on the inventory, regulatory obligations/restrictions apply
- DSL : All components of this product are on the Canadian DSL
- ENCS : Not in compliance with the inventory
- KECI : Not in compliance with the inventory
- PICCS : Not in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- NZIoC : Not in compliance with the inventory



Valvoline™
Global

SAFETY DATA SHEET
ZEREX™ G05® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:
04/12/2025

TSCA list

No substances are subject to a Significant New Use Rule.

The following substance(s) is/are subject to TSCA 12(b) export notification requirements:
SODIUM NITRITE 7632-00-0


Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

| | | |
|------------------------|---|----------|
| HEALTH | * | 2 |
| FLAMMABILITY | | 1 |
| PHYSICAL HAZARD | | 0 |

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIH / STEL : Short-term exposure limit
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- OSHA P0 / TWA : 8-hour time weighted average



Valvoline
Global

SAFETY DATA SHEET
ZEREX™ G05® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:
04/12/2025

OSHA P0 / C : Ceiling limit

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 06/29/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN



ValvolineTM

Global

SAFETY DATA SHEET
ZEREXTM G05® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:
04/12/2025

Internal information : R0321370