



SAFETY DATA SHEET
ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 08/09/2023

Print Date:
04/13/2025

SECTION 1. IDENTIFICATION

Product name : ZEREX™ G30® 50/50
Antifreeze Coolant

Product code : ZXG30RU2

Manufacturer or supplier's details

Company name of supplier : Valvoline Global Operations

Address : 100 Valvoline Way
Lexington, KY 40509
United States of America (USA)

Telephone : 1-800-TEAMVAL (1-800-832-6825)

E-mail address : SDS@valvolineglobal.com

Emergency telephone number : +1-800-VALVOLUME (+1-800-825-8654)

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity (Oral) : Category 4

Specific target organ toxicity - repeated exposure (Oral) : Category 2 (Kidney, Liver)

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H302 Harmful if swallowed.
H373 May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.

Precautionary statements : **Prevention:**
P260 Do not breathe mist or vapours.



SAFETY DATA SHEET
ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 08/09/2023

Print Date:
04/13/2025

P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P314 Get medical advice/ attention if you feel unwell.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components

Chemical name	CAS-No.	Concentration (% w/w)
ETHYLENE GLYCOL	107-21-1	>= 40 - < 50

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : No symptoms known or expected.
Harmful if swallowed.
May cause damage to organs through prolonged or repeated exposure if swallowed.
- Notes to physician : Treat symptomatically.



Valvoline™
Global

SAFETY DATA SHEET
ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 08/09/2023

Print Date:
04/13/2025

No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Unsuitable extinguishing media : High volume water jet
- Hazardous combustion products : No hazardous combustion products are known
- Further information : Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Environmental precautions : Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapours/dust.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.



SAFETY DATA SHEET
 ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 08/09/2023

Print Date:
04/13/2025

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ETHYLENE GLYCOL	107-21-1	TWA (Vapour)	25 ppm	ACGIH
		STEL (Vapour)	50 ppm	ACGIH
		STEL (Inhalable fraction, Aerosol only)	10 mg/m3	ACGIH
		C	50 ppm 125 mg/m3	OSHA P0

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : pink

Odour : No data available

Odour Threshold : No data available

pH : Average 8.3

Melting point/freezing point : No data available



ValvolineTM
Global

SAFETY DATA SHEET
ZEREXTM G30® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 08/09/2023

Print Date:
04/13/2025

Boiling point/boiling range	:	225 °F / 107 °C (1013 hPa)
Flash point	:	> 250 °F / > 121 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	15.3 %(V) GLP: Calculated Explosive Limit
Lower explosion limit / Lower flammability limit	:	3.2 %(V) GLP: Calculated Explosive Limit
Vapour pressure	:	23.3333333 hPa (68 °F / 20 °C) Calculated Vapor Pressure
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	1.0740 g/cm ³ (60.1 °F / 15.6 °C)
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Oxidizing properties	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous	:	No decomposition if stored and applied as directed.



Valvoline™
Global

SAFETY DATA SHEET
ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 08/09/2023

Print Date:
04/13/2025

reactions
Conditions to avoid : excessive heat
Incompatible materials : Aldehydes
Alkali metals
Alkaline earth metals
Strong acids
strong alkalis
Strong oxidizing agents
Sulphur compounds
Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity : Acute toxicity estimate: 1,006 mg/kg
Method: Calculation method

Components:

ETHYLENE GLYCOL:

Acute oral toxicity : LD0 (Human): estimated 1.56 g/kg

Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : LC50 (Rat): 10.9 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): 9,530 mg/kg

Acute toxicity (other routes of administration) : LD50 (Rat): 5,010 mg/kg
Application Route: Intraperitoneal

LD50 (Rat): 3,260 mg/kg
Application Route: Intravenous

Skin corrosion/irritation

Not classified based on available information.



Valvoline™
Global

SAFETY DATA SHEET
ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 08/09/2023

Print Date:
04/13/2025

Components:

ETHYLENE GLYCOL:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Result : Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Test Type : Maximisation Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Carcinogenicity

Not classified based on available information.

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.



Valvoline™
Global

SAFETY DATA SHEET
ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 08/09/2023

Print Date:
04/13/2025

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.

Components:

ETHYLENE GLYCOL:

Exposure routes : Ingestion
Target Organs : Kidney, Liver
Assessment : May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Components:

ETHYLENE GLYCOL:

Ingestion : Target Organs: Kidney

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.



SAFETY DATA SHEET
ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 08/09/2023

Print Date:
04/13/2025

Components:

ETHYLENE GLYCOL:

- Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 27,540 mg/l
Exposure time: 96 h
Test Type: static test
- LC50 (Pimephales promelas (fathead minnow)): 8,050 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other : LC50 (Daphnia magna (Water flea)): > 10,000 mg/l
aquatic invertebrates : Exposure time: 48 h
Test Type: static test
- Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (green algae)): 6,500 -
plants : 13,000 mg/l
End point: Growth inhibition
Exposure time: 7 Days
- Toxicity to fish (Chronic : NOEC (Pimephales promelas (fathead minnow)): 32,000 mg/l
toxicity) : Exposure time: 7 d
- Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): 24,000 mg/l
aquatic invertebrates : Exposure time: 7 d
(Chronic toxicity)

Ecotoxicology Assessment

- Acute aquatic toxicity : Not classified based on available information.
- Chronic aquatic toxicity : Not classified based on available information.

Persistence and degradability

Components:

ETHYLENE GLYCOL:

- Biodegradability : Result: Readily biodegradable.
Biodegradation: 90 - 100 %
Exposure time: 10 d
Method: OECD Test Guideline 301

Bioaccumulative potential

Components:

ETHYLENE GLYCOL:

- Bioaccumulation : Species: Crayfish (Procambarus)



ValvolineTM
Global

SAFETY DATA SHEET
ZEREXTM G30® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 08/09/2023

Print Date:
04/13/2025

Bioconcentration factor (BCF): 0.27
Exposure time: 61 d
Concentration: 1000 mg/l
Method: Flow through

Partition coefficient: n-
octanol/water : log Pow: -1.36

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82
Protection of Stratospheric Ozone - CAA Section 602 Class I
Substances
Remarks: This product neither contains, nor was
manufactured with a Class I or Class II ODS as defined by the
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +
B).

Additional ecological
information : No data available

Global warming potential

**Assessment Report of the Intergovernmental Panel on Climate Change (IPCC) of the
United Nations Framework Convention on Climate Change (UNFCCC)**

Components:

OCTAMETHYLCYCLOTETRASILOXANE:

20-year global warming potential: 2.66
100-year global warming potential: 0.739
500-year global warming potential: 0.211
Atmospheric lifetime: 0.027 yr
Radiative efficiency: 0.12 Wm²ppb
Further information: Miscellaneous compounds

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with
chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.



ValvolineTM
Global

SAFETY DATA SHEET
ZEREXTM G30[®] 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 08/09/2023

Print Date:
04/13/2025

Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
TOLUENE	108-88-3	100	100 (F005)

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards

: Acute toxicity (any route of exposure)
Specific target organ toxicity (single or repeated exposure)



Valvoline™
Global

SAFETY DATA SHEET
ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 08/09/2023

Print Date:
04/13/2025

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

ETHYLENE 107-21-1 >= 30 - < 50 %
GLYCOL

Clean Air Act

CAA_90 :

HON_HAP :

HON_SOC : Group I

CAA_111 :

CA AIR

Applicable Degree of Accuracy::

WI HAPS A

Threshold for emissions from stacks less than 25 ft::

Threshold for emissions from stacks 25 to less than 40 ft::

Threshold for emissions from stacks 40 to less than 75 ft::

Threshold for emissions from stacks greater than or equal to 75 ft::

Ambient air standard::

VOC RE :

VOC DI :

VOC EQ :

VOC AE

Reactivity factor::

CA PTACS :

SC TAP

MAC Value::

CA TAC :

CAA_90 :

HON_HAP :

HON_SOC : Group I



SAFETY DATA SHEET
 ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 08/09/2023

Print Date:
04/13/2025

CAA_111	:
CA AIR	Applicable Degree of Accuracy::
WI HAPS A	Threshold for emissions from stacks less than 25 ft:: Threshold for emissions from stacks 25 to less than 40 ft:: Threshold for emissions from stacks 40 to less than 75 ft:: Threshold for emissions from stacks greater than or equal to 75 ft:: Ambient air standard::
VOC RE	:
VOC DI	:
VOC EQ	:
VOC AE	Reactivity factor::
CA PTACS	:
SC TAP	MAC Value::
CA TAC	:

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

ETHYLENE GLYCOL 107-21-1 >= 30 - < 50 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

ETHYLENE GLYCOL 107-21-1 >= 30 - < 50 %

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

SODIUM HYDROXIDE	1310-73-2	>= 0.1 - < 1 %
ADIPIC ACID	124-04-9	>= 0.1 - < 1 %
POTASSIUM HYDROXIDE	1310-58-3	>= 0 - < 0.1 %
TOLUENE	108-88-3	>= 0 - < 0.1 %



Valvoline™
Global

SAFETY DATA SHEET
ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 08/09/2023

Print Date:
04/13/2025

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

SODIUM HYDROXIDE	1310-73-2	>= 0.1 - < 1 %
ADIPIC ACID	124-04-9	>= 0.1 - < 1 %
POTASSIUM HYDROXIDE	1310-58-3	>= 0 - < 0.1 %
TOLUENE	108-88-3	>= 0 - < 0.1 %

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

ETHYLENE GLYCOL	107-21-1
WATER	7732-18-5

Pennsylvania Right To Know

ETHYLENE GLYCOL	107-21-1
WATER	7732-18-5
SODIUM HYDROXIDE	1310-73-2
ADIPIC ACID	124-04-9
POTASSIUM HYDROXIDE	1310-58-3

Maine Chemicals of High Concern

WATER	7732-18-5
TOLUENE	108-88-3
OCTAMETHYLCYCLOTETRASILOXANE	556-67-2
COPPER	7440-50-8

Vermont Chemicals of High Concern

ETHYLENE GLYCOL	107-21-1
WATER	7732-18-5
TOLUENE	108-88-3
OCTAMETHYLCYCLOTETRASILOXANE	556-67-2
COPPER	7440-50-8

Washington Chemicals of High Concern

ETHYLENE GLYCOL	107-21-1
WATER	7732-18-5
TOLUENE	108-88-3
COPPER	7440-50-8

California Prop. 65

WARNING: This product can expose you to chemicals including ETHYLENE GLYCOL, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

ETHYLENE GLYCOL	107-21-1
-----------------	----------



ValvolineTM
Global

SAFETY DATA SHEET
ZEREXTM G30® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 08/09/2023

Print Date:
04/13/2025

California Permissible Exposure Limits for Chemical Contaminants

ETHYLENE GLYCOL

107-21-1

The components of this product are reported in the following inventories:

TCSI	: Not in compliance with the inventory
TSCA	: All substances listed as active on the TSCA inventory
AIIC	: Not in compliance with the inventory
DSL	: All components of this product are on the Canadian DSL
ENCS	: Not in compliance with the inventory
KECI	: Not in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
NZIoC	: Not in compliance with the inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information




SAFETY DATA SHEET
 ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 08/09/2023

Print Date:
04/13/2025

NFPA 704:



HMIS® IV:

HEALTH	*	2
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIH / STEL : Short-term exposure limit
- OSHA P0 / C : Ceiling limit

AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA -



Valvoline[™]
Global

SAFETY DATA SHEET
ZEREX[™] G30[®] 50/50 Antifreeze Coolant

Version: 2.0

Revision Date: 08/09/2023

Print Date:
04/13/2025

National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 08/09/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

Internal information : 000000091711