



**Valvoline™**  
**Global**

**SAFETY DATA SHEET**  
Zerex™ G40® Antifreeze Coolant

Version: 6.0

Revision Date: 01/31/2024

Print Date:  
04/13/2025

---

**SECTION 1. IDENTIFICATION**

Product name : Zerex™ G40®  
Antifreeze Coolant

Product code : 905560

**Manufacturer or supplier's details**

Company name of supplier : Valvoline Global Operations

Address : 100 Valvoline Way  
Lexington, KY 40509  
United States of America (USA)

Telephone : 1-800-TEAMVAL (1-800-832-6825)

E-mail address : SDS@valvolineglobal.com

Emergency telephone number : +1-800-VALVOLINE (+1-800-825-8654)

---

**SECTION 2. HAZARDS IDENTIFICATION**

**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Acute toxicity (Oral) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Specific target organ toxicity - repeated exposure (Oral) : Category 2 (Kidney)

**GHS label elements**

Hazard pictograms :



Signal word : Warning

Hazard statements : H302 Harmful if swallowed.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.



# SAFETY DATA SHEET

Zerex™ G40® Antifreeze Coolant

Version: 6.0

Revision Date: 01/31/2024

Print Date:  
04/13/2025

H373 May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.

Precautionary statements

:

**Prevention:**

P260 Do not breathe mist or vapours.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P280 Wear protective gloves/ eye protection/ face protection.

**Response:**

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.  
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P314 Get medical advice/ attention if you feel unwell.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 Take off contaminated clothing and wash before reuse.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

---

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
ETHYLENE GLYCOL	107-21-1	>= 90 - <= 100
SODIUM HYDROXIDE	1310-73-2	>= 1 - < 5

Actual concentration is withheld as a trade secret

---

## SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.



**SAFETY DATA SHEET**  
Zerex™ G40® Antifreeze Coolant

Version: 6.0

Revision Date: 01/31/2024

Print Date:  
04/13/2025

---

If inhaled	:	If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	:	If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Clean mouth with water and drink afterwards plenty of water. Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	:	No symptoms known or expected. Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. May cause damage to organs through prolonged or repeated exposure if swallowed.
Notes to physician	:	No hazards which require special first aid measures. Treat symptomatically.

---

**SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	:	High volume water jet
Hazardous combustion products	:	No hazardous combustion products are known
Further information	:	Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment.
---	---	------------------------------------



**SAFETY DATA SHEET**  
Zerex™ G40® Antifreeze Coolant

Version: 6.0

Revision Date: 01/31/2024

Print Date:  
04/13/2025

- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapours/dust.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ETHYLENE GLYCOL	107-21-1	TWA (Vapour)	25 ppm	ACGIH
		STEL (Vapour)	50 ppm	ACGIH
		STEL (Inhalable fraction, Aerosol only)	10 mg/m3	ACGIH
		C	50 ppm 125 mg/m3	OSHA P0



**Valvoline™**  
**Global**

## SAFETY DATA SHEET

Zerex™ G40® Antifreeze Coolant

Version: 6.0

Revision Date: 01/31/2024

Print Date:  
04/13/2025

SODIUM HYDROXIDE	1310-73-2	C	2 mg/m3	ACGIH
		C	2 mg/m3	NIOSH REL
		TWA	2 mg/m3	OSHA Z-1
		C	2 mg/m3	OSHA P0

### Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : violet

Odour : No data available

Odour Threshold : No data available

pH : 8.4

Melting point/freezing point : No data available

Boiling point/boiling range : 293 °F / 145 °C  
(1,013.33 hPa)  
Calculated Phase Transition Liquid/Gas

Flash point : > 250 °F / > 121 °C

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available



**Valvoline™**  
**Global**

**SAFETY DATA SHEET**  
Zerex™ G40® Antifreeze Coolant

Version: 6.0

Revision Date: 01/31/2024

Print Date:  
04/13/2025

---

Upper explosion limit / Upper flammability limit	:	15.1 %(V) Method: DIN 51649
Lower explosion limit / Lower flammability limit	:	3.4 %(V) Method: DIN 51649
Vapour pressure	:	2 hPa (68 °F / 20 °C) Calculated Vapor Pressure
Relative vapour density	:	No data available
Relative density	:	1.1231 (60.1 °F / 15.6 °C)
Density	:	1.1231 g/cm <sup>3</sup> (60.1 °F / 15.6 °C)
Solubility(ies)		
Water solubility	:	soluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Oxidizing properties	:	No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed.
Conditions to avoid	:	excessive heat
Incompatible materials	:	Acids Aldehydes Alkali metals Alkaline earth metals aluminum Lead organic nitro compounds sodium strong bases



**Valvoline™**  
**Global**

## SAFETY DATA SHEET

Zerex™ G40® Antifreeze Coolant

Version: 6.0

Revision Date: 01/31/2024

Print Date:  
04/13/2025

Hazardous decomposition products : Strong oxidizing agents  
Sulphur compounds  
Zinc  
Peroxides  
: No hazardous decomposition products are known.  
No hazardous decomposition products are known.

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Harmful if swallowed.

#### Product:

Acute oral toxicity : Acute toxicity estimate: 545.75 mg/kg  
Method: Calculation method

#### Components:

##### **ETHYLENE GLYCOL:**

Acute oral toxicity : LD0 (Human): estimated 1.56 g/kg

Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : LC50 (Rat): 10.9 mg/l  
Exposure time: 1 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): 9,530 mg/kg

Acute toxicity (other routes of administration) : LD50 (Rat): 5,010 mg/kg  
Application Route: Intraperitoneal

LD50 (Rat): 3,260 mg/kg  
Application Route: Intravenous

##### **SODIUM HYDROXIDE:**

Acute oral toxicity : LDLo (Rabbit): 500 mg/kg

Acute inhalation toxicity : Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Moderate respiratory irritant

Acute dermal toxicity : Symptoms: Corrosion



**Valvoline™**  
**Global**

**SAFETY DATA SHEET**  
Zerex™ G40® Antifreeze Coolant

Version: 6.0

Revision Date: 01/31/2024

Print Date:  
04/13/2025

Assessment: The substance or mixture has no acute dermal toxicity

**Skin corrosion/irritation**

Causes skin irritation.

**Product:**

Remarks : May cause skin irritation in susceptible persons.

**Components:**

**ETHYLENE GLYCOL:**

Species : Rabbit  
Result : No skin irritation

**SODIUM HYDROXIDE:**

Result : Corrosive after 3 minutes or less of exposure

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Product:**

Remarks : May cause irreversible eye damage.

**Components:**

**ETHYLENE GLYCOL:**

Result : Slight, transient irritation

**SODIUM HYDROXIDE:**

Result : Corrosive  
Assessment : Corrosive

**Respiratory or skin sensitisation**

**Skin sensitisation**

Not classified due to lack of data.

**Respiratory sensitisation**

Not classified due to lack of data.

**Components:**

**ETHYLENE GLYCOL:**

Test Type : Maximisation Test



**Valvoline™**  
**Global**

## SAFETY DATA SHEET

Zerex™ G40® Antifreeze Coolant

Version: 6.0

Revision Date: 01/31/2024

Print Date:  
04/13/2025

Species : Guinea pig  
Assessment : Does not cause skin sensitisation.

### **SODIUM HYDROXIDE:**

Exposure routes : Skin contact  
Species : Humans  
Result : negative

### **Germ cell mutagenicity**

Not classified due to lack of data.

### **Components:**

#### **ETHYLENE GLYCOL:**

Genotoxicity in vitro : Test Type: Ames test  
Test system: Salmonella typhimurium  
Metabolic activation: with and without metabolic activation  
Result: negative

### **Carcinogenicity**

Not classified due to lack of data.

**IARC** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### **Reproductive toxicity**

Not classified due to lack of data.

#### **STOT - single exposure**

Not classified due to lack of data.

#### **STOT - repeated exposure**

May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.

### **Components:**

#### **ETHYLENE GLYCOL:**

Exposure routes : Ingestion  
Target Organs : Kidney  
Assessment : May cause damage to organs through prolonged or repeated exposure.



**Valvoline™**  
**Global**

## SAFETY DATA SHEET

Zerex™ G40® Antifreeze Coolant

Version: 6.0

Revision Date: 01/31/2024

Print Date:  
04/13/2025

### Aspiration toxicity

Not classified due to lack of data.

### Experience with human exposure

#### Components:

#### ETHYLENE GLYCOL:

Ingestion : Target Organs: Kidney

#### Further information

#### Product:

Remarks : No data available

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Product:

#### Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

#### Components:

#### ETHYLENE GLYCOL:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 27,540 mg/l  
Exposure time: 96 h  
Test Type: static test

LC50 (Pimephales promelas (fathead minnow)): 8,050 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Test Type: static test

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 6,500 - 13,000 mg/l  
End point: Growth inhibition  
Exposure time: 7 Days

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 32,000 mg/l  
Exposure time: 7 d



**Valvoline™**  
**Global**

## SAFETY DATA SHEET

Zerex™ G40® Antifreeze Coolant

Version: 6.0

Revision Date: 01/31/2024

Print Date:  
04/13/2025

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 24,000 mg/l  
Exposure time: 7 d

### Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

### SODIUM HYDROXIDE:

Toxicity to fish : LC50 (Gambusia affinis (Mosquito fish)): 125 mg/l  
Exposure time: 96 h  
Method: Static  
Remarks: Mortality

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 34.59 - 47.13 mg/l  
Exposure time: 48 h  
Remarks: Intoxication

Toxicity to microorganisms : Remarks: Not applicable

### Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

### Persistence and degradability

#### Components:

#### ETHYLENE GLYCOL:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 90 - 100 %  
Exposure time: 10 d  
Method: OECD Test Guideline 301

### Bioaccumulative potential

#### Components:

#### ETHYLENE GLYCOL:

Bioaccumulation : Species: Crayfish (Procambarus)  
Bioconcentration factor (BCF): 0.27  
Exposure time: 61 d  
Concentration: 1000 mg/l  
Method: Flow through



**Valvoline™**  
**Global**

## SAFETY DATA SHEET

Zerex™ G40® Antifreeze Coolant

Version: 6.0

Revision Date: 01/31/2024

Print Date:  
04/13/2025

Partition coefficient: n-octanol/water : log Pow: -1.36

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances  
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

### Global warming potential

**Assessment Report of the Intergovernmental Panel on Climate Change (IPCC) of the United Nations Framework Convention on Climate Change (UNFCCC)**

#### Components:

##### **OCTAMETHYLCYCLOTETRASILOXANE:**

20-year global warming potential: 2.66  
100-year global warming potential: 0.739  
500-year global warming potential: 0.211  
Atmospheric lifetime: 0.027 yr  
Radiative efficiency: 0.12 Wm<sup>2</sup>ppb  
Further information: Miscellaneous compounds

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.



**SAFETY DATA SHEET**  
Zerex™ G40® Antifreeze Coolant

Version: 6.0

Revision Date: 01/31/2024

Print Date:  
04/13/2025

---

**SECTION 14. TRANSPORT INFORMATION**

**International Regulations**

**UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations**

**49 CFR**

Not regulated as a dangerous good

**49 CFR**

Not regulated as a dangerous good

**Special precautions for user**

Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

---

**SECTION 15. REGULATORY INFORMATION**

**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
METHANOL	67-56-1	100	100 (F003)
TOLUENE	108-88-3	100	100 (F005)

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Acute toxicity (any route of exposure)  
Specific target organ toxicity (single or repeated exposure)  
Skin corrosion or irritation  
Serious eye damage or eye irritation



**Valvoline™**  
**Global**

**SAFETY DATA SHEET**

Zerex™ G40® Antifreeze Coolant

Version: 6.0

Revision Date: 01/31/2024

Print Date:  
04/13/2025

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

ETHYLENE GLYCOL	107-21-1	>= 90 - <= 100 %
-----------------	----------	------------------

**Clean Air Act**

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

ETHYLENE GLYCOL	107-21-1	>= 90 - <= 100 %
-----------------	----------	------------------

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

ETHYLENE GLYCOL	107-21-1	>= 90 - <= 100 %
-----------------	----------	------------------

**Clean Water Act**

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

SODIUM HYDROXIDE	1310-73-2	>= 1 - < 5 %
ADIPIC ACID	124-04-9	>= 0.1 - < 1 %
POTASSIUM HYDROXIDE	1310-58-3	>= 0.1 - < 1 %
TOLUENE	108-88-3	>= 0 - < 0.1 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

SODIUM HYDROXIDE	1310-73-2	>= 1 - < 5 %
ADIPIC ACID	124-04-9	>= 0.1 - < 1 %
POTASSIUM HYDROXIDE	1310-58-3	>= 0.1 - < 1 %
TOLUENE	108-88-3	>= 0 - < 0.1 %

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

**US State Regulations**

**Massachusetts Right To Know**

ETHYLENE GLYCOL	107-21-1
WATER	7732-18-5
SODIUM HYDROXIDE	1310-73-2

**Pennsylvania Right To Know**

ETHYLENE GLYCOL	107-21-1
SEBACIC ACID	111-20-6



**Valvoline™**  
**Global**

## SAFETY DATA SHEET

Zerex™ G40® Antifreeze Coolant

Version: 6.0

Revision Date: 01/31/2024

Print Date:  
04/13/2025

SODIUM HYDROXIDE	1310-73-2
ADIPIC ACID	124-04-9
POTASSIUM HYDROXIDE	1310-58-3

### Maine Chemicals of High Concern

WATER	7732-18-5
TOLUENE	108-88-3
OCTAMETHYLCYCLOTETRASILOXANE	556-67-2

### Vermont Chemicals of High Concern

ETHYLENE GLYCOL	107-21-1
WATER	7732-18-5
TOLUENE	108-88-3
OCTAMETHYLCYCLOTETRASILOXANE	556-67-2

### Washington Chemicals of High Concern

ETHYLENE GLYCOL	107-21-1
WATER	7732-18-5
TOLUENE	108-88-3

### California Prop. 65

WARNING: This product can expose you to chemicals including ETHYLENE GLYCOL, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### California List of Hazardous Substances

ETHYLENE GLYCOL	107-21-1
SODIUM HYDROXIDE	1310-73-2

### California Permissible Exposure Limits for Chemical Contaminants

ETHYLENE GLYCOL	107-21-1
SODIUM HYDROXIDE	1310-73-2

### The components of this product are reported in the following inventories:

TCSI	: On the inventory, or in compliance with the inventory
TSCA	: All substances listed as active on the TSCA inventory
AIIC	: On the inventory, or in compliance with the inventory
DSL	: All components of this product are on the Canadian DSL
ENCS	: Not in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory



**Valvoline™**  
**Global**

**SAFETY DATA SHEET**  
Zerex™ G40® Antifreeze Coolant

Version: 6.0

Revision Date: 01/31/2024

Print Date:  
04/13/2025

NZIoC : Not in compliance with the inventory

**TSCA list**

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.


**Inventories**

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

**SECTION 16. OTHER INFORMATION**

**Further information**

**NFPA 704:**



**HMIS® IV:**

<b>HEALTH</b>	*	<b>2</b>
<b>FLAMMABILITY</b>		<b>1</b>
<b>PHYSICAL HAZARD</b>		<b>0</b>

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

**Full text of other abbreviations**

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- ACGIH / TWA : 8-hour, time-weighted average



**Valvoline**<sup>™</sup>

**Global**

## SAFETY DATA SHEET

Zerex<sup>™</sup> G40<sup>®</sup> Antifreeze Coolant

Version: 6.0

Revision Date: 01/31/2024

Print Date:  
04/13/2025

---

ACGIH / STEL	:	Short-term exposure limit
ACGIH / C	:	Ceiling limit
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA P0 / C	:	Ceiling limit
OSHA Z-1 / TWA	:	8-hour time weighted average

AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 01/31/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the



**Valvoline**<sup>TM</sup>

**Global**

## **SAFETY DATA SHEET**

Zerex<sup>TM</sup> G40<sup>®</sup> Antifreeze Coolant

Version: 6.0

Revision Date: 01/31/2024

Print Date:  
04/13/2025

---

specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

Internal information : 000000098616