



**SAFETY DATA SHEET**  
Zerex™ G05® Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:  
04/13/2025

---

**SECTION 1. IDENTIFICATION**

Product name : Zerex™ G05®  
Antifreeze Coolant

Product code : 896522

**Manufacturer or supplier's details**

Company name of supplier : Valvoline Global Operations

Address : 100 Valvoline Way  
Lexington, KY 40509  
United States of America (USA)

Telephone : 1-800-TEAMVAL (1-800-832-6825)

E-mail address : SDS@valvolineglobal.com

Emergency telephone number : +1-800-VALVOLUME (+1-800-825-8654)

---

**SECTION 2. HAZARDS IDENTIFICATION**

**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Acute toxicity (Oral) : Category 4

Carcinogenicity : Category 1B

Reproductive toxicity : Category 1B

Specific target organ toxicity : Category 2 (Kidney, Liver)  
- repeated exposure (Oral)

**GHS label elements**

Hazard pictograms : The hazard pictograms consist of two red diamond-shaped symbols. The first symbol shows a human silhouette with a starburst on the chest, representing a health hazard. The second symbol is a red diamond with a black exclamation mark inside, representing a general hazard.

Signal word : Danger

Hazard statements : H302 Harmful if swallowed.  
H350 May cause cancer.  
H360 May damage fertility or the unborn child.



# SAFETY DATA SHEET

Zerex™ G05® Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:  
04/13/2025

H373 May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.

Precautionary statements

:

### Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe mist or vapours.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

### Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

### Storage:

P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

:

Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
ETHYLENE GLYCOL	107-21-1	>= 90 - <= 100
SODIUM BENZOATE	532-32-1	>= 1.5 - < 5
SODIUM BORATE DECAHYDRATE	1303-96-4	>= 1.5 - < 5
SODIUM NITRITE	7632-00-0	>= 0.1 - < 0.5
SODIUM NITRATE	7631-99-4	>= 0.1 - < 0.5

Actual concentration is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

General advice

:

Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.



**Valvoline™**  
**Global**

## SAFETY DATA SHEET

Zerex™ G05® Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:  
04/13/2025

---

	Do not leave the victim unattended.
If inhaled	: If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of eye contact	: Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	: Harmful if swallowed. May cause cancer. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure if swallowed.
Notes to physician	: No symptoms known or expected. Treat symptomatically. No hazards which require special first aid measures.

---

### SECTION 5. FIREFIGHTING MEASURES

Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: No hazardous combustion products are known
Specific extinguishing methods	: Product is compatible with standard fire-fighting agents.
Further information	: Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES



**SAFETY DATA SHEET**  
Zerex™ G05® Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:  
04/13/2025

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ETHYLENE GLYCOL	107-21-1	TWA (Vapour)	25 ppm	ACGIH



**Valvoline™**  
**Global**

**SAFETY DATA SHEET**

Zerex™ G05® Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:  
04/13/2025

		STEL (Vapour)	50 ppm	ACGIH
		STEL (Inhalable fraction, Aerosol only)	10 mg/m3	ACGIH
		C	50 ppm 125 mg/m3	OSHA P0
SODIUM BENZOATE	532-32-1	TWA (Inhalable particulate matter)	2.5 mg/m3	ACGIH
SODIUM BORATE DECAHYDRATE	1303-96-4	TWA	5 mg/m3	NIOSH REL
		TWA	10 mg/m3	OSHA P0
		TWA (Inhalable particulate matter)	2 mg/m3 (Borate)	ACGIH
		STEL (Inhalable particulate matter)	6 mg/m3 (Borate)	ACGIH

**Personal protective equipment**

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : light yellow

Odour : mild

Odour Threshold : No data available



**Valvoline™**  
**Global**

## SAFETY DATA SHEET

Zerex™ G05® Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:  
04/13/2025

---

pH	:	Average 6.5
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	330 °F / 166 °C (1013 hPa)
Flash point	:	> 250.0 °F / > 121.1 °C  Method: closed cup
Evaporation rate	:	> 1 Ethyl Ether
Flammability (solid, gas)	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	15.3 %(V)
Lower explosion limit / Lower flammability limit	:	3.2 %(V)
Vapour pressure	:	1.1 mmHg (68 °F / 20 °C)
Relative vapour density	:	> 1 AIR=1
Relative density	:	No data available
Density	:	Average 1.1362 g/cm <sup>3</sup> (60.01 °F / 15.56 °C)
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Oxidizing properties	:	No data available



**Valvoline™**  
**Global**

## SAFETY DATA SHEET

Zerex™ G05® Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:  
04/13/2025

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed.
Conditions to avoid	:	excessive heat Exposure to moisture
Incompatible materials	:	Acids Aldehydes Alkali metals Alkaline earth metals aluminum Fluorine Hydrogen fluoride iron salts lithium metal hydrides metal salts strong alkalis Strong oxidizing agents strong reducing agents Sulphur compounds
Hazardous decomposition products	:	No hazardous decomposition products are known.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Harmful if swallowed.

#### Product:

Acute oral toxicity : Acute toxicity estimate: 523.96 mg/kg  
Method: Calculation method

#### Components:

##### ETHYLENE GLYCOL:

Acute oral toxicity : LD0 (Human): estimated 1.56 g/kg

Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : LC50 (Rat): 10.9 mg/l  
Exposure time: 1 h  
Test atmosphere: dust/mist



**Valvoline™**  
**Global**

## SAFETY DATA SHEET

Zerex™ G05® Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:  
04/13/2025

Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): 9,530 mg/kg

Acute toxicity (other routes of administration) : LD50 (Rat): 5,010 mg/kg  
Application Route: Intraperitoneal

LD50 (Rat): 3,260 mg/kg  
Application Route: Intravenous

### **SODIUM BENZOATE:**

Acute oral toxicity : LD50 (Rat, male and female): 3,450 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 12.2 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Remarks: The toxicological data has been taken from products of similar composition.

### **SODIUM BORATE DECAHYDRATE:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: The toxicological data has been taken from products of similar composition.  
No mortality observed at this dose.

Acute inhalation toxicity : LC50 (Rat): > 2.04 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
GLP: yes  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: The toxicological data has been taken from products of similar composition.  
No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
GLP: yes  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: The toxicological data has been taken from products of similar composition.  
No mortality observed at this dose.



**Valvoline™**  
**Global**

## SAFETY DATA SHEET

Zerex™ G05® Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:  
04/13/2025

### **SODIUM NITRITE:**

Acute oral toxicity : LD50 (Rat): 180 mg/kg  
Acute inhalation toxicity : LC50 (Rat): 5.5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

### **SODIUM NITRATE:**

Acute oral toxicity : LD50 (Rat): ca. 3,430 mg/kg  
Method: OECD Test Guideline 401

### **Skin corrosion/irritation**

Not classified based on available information.

### **Components:**

#### **ETHYLENE GLYCOL:**

Species : Rabbit  
Result : No skin irritation

#### **SODIUM BENZOATE:**

Assessment : Slight, transient irritation  
Result : Slight, transient irritation

#### **SODIUM BORATE DECAHYDRATE:**

Species : Rabbit  
Result : Slight, transient irritation

#### **SODIUM NITRITE:**

Assessment : No skin irritation  
Result : No skin irritation

#### **SODIUM NITRATE:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : The toxicological data has been taken from products of similar composition.

### **Serious eye damage/eye irritation**

Not classified based on available information.



**Valvoline™**  
**Global**

**SAFETY DATA SHEET**  
Zerex™ G05® Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:  
04/13/2025

**Components:**

**ETHYLENE GLYCOL:**

Result : Slight, transient irritation

**SODIUM BENZOATE:**

Species : Rabbit  
Result : Irritating to eyes.  
Method : OECD Test Guideline 405

**SODIUM BORATE DECAHYDRATE:**

Species : Rabbit  
Result : Irritating to eyes.

**SODIUM NITRITE:**

Result : Irritating to eyes.  
Assessment : Irritating to eyes.

**SODIUM NITRATE:**

Species : Rabbit  
Result : Irritating to eyes.  
Method : OECD Test Guideline 405

**Respiratory or skin sensitisation**

**Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Components:**

**ETHYLENE GLYCOL:**

Test Type : Maximisation Test  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.

**SODIUM BORATE DECAHYDRATE:**

Test Type : Buehler Test  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.  
Remarks : The toxicological data has been taken from products of similar composition.



**Valvoline™**  
**Global**

**SAFETY DATA SHEET**  
Zerex™ G05® Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:  
04/13/2025

**Germ cell mutagenicity**

Not classified based on available information.

**Components:**

**ETHYLENE GLYCOL:**

Genotoxicity in vitro : Test Type: Ames test  
Test system: Salmonella typhimurium  
Metabolic activation: with and without metabolic activation  
Result: negative

**Carcinogenicity**

May cause cancer.

**IARC** Group 2A: Probably carcinogenic to humans  
SODIUM NITRITE 7632-00-0  
(nitrite (ingested) under conditions that result in endogenous nitrosation)  
Group 2A: Probably carcinogenic to humans  
SODIUM NITRATE 7631-99-4  
(nitrate (ingested) under conditions that result in endogenous nitrosation)

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

May damage fertility or the unborn child.

**Components:**

**SODIUM BORATE DECAHYDRATE:**

Reproductive toxicity - Assessment : Clear evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.

**Components:**

**ETHYLENE GLYCOL:**

Exposure routes : Ingestion  
Target Organs : Kidney, Liver



**Valvoline™**  
**Global**

## SAFETY DATA SHEET

Zerex™ G05® Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:  
04/13/2025

Assessment : May cause damage to organs through prolonged or repeated exposure.

### Aspiration toxicity

Not classified based on available information.

### Experience with human exposure

#### Components:

#### ETHYLENE GLYCOL:

Ingestion : Target Organs: Kidney

#### Further information

#### Product:

Remarks : No data available

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Product:

#### Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 3; Harmful to aquatic life.

Chronic aquatic toxicity : Not classified based on available information.

#### Components:

#### ETHYLENE GLYCOL:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 27,540 mg/l  
Exposure time: 96 h  
Test Type: static test

LC50 (Pimephales promelas (fathead minnow)): 8,050 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Test Type: static test

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 6,500 - 13,000 mg/l  
End point: Growth inhibition



**Valvoline™**  
**Global**

## SAFETY DATA SHEET

Zerex™ G05® Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:  
04/13/2025

Exposure time: 7 Days

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 32,000 mg/l  
Exposure time: 7 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 24,000 mg/l  
Exposure time: 7 d

### Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

### SODIUM BENZOATE:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: Static  
Remarks: Mortality

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: Static  
Remarks: Mortality

### Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

### SODIUM BORATE DECAHYDRATE:

Toxicity to fish : LC50 (Fish): > 100 mg/l  
Exposure time: 96 h  
Remarks: The toxicological data has been taken from products of similar composition.

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 133 mg/l  
Exposure time: 48 h  
Test Type: static test  
Remarks: The toxicological data has been taken from products of similar composition.

Toxicity to algae/aquatic plants : NOEC (Dunaliella tertiolecta (marine algae)): 50 mg/l  
End point: Growth inhibition  
Exposure time: 240 h



**SAFETY DATA SHEET**  
Zerex™ G05® Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:  
04/13/2025

Test Type: static test  
Remarks: Information refers to the main component.

Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): 13 mg/l  
Exposure time: 4 d  
Remarks: Information refers to the main component.

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 16.6 mg/l  
Exposure time: 28 d  
Test Type: flow-through test  
Remarks: Information refers to the main component.

**Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

**SODIUM NITRITE:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.35 - 3.81 mg/l  
Exposure time: 96 h  
Test Type: flow-through test

LC50 (Oncorhynchus mykiss (rainbow trout)): 0.54 - 26.3 mg/l  
Exposure time: 96 h  
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 15.4 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l  
Exposure time: 72 h  
Test Type: Growth inhibition  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC (Ictalurus catus (catfish)): 6.16 mg/l  
Exposure time: 31 d  
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 9.86 mg/l  
Exposure time: 80 d  
Test Type: static test

Toxicity to microorganisms : EC10 (activated sludge): 210 mg/l  
Exposure time: 3 h



**Valvoline™**  
**Global**

## SAFETY DATA SHEET

Zerex™ G05® Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:  
04/13/2025

Test Type: Static  
Method: OECD Test Guideline 209

### Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 1; Very toxic to aquatic life.

Chronic aquatic toxicity : Not classified based on available information.

### SODIUM NITRATE:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1,355 - 2,063 mg/l  
Exposure time: 96 h  
Method: Static  
Remarks: Mortality

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 3,581 mg/l  
Exposure time: 48 h  
Method: Static

LC50 (Daphnia magna (Water flea)): 665 mg/l  
Exposure time: 96 h  
Method: Static

### Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

### Persistence and degradability

#### Components:

#### ETHYLENE GLYCOL:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 90 - 100 %  
Exposure time: 10 d  
Method: OECD Test Guideline 301

#### SODIUM BENZOATE:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 88 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301



**SAFETY DATA SHEET**  
Zerex™ G05® Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:  
04/13/2025

**Bioaccumulative potential**

**Components:**

**ETHYLENE GLYCOL:**

Bioaccumulation : Species: Crayfish (Procambarus)  
Bioconcentration factor (BCF): 0.27  
Exposure time: 61 d  
Concentration: 1000 mg/l  
Method: Flow through

Partition coefficient: n-octanol/water : log Pow: -1.36

**SODIUM NITRITE:**

Partition coefficient: n-octanol/water : log Pow: -3.700 (77 °F / 25 °C)

**Mobility in soil**

**Components:**

**SODIUM NITRITE:**

Stability in soil : Remarks: Not expected to adsorb on soil.

**Other adverse effects**

**Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82  
Protection of Stratospheric Ozone - CAA Section 602 Class I  
Substances  
Remarks: This product neither contains, nor was  
manufactured with a Class I or Class II ODS as defined by the  
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +  
B).

Additional ecological information : An environmental hazard cannot be excluded in the event of  
unprofessional handling or disposal.  
Harmful to aquatic life.

---

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water  
courses or the soil.  
Do not contaminate ponds, waterways or ditches with  
chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.



**Valvoline**<sup>TM</sup>  
**Global**

**SAFETY DATA SHEET**  
Zerex<sup>TM</sup> G05<sup>®</sup> Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:  
04/13/2025

Dispose of as unused product.  
Do not re-use empty containers.

---

**SECTION 14. TRANSPORT INFORMATION**

**International Regulations**

**UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations**

**49 CFR**

Not regulated as a dangerous good

**49 CFR**

Not regulated as a dangerous good

**49 CFR**

Not regulated as a dangerous good

**49 CFR**

Not regulated as a dangerous good

**Special precautions for user**

Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

---

**SECTION 15. REGULATORY INFORMATION**

**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
METHANOL	67-56-1	100	100 (F003)

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.



**SAFETY DATA SHEET**  
Zerex™ G05® Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:  
04/13/2025

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Acute toxicity (any route of exposure)  
Carcinogenicity  
Reproductive toxicity  
Specific target organ toxicity (single or repeated exposure)

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

ETHYLENE	107-21-1	>= 90 - <= 100 %
GLYCOL		

**Clean Air Act**

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

ETHYLENE GLYCOL	107-21-1	>= 90 - <= 100 %
-----------------	----------	------------------

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

ETHYLENE GLYCOL	107-21-1	>= 90 - <= 100 %
SODIUM BENZOATE	532-32-1	>= 1 - < 5 %

**Clean Water Act**

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

SODIUM NITRITE	7632-00-0	>= 0.1 - < 1 %
SODIUM HYDROXIDE	1310-73-2	>= 0 - < 0.1 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

SODIUM NITRITE	7632-00-0	>= 0.1 - < 1 %
SODIUM HYDROXIDE	1310-73-2	>= 0 - < 0.1 %

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

**US State Regulations**

**Massachusetts Right To Know**

ETHYLENE GLYCOL	107-21-1
SODIUM BORATE DECAHYDRATE	1303-96-4

**Pennsylvania Right To Know**

ETHYLENE GLYCOL	107-21-1
SODIUM BORATE DECAHYDRATE	1303-96-4



**SAFETY DATA SHEET**  
Zerex™ G05® Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:  
04/13/2025

SODIUM NITRITE 7632-00-0  
SODIUM HYDROXIDE 1310-73-2

**Maine Chemicals of High Concern**

WATER 7732-18-5

**Vermont Chemicals of High Concern**

ETHYLENE GLYCOL 107-21-1  
WATER 7732-18-5  
ACETALDEHYDE 75-07-0  
1,4-DIOXANE 123-91-1

**Washington Chemicals of High Concern**

ETHYLENE GLYCOL 107-21-1  
WATER 7732-18-5  
ACETALDEHYDE 75-07-0  
1,4-DIOXANE 123-91-1

**California Prop. 65**

WARNING: This product can expose you to chemicals including ETHYLENE GLYCOL, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**California List of Hazardous Substances**

ETHYLENE GLYCOL 107-21-1  
SODIUM BORATE DECAHYDRATE 1303-96-4

**California Permissible Exposure Limits for Chemical Contaminants**

ETHYLENE GLYCOL 107-21-1  
SODIUM BORATE DECAHYDRATE 1303-96-4

**The components of this product are reported in the following inventories:**

- TCSI : Not in compliance with the inventory
- TSCA : All substances listed as active on the TSCA inventory
- AIIC : Not in compliance with the inventory
- DSL : All components of this product are on the Canadian DSL
- ENCS : Not in compliance with the inventory
- ISHL : Not in compliance with the inventory
- KECI : Not in compliance with the inventory
- PICCS : Not in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory



**Valvoline™**  
**Global**

**SAFETY DATA SHEET**

Zerex™ G05® Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:  
04/13/2025

NZIoC : Not in compliance with the inventory  
TECI : Not in compliance with the inventory

**TSCA list**

No substances are subject to a Significant New Use Rule.

The following substance(s) is/are subject to TSCA 12(b) export notification requirements:  
SODIUM NITRITE 7632-00-0


**Inventories**

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

**SECTION 16. OTHER INFORMATION**

**Further information**

**NFPA 704:**



**HMIS® IV:**

<b>HEALTH</b>	*	2
<b>FLAMMABILITY</b>		1
<b>PHYSICAL HAZARD</b>		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

**Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
NIOSH REL : USA. NIOSH Recommended Exposure Limits  
OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)



**Valvoline**<sup>™</sup>

**Global**

## SAFETY DATA SHEET

Zerex<sup>™</sup> G05<sup>®</sup> Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:

04/13/2025

---

ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / C	:	Ceiling limit

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 06/29/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the



**Valvoline™**

**Global**

**SAFETY DATA SHEET**  
Zerex™ G05® Antifreeze Coolant

Version: 2.0

Revision Date: 06/29/2023

Print Date:  
04/13/2025

---

specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

Internal information : R0296766